



FCC TEST REPORT

FCC ID:2AXCX-7BT822

Report Number.....: ZKT-2209016372E-1

Date of Test..... Sep. 01, 2022 to Sep. 09, 2022

Date of issue.....: Sep. 09, 2022

Total number of pages..... 80

Test Result: PASS

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address: 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name: Shenzhen Foxwell Technology Co., Ltd

Address: 5/F, Plant C, Baocheng 71st Zone, Xin'an Street, Baoan District, Shenzhen 518106, China

Manufacturer's name: Shenzhen Foxwell Technology Co., Ltd

Address: 5/F, Plant C, Baocheng 71st Zone, Xin'an Street, Baoan District, Shenzhen 518106, China

Test specification:

Standard.....: FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

Test procedure.....: /

Non-standard test method: N/A

Test Report Form No.....: TRF-EL-112_V0**Test Report Form(s) Originator.....: ZKT Testing****Master TRF: Dated: 2021-04-22**

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....: Automotive Diagnostic tool

Trademark: FOXWELL

Model/Type reference.....: NT819BT

RS910PRO TS, NT809BT, i70BT, UCAN-II, CJ4SHARK

Ratings.....: Input: DC 5V or is powered by a 3.7V battery



Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Tom Zou

Tom Zou

Reviewer (name + signature).....: Jackson Fang

Jackson Fang

Approved (name + signature).....: Lake Xie





Table of Contents

	Page
1. VERSION	5
2. TEST SUMMARY	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 Test Setup Configuration	10
3.3 Support Equipment	10
3.4 Test Mode	11
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
4. EMC EMISSION TEST	14
4.1 Conducted emissions	14
4.1.1 POWER LINE CONDUCTED EMISSION Limits	14
4.1.2 TEST PROCEDURE	14
4.1.3 DEVIATION FROM TEST STANDARD	14
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	15
4.1.6 Test Result	16
4.2 Radiated emissions	18
4.2.1 Radiated Emission Limits	18
4.2.2 TEST PROCEDURE	18
4.2.3 DEVIATION FROM TEST STANDARD	19
4.2.4 TEST SETUP	19
4.2.5 EUT OPERATING CONDITIONS	20
4.2.6 TEST RESULTS	21
5. RADIATED BAND EMISSION MEASUREMENT	30
5.1 Test Requirement:	30
5.2 TEST PROCEDURE	30
5.3 DEVIATION FROM TEST STANDARD	31
5.4 TEST SETUP	31
5.5 EUT OPERATING CONDITIONS	31
5.6 TEST RESULT	32
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	34
6.1 Limit	34
6.2 Test Setup	34
6.3 Test procedure	34
6.4 DEVIATION FROM STANDARD	34
6.5 Test Result	35
7. 20DB&99% BANDWIDTH	50
7.1 Test Setup	50
7.2 Limit	50
7.3 Test procedure	50
7.4 DEVIATION FROM STANDARD	50



7.5 Test Result	50
8. MAXIMUM PEAK OUTPUT POWER	57
8.1 Block Diagram Of Test Setup	57
8.2 Limit	57
8.3 Test procedure	57
8.4 DEVIATION FROM STANDARD	57
8.5 Test Result	57
9. HOPPING CHANNEL SEPARATION	63
9.1 Test Setup	63
9.2 Test procedure	63
9.3 DEVIATION FROM STANDARD	63
9.4 Test Result	64
10.NUMBER OF HOPPING FREQUENCY	69
10.1 Test Setup	69
10.2 Test procedure	69
10.3 DEVIATION FROM STANDARD	69
10.4 Test Result	70
11. DWELL TIME	72
11.1 Test Setup	72
11.2 Test procedure	72
11.3 DEVIATION FROM STANDARD	72
11.4 Test Result	73
12. ANTENNA REQUIREMENT	79
13. TEST SETUP PHOTO	80
14. EUT CONSTRUCTIONAL DETAILS	80



1. VERSION

Report No.	Version	Description	Approved
ZKT-2209016372E-1	Rev.01	Initial issue of report	Sep. 09, 2022



2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth 99% OCB	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission and Restricted Band	PASS	
15.247(d)	Conducted Unwanted emissions and Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

Designation Number: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8dB
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59℃



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Automotive Diagnostic tool
Model No.:	NT819BT RS910PRO TS, NT809BT, i70BT, UCAN-II, CJ4SHARK
Model Different.:	Only for different model name
Sample ID	ZKT-2209016372E-1
Sample(s) Status:	Engineer sample
Channel numbers:	79
Operation Frequency:	2402MHz~2480MHz
Modulation technology:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	FPCB Antenna
Antenna gain:	2.88 dBi
Power supply:	Input: DC 5V or is powered by a 3.7V battery



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz



3.2 Test Setup Configuration

Conducted Emission

AC Line

Radiated Emission

AC Line

Conducted Spurious

AC Line

3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Automotive Diagnostic tool	N/A	NT819BT	N/A	EUT
A-1	AC Adapter	HuaWei	ZKT-01	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	BT Test Tool
Power level setup	<7dBm



3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer	KEYSIGHT	9020A	MY55370835	Oct. 18, 2021	Oct. 17, 2022
	(9kHz-26.5GHz)					
2	Spectrum Analyzer	R&S	FSQ	100363	Oct. 17, 2021	Oct. 16, 2022
	(1GHz-40GHz)					
3	EMI Test Receiver	R&S	ESCI7	101169	Oct. 18, 2021	Oct. 17, 2022
	(9kHz-7GHz)					
4	Bilog Antenna	Schwarzbeck	VULB9168	N/A	Oct. 17, 2021	Oct. 16, 2022
	(30MHz-1500MHz)					
5	Horn Antenna	Agilent	AH-118	071145	Oct. 17, 2021	Oct. 16, 2022
	(1GHz-18GHz)					
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 17, 2021	Oct. 16, 2022
7	Amplifier	EM Electronics	EM330 Amplifier	060747	Oct. 18, 2021	Oct. 17, 2022
	(30-1000MHz)					
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2021	Oct. 17, 2022
9	RF cables1	N/A	9kHz-30MHz	N/A	Oct. 18, 2021	Oct. 17, 2022
	(9kHz-30MHz)					
10	RF cables2	N/A	30MHz-1GHz	N/A	Oct. 18, 2021	Oct. 17, 2022
	(30MHz-1GHz)					
11	RF cables3	N/A	1GHz-40GHz	N/A	Oct. 18, 2021	Oct. 17, 2022
	(1GHz-40GHz)					
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 22, 2021	Oct. 21, 2022
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2021	Oct. 21, 2022
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 17, 2021	Oct. 16, 2022
15	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 22, 2021	Oct. 21, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
17	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
18	RF Software	MW	MTS8310	V2.0.0.0	\	\
19	Turntable	MF	MF-7802BS	N/A	\	\
20	Antenna tower	MF	MF-7802BS	N/A	\	\



Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 22, 2021	Oct. 21, 2022
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 22, 2021	Oct. 21, 2022
3	Test Cable	N/A	C01	N/A	Oct. 18, 2021	Oct. 17, 2022
4	Test Cable	N/A	C02	N/A	Oct. 18, 2021	Oct. 17, 2022
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 17, 2021	Oct. 16, 2022
6	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	\	\



4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 Test Result

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
		MHz					dB		
1	*	0.1590	41.15	12.81	53.96	65.52	-11.56	QP	
2		0.1590	21.29	12.81	34.10	55.52	-21.42	AVG	
3		0.4334	24.84	10.85	35.69	57.19	-21.50	QP	
4		0.4560	19.30	10.75	30.05	46.77	-16.72	AVG	
5		1.3150	15.66	10.36	26.02	56.00	-29.98	QP	
6		1.3690	8.37	10.35	18.72	46.00	-27.28	AVG	
7		8.6865	22.31	8.51	30.82	60.00	-29.18	QP	
8		9.2400	11.52	8.49	20.01	50.00	-29.99	AVG	
9		12.4931	30.17	8.81	38.98	60.00	-21.02	QP	
10		12.4931	21.49	8.81	30.30	50.00	-19.70	AVG	
11		18.4920	24.21	9.65	33.86	60.00	-26.14	QP	
12		18.4920	10.15	9.65	19.80	50.00	-30.20	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment				
1	*	0.1544	44.22	12.91	57.13	65.76	-8.63	QP	
2		0.1590	24.95	12.81	37.76	55.52	-17.76	AVG	
3		0.4560	27.19	10.75	37.94	56.77	-18.83	QP	
4		0.4560	24.27	10.75	35.02	46.77	-11.75	AVG	
5		1.0904	15.31	10.42	25.73	56.00	-30.27	QP	
6		1.0904	6.51	10.42	16.93	46.00	-29.07	AVG	
7		7.1158	20.58	8.57	29.15	60.00	-30.85	QP	
8		7.1653	9.83	8.56	18.39	50.00	-31.61	AVG	
9		12.5563	28.02	8.82	36.84	60.00	-23.16	QP	
10		12.5967	18.81	8.82	27.63	50.00	-22.37	AVG	
11		25.6020	7.13	9.92	17.05	50.00	-32.95	AVG	
12		26.5560	17.50	9.93	27.43	60.00	-32.57	QP	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	MX5Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.



- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation


4.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz






(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



4.2.6 TEST RESULTS


Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz


Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7V(Powered by batteries)		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	53.5052	37.36	-14.10	23.26	40.00	-16.74	QP
2	103.2609	41.00	-19.62	21.38	43.50	-22.12	QP
3	177.8206	47.77	-17.66	30.11	43.50	-13.39	QP
4	340.1847	42.27	-16.82	25.45	46.00	-20.55	QP
5	674.0252	29.78	-7.26	22.52	46.00	-23.48	QP
6	900.1471	37.40	-6.99	30.41	46.00	-15.59	QP



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 3.7V(Powered by batteries)		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.3680	47.39	-16.96	30.43	40.00	-9.57	QP
2	93.7681	45.60	-21.39	24.21	43.50	-19.29	QP
3	173.2050	39.20	-19.96	19.24	43.50	-24.26	QP
4	377.9211	31.85	-15.76	16.09	46.00	-29.91	QP
5	565.6295	29.92	-9.08	20.84	46.00	-25.16	QP
6	957.1145	30.96	-0.44	30.52	46.00	-15.48	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case GFSK mode



1GHz~25GHz

GFSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	50.67	30.55	5.77	24.66	50.55	74.00	-23.45	Pk
V	4804.00	43.63	30.55	5.77	24.66	43.51	54.00	-10.49	AV
V	7206.00	51.93	30.33	6.32	24.55	52.47	74.00	-21.53	Pk
V	7206.00	43.38	30.33	6.32	24.55	43.92	54.00	-10.08	AV
V	9608.00	50.72	30.85	7.45	24.69	52.01	74.00	-21.99	Pk
V	9608.00	43.29	30.85	7.45	24.69	44.58	54.00	-9.42	AV
V	12010.00	52.05	31.02	8.99	25.57	55.59	74.00	-18.41	Pk
V	12010.00	43.73	31.02	8.99	25.57	47.27	54.00	-6.73	AV
H	4804.00	52.55	30.55	5.77	24.66	52.43	74.00	-21.57	Pk
H	4804.00	43.95	30.55	5.77	24.66	43.83	54.00	-10.17	AV
H	7206.00	54.03	30.33	6.32	24.55	54.57	74.00	-19.43	Pk
H	7206.00	43.61	30.33	6.32	24.55	44.15	54.00	-9.85	AV
H	9608.00	53.70	30.85	7.45	24.69	54.99	74.00	-19.01	Pk
H	9608.00	43.04	30.85	7.45	24.69	44.33	54.00	-9.67	AV
H	12010.00	50.61	31.02	8.99	25.57	54.15	74.00	-19.85	Pk
H	12010.00	43.07	31.02	8.99	25.57	46.61	54.00	-7.39	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	54.32	30.55	5.77	24.66	54.20	74.00	-19.80	Pk
V	4882.00	43.41	30.55	5.77	24.66	43.29	54.00	-10.71	AV
V	7323.00	53.04	30.33	6.32	24.55	53.58	74.00	-20.42	Pk
V	7323.00	43.46	30.33	6.32	24.55	44.00	54.00	-10.00	AV
V	9764.00	51.81	30.85	7.45	24.69	53.10	74.00	-20.90	Pk
V	9764.00	43.57	30.85	7.45	24.69	44.86	54.00	-9.14	AV
V	12205.00	51.58	31.02	8.99	25.57	55.12	74.00	-18.88	Pk
V	12205.00	43.45	31.02	8.99	25.57	46.99	54.00	-7.01	AV
H	4882.00	54.92	30.55	5.77	24.66	54.80	74.00	-19.20	Pk
H	4882.00	43.62	30.55	5.77	24.66	43.50	54.00	-10.50	AV
H	7323.00	53.54	30.33	6.32	24.55	54.08	74.00	-19.92	Pk
H	7323.00	43.08	30.33	6.32	24.55	43.62	54.00	-10.38	AV
H	9764.00	53.59	30.85	7.45	24.69	54.88	74.00	-19.12	Pk
H	9764.00	43.49	30.85	7.45	24.69	44.78	54.00	-9.22	AV
H	12205.00	51.36	31.02	8.99	25.57	54.90	74.00	-19.10	Pk
H	12205.00	43.15	31.02	8.99	25.57	46.69	54.00	-7.31	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960.00	53.98	30.55	5.77	24.66	53.86	74.00	-20.14	Pk
V	4960.00	43.62	30.55	5.77	24.66	43.50	54.00	-10.50	AV
V	7440.00	50.81	30.33	6.32	24.55	51.35	74.00	-22.65	Pk
V	7440.00	43.16	30.33	6.32	24.55	43.70	54.00	-10.30	AV
V	9920.00	50.51	30.85	7.45	24.69	51.80	74.00	-22.20	Pk
V	9920.00	43.49	30.85	7.45	24.69	44.78	54.00	-9.22	AV
V	12400.00	51.39	31.02	8.99	25.57	54.93	74.00	-19.07	Pk
V	12400.00	43.68	31.02	8.99	25.57	47.22	54.00	-6.78	AV
H	4960.00	53.02	30.55	5.77	24.66	52.90	74.00	-21.10	Pk
H	4960.00	43.91	30.55	5.77	24.66	43.79	54.00	-10.21	AV
H	7440.00	54.64	30.33	6.32	24.55	55.18	74.00	-18.82	Pk
H	7440.00	43.75	30.33	6.32	24.55	44.29	54.00	-9.71	AV
H	9920.00	54.39	30.85	7.45	24.69	55.68	74.00	-18.32	Pk
H	9920.00	43.31	30.85	7.45	24.69	44.60	54.00	-9.40	AV
H	12400.00	53.44	31.02	8.99	25.57	56.98	74.00	-17.02	Pk
H	12400.00	43.87	31.02	8.99	25.57	47.41	54.00	-6.59	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



$\pi/4$ -DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	54.50	30.55	5.77	24.66	54.38	74.00	-19.62	Pk
V	4804.00	43.42	30.55	5.77	24.66	43.30	54.00	-10.70	AV
V	7206.00	54.94	30.33	6.32	24.55	55.48	74.00	-18.52	Pk
V	7206.00	44.00	30.33	6.32	24.55	44.54	54.00	-9.46	AV
V	9608.00	50.79	30.85	7.45	24.69	52.08	74.00	-21.92	Pk
V	9608.00	43.41	30.85	7.45	24.69	44.70	54.00	-9.30	AV
V	12010.00	51.91	31.02	8.99	25.57	55.45	74.00	-18.55	Pk
V	12010.00	43.00	31.02	8.99	25.57	46.54	54.00	-7.46	AV
H	4804.00	53.47	30.55	5.77	24.66	53.35	74.00	-20.65	Pk
H	4804.00	43.99	30.55	5.77	24.66	43.87	54.00	-10.13	AV
H	7206.00	54.03	30.33	6.32	24.55	54.57	74.00	-19.43	Pk
H	7206.00	43.05	30.33	6.32	24.55	43.59	54.00	-10.41	AV
H	9608.00	50.47	30.85	7.45	24.69	51.76	74.00	-22.24	Pk
H	9608.00	43.13	30.85	7.45	24.69	44.42	54.00	-9.58	AV
H	12010.00	52.75	31.02	8.99	25.57	56.29	74.00	-17.71	Pk
H	12010.00	43.71	31.02	8.99	25.57	47.25	54.00	-6.75	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	50.17	30.55	5.77	24.66	50.05	74.00	-23.95	Pk
V	4882.00	43.16	30.55	5.77	24.66	43.04	54.00	-10.96	AV
V	7323.00	51.23	30.33	6.32	24.55	51.77	74.00	-22.23	Pk
V	7323.00	43.73	30.33	6.32	24.55	44.27	54.00	-9.73	AV
V	9764.00	51.10	30.85	7.45	24.69	52.39	74.00	-21.61	Pk
V	9764.00	43.59	30.85	7.45	24.69	44.88	54.00	-9.12	AV
V	12205.00	50.19	31.02	8.99	25.57	53.73	74.00	-20.27	Pk
V	12205.00	43.88	31.02	8.99	25.57	47.42	54.00	-6.58	AV
H	4882.00	51.45	30.55	5.77	24.66	51.33	74.00	-22.67	Pk
H	4882.00	43.79	30.55	5.77	24.66	43.67	54.00	-10.33	AV
H	7323.00	52.30	30.33	6.32	24.55	52.84	74.00	-21.16	Pk
H	7323.00	43.41	30.33	6.32	24.55	43.95	54.00	-10.05	AV
H	9764.00	53.19	30.85	7.45	24.69	54.48	74.00	-19.52	Pk
H	9764.00	43.67	30.85	7.45	24.69	44.96	54.00	-9.04	AV
H	12205.00	54.24	31.02	8.99	25.57	57.78	74.00	-16.22	Pk
H	12205.00	43.36	31.02	8.99	25.57	46.90	54.00	-7.10	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960.00	50.08	30.55	5.77	24.66	49.96	74.00	-24.04	Pk
V	4960.00	43.10	30.55	5.77	24.66	42.98	54.00	-11.02	AV
V	7440.00	54.15	30.33	6.32	24.55	54.69	74.00	-19.31	Pk
V	7440.00	43.61	30.33	6.32	24.55	44.15	54.00	-9.85	AV
V	9920.00	54.45	30.85	7.45	24.69	55.74	74.00	-18.26	Pk
V	9920.00	43.42	30.85	7.45	24.69	44.71	54.00	-9.29	AV
V	12400.00	53.66	31.02	8.99	25.57	57.20	74.00	-16.80	Pk
V	12400.00	43.63	31.02	8.99	25.57	47.17	54.00	-6.83	AV
H	4960.00	51.82	30.55	5.77	24.66	51.70	74.00	-22.30	Pk
H	4960.00	43.98	30.55	5.77	24.66	43.86	54.00	-10.14	AV
H	7440.00	50.14	30.33	6.32	24.55	50.68	74.00	-23.32	Pk
H	7440.00	43.98	30.33	6.32	24.55	44.52	54.00	-9.48	AV
H	9920.00	50.54	30.85	7.45	24.69	51.83	74.00	-22.17	Pk
H	9920.00	43.49	30.85	7.45	24.69	44.78	54.00	-9.22	AV
H	12400.00	53.84	31.02	8.99	25.57	57.38	74.00	-16.62	Pk
H	12400.00	43.66	31.02	8.99	25.57	47.20	54.00	-6.80	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



8-DPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	54.42	30.55	5.77	24.66	54.30	74.00	-19.70	Pk
V	4804.00	43.20	30.55	5.77	24.66	43.08	54.00	-10.92	AV
V	7206.00	52.71	30.33	6.32	24.55	53.25	74.00	-20.75	Pk
V	7206.00	43.80	30.33	6.32	24.55	44.34	54.00	-9.66	AV
V	9608.00	50.04	30.85	7.45	24.69	51.33	74.00	-22.67	Pk
V	9608.00	43.90	30.85	7.45	24.69	45.19	54.00	-8.81	AV
V	12010.00	53.94	31.02	8.99	25.57	57.48	74.00	-16.52	Pk
V	12010.00	43.38	31.02	8.99	25.57	46.92	54.00	-7.08	AV
H	4804.00	54.57	30.55	5.77	24.66	54.45	74.00	-19.55	Pk
H	4804.00	43.85	30.55	5.77	24.66	43.73	54.00	-10.27	AV
H	7206.00	54.16	30.33	6.32	24.55	54.70	74.00	-19.30	Pk
H	7206.00	43.20	30.33	6.32	24.55	43.74	54.00	-10.26	AV
H	9608.00	50.10	30.85	7.45	24.69	51.39	74.00	-22.61	Pk
H	9608.00	43.57	30.85	7.45	24.69	44.86	54.00	-9.14	AV
H	12010.00	50.84	31.02	8.99	25.57	54.38	74.00	-19.62	Pk
H	12010.00	43.46	31.02	8.99	25.57	47.00	54.00	-7.00	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	52.55	30.55	5.77	24.66	52.43	74.00	-21.57	Pk
V	4882.00	43.15	30.55	5.77	24.66	43.03	54.00	-10.97	AV
V	7323.00	52.49	30.33	6.32	24.55	53.03	74.00	-20.97	Pk
V	7323.00	43.60	30.33	6.32	24.55	44.14	54.00	-9.86	AV
V	9764.00	53.77	30.85	7.45	24.69	55.06	74.00	-18.94	Pk
V	9764.00	43.36	30.85	7.45	24.69	44.65	54.00	-9.35	AV
V	12205.00	54.17	31.02	8.99	25.57	57.71	74.00	-16.29	Pk
V	12205.00	43.88	31.02	8.99	25.57	47.42	54.00	-6.58	AV
H	4882.00	53.00	30.55	5.77	24.66	52.88	74.00	-21.12	Pk
H	4882.00	43.75	30.55	5.77	24.66	43.63	54.00	-10.37	AV
H	7323.00	51.65	30.33	6.32	24.55	52.19	74.00	-21.81	Pk
H	7323.00	43.59	30.33	6.32	24.55	44.13	54.00	-9.87	AV
H	9764.00	53.34	30.85	7.45	24.69	54.63	74.00	-19.37	Pk
H	9764.00	43.35	30.85	7.45	24.69	44.64	54.00	-9.36	AV
H	12205.00	52.48	31.02	8.99	25.57	56.02	74.00	-17.98	Pk
H	12205.00	43.05	31.02	8.99	25.57	46.59	54.00	-7.41	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960.00	53.89	30.55	5.77	24.66	53.77	74.00	-20.23	Pk
V	4960.00	43.22	30.55	5.77	24.66	43.10	54.00	-10.90	AV
V	7440.00	50.46	30.33	6.32	24.55	51.00	74.00	-23.00	Pk
V	7440.00	43.28	30.33	6.32	24.55	43.82	54.00	-10.18	AV
V	9920.00	53.09	30.85	7.45	24.69	54.38	74.00	-19.62	Pk
V	9920.00	43.79	30.85	7.45	24.69	45.08	54.00	-8.92	AV
V	12400.00	54.22	31.02	8.99	25.57	57.76	74.00	-16.24	Pk
V	12400.00	43.80	31.02	8.99	25.57	47.34	54.00	-6.66	AV
H	4960.00	51.54	30.55	5.77	24.66	51.42	74.00	-22.58	Pk
H	4960.00	43.88	30.55	5.77	24.66	43.76	54.00	-10.24	AV
H	7440.00	53.95	30.33	6.32	24.55	54.49	74.00	-19.51	Pk
H	7440.00	43.81	30.33	6.32	24.55	44.35	54.00	-9.65	AV
H	9920.00	54.84	30.85	7.45	24.69	56.13	74.00	-17.87	Pk
H	9920.00	43.80	30.85	7.45	24.69	45.09	54.00	-8.91	AV
H	12400.00	54.31	31.02	8.99	25.57	57.85	74.00	-16.15	Pk
H	12400.00	43.47	31.02	8.99	25.57	47.01	54.00	-6.99	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported




5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
GFSK	Low Channel: 2402MHz									
	H	2390.00	54.70	30.22	4.85	23.98	53.31	74.00	PK	PASS
	H	2390.00	44.23	30.22	4.85	23.98	42.84	54.00	AV	PASS
	H	2400.00	54.30	30.22	4.85	23.98	52.91	74.00	PK	PASS
	H	2400.00	44.33	30.22	4.85	23.98	42.94	54.00	AV	PASS
	V	2390.00	53.57	30.22	4.85	23.98	52.18	74.00	PK	PASS
	V	2390.00	44.12	30.22	4.85	23.98	42.73	54.00	AV	PASS
	V	2400.00	54.14	30.22	4.85	23.98	52.75	74.00	PK	PASS
	V	2400.00	44.28	30.22	4.85	23.98	42.89	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	53.00	30.22	4.85	23.98	51.61	74.00	Pk	PASS
	H	2483.50	44.72	30.22	4.85	23.98	43.33	54.00	AV	PASS
	H	2500.00	53.33	30.22	4.85	23.98	51.94	74.00	Pk	PASS
	H	2500.00	44.81	30.22	4.85	23.98	43.42	54.00	AV	PASS
	V	2483.50	54.26	30.22	4.85	23.98	52.87	74.00	Pk	PASS
	V	2483.50	44.09	30.22	4.85	23.98	42.70	54.00	AV	PASS
	V	2500.00	53.15	30.22	4.85	23.98	51.76	74.00	Pk	PASS
	V	2500.00	44.84	30.22	4.85	23.98	43.45	54.00	AV	PASS
$\pi/4$ -DQPSK	Low Channel: 2402MHz									
	H	2390.00	53.52	30.22	4.85	23.98	52.13	74.00	PK	PASS
	H	2390.00	44.99	30.22	4.85	23.98	43.60	54.00	AV	PASS
	H	2400.00	54.59	30.22	4.85	23.98	53.20	74.00	PK	PASS
	H	2400.00	44.56	30.22	4.85	23.98	43.17	54.00	AV	PASS
	V	2390.00	53.48	30.22	4.85	23.98	52.09	74.00	PK	PASS
	V	2390.00	44.26	30.22	4.85	23.98	42.87	54.00	AV	PASS
	V	2400.00	53.69	30.22	4.85	23.98	52.30	74.00	PK	PASS
	V	2400.00	44.00	30.22	4.85	23.98	42.61	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	53.67	30.22	4.85	23.98	52.28	74.00	PK	PASS
	H	2483.50	44.65	30.22	4.85	23.98	43.26	54.00	AV	PASS
	H	2500.00	53.72	30.22	4.85	23.98	52.33	74.00	PK	PASS
	H	2500.00	44.73	30.22	4.85	23.98	43.34	54.00	AV	PASS
	V	2483.50	53.74	30.22	4.85	23.98	52.35	74.00	PK	PASS
	V	2483.50	44.64	30.22	4.85	23.98	43.25	54.00	AV	PASS
	V	2500.00	54.52	30.22	4.85	23.98	53.13	74.00	PK	PASS
	V	2500.00	44.95	30.22	4.85	23.98	43.56	54.00	AV	PASS
8-DPSK	Low Channel: 2402MHz									
	H	2390.00	54.89	30.22	4.85	23.98	53.50	74.00	PK	PASS
	H	2390.00	44.57	30.22	4.85	23.98	43.18	54.00	AV	PASS
	H	2400.00	53.71	30.22	4.85	23.98	52.32	74.00	PK	PASS
	H	2400.00	44.53	30.22	4.85	23.98	43.14	54.00	AV	PASS
	V	2390.00	53.52	30.22	4.85	23.98	52.13	74.00	PK	PASS
	V	2390.00	44.65	30.22	4.85	23.98	43.26	54.00	AV	PASS
	V	2400.00	54.72	30.22	4.85	23.98	53.33	74.00	PK	PASS
	V	2400.00	44.50	30.22	4.85	23.98	43.11	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	53.59	30.22	4.85	23.98	52.20	74.00	PK	PASS
	H	2483.50	44.28	30.22	4.85	23.98	42.89	54.00	AV	PASS
	H	2500.00	53.64	30.22	4.85	23.98	52.25	74.00	PK	PASS
	H	2500.00	44.63	30.22	4.85	23.98	43.24	54.00	AV	PASS
	V	2483.50	54.02	30.22	4.85	23.98	52.63	74.00	PK	PASS
	V	2483.50	44.25	30.22	4.85	23.98	42.86	54.00	AV	PASS



	V	2500.00	53.92	30.22	4.85	23.98	52.53	74.00	PK	PASS
	V	2500.00	44.34	30.22	4.85	23.98	42.95	54.00	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit



6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 Limit

Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD


No deviation.



6.5 Test Result

GFSK mode:

Test channel:	Lowest channel
---------------	----------------




30MHz~26.5GHz



Test channel:


Middle channel



30MHz~26.5GHz



Test channel:	Highest channel
---------------	-----------------





30MHz~26.5GHz



$\pi/4$ -DQPSK mode:


Test channel:	Lowest channel
---------------	----------------



30MHz~26.5GHz




Test channel:	Middle channel
---------------	----------------



30MHz~26.5GHz



Test channel:	Highest channel
---------------	-----------------



30MHz~26.5GHz