

# **FCC Test Report**

Report No.: AGC00748210801FE10

FCC ID : 2AXDPDB90

**PRODUCT DESIGNATION**: Mobile Radio

**BRAND NAME**: The COM

**MODEL NAME** : COM-DB90

APPLICANT : Stingray UTV LLC

**DATE OF ISSUE** : Aug. 18, 2021

STANDARD(S) : FCC Part 90 Rules

FCC Part 22 Rules

**REPORT VERSION**: V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE, he test result presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 2 of 65

# REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	1	Aug. 18, 2021	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Resting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



# Report No.: AGC00748210801FE10 Page 3 of 65

# TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	7
2.3 RELATED SUBMITTAL(S) / GRANT (S)	
2.4 TEST METHODOLOGY	
2.5 CALCULATION OF EMISSION INDICATORS	
2.6 SPECIAL ACCESSORIES	9
2.7 EQUIPMENT MODIFICATIONS	9
3. TEST ENVIRONMENT	
3.1 ADDRESS OF THE TEST LABORATORY	
3.2 TEST FACILITY	10
3.3 ENVIRONMENTAL CONDITIONS	
3.4 MEASUREMENT UNCERTAINTY	11
3.5 LIST OF EQUIPMENTS USED	12
4.SYSTEM TEST CONFIGURATION	
4.1 EUT CONFIGURATION	
4.2 EUT EXERCISE	13
4.3 CONFIGURATION OF TESTED SYSTEM	13
4.4 EQUIPMENT USED IN TESTED SYSTEM	13
4.5 SUMMARY OF TEST RESULTS	14
5.DESCRIPTION OF TEST MODES	15
6.FREQUENCY TOLERANCE	16
6.1 PROVISIONS APPLICABLE	16
6.2 MEASUREMENT PROCEDURE	
6.3 MEASUREMENT SETUP	
6.4 MEASUREMENT RESULTS	17
7. EMISSION BANDWIDTH	18
7.1 PROVISIONS APPLICABLE	18
7.2 MEASUREMENT PROCEDURE	18
7.3 MEASUREMENT SETUP	
7.4 MEASUREMENT RESULTS	19
8. SPURIOUS RATIATED EMISSION	
8.1 PROVISIONS APPLICABLE	
O O MEACUREMENT PROCEDURE	

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Dedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC whe test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issued by the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





8.3 MEASUREMENT SETUP	22
8.4 MEASUREMENT RESULTS	24
8.5 EMISSION MASK PLOT	25
9.MODULATION CHARACTERISTICS	40
9.1 PROVISIONS APPLICABLE	40
9.2 MEASUREMENT METHOD	40
9.3 MEASUREMENT SETUP	40
9.4 MEASUREMENT RESULTS	
10. MAXIMUMN TRANSMITTER POWER	4.
10.1 PROVISIONS APPLICABLE	
10.2 MEASUREMENT METHOD	
10.3 MEASUREMENT METHOD	
10.4 MEASUREMENT RESULTS	
11. SPURIOUS EMISSION ON ANTENNA PORT	
11.1 PROVISIONS APPLICABLE	
11.2 MEASUREMENT METHOD	
11.3 MEASUREMENT SETUP	
11.4 MEASUREMENT RESULTS	
12.TRANSMITTER FREQUENCY BEHAVIOR	54
12.1 PROVISIONS APPLICABLE	
13.2 MEASUREMENT SETUP	54
12.3 MEASUREMENT METHOD	55
12.4 MEASURET RESULTS	
13. AUDIO LOW PASS FILTER RESPONSE	59
13.1 PROVISIONS APPLICABLE	59
13.2 MEASUREMENT METHOD	60
13.3 MEASUREMENT SETUP	60
13.4 MEASURET RESULTS	6^
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	63
ADDENDIY II. DUOTOGDADUS OF TEST ELIT	GI

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 5 of 65

#### 1. GENERAL INFORMATION

Applicant	Stingray UTV LLC
Address	18092 Lantana Ave Nampa, Idaho 83687 United States Of America
Manufacturer	QYT ELECTRONICS CO., LTD
Address	NO.166 Gaoyang, Houtian, Fengzhou, Nan'an, Quanzhou, Fujian, China
Factory	QYT ELECTRONICS CO., LTD
Address	NO.166 Gaoyang, Houtian, Fengzhou, Nan'an, Quanzhou, Fujian, China
Product Designation	Mobile Radio
Brand Name	TheCOM
Test Model	COM-DB90
Deviation from Standard	None
Date of Receipt	Aug. 06, 2021
Date of Test	Aug. 06, 2021~Aug. 16, 2021
Test Result	Pass

#### WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E-2016. The sample tested as described in this report is in compliance with the FCC Rules Part 22 and 90. The test results of this report relate only to the tested sample identified in this report.

Bibo Zhang
(Project Engineer)

Reviewed By

Calvin Liu
(Reviewer)

Aug. 16, 2021

Aug. 18, 2021

Forrest Lei
Authorized Officer

Aug. 18, 2021

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Postuo/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Page 6 of 65

#### 2. PRODUCT INFORMATION

# 2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	V1.0	· F SO SO	
Software Version	V1.0		
Power Supply	DC 13.8V	100 - C	
Communication Type	Voice /Tone only		
Operation Frequency Range	From 136MHz to 174M From 400MHz to 480M		
Modulation Type	Analog Voice:	FM	
Channel Separation	Analog Voice:	12.5 kHz	
Analog Voice:	11K0F3E	70 - CO - C	
Rated Output Power	VHF:25W/UHF:20W (It was fixed by the ma	nufacturer, any individual can't arbitrarily change it.)	
Maximum Transmitter Power	VHF: 43.85dBm(25W-12.5kHz)		
Maximum Transmiller Power	UHF: 42.86dBm(20W-12.5kHz)		
Antenna Designation	Detachable Antenna		
Antenna Gain	0dBi (Typical), 3.5dBi (Max)		
Frequency Tolerance	1.076ppm		

Note: The actual working frequency band of the device is UHF: 400-480MHz. According to the frequency divisi on requirements of KDB634817 and the federal frequency allocation requirements, the working frequency ban d that the device needs to meet is UHF: 406.1-480MHz

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festivo/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written purportization of AGC within 15day after the issue of the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issue of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 7 of 65

#### 2.2 TEST FREQUENCY LIST

Operation mode	Channel Separation	Operation Frequency Range	Test channel	Test Frequency
	12.5 kHz	400-480MHz	Bottom	406.125 MHz
-6	12.5 kHz	400-480MHz	Middle	453.2125 MHz
Analog	12.5 kHz	400-480MHz	Middle	454.025 MHz
, C	12.5 kHz	400-480MHz	Middle	458.2125 MHz
	12.5 kHz	400-480MHz	Тор	479.975 MHz
Analog	12.5 kHz	136-174MHz	Bottom	136.025 MHz
	12.5 kHz	136-174MHz	Middle	151.850 MHz
	12.5 kHz	136-174MHz	Middle	155.7525MHz
	12.5 kHz	136-174MHz	Middle	161.610 MHz
	12.5 kHz	136-174MHz	Тор	173.975 MHz

#### Note:

In section KDB 634817 D01 Sections II) (f) (1) and (2):

Test at least one frequency in each band for each rule part applied under and ensure the device is capable of operating on the frequency under each rule part. This requirement may result in testing on multiple frequencies. Testing on one frequency may be acceptable if multiple listed bands for a rule part with a continuous frequency range are split to remove a conflict with other rules and the technical requirements in the split bands are the same. Additional requirements for RF exposure may apply.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 8 of 65

### 2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **2AXDPDB90**, filing to comply with Part 2, Part 22, and Part 90 of the Federal Communication Commission rules.

#### 2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title		
1	FCC 47 CFR Part 22	Public Mobile Services		
2	FCC 47 CFR Part 90	Private Land Mobile Radio Services		
3	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
4	ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards		
5	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services		
6	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03r01		
7	KDB 579009 D03	KDB 579009 D03 Applications Part 90 Refarming Bands v01		
8	KDB 634817 D01	KDB 634817 D01 Freq Range Listing for Grants v04r01		

#### 2.5 CALCULATION OF EMISSION INDICATORS

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

#### For FM Mode (ChannelSpacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

BW = 2(M+D) = 2\*(3.0 kHz + 2.5 kHz) = 11 kHz = 11KO

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

## For FM Mode (Channel Spacing: 25kHz)

Emission Designator 16K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 5.0 kHz deviation.

BW = 2(M+D) = 2\*(3.0 kHz + 5.0 kHz) = 16 kHz = 16K0

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 25 kHz channel spacing FM mode is 16K0F3E.

#### For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1W

The 99% energy rule was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz.

F1D and F1W portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1W.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated restrou/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 9 of 65

#### 2.6 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

#### 2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 10 of 65

### 3. TEST ENVIRONMENT

#### 3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

# CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

## A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

# FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

## IC-Registration No.: 24842

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Residual Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Page 11 of 65

# 3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS
Temperature range (℃)	15 - 35	-20 - 50
Relative humidty range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	DC 13.8V	LV: DC 11.73V/HV: DC 15.87V

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

#### 3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty		
Frequency stability	±0.5%		
Transmitter power conducted	±0.8dB		
Transmitter power Radiated	±1.3dB		
Conducted spurious emission 9kHz-40 GHz	±2.7dB		
Conducted Emission	±3.2 dB		
Radiated Emission below 1GHz	±3.9 dB		
Radiated Emission above 1GHz	±4.8 dB		
Occupied Channel Bandwidth	±2 %		
FM deviation	±2 %		
Audio level	±0.98dB		
Low Pass Filter Response	±0.65dB		
Modulation Limiting	0.42 %		
Transient Frequency Behavior	6.8 %		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Past not/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 12 of 65

# 3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Apr. 14, 2021	Apr. 13, 2022
EXA Signal Analyzer	Aglient	N9020A	W1312-60196	Aug. 21, 2020	Aug. 20, 2021
EXA Signal Analyzer	Aglient	N9020A	MY52090123	Sep. 03, 2020	Sep. 02, 2021
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.16, 2019	Sep.15, 2021
preamplifier	ChengYi	EMC184045SE	980508	Sep. 23, 2019	Sep. 22, 2021
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun. 07, 2021	Jun. 06, 2022
HORN ANTENNA	EM	EM-AH-10180	/	Feb.26, 2021	Feb.25, 2022
SIGNAL GENERATOR	AGILENT	E4421B	MY43351603	May 11, 2021	May 10, 2022
SIGNAL GENERATOR	R&S	SMT03	A0304261	Jun. 07, 2021	Jun. 06, 2022
ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep. 20, 2019	Sep. 19, 2021
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	May 22, 2020	May 21, 2022
Modulation Domain Analyzer	HP	53310A	3121A02467	Aug. 26, 2020	Aug. 25, 2021
Small environmental tester	ESPEC	SH-242	) <u></u> °	Sep. 03, 2020	Sep. 02, 2022
RF Communication Test Set	НР	8920B	US35010261	Sep. 03, 2020	Sep. 02, 2021
Attenuator	Weinachel Corp	58-30-33	ML030	Oct. 26, 2020	Oct. 25, 2021
RF Cable	R&S	1#	(	Each time	N/A
RF Cable	R&S	2#	·	Each time	N/A
Fliter-UHF	Microwave	N25155M2	498705	May 09, 2021	May 08, 2022
Fliter-VHF	Microwave	N26460M1	498703	May 09, 2021	May 08, 2022

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 13 of 65

# **4.SYSTEM TEST CONFIGURATION**

#### **4.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### **4.2 EUT EXERCISE**

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

#### 4.3 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System

EUT

Table 2-1 Equipment Used in Tested System

#### 4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

☐ Test Accessories Come From The Laboratory

☐ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	Mobile Radio	COM-DB90	FCC ID: 2AXDPDB90	EUT
2	Hand microphone	N/A	N/A	Accessories
3	Car Charger	N/A	N/A	Accessories

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the common stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Report No.: AGC00748210801FE10 Page 14 of 65

# 4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	FCC 47 CFR PART 90/22	Antenna Equipment	Pass
2	§90.205&22.565& 2.1046	Maximum Transmitter Power	Pass
3	§90.207& 2.1047	Modulation Characteristic	Pass
4	§2.1047	Audio Low Pass Filter Response	Pass
5	§90.209& 22.359& 2.1049	Occupied Bandwidth	Pass
6	§90.210& 22.359& 2.1049	Emission Mask	Pass
7	§90.213& 22.355& 2.1055	Frequency Tolerance	Pass
8	§90.214	Transmitter Frequency Behavior	Pass
9	§90.210&22.359& 2.1051	Spurious Emission on Antenna Port	Pass
10	§90.210&22.359& 2.1053	Spurious Ratiated Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Pest Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issue of Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com. g/Inspection he test results



Page 15 of 65

### **5.DESCRIPTION OF TEST MODES**

The EUT (**Two-way radio**) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

NO.	TEST MODE DESCRIPTION	CHANNEL SEPARATION
1 6	TX Bottom channel-UHF	12.5 kHz
2	TX Middle channel-UHF	12.5 kHz
3	TX Middle channel-UHF	12.5 kHz
4	TX Top channel-UHF	12.5 kHz
5	TX Bottom channel-VHF	12.5 kHz
6	TX Middle channel-VHF	12.5 kHz
7	TX Middle channel-VHF	12.5 kHz
8	TX Middle channel-VHF	12.5 kHz
9	TX Top channel-VHF	12.5 kHz

#### Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
- 4. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Feat Q/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of ACC whe test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 16 of 65

### **6.FREQUENCY TOLERANCE**

#### **6.1 PROVISIONS APPLICABLE**

- a). According to FCC §2.1055, § 22.355 and §90.213, the frequency stability shall be measured with variation of ambient temperature from  $-30^{\circ}$ C to  $+50^{\circ}$ C centigrade.
- b). According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- c). According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5 kHz channel separation and 0.0001% for 6.25 kHz channel separation.
- d). According to FCC Part 22 Section 22.355, Frequency error must be kept within plus or minus 5ppm.

#### **6.2 MEASUREMENT PROCEDURE**


#### 6.2.1 Frequency stability versus environmental temperature

- 1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- 2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz.Record this frequency as reference frequency.
- 3. Set the temperature of chamber to  $50^{\circ}$ C. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- 4. Repeat step 2 with a 10℃ decreased per stage until the lowest temperature -30℃ is measured, record all measured frequencies on each temperature step.

## 6.2.2 Frequency stability versus input voltage

- 1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within  $15^{\circ}$ C to  $25^{\circ}$ C. Otherwise, an environment chamber set for a temperature of  $20^{\circ}$ C shall be used. The EUT shall be powered by DC13.8V.
- 2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
- 3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

#### **6.3 MEASUREMENT SETUP**



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Page 17 of 65

# **6.4 MEASUREMENT RESULTS**

	12.5 kHz Cha	annel Separa	tion, Analog	modulation, A	Assigned Fre	quency For \	/HF-25W	
Test c	onditions		Freq	uency error (	ppm)		Limit	
Voltage	Temp		Test Frequency (MHz)					
(V)	(℃)	136.025	151.850	155.7525	161.610	173.975	(ppm)	
	-30	0.865	0.653	1.017	0.818	0.342	90	-6
8	-20	0.785	0.705	0.839	0.802	0.594		
	-10	0.685	1.059	0.511	0.490	0.739	©	
	0	0.512	0.742	0.519	0.545	0.634		
13.80	10	0.885	0.715	0.716	0.897	0.575		
	20	0.703	0.530	0.571	0.795	0.380	5	Pass
	30	0.982	0.611	0.994	0.677	0.656		
	40	0.830	1.017	0.512	0.790	0.686		
	50	0.939	0.632	0.587	0.740	0.626		
15.87	20	0.882	0.866	0.797	0.472	0.423	8	
11.73	20	1.030	0.912	0.922	0.938	0.939	GU	

	12.5 kHz Cha	annel Separa	tion, Analog r	modulation, /	Assigned Free	quency For l	JHF-20W	
Test co	onditions		Frequ	uency error (	(ppm)			
Voltage	Temp		Limit (ppm)	Result				
(V)	(℃)	406.125	453.2125	454.025	458.2125	479.975	(ββ)	
	-30	0.581	0.395	0.944	0.653	0.749		
8	-20	0.407	0.436	0.811	0.541	0.770		
GU	-10	0.455	0.744	0.444	0.921	0.675	(8)	
	0	0.428	0.650	0.624	0.813	0.903	-C	
13.80	10	0.444	0.874	0.995	0.595	0.764		
	20	0.891	0.618	0.386	0.792	0.791	5	Pass
	30	0.325	0.515	0.504	0.519	0.766	C	
8	40	0.418	0.979	0.575	0.644	0.768		
	50	0.990	0.478	0.383	1.076	1.022		
15.87	20	0.725	0.309	0.381	1.017	0.766		
11.73	20	0.301	0.948	0.680	0.597	0.960		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Page 18 of 65

### 7. EMISSION BANDWIDTH

#### 7.1 PROVISIONS APPLICABLE

FCC Part 90.209 & FCC Part 22.359& FCC Part 2.1049:

The authorized bandwidth shall be 11.25 kHz for 12.5 kHz channel separation and 6 kHz for 6.25 kHz channel separation.

#### 7.2 MEASUREMENT PROCEDURE

1.The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.

Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).

2.Spectrum set as follow:

Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing, RBW=100Hz, VBW=300Hz, Sweep = auto,

Detector function = peak, Trace = max hold

- 3.Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.
- 4. Measure and record the results in the test report.

#### 7.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the condicated restrouting portion of Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.




Report No.: AGC00748210801FE10 Page 19 of 65

# 7.4 MEASUREMENT RESULTS

Measurement Result of VHF-Analog Modulation-25W										
Operating Frequency	12.5 kHz Channel Separation									
Operating Frequency	Occupied Bandwidth	Emission Bandwidth	Limits	Result						
136.025MHz	9.993 kHz	10.18 kHz	11.25 kHz	Pass						
151.850MHz	9.993 kHz	10.18 kHz	11.25 kHz	Pass						
155.7525MHz	9.993 kHz	10.19 kHz	11.25 kHz	Pass						
161.610MHz	9.993 kHz	10.18 kHz	11.25 kHz	Pass						
173.975MHz	9.993 kHz	10.18 kHz	11.25 kHz	Pass						


Measurement Result of UHF-Analog Modulation-20W										
Operating Fraguency	12.5 kHz Channel Separation									
Operating Frequency	Occupied Bandwidth	Emission Bandwidth	Limits	Result						
406.125MHz	9.993 kHz	10.18 kHz	11.25 kHz	Pass						
453.2125MHz	9.993 kHz	10.20 kHz	11.25 kHz	Pass						
454.025MHz	9.993 kHz	10.19 kHz	11.25 kHz	Pass						
458.2125MHz	9.993 kHz	10.20 kHz	11.25 kHz	Pass						
479.975MHz	9.994 kHz	10.18 kHz	11.25 kHz	Pass						

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Pest Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issue of Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com. /Inspection The test results







# Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Resting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written exhorization of AGC he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.







Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written exchorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 22 of 65

# 8. SPURIOUS RATIATED EMISSION

#### **8.1 PROVISIONS APPLICABLE**

According to FCC §2.1053 §22.359 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation. Emission Mask D -for 12.5 kHz Channel Separation:

- (1) On any frequency removed from the center of the authorized bandwidth fo to 5.625 kHz removed from fo: Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (fd in kHz) fo of more than 5.625 kHz but no more than 12.5 kHz: At least 7.27(fd-2.88 kHz) dB
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (fd in kHz)fo of more than 12.5 kHz: At least 50+10 log(P) dB or 70 dB, whichever is lesser attenuation.

According to FCC §22.359:


(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

#### **8.2 MEASUREMENT PROCEDURE**

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall than be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- (14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- (15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- (16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- (17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.


#### 8.3 MEASUREMENT SETUP


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated resting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc=cert.com.







# Radiated Emissions 30MHz to 1GHz Test setup





Radiated Emissions Above 1GHz Test setup





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Restriction Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter purportion of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 24 of 65

#### **8.4 MEASUREMENT RESULTS**

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.

The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.

EIRP = "Read Value" + Measured substitution value + 2.15.

#### Test limit calculation:

Preliminary calculation	Final Result				
At least 50+10 log (P) =50+10log (25) =63.98 (dB)	Limit=P- Preliminary calculation=43.98-63.98=-20 dBm				
At least 50+10 log (P) =50+10log (20) =63.01 (dB)	Limit=P- Preliminary calculation=43.01-63.01=-20 dBm				
At least 43+10 log (P) =43+10log (25) =56.98(dB)	Limit=P- Preliminary calculation=43.98-56.98=-13 dBm				
At least 43+10 log (P) =43+10log (20) =56.01 (dB)	Limit=P- Preliminary calculation=43.01-56.01=-13 dBm				

**Note:** In this case, Part 22 (-13 dBm) is less than the limit of Part 90 (-20 dBm), so we do not need to test Part 22, which meets the spurious limits of PART 90+22.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.






Test Mode: TX:136.025MHz-FM Polarity: Horizontal

	NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
	1	271.5300	-66.42	-33.36	-20.00	13.36	33.06	311	Horizontal
	2	679.9000	-65.33	-25.26	-20.00	5.26	40.07	19	Horizontal
	3	952.4700	-71.34	-27.26	-20.00	7.26	44.08	254	Horizontal
	4	1089.3089	-23.76	-27.83	-20.00	7.83	-4.07	9	Horizontal
	5	1360.7611	-25.11	-28.61	-20.00	8.61	-3.50	9	Horizontal
,	6	1632.2132	-22.76	-24.98	-20.00	4.98	-2.22	9	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.5300	-58.77	-28.59	-20.00	8.59	30.18	126	Vertical
2	679.9000	-68.85	-28.73	-20.00	8.73	40.12	135	Vertical
3	1088.1338	-27.02	-27.59	-20.00	7.59	-0.57	286	Vertical
4	1360.7611	-29.55	-28.31	-20.00	8.31	1.24	267	Vertical
5	1495.8996	-31.26	-29.13	-20.00	9.13	2.13	304	Vertical
6	1632.2132	-29.47	-27.77	-20.00	7.77	1.70	351	Vertical


Any leport having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the action of the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.








NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	528.5800	-64.47	-27.13	-20.00	7.13	37.34	243	Horizontal
2	906.8800	-66.87	-23.78	-20.00	3.78	43.09	186	Horizontal
3	1057.5808	-22.93	-27.07	-20.00	7.07	-4.14	9	Horizontal
4	1132.7883	-22.29	-26.27	-20.00	6.27	-3.98	234	Horizontal
5	1888.3888	-25.82	-26.12	-20.00	6.12	-0.30	280	Horizontal
6	2870.7871	-26.68	-24.61	-20.00	4.61	2.07	37	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	302.5700	-61.60	-30.57	-20.00	10.57	31.03	106	Vertical
2	1057.5808	-26.63	-27.41	-20.00	7.41	-0.78	294	Vertical
3	1511.1761	-27.68	-25.56	-20.00	5.56	2.12	68	Vertical
4	1812.0062	-25.79	-24.72	-20.00	4.72	1.07	21	Vertical
5	2417.1917	-26.31	-27.15	-20.00	7.15	-0.84	106	Vertical
6	3470.0970	-28.09	-25.02	-20.00	5.02	3.07	21	Vertical

Any leport having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Stadicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.











	NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
	1	322.9400	-61.30	-28.78	-20.00	8.78	32.52	212	Horizontal
Ī	2	484.9300	-65.71	-29.67	-20.00	9.67	36.04	250	Horizontal
	3	646.9200	-68.91	-28.93	-20.00	8.93	39.98	296	Horizontal
	4	1131.6132	-23.58	-27.56	-20.00	7.56	-3.98	277	Horizontal
	5	1292.6043	-19.58	-23.23	-20.00	3.23	-3.65	1	Horizontal
	6	1454.7705	-21.48	-24.78	-20.00	4.78	-3.30	333	Horizontal




	NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
	1	646.9200	-67.23	-27.69	-20.00	7.69	39.54	217	Vertical
	2	969.9300	-69.37	-25.35	-20.00	5.35	44.02	28	Vertical
	3	1131.6132	-23.42	-23.71	-20.00	3.71	-0.29	291	Vertical
7	4	1292.6043	-25.84	-25.06	-20.00	5.06	0.78	9	Vertical
	5	1453.5954	-28.20	-26.35	-20.00	6.35	1.85	348	Vertical
	6	2401.9152	-25.37	-26.17	-20.00	6.17	-0.80	329	Vertical


Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.








NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	467.4700	-67.23	-31.52	-20.00	11.52	35.71	9	Horizontal
2	935.0100	-72.05	-28.35	-20.00	8.35	43.70	224	Horizontal
3	1558.1808	-24.23	-27.00	-20.00	7.00	-2.77	205	Horizontal
4	2180.9931	-27.47	-27.65	-20.00	7.65	-0.18	326	Horizontal
5	2336.1086	-27.27	-28.06	-20.00	8.06	-0.79	177	Horizontal
6	3738.0238	-32.29	-27.84	-20.00	7.84	4.45	289	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1246.7747	-28.40	-27.92	-20.00	7.92	0.48	220	Vertical
2	1401.8902	-28.95	-27.44	-20.00	7.44	1.51	192	Vertical
3	1557.0057	-29.39	-27.43	-20.00	7.43	1.96	295	Vertical
4	1713.2963	-29.75	-28.34	-20.00	8.34	1.41	126	Vertical
5	3271.5022	-28.82	-25.69	-20.00	5.69	3.13	14	Vertical
6	3425.4425	-29.94	-26.86	-20.00	6.86	3.08	304	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Restriction Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.








— Limit # Final Test — Horizonta

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1454.7705	-25.24	-28.54	-20.00	8.54	-3.30	9	Horizontal
2	1618.1118	-24.81	-27.14	-20.00	7.14	-2.33	251	Horizontal
3	1779.1029	-24.63	-25.75	-20.00	5.75	-1.12	186	Horizontal
4	2424.2424	-26.76	-27.90	-20.00	7.90	-1.14	54	Horizontal
5	3070.5571	-29.51	-26.09	-20.00	6.09	3.42	214	Horizontal
6	3393.7144	-30.00	-26.01	-20.00	6.01	3.99	223	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	646.9200	-70.07	-30.53	-20.00	10.53	39.54	359	Vertical
2	1292.6043	-30.45	-29.67	-20.00	9.67	0.78	359	Vertical
3	2101.0851	-28.63	-28.52	-20.00	8.52	0.11	359	Vertical
4	2424.2424	-26.06	-26.92	-20.00	6.92	-0.86	359	Vertical
5	2586.4086	-25.27	-25.62	-20.00	5.62	-0.35	334	Vertical
6	4363.1863	-30.65	-27.53	-20.00	7.53	3.12	315	Vertical

Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter application of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.