

FCC TEST REPORT

FCC ID:2AXDQ-ONESCREENTL6

Report Number..... : ZKT-210826L4492E-1-1

Date of Test..... Mar. 11 to Apr. 02, 2022

Date of issue : Apr. 02, 2022

Total number of pages 33

Test Result : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : NZS Inc.

Address : 8168 Miramar Road, San Diego, CA 92126

Manufacturer's name : Heyuan lianteng industrial co., LTD

Address : Yc-ah13, longling fourth road, longling industrial park, yuancheng district, heyuan city

Test specification:Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-110_V0**Test Report Form(s) Originator** : ZKT Testing**Master TRF** : Dated: 2021-09-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : Interactive Touch Screen / Interactive Flat Panel

Trademark : OneScreen

Model/Type reference : OneScreen TL6,
OneScreen * (*stands for 0-9, or A-Z, or a-z, or blank)

Ratings..... : AC100-240V,50/60Hz

Testing procedure and testing location:


Testing Laboratory: Shenzhen ZKT Technology Co., Ltd.

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature): Alen He



Reviewer (name + signature).....: Joe Liu



Approved (name + signature): Lake Xie



Table of Contents

	Page
1. VERSION	4
2. SUMMARY OF TEST RESULTS	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	10
4. EMC EMISSION TEST	11
4.1 RADIATED EMISSION MEASUREMENT	11
4.1.1 RADIATED EMISSION LIMITS	11
4.1.2 TEST PROCEDURE	11
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	12
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 TEST RESULTS	14
5.RADIATED BAND EMISSIONMEASUREMENT	25
5.1 TEST REQUIREMENT:	25
5.2 TEST PROCEDURE	25
5.3 DEVIATION FROM TEST STANDARD	25
5.4 TEST SETUP	26
5.5 EUT OPERATING CONDITIONS	26
5.6 TEST RESULT	27
6.PEAK OUTPUT POWER TEST	29
6.1 APPLIED PROCEDURES/LIMIT	29
6.2 TEST PROCEDURE	29
6.3 DEVIATION FROM STANDARD	29
6.4 TEST SETUP	29
6.5 EUT OPERATION CONDITIONS	29
6.6 TEST RESULT	30
7. TEST SETUP PHOTO	33
8. EUT CONSTRUCTIONAL DETAILS	33

1. VERSION

Report No.	Version	Description	Approved
ZKT-210826L4492E-1-1	Rev.01-1	Initial issue of report	Apr. 02, 2022

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Interactive Touch Screen / Interactive Flat Panel
Model No.:	OneScreen TL6, OneScreen * (*stands for 0-9, or A-Z, or a-z, or blank)
Model Different.:	Only for different model name.
Serial No.:	N/A
Hardware Version:	H1.0
Software Version:	S1.0
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/802.11n(OneScreen TL60)/802.11n(HT40): Orthogonal Frequency Division Multiplexing(OFDM)
Antenna Type:	FPCB Antenna
Antenna gain:	2.0dBi
Power supply:	AC 110-240V 50/60Hz
SWITCHING POWER ADAPTER:	N/A
Battery:	N/A

Operation Frequency each of channel							
Channel	Frequency	Chann el	Frequency	Chann el	Frequency	Chann el	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

Test Software	Realtek Test Tool
Power level setup	<8dBm

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Interactive Touch Screen / Interactive Flat Panel	N/A	OneScreen TL6	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 22, 2021	Sep. 21, 2022
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 22, 2021	Sep. 21, 2022
3	Test Receiver (9kHz-7GHz)	R&S	ESC17	101169	Sep. 22, 2021	Sep. 21, 2022
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 22, 2021	Sep. 21, 2022
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 22, 2021	Sep. 21, 2022
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 22, 2021	Sep. 21, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 22, 2021	Sep. 21, 2022
8	Amplifier (1GHz-40GHz)	全聚达	DLE-161	097	Sep. 22, 2021	Sep. 21, 2022
9	Loop Antenna (9KHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 22, 2021	Sep. 21, 2022
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 22, 2021	Sep. 21, 2022
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 22, 2021	Sep. 21, 2022
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 22, 2021	Sep. 21, 2022
13	CMW500 Test	R&S	CMW500	106504	Sep. 22, 2021	Sep. 21, 2022
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 22, 2021	Sep. 21, 2022
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 22, 2021	Sep. 21, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
17	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 22, 2021	Sep. 21, 2022
2	LISN	CYBERTEK	EM5040A	E1850400149	Sep. 22, 2021	Sep. 21, 2022
3	Test Cable	N/A	C01	N/A	Sep. 22, 2021	Sep. 21, 2022
4	Test Cable	N/A	C02	N/A	Sep. 22, 2021	Sep. 21, 2022
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 22, 2021	Sep. 21, 2022
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 22, 2021	Sep. 21, 2022

4. EMC EMISSION TEST

4.1 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.1.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.1.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.1.3 DEVIATION FROM TEST STANDARD


No deviation

4.1.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.1.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.1.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.


Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	53.9763	49.16	-17.71	31.45	40.00	-8.55	QP
2	371.3528	50.64	-17.98	32.66	46.00	-13.34	QP
3	446.4139	51.77	-15.43	36.34	46.00	-9.66	QP
4	742.2586	47.25	-7.93	39.32	46.00	-6.68	QP
5	817.3995	45.64	-5.09	40.55	46.00	-5.45	QP
6	965.5420	45.06	-2.40	42.66	54.00	-11.34	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	213.7634	55.47	-19.24	36.23	43.50	-7.27	QP
2	298.2681	55.71	-18.73	36.98	46.00	-9.02	QP
3	668.1422	49.89	-9.39	40.50	46.00	-5.50	QP
4	742.2587	50.18	-8.81	41.37	46.00	-4.63	QP
5	892.2908	51.15	-8.99	42.16	46.00	-3.84	QP
6	965.5420	46.28	-7.61	38.67	54.00	-15.33	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case 802.11b mode

1GHz~25GHz

802.11b

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	51.41	30.55	5.77	31.12	57.75	74.00	-16.25	PK
V	4824.00	31.27	30.55	5.77	31.12	37.61	54.00	-16.39	AV
V	7236.00	49.50	30.33	6.32	36.00	61.49	74.00	-12.51	PK
V	7236.00	31.98	30.33	6.32	36.00	43.97	54.00	-10.03	AV
V	9648.00	50.00	30.85	7.45	37.14	63.74	74.00	-10.26	PK
V	9648.00	31.88	30.85	7.45	37.14	45.62	54.00	-8.38	AV
V	12060.00	45.10	31.02	8.99	39.10	62.17	74.00	-11.83	PK
V	12060.00	27.88	31.02	8.99	39.10	44.95	54.00	-9.05	AV
H	4824.00	51.75	30.55	5.77	31.12	58.09	74.00	-15.91	PK
H	4824.00	31.60	30.55	5.77	31.12	37.94	54.00	-16.06	AV
H	7236.00	50.39	30.33	6.32	36.00	62.38	74.00	-11.62	PK
H	7236.00	31.65	30.33	6.32	36.00	43.64	54.00	-10.36	AV
H	9648.00	50.39	30.85	7.45	37.14	64.13	74.00	-9.87	PK
H	9648.00	31.65	30.85	7.45	37.14	45.39	54.00	-8.61	AV
H	12060.00	45.39	31.02	8.99	39.10	62.46	74.00	-11.54	PK
H	12060.00	26.65	31.02	8.99	39.10	43.72	54.00	-10.28	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	49.55	30.55	5.77	31.45	56.22	74.00	-17.78	PK
V	4874.00	30.44	30.55	5.77	31.45	37.11	54.00	-16.89	AV
V	7311.00	48.08	30.33	6.32	36.10	60.17	74.00	-13.83	PK
V	7311.00	30.12	30.33	6.32	36.10	42.21	54.00	-11.79	AV
V	9748.00	48.15	30.85	7.45	36.50	61.25	74.00	-12.75	PK
V	9748.00	30.12	30.85	7.45	36.50	43.22	54.00	-10.78	AV
V	12185.00	43.05	31.02	8.99	39.11	60.13	74.00	-13.87	PK
V	12185.00	23.69	31.02	8.99	39.11	40.77	54.00	-13.23	AV
H	4874.00	50.91	30.55	5.77	31.45	57.58	74.00	-16.42	PK
H	4874.00	30.47	30.55	5.77	31.45	37.14	54.00	-16.86	AV
H	7311.00	51.62	30.33	6.32	36.10	63.71	74.00	-10.29	PK
H	7311.00	30.25	30.33	6.32	36.10	42.34	54.00	-11.66	AV
H	9748.00	51.62	30.85	7.45	36.50	64.72	74.00	-9.28	PK
H	9748.00	30.25	30.85	7.45	36.50	43.35	54.00	-10.65	AV
H	12185.00	45.10	31.02	8.99	39.11	62.18	74.00	-11.82	PK
H	12185.00	24.25	31.02	8.99	39.11	41.33	54.00	-12.67	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
High Channel:2462MHz									
V	4924.00	51.29	30.55	5.77	31.79	58.30	74.00	-15.70	PK
V	4924.00	32.83	30.55	5.77	31.79	39.84	54.00	-14.16	AV
V	7386.00	53.80	30.33	6.32	36.21	66.00	74.00	-8.00	PK
V	7386.00	33.15	30.33	6.32	36.21	45.35	54.00	-8.65	AV
V	9848.00	53.80	30.85	7.45	36.50	66.90	74.00	-7.10	PK
V	9848.00	33.64	30.85	7.45	36.50	46.74	54.00	-7.26	AV
V	12310.00	45.80	31.02	8.99	39.15	62.92	74.00	-11.08	PK
V	12310.00	28.04	31.02	8.99	39.15	45.16	54.00	-8.84	AV
H	4924.00	51.35	30.55	5.77	31.79	58.36	74.00	-15.64	PK
H	4924.00	32.99	30.55	5.77	31.79	40.00	54.00	-14.00	AV
H	7386.00	52.97	30.33	6.32	36.21	65.17	74.00	-8.83	PK
H	7386.00	33.31	30.33	6.32	36.21	45.51	54.00	-8.49	AV
H	9848.00	53.57	30.85	7.45	36.50	66.67	74.00	-7.33	PK
H	9848.00	33.01	30.85	7.45	36.50	46.11	54.00	-7.89	AV
H	12310.00	47.47	31.02	8.99	39.15	64.59	74.00	-9.41	PK
H	12310.00	26.40	31.02	8.99	39.15	43.52	54.00	-10.48	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	50.69	30.55	5.77	31.12	57.03	74.00	-16.97	PK
V	4824.00	30.45	30.55	5.77	31.12	36.79	54.00	-17.21	AV
V	7236.00	48.48	30.33	6.32	36.00	60.47	74.00	-13.53	PK
V	7236.00	31.40	30.33	6.32	36.00	43.39	54.00	-10.61	AV
V	9648.00	48.48	30.85	7.45	37.14	62.22	74.00	-11.78	PK
V	9648.00	30.96	30.85	7.45	37.14	44.70	54.00	-9.30	AV
V	12060.00	45.58	31.02	8.99	39.10	62.65	74.00	-11.35	PK
V	12060.00	26.86	31.02	8.99	39.10	43.93	54.00	-10.07	AV
H	4824.00	51.03	30.55	5.77	31.12	57.37	74.00	-16.63	PK
H	4824.00	30.88	30.55	5.77	31.12	37.22	54.00	-16.78	AV
H	7236.00	49.78	30.33	6.32	36.00	61.77	74.00	-12.23	PK
H	7236.00	31.09	30.33	6.32	36.00	43.08	54.00	-10.92	AV
H	9648.00	49.80	30.85	7.45	37.14	63.54	74.00	-10.46	PK
H	9648.00	31.11	30.85	7.45	37.14	44.85	54.00	-9.15	AV
H	12060.00	44.83	31.02	8.99	39.10	61.90	74.00	-12.10	PK
H	12060.00	24.12	31.02	8.99	39.10	41.19	54.00	-12.81	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	49.60	30.55	5.77	31.45	56.27	74.00	-17.73	PK
V	4874.00	30.45	30.55	5.77	31.45	37.12	54.00	-16.88	AV
V	7311.00	48.20	30.33	6.32	36.10	60.29	74.00	-13.71	PK
V	7311.00	30.31	30.33	6.32	36.10	42.40	54.00	-11.60	AV
V	9748.00	48.28	30.85	7.45	36.50	61.38	74.00	-12.62	PK
V	9748.00	29.54	30.85	7.45	36.50	42.64	54.00	-11.36	AV
V	12185.00	45.31	31.02	8.99	39.11	62.39	74.00	-11.61	PK
V	12185.00	23.65	31.02	8.99	39.11	40.73	54.00	-13.27	AV
H	4874.00	50.87	30.55	5.77	31.45	57.54	74.00	-16.46	PK
H	4874.00	30.82	30.55	5.77	31.45	37.49	54.00	-16.51	AV
H	7311.00	51.57	30.33	6.32	36.10	63.66	74.00	-10.34	PK
H	7311.00	30.39	30.33	6.32	36.10	42.48	54.00	-11.52	AV
H	9748.00	51.77	30.85	7.45	36.50	64.87	74.00	-9.13	PK
H	9748.00	30.20	30.85	7.45	36.50	43.30	54.00	-10.70	AV
H	12185.00	46.02	31.02	8.99	39.11	63.10	74.00	-10.90	PK
H	12185.00	25.33	31.02	8.99	39.11	42.41	54.00	-11.59	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
High Channel:2462MHz									
V	4924.00	49.60	30.55	5.77	31.79	56.61	74.00	-17.39	PK
V	4924.00	31.10	30.55	5.77	31.79	38.11	54.00	-15.89	AV
V	7386.00	51.94	30.33	6.32	36.21	64.14	74.00	-9.86	PK
V	7386.00	31.44	30.33	6.32	36.21	43.64	54.00	-10.36	AV
V	9848.00	51.94	30.85	7.45	36.50	65.04	74.00	-8.96	PK
V	9848.00	31.88	30.85	7.45	36.50	44.98	54.00	-9.02	AV
V	12310.00	45.04	31.02	8.99	39.15	62.16	74.00	-11.84	PK
V	12310.00	27.08	31.02	8.99	39.15	44.20	54.00	-9.80	AV
H	4924.00	49.62	30.55	5.77	31.79	56.63	74.00	-17.37	PK
H	4924.00	31.29	30.55	5.77	31.79	38.30	54.00	-15.70	AV
H	7386.00	51.11	30.33	6.32	36.21	63.31	74.00	-10.69	PK
H	7386.00	31.61	30.33	6.32	36.21	43.81	54.00	-10.19	AV
H	9848.00	51.81	30.85	7.45	36.50	64.91	74.00	-9.09	PK
H	9848.00	31.65	30.85	7.45	36.50	44.75	54.00	-9.25	AV
H	12310.00	45.71	31.02	8.99	39.15	62.83	74.00	-11.17	PK
H	12310.00	24.65	31.02	8.99	39.15	41.77	54.00	-12.23	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n20

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	51.16	30.55	5.77	31.12	57.50	74.00	-16.50	PK
V	4824.00	30.96	30.55	5.77	31.12	37.30	54.00	-16.70	AV
V	7236.00	48.05	30.33	6.32	36.00	60.04	74.00	-13.96	PK
V	7236.00	31.96	30.33	6.32	36.00	43.95	54.00	-10.05	AV
V	9648.00	49.25	30.85	7.45	37.14	62.99	74.00	-11.01	PK
V	9648.00	31.33	30.85	7.45	37.14	45.07	54.00	-8.93	AV
V	12060.00	45.05	31.02	8.99	39.10	62.12	74.00	-11.88	PK
V	12060.00	26.40	31.02	8.99	39.10	43.47	54.00	-10.53	AV
H	4824.00	51.30	30.55	5.77	31.12	57.64	74.00	-16.36	PK
H	4824.00	31.15	30.55	5.77	31.12	37.49	54.00	-16.51	AV
H	7236.00	50.25	30.33	6.32	36.00	62.24	74.00	-11.76	PK
H	7236.00	31.46	30.33	6.32	36.00	43.45	54.00	-10.55	AV
H	9648.00	50.17	30.85	7.45	37.14	63.91	74.00	-10.09	PK
H	9648.00	31.38	30.85	7.45	37.14	45.12	54.00	-8.88	AV
H	12060.00	44.30	31.02	8.99	39.10	61.37	74.00	-12.63	PK
H	12060.00	25.49	31.02	8.99	39.10	42.56	54.00	-11.44	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	50.73	30.55	5.77	31.45	57.40	74.00	-16.60	PK
V	4874.00	31.62	30.55	5.77	31.45	38.29	54.00	-15.71	AV
V	7311.00	48.59	30.33	6.32	36.10	60.68	74.00	-13.32	PK
V	7311.00	31.45	30.33	6.32	36.10	43.54	54.00	-10.46	AV
V	9748.00	49.64	30.85	7.45	36.50	62.74	74.00	-11.26	PK
V	9748.00	31.62	30.85	7.45	36.50	44.72	54.00	-9.28	AV
V	12185.00	46.54	31.02	8.99	39.11	63.62	74.00	-10.38	PK
V	12185.00	25.55	31.02	8.99	39.11	42.63	54.00	-11.37	AV
H	4874.00	52.02	30.55	5.77	31.45	58.69	74.00	-15.31	PK
H	4874.00	31.75	30.55	5.77	31.45	38.42	54.00	-15.58	AV
H	7311.00	52.75	30.33	6.32	36.10	64.84	74.00	-9.16	PK
H	7311.00	31.53	30.33	6.32	36.10	43.62	54.00	-10.38	AV
H	9748.00	52.90	30.85	7.45	36.50	66.00	74.00	-8.00	PK
H	9748.00	31.53	30.85	7.45	36.50	44.63	54.00	-9.37	AV
H	12185.00	45.53	31.02	8.99	39.11	62.61	74.00	-11.39	PK
H	12185.00	26.61	31.02	8.99	39.11	43.69	54.00	-10.31	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
High Channel:2462MHz									
V	4924.00	52.01	30.55	5.77	31.79	59.02	74.00	-14.98	PK
V	4924.00	33.21	30.55	5.77	31.79	40.22	54.00	-13.78	AV
V	7386.00	54.25	30.33	6.32	36.21	66.45	74.00	-7.55	PK
V	7386.00	33.93	30.33	6.32	36.21	46.13	54.00	-7.87	AV
V	9848.00	54.35	30.85	7.45	36.50	67.45	74.00	-6.55	PK
V	9848.00	34.35	30.85	7.45	36.50	47.45	54.00	-6.55	AV
V	12310.00	47.25	31.02	8.99	39.15	64.37	74.00	-9.63	PK
V	12310.00	26.49	31.02	8.99	39.15	43.61	54.00	-10.39	AV
H	4924.00	52.03	30.55	5.77	31.79	59.04	74.00	-14.96	PK
H	4924.00	33.70	30.55	5.77	31.79	40.71	54.00	-13.29	AV
H	7386.00	53.52	30.33	6.32	36.21	65.72	74.00	-8.28	PK
H	7386.00	34.16	30.33	6.32	36.21	46.36	54.00	-7.64	AV
H	9848.00	54.22	30.85	7.45	36.50	67.32	74.00	-6.68	PK
H	9848.00	34.15	30.85	7.45	36.50	47.25	54.00	-6.75	AV
H	12310.00	48.12	31.02	8.99	39.15	65.24	74.00	-8.76	PK
H	12310.00	27.06	31.02	8.99	39.15	44.18	54.00	-9.82	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n40

Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Low Channel:2422MHz									
V	4844.00	51.42	30.55	5.77	31.14	57.78	74.00	-16.22	PK
V	4844.00	32.61	30.55	5.77	31.14	38.97	54.00	-15.03	AV
V	7266.00	53.66	30.33	6.32	36.09	65.74	74.00	-8.26	PK
V	7266.00	33.47	30.33	6.32	36.09	45.55	54.00	-8.45	AV
V	9688.00	53.74	30.85	7.45	37.16	67.50	74.00	-6.50	PK
V	9688.00	33.72	30.85	7.45	37.16	47.48	54.00	-6.52	AV
V	12110.00	46.29	31.02	8.99	39.15	63.41	74.00	-10.59	PK
V	12110.00	26.98	31.02	8.99	39.15	44.10	54.00	-9.90	AV
H	4844.00	51.67	30.55	5.77	31.14	58.03	74.00	-15.97	PK
H	4844.00	33.14	30.55	5.77	31.14	39.50	54.00	-14.50	AV
H	7266.00	52.94	30.33	6.32	36.09	65.02	74.00	-8.98	PK
H	7266.00	33.62	30.33	6.32	36.09	45.70	54.00	-8.30	AV
H	9688.00	53.61	30.85	7.45	37.16	67.37	74.00	-6.63	PK
H	9688.00	33.19	30.85	7.45	37.16	46.95	54.00	-7.05	AV
H	12110.00	45.66	31.02	8.99	39.15	62.78	74.00	-11.22	PK
H	12110.00	26.50	31.02	8.99	39.15	43.62	54.00	-10.38	AV

Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Middle Channel:2437MHz									
V	4874.00	49.38	30.55	5.77	31.45	56.05	74.00	-17.95	PK
V	4874.00	30.58	30.55	5.77	31.45	37.25	54.00	-16.75	AV
V	7311.00	51.62	30.33	6.32	36.10	63.71	74.00	-10.29	PK
V	7311.00	31.30	30.33	6.32	36.10	43.39	54.00	-10.61	AV
V	9748.00	51.72	30.85	7.45	36.50	64.82	74.00	-9.18	PK
V	9748.00	31.72	30.85	7.45	36.50	44.82	54.00	-9.18	AV
V	12185.00	44.62	31.02	8.99	39.11	61.70	74.00	-12.30	PK
V	12185.00	24.86	31.02	8.99	39.11	41.94	54.00	-12.06	AV
H	4874.00	49.40	30.55	5.77	31.45	56.07	74.00	-17.93	PK
H	4874.00	31.07	30.55	5.77	31.45	37.74	54.00	-16.26	AV
H	7311.00	50.89	30.33	6.32	36.10	62.98	74.00	-11.02	PK
H	7311.00	31.53	30.33	6.32	36.10	43.62	54.00	-10.38	AV
H	9748.00	51.59	30.85	7.45	36.50	64.69	74.00	-9.31	PK
H	9748.00	31.52	30.85	7.45	36.50	44.62	54.00	-9.38	AV
H	12185.00	46.49	31.02	8.99	39.11	63.57	74.00	-10.43	PK
H	12185.00	25.43	31.02	8.99	39.11	42.51	54.00	-11.49	AV

Page 2 of 6

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904.00	50.19	30.55	5.77	31.69	57.10	74.00	-16.90	PK
V	4904.00	31.13	30.55	5.77	31.69	38.04	54.00	-15.96	AV
V	7356.00	51.82	30.33	6.32	36.15	63.96	74.00	-10.04	PK
V	7356.00	31.76	30.33	6.32	36.15	43.90	54.00	-10.10	AV
V	9808.00	52.52	30.85	7.45	37.32	66.44	74.00	-7.56	PK
V	9808.00	32.18	30.85	7.45	37.32	46.10	54.00	-7.90	AV
V	12260.00	46.03	31.02	8.99	39.13	63.13	74.00	-10.87	PK
V	12260.00	25.11	31.02	8.99	39.13	42.21	54.00	-11.79	AV
H	4904.00	49.87	30.55	5.77	31.69	56.78	74.00	-17.22	PK
H	4904.00	32.27	30.55	5.77	31.69	39.18	54.00	-14.82	AV
H	7356.00	51.45	30.33	6.32	36.15	63.59	74.00	-10.41	PK
H	7356.00	32.53	30.33	6.32	36.15	44.67	54.00	-9.33	AV
H	9808.00	52.08	30.85	7.45	37.32	66.00	74.00	-8.00	PK
H	9808.00	31.92	30.85	7.45	37.32	45.84	54.00	-8.16	AV
H	12260.00	45.07	31.02	8.99	39.13	62.17	74.00	-11.83	PK
H	12260.00	26.93	31.02	8.99	39.13	44.03	54.00	-9.97	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5.RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	60.51	30.22	4.85	27.59	62.73	74.00	PK	PASS
	H	2390.00	41.29	30.22	4.85	27.59	43.51	54.00	AV	PASS
	H	2400.00	62.24	30.22	4.85	27.58	64.45	74.00	PK	PASS
	H	2400.00	40.95	30.22	4.85	27.58	43.16	54.00	AV	PASS
	V	2390.00	60.33	30.22	4.85	27.59	62.55	74.00	PK	PASS
	V	2390.00	42.20	30.22	4.85	27.59	44.42	54.00	AV	PASS
	V	2400.00	62.09	30.22	4.85	27.58	64.30	74.00	PK	PASS
	V	2400.00	41.02	30.22	4.85	27.58	43.23	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	59.47	30.22	4.85	27.40	61.50	74.00	PK	PASS
	H	2485.50	40.51	30.22	4.85	27.40	42.54	54.00	AV	PASS
	H	2483.50	60.98	30.22	4.85	27.40	63.01	74.00	PK	PASS
	H	2485.50	41.09	30.22	4.85	27.40	43.12	54.00	AV	PASS
	V	2483.50	60.28	30.22	4.85	27.40	62.31	74.00	PK	PASS
	V	2485.50	41.90	30.22	4.85	27.40	43.93	54.00	AV	PASS
	V	2483.50	60.67	30.22	4.85	27.40	62.70	74.00	PK	PASS
	V	2485.50	41.36	30.22	4.85	27.40	43.39	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	58.36	30.22	4.85	27.59	60.58	74.00	PK	PASS
	H	2390.00	40.59	30.22	4.85	27.59	42.81	54.00	AV	PASS
	H	2400.00	60.39	30.22	4.85	27.58	62.60	74.00	PK	PASS
	H	2400.00	40.49	30.22	4.85	27.58	42.70	54.00	AV	PASS
	V	2390.00	58.61	30.22	4.85	27.59	60.83	74.00	PK	PASS
	V	2390.00	40.39	30.22	4.85	27.59	42.61	54.00	AV	PASS
	V	2400.00	58.36	30.22	4.85	27.58	60.57	74.00	PK	PASS
	V	2400.00	40.59	30.22	4.85	27.58	42.80	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	59.37	30.22	4.85	27.40	61.40	74.00	PK	PASS
	H	2485.50	41.10	30.22	4.85	27.40	43.13	54.00	AV	PASS
	H	2483.50	61.20	30.22	4.85	27.40	63.23	74.00	PK	PASS
	H	2485.50	41.30	30.22	4.85	27.40	43.33	54.00	AV	PASS
	V	2483.50	59.27	30.22	4.85	27.40	61.30	74.00	PK	PASS
	V	2485.50	41.20	30.22	4.85	27.40	43.23	54.00	AV	PASS
	V	2483.50	61.25	30.22	4.85	27.40	63.28	74.00	PK	PASS
	V	2485.50	41.37	30.22	4.85	27.40	43.40	54.00	AV	PASS
802.11n20	Low Channel 2412MHz									
	H	2390.00	59.29	30.22	4.85	27.59	61.51	74.00	PK	PASS
	H	2390.00	41.15	30.22	4.85	27.59	43.37	54.00	AV	PASS
	H	2400.00	61.69	30.22	4.85	27.58	63.90	74.00	PK	PASS
	H	2400.00	41.10	30.22	4.85	27.58	43.31	54.00	AV	PASS
	V	2390.00	59.16	30.22	4.85	27.59	61.38	74.00	PK	PASS
	V	2390.00	41.11	30.22	4.85	27.59	43.33	54.00	AV	PASS
	V	2400.00	61.53	30.22	4.85	27.58	63.74	74.00	PK	PASS
	V	2400.00	49.29	30.22	4.85	27.58	51.50	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	58.49	30.22	4.85	27.40	60.52	74.00	PK	PASS
	H	2485.50	40.42	30.22	4.85	27.40	42.45	54.00	AV	PASS
	H	2483.50	60.23	30.22	4.85	27.40	62.26	74.00	PK	PASS
	H	2485.50	40.30	30.22	4.85	27.40	42.33	54.00	AV	PASS
	V	2483.50	58.52	30.22	4.85	27.40	60.55	74.00	PK	PASS
	V	2485.50	40.27	30.22	4.85	27.40	42.30	54.00	AV	PASS
	V	2483.50	60.75	30.22	4.85	27.40	62.78	74.00	PK	PASS

802.11n40	V	2485.50	40.10	30.22	4.85	27.40	42.13	54.00	AV	PASS
	LowChannel 2422MHz									
	H	2390.00	59.61	30.22	4.85	27.59	61.83	74.00	PK	PASS
	H	2390.00	41.49	30.22	4.85	27.59	43.71	54.00	AV	PASS
	H	2400.00	61.81	30.22	4.85	27.58	64.02	74.00	PK	PASS
	H	2400.00	41.45	30.22	4.85	27.58	43.66	54.00	AV	PASS
	V	2390.00	59.42	30.22	4.85	27.59	61.64	74.00	PK	PASS
	V	2390.00	41.51	30.22	4.85	27.59	43.73	54.00	AV	PASS
	V	2400.00	61.57	30.22	4.85	27.58	63.78	74.00	PK	PASS
	V	2400.00	41.43	30.22	4.85	27.58	43.64	54.00	AV	PASS
	High Channel 2452MHz									
	H	2483.50	58.92	30.22	4.85	27.40	60.95	74.00	PK	PASS
	H	2485.50	40.85	30.22	4.85	27.40	42.88	54.00	AV	PASS
	H	2483.50	60.42	30.22	4.85	27.40	62.45	74.00	PK	PASS
	H	2485.50	40.73	30.22	4.85	27.40	42.76	54.00	AV	PASS
	V	2483.50	58.85	30.22	4.85	27.40	60.88	74.00	PK	PASS
	V	2485.50	40.63	30.22	4.85	27.40	42.66	54.00	AV	PASS
	V	2483.50	61.20	30.22	4.85	27.40	63.23	74.00	PK	PASS
	V	2485.50	48.26	30.22	4.85	27.40	50.29	74.00	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

6.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT


Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz

Test CH	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	17.244	16.452	15.576	12.714	30.00	Pass
Middle	17.358	16.109	15.148	12.466		
Highest	17.176	16.314	15.267	12.535		

	Frequency	Output Power	Antenna gain	EIRP
	(MHz)	(dBm)	(dBi)	(dBm)
802.11b	Lowest	17.244	2.0	19.244
	Middle	17.358	2.0	19.358
	Highest	17.176	2.0	19.176
802.11g	Lowest	16.452	2.0	18.452
	Middle	16.109	2.0	18.109
	Highest	16.314	2.0	18.314
802.11n20	Lowest	15.576	2.0	17.576
	Middle	15.148	2.0	17.148
	Highest	15.267	2.0	17.267
802.11n40	Lowest	12.714	2.0	14.714
	Middle	12.466	2.0	14.466
	Highest	12.535	2.0	14.535


Duty Cyclcy:

802.11b




Ton	Tp	Duty cyclcy(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

802.11g




Ton	Tp	Duty cyclcy(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

802.11n20



Ton	Tp	Duty cycly(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

802.11n40



Ton	Tp	Duty cycly(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

7. TEST SETUP PHOTO

Reference to the appendix I for details.

8. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****