



RADIO TEST REPORT

Report No.: STS2108163W20

Issued for

SHENZHEN PUDU TECHNOLOGY CO., LTD.

Room 501, Building A, Block 1, Phase 1, Shenzhen
International Inno Valley, Dashi 1st Road, Nanshan District,
Shenzhen, China

Product Name:	FlashBot
Brand Name:	PUDU
Model Name:	FBBDR1
Series Model:	N/A
FCC ID:	2AXDW-FBBDR1
Test Standard:	FCC Part 22H and 24E, 27

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.



**TEST RESULT CERTIFICATION**

Applicant's Name: SHENZHEN PUDU TECHNOLOGY CO., LTD.
Address.....: Room 501, Building A, Block 1, Phase 1, Shenzhen International Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China
Manufacturer's Name: SHENZHEN PUDU TECHNOLOGY CO., LTD.
Address.....: Room 501, Building A, Block 1, Phase 1, Shenzhen International Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China

Product Description

Product Name: FlashBot
Brand Name: PUDU
Model Name.....: FBBDR1
Series Model: N/A
Test Standards: FCC Part 22H and 24E, 27
Test Procedure: KDB 971168 D01 v03r01, ANSI C63.26(2015)

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document..

Date of Test.....:

Date of receipt of test item: 25 Aug. 2021
Date (s) of performance of tests : 25 Aug. 2021 ~ 22 Sept. 2021
Date of Issue: 22 Sept. 2021
Test Result: Pass

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





Table of Contents	Page
1 INTRODUCTION	6
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 PRODUCT INFORMATION	7
3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
4 MEASUREMENT INSTRUMENTS	9
5 TEST ITEMS	10
5.1 CONDUCTED OUTPUT POWER	10
5.2 PEAK TO AVERAGE RATIO	11
5.3 TRANSMITTER RADIATED POWER (EIRP/ERP)	12
5.4 OCCUPIED BANDWIDTH	13
5.5 FREQUENCY STABILITY	14
5.6 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	15
5.7 BAND EDGE	16
5.8 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	17
APPENDIX A.TESTRESULT	19
A1. CONDUCTED OUTPUT POWER	19
A2. PEAK-TO-AVERAGE RADIO	22
A3. TRANSMITTER RADIATED POWER (EIRP/ERP)	29
A4. OCCUPIED BANDWIDTH (99% OCCUPIED BANDWIDTH/26DB BANDWIDTH)	31
A5. FREQUENCY STABILITY	38
A6. SPURIOUS EMISSIONS AT ANTENNA TERMINALS	41
A7. BAND EDGE	47
A8. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	52
APPENDIX-PHOTOS OF TEST SETUP	61

**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	22 Sept. 2021	STS2108163W20	ALL	Initial Issue





SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

The radiated emission testing was performed according to the procedures of KDB 971168 D01 v03r01 and ANSI C63.26(2015)

FCC Rules	Test Description	Test Limit	Test Result	Reference
2.1046	Conducted Output Power	Reporting Only	PASS	
22.913d 24.232d	Peak-to-Average Ratio	< 13 dB	PASS	
2.1046 22.913 24.232 27.50	Effective Radiated Power/Equivalent Isotropic Radiated Power	< 7 Watts max. ERP(Part 22) < 2 Watts max. EIRP(Part 24) <1 Watts max. EIRP(Part 27)	PASS	
2.1049 22.917 24.238 27.53	Occupied Bandwidth	Reporting Only	PASS	
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24) Emission must remain in band (Part 27)	PASS	
2.1051 22.917 24.238 27.53	Spurious Emission at Antenna Terminals	< 43+10log10(P[Watts])	PASS	
2.1053 22.917 24.238 27.53	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	
2.1051 22.917 24.238 27.53	Band Edge	< 43+10log10(P[Watts])	PASS	



1 INTRODUCTION

1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated >6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$



2 PRODUCT INFORMATION

Product Name	FlashBot
Trade Name	PUDU
Model Name	FBBDR1
Series Model	N/A
Model Difference	N/A
Tx Frequency:	WCDMA: Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
Rx Frequency:	WCDMA: Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
Max RF Output Power:	WCDMA 850:24.50dBm, WCDMA 1900:24.71dBm WCDMA 1700:23.19dBm
Type of Emission:	WCDMA850: 4M13F9W WCDMA1900: 4M16F9W WCDMA1700: 4M13F9W
Modulation Characteristics:	WCDMA: QPSK; HSDPA:QPSK/16QAM; HSUPA:BPSK
SIM Card:	Only support single SIM Card.
Antenna:	FPC
Antenna gain:	WCDMA 850: 1.94dBi, WCDMA1900: 2.1dBi, WCDMA1700: 1.4dBi
Battery parameter:	Rated Voltage: 25.41V Charge Limit Voltage:29.4V Capacity: 15300mAh
Input:	DC 29.4V, 3.5A
GPRS/EDGE Class:	Multi-Class12
Extreme Vol. Limits:	DC 22.87V~ DC 27.95V(Normal: DC 25.41V)
Extreme Temp. Tolerance:	-30℃ to +50℃
Hardware version number:	V3
Software version number:	V8.1.0.12
Note: 1. The High Voltage 27.95V and Low Voltage 22.87V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage. 2. The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.	



3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 and ANSI C63.26 2015 Power Meas. License Digital Systems with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

	TEST MODES	
	RADIATED TCS	CONDUCTED TCS
BAND		
WCDMA BAND V	RMC 12.2KBPS LINK	RMC 12.2KBPS LINK
WCDMA BAND II	RMC 12.2KBPS LINK	RMC 12.2KBPS LINK
WCDMA BAND IV	RMC 12.2KBPS LINK	RMC 12.2KBPS LINK



4 MEASUREMENT INSTRUMENTS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
Signal Analyzer	R&S	FSV 40-N	101823	2020.10.10	2021.10.09
Signal Generator	Agilent	83752A	3610A02740	2020.10.10	2021.10.09
Wireless Communications Test Set	R&S	CMW 500	133884	2021.03.04	2022.03.03
Bilog Antenna	TESEQ	CBL6111D	34678	2020.10.12	2022.10.11
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2019.10.15	2021.10.14
Bilog Antenna	TESEQ	CBL6111D	45873	2020.10.12	2022.10.11
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1343	2020.10.12	2022.10.11
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2020.10.12	2022.10.11
Pre-Amplifier (0.1M-3GHz)	EM	EM330	060665	2020.10.12	2021.10.11
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2020.10.12	2021.10.11
Pre-Amplifier (18G-40GHz)	SKET	LNPA-1840-50	SK2018101801	2020.10.10	2021.10.09
Turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Test SW	BALUN	BL410-E/18.905			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Universal Radio communication tester	R&S	CMU200	119907	2020.10.12	2021.10.11
Wireless Communications Test Set	R&S	CMW 500	133884	2021.03.04	2022.03.03
Signal Analyzer	Agilent	N9020A	MY52440124	2021.03.04	2022.03.03
Temperature & Humidity test chamber	Safety test	AG80L	171200018	2021.03.04	2022.03.03
Programmable power supply	Agilent	E3642A	MY40002025	2020.10.12	2021.10.11
Temperature & Humidity	SW-108	SuWei	N/A	2021.03.04	2022.03.03
Test SW	FARAD	LZ-RF /LzRf-3A3			

Equipment with a calibration date of "NCR" shown in this list was not used to make direct calibrated measurements.

5 TEST ITEMS

5.1 CONDUCTED OUTPUT POWER

TEST OVERVIEW

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

TEST PROCEDURES

1. The transmitter output port was connected to the system simulator.
2. Set eut at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

TEST SETUP



TEST RESULT

Note: Test data See Appendix 1.

5.2 PEAK TO AVERAGE RATIO


TEST OVERVIEW

According to §24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 db.

TEST PROCEDURES

1. The testing follows FCC KDB 971168 v03r01 section.
2. The EUT was connected to the peak and av system simulator & spectrum analyzer.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Set the test probe and measure average power of the spectrum analysis.

TEST SETUP



TEST RESULT

Note: Test data See Appendix 2.



5.3 TRANSMITTER RADIATED POWER (EIRP/ERP)

TEST OVERVIEW

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI C63.26 2015 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

TEST PROCEDURE

1. The testing follows FCC KDB 971168 Section 5.8 and ANSI C63.26-2015 Section 5.2.
2. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.
3. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
4. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
5. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a nonradiating cable. The absolute levels of the spurious emissions were measured by the substitution.
6. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to ANSI C63.26-2015. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna.
 $EIRP = S.G \text{ Level} + \text{Gain} - \text{Cable loss}$; $ERP = S.G \text{ Level} + \text{Gain} - \text{Cable loss} - 2.15$.

TEST RESULT

Note: Test data See Appendix 3.

5.4 OCCUPIED BANDWIDTH

TEST OVERVIEW

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.


The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

All modes of operation were investigated and the worst case configuration results are reported in this section.

TEST PROCEDURE

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

TEST SETUP



TEST RESULT

Note: Test data See Appendix 4.

5.5 FREQUENCY STABILITY

TEST OVERVIEW

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26 2015. The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

TEST PROCEDURE


Temperature Variation

1. The testing follows FCC KDB 971168 D01 section 9.0
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

Voltage Variation

1. The testing follows FCC KDB 971168 D01 Section 9.0.
2. The EUT was placed in a temperature chamber at $25 \pm 5^\circ \text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

TEST SETUP



TEST RESULT

Note: Test data See Appendix 5.

5.6 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

TEST OVERVIEW

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

TEST PROCEDURE

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0. and ANSI C63.26-2015-Section 5.5
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$

TEST SETUP



TEST RESULT

Note: Test data See Appendix 6.

5.7 BAND EDGE

OVERVIEW

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.


The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P[\text{Watts}])$, where P is the transmitter power in Watts.

TEST PROCEDURE

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0. and ANSI C63.26-2015-Section 5.7
2. Start and stop frequency were set such that the band edge would be placed in the center of the Plot.
3. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
4. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
5. The band edges of low and high channels for the highest RF powers were measured.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

TEST SETUP



TEST RESULT

Note: Test data See Appendix 7.



5.8 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

TEST OVERVIEW

Radiated spurious emissions measurements are performed using the substitution method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power and at the appropriate frequencies.


It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

TEST PROCEDURE


1. The testing FCC KDB 971168 D01 Section 5.8 and ANSI C63.26-2015-Section 5.5.
2. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $> 2 \times$ span/RBW
6. Detector = Peak
7. Trace mode = max hold
8. The trace was allowed to stabilize
9. Effective Isotropic Spurious Radiation was measured by substitution method according to TIA/EIA-603-E. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna.
 $P_{Mea} = S.G \text{ Level} + \text{Ant-Cable loss}$; $\text{Margin} = P_{Mea} - \text{Limit}$.

TEST SETUP

For radiated test from 30MHz to 1GHz



For radiated test from above 1GHz



TEST RESULT

Note: Test data See Appendix 8.



APPENDIX A.TESTRESULT
A1. CONDUCTED OUTPUT POWER
UMTS BAND V

UMTS BAND 5		
Mode	Frequency(MHz)	AVG Power
WCDMA 850 RMC	826.4	24.27
	836.6	24.28
	846.6	24.50
HSDPA Subtest 1	826.4	23.99
	836.6	24.20
	846.6	23.89
HSDPA Subtest 2	826.4	23.55
	836.6	23.71
	846.6	23.40
HSDPA Subtest 3	826.4	23.16
	836.6	23.24
	846.6	23.00
HSDPA Subtest 4	826.4	22.67
	836.6	22.88
	846.6	22.62
HSUPA Subtest 1	826.4	23.52
	836.6	23.98
	846.6	23.41
HSUPA Subtest 2	826.4	22.54
	836.6	23.05
	846.6	22.42
HSUPA Subtest 3	826.4	22.52
	836.6	22.60
	846.6	22.11
HSUPA Subtest 4	826.4	22.11
	836.6	22.12
	846.6	21.81
HSUPA Subtest 5	826.4	20.70
	836.6	20.69
	846.6	20.38



UMTS BAND II

UMTS BAND 2		
Mode	Frequency(MHz)	AVG Power
WCDMA 1900 RMC	1852.4	24.37
	1880	24.41
	1907.6	24.71
HSDPA Subtest 1	1852.4	24.02
	1880	24.03
	1907.6	24.25
HSDPA Subtest 2	1852.4	23.60
	1880	23.61
	1907.6	23.77
HSDPA Subtest 3	1852.4	23.29
	1880	23.12
	1907.6	23.32
HSDPA Subtest 4	1852.4	22.98
	1880	22.63
	1907.6	22.91
HSUPA Subtest 1	1852.4	23.58
	1880	23.68
	1907.6	24.04
HSUPA Subtest 2	1852.4	22.60
	1880	22.75
	1907.6	23.06
HSUPA Subtest 3	1852.4	22.48
	1880	22.27
	1907.6	22.59
HSUPA Subtest 4	1852.4	22.04
	1880	21.90
	1907.6	22.16
HSUPA Subtest 5	1852.4	20.61
	1880	20.44
	1907.6	20.73



UMTS BAND IV

UMTS BAND 4		
Mode	Frequency(MHz)	AVG Power
WCDMA 1700 RMC	1712.6	23.19
	1740	22.32
	1752.4	23.04
HSDPA Subtest 1	1712.6	23.00
	1740	22.34
	1752.4	23.02
HSDPA Subtest 2	1712.6	22.55
	1740	21.91
	1752.4	22.54
HSDPA Subtest 3	1712.6	22.11
	1740	21.46
	1752.4	22.20
HSDPA Subtest 4	1712.6	21.73
	1740	20.96
	1752.4	21.84
HSUPA Subtest 1	1712.6	22.87
	1740	22.10
	1752.4	22.73
HSUPA Subtest 2	1712.6	21.95
	1740	21.17
	1752.4	21.82
HSUPA Subtest 3	1712.6	21.93
	1740	20.76
	1752.4	21.35
HSUPA Subtest 4	1712.6	21.57
	1740	20.30
	1752.4	20.89
HSUPA Subtest 5	1712.6	20.15
	1740	18.83
	1752.4	19.42




A2. PEAK-TO-AVERAGE RADIO


UMTS Band 2		
Mode	Frequency (MHz)	PAR
WCDMA 1900 RMC	1852.4	3.06
	1880	3.03
	1907.6	2.92
HSDPA 1900	1852.4	3.26
	1880	3.41
	1907.6	3.24
HSUPA 1900	1852.4	3.39
	1880	3.35
	1907.6	3.44

UMTS Band 5		
Mode	Frequency (MHz)	PAR
WCDMA 850 RMC	826.4	2.89
	836.6	2.96
	846.6	2.95
HSDPA 850	826.4	3.15
	836.6	3.30
	846.6	3.22
HSUPA 850	826.4	3.29
	836.6	3.35
	846.6	3.11


UMTS Band 4		
Mode	Frequency (MHz)	PAR
WCDMA 1700 RMC	1712.6	2.85
	1740	2.95
	1752.4	2.82
HSDPA 1700	1712.6	3.08
	1740	3.04
	1752.4	3.10
HSUPA 1700	1712.6	3.22
	1740	3.02
	1752.4	3.03




WCDMA Band 2_Low




WCDMA Band 2_Middle



WCDMA Band 2_High




HSDPA Band 2_Low




HSDPA Band 2_Middle




HSDPA Band 2_High




HSUPA Band 2_Low




HSUPA Band 2_Middle




HSUPA Band 2_High



WCDMA Band 4_Low



WCDMA Band 4_Middle



WCDMA Band 4_High




HSDPA Band 4_Low




HSDPA Band 4_Middle




HSDPA Band 4_High




HSUPA Band 4_Low




HSUPA Band 4_Middle



HSUPA Band 4_High




WCDMA Band 5_Low



WCDMA Band 5_Middle



WCDMA Band 5_High




HSDPA Band 5_Low




HSDPA Band 5_Middle




HSDPA Band 5_High



HSUPA Band 5_Low



HSUPA Band 5_Middle



HSUPA Band 5_High



A3. TRANSMITTER RADIATED POWER (EIRP/ERP)

Note: Test is divided into three directions, X/Y/Z. X pattern for the worst

Radiated Power (EIRP) for WCDMA Band 2							
Mode	Frequency	Result					Conclusion
		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
WCDMA	1852.4	13.99	2.41	10.35	21.93	Horizontal	Pass
	1852.4	15.75	2.41	10.35	23.69	Vertical	Pass
	1880	14.08	2.42	10.35	22.01	Horizontal	Pass
	1880	15.97	2.42	10.35	23.90	Vertical	Pass
	1907.4	14.45	2.43	10.35	22.37	Horizontal	Pass
	1907.4	16.24	2.43	10.35	24.16	Vertical	Pass
HSUPA	1852.4	13.76	2.41	10.35	21.70	Horizontal	Pass
	1852.4	15.46	2.41	10.35	23.40	Vertical	Pass
	1880	13.44	2.42	10.35	21.37	Horizontal	Pass
	1880	15.31	2.42	10.35	23.24	Vertical	Pass
	1907.4	13.79	2.43	10.35	21.71	Horizontal	Pass
	1907.4	15.76	2.43	10.35	23.68	Vertical	Pass
HSDPA	1852.4	13.39	2.41	10.35	21.33	Horizontal	Pass
	1852.4	15.13	2.41	10.35	23.07	Vertical	Pass
	1880	13	2.42	10.35	20.93	Horizontal	Pass
	1880	14.95	2.42	10.35	22.88	Vertical	Pass
	1907.4	13.37	2.43	10.35	21.29	Horizontal	Pass
	1907.4	15.35	2.43	10.35	23.27	Vertical	Pass
Limit	EIRP<2W=33dBm						

Radiated Power (ERP) for WCDMA Band 5								
Mode	Frequency	Result						Conclusion
		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
WCDMA	826.4	17.99	0.44	6.5	2.15	21.90	Horizontal	Pass
	826.4	19.78	0.44	6.5	2.15	23.69	Vertical	Pass
	836.6	17.87	0.45	6.5	2.15	21.77	Horizontal	Pass
	836.6	19.86	0.45	6.5	2.15	23.76	Vertical	Pass
	846.4	18.09	0.46	6.5	2.15	21.98	Horizontal	Pass
	846.4	19.92	0.46	6.5	2.15	23.81	Vertical	Pass
HSUPA	826.4	17.52	0.44	6.5	2.15	21.43	Horizontal	Pass
	826.4	19.37	0.44	6.5	2.15	23.28	Vertical	Pass
	836.6	17.90	0.45	6.5	2.15	21.80	Horizontal	Pass
	836.6	19.65	0.45	6.5	2.15	23.55	Vertical	Pass
	846.4	17.43	0.46	6.5	2.15	21.32	Horizontal	Pass
	846.4	19.32	0.46	6.5	2.15	23.21	Vertical	Pass
HSDPA	826.4	17.17	0.44	6.5	2.15	21.08	Horizontal	Pass
	826.4	18.98	0.44	6.5	2.15	22.89	Vertical	Pass
	836.6	17.73	0.45	6.5	2.15	21.63	Horizontal	Pass
	836.6	19.48	0.45	6.5	2.15	23.38	Vertical	Pass
	846.4	17.06	0.46	6.5	2.15	20.95	Horizontal	Pass
	846.4	18.80	0.46	6.5	2.15	22.69	Vertical	Pass
Limit	ERP<7W=38.45dBm							



Radiated Power (EIRP) for WCDMA Band 4							
Mode	Frequency	Result					Conclusion
		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
WCDMA	1712.6	12.64	2.07	10.13	20.70	Horizontal	Pass
	1712.6	14.46	2.07	10.13	22.52	Vertical	Pass
	1740	11.99	2.08	10.13	20.04	Horizontal	Pass
	1740	13.69	2.08	10.13	21.74	Vertical	Pass
	1752.4	12.33	2.09	10.13	20.37	Horizontal	Pass
	1752.4	14.32	2.09	10.13	22.36	Vertical	Pass
HSUPA	1712.6	12.54	2.07	10.13	20.60	Horizontal	Pass
	1712.6	14.34	2.07	10.13	22.40	Vertical	Pass
	1740	11.97	2.08	10.13	20.02	Horizontal	Pass
	1740	13.79	2.08	10.13	21.84	Vertical	Pass
	1752.4	12.33	2.09	10.13	20.37	Horizontal	Pass
	1752.4	14.19	2.09	10.13	22.23	Vertical	Pass
HSDPA	1712.6	12.31	2.07	10.13	20.37	Horizontal	Pass
	1712.6	14.18	2.07	10.13	22.24	Vertical	Pass
	1740	11.44	2.08	10.13	19.49	Horizontal	Pass
	1740	13.42	2.08	10.13	21.47	Vertical	Pass
	1752.4	11.96	2.09	10.13	20.00	Horizontal	Pass
	1752.4	13.94	2.09	10.13	21.98	Vertical	Pass
Limit	EIRP<1W=30dBm						




A4. OCCUPIED BANDWIDTH (99% OCCUPIED BANDWIDTH/26dB BANDWIDTH)

WCDMA Bandwidth [MHz]						
Mode	Lowest		Middle		Highest	
	99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
WCDMA 2	4.119	4.689	4.114	4.678	4.118	4.696
HSDPA 2	4.114	4.687	4.125	4.659	4.11	4.674
HSUPA 2	4.115	4.68	4.118	4.684	4.121	4.673


WCDMA Bandwidth [MHz]						
Mode	Lowest		Middle		Highest	
	99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
WCDMA 5	4.153	4.722	4.155	4.703	4.153	4.706
HSDPA 5	4.162	4.732	4.148	4.707	4.158	4.721
HSUPA 5	4.155	4.713	4.153	4.726	4.148	4.736

WCDMA Bandwidth [MHz]						
Mode	Lowest		Middle		Highest	
	99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
WCDMA 4	4.1273	4.7	4.128	4.699	4.12	4.708
HSDPA 4	4.118	4.691	4.126	4.703	4.129	4.693
HSUPA 4	4.122	4.707	4.128	4.689	4.122	4.69







WCDMA_Band 2_Low




WCDMA_Band 2_Middle




WCDMA_Band 2_High




HSDPA_Band 2_Low




HSDPA_Band 2_Middle




HSDPA_Band 2_High




HSUPA_Band 2_Low




HSUPA_Band 2_Middle




HSUPA_Band 2_High




WCDMA_Band 4_Low




WCDMA_Band 4_Middle




WCDMA_Band 4_High




HSDPA_Band 4_Low




HSDPA_Band 4_Middle




HSDPA_Band 4_High




HSUPA_Band 4_Low




HSUPA_Band 4_Middle




HSUPA_Band 4_High




WCDMA_Band 5_Low




WCDMA_Band 5_Middle




WCDMA_Band 5_High




HSDPA_Band 5_Low




HSDPA_Band 5_Middle




HSDPA_Band 5_High



HSUPA_Band 5_Low



HSUPA_Band 5_Middle



HSUPA_Band 5_High



A5. FREQUENCY STABILITY

UMTS Band 2 /1880MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	32.64	0.017	Within Authorized Band	PASS
40		34.78	0.019		
30		30.08	0.016		
20		16.79	0.009		
10		33.05	0.018		
0		32.46	0.017		
-10		19.19	0.010		
-20		34.21	0.018		
-30		25.61	0.014		
20	Maximum Voltage	26.94	0.014		
20	BEP	20.70	0.011		

HSDPA Band 2 /1880MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	14.00	0.007	Within Authorized Band	PASS
40		13.11	0.007		
30		13.46	0.007		
20		34.09	0.018		
10		32.60	0.017		
0		35.74	0.019		
-10		30.32	0.016		
-20		22.16	0.012		
-30		30.26	0.016		
20	Maximum Voltage	23.97	0.013		
20	BEP	22.75	0.012		

HSUPA Band 2 /1880MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	24.13	0.013	Within Authorized Band	PASS
40		23.68	0.013		
30		34.28	0.018		
20		12.96	0.007		
10		26.65	0.014		
0		30.59	0.016		
-10		16.23	0.009		
-20		31.04	0.017		
-30		28.53	0.015		
20	Maximum Voltage	36.22	0.019		
20	BEP	33.10	0.018		



UMTS Band 5 / 836.6MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	26.65	0.032	2.5ppm	PASS
40		24.85	0.030		
30		29.40	0.035		
20		17.43	0.021		
10		12.37	0.015		
0		14.18	0.017		
-10		15.76	0.019		
-20		29.95	0.036		
-30		19.36	0.023		
20	Maximum Voltage	27.59	0.033		
20	BEP	22.50	0.027		

HSDPA Band 5 / 836.6MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)		(ppm)		
50	Normal Voltage	35.01	0.042	2.5ppm	PASS
40		17.44	0.021		
30		12.42	0.015		
20		34.04	0.041		
10		22.33	0.027		
0		30.30	0.036		
-10		15.66	0.019		
-20		31.73	0.038		
-30		13.90	0.017		
20	Maximum Voltage	13.66	0.016		
20	BEP	13.88	0.017		

HSUPA Band 5 / 836.6MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	21.08	0.025	2.5ppm	PASS
40		34.69	0.041		
30		28.06	0.034		
20		24.59	0.029		
10		17.08	0.020		
0		19.53	0.023		
-10		26.61	0.032		
-20		21.78	0.026		
-30		18.65	0.022		
20	Maximum Voltage	19.15	0.023		
20	BEP	13.46	0.016		



UMTS Band 4 /1740MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	30.64	0.016	Within Authorized Band	PASS
40		16.80	0.009		
30		34.09	0.018		
20		13.53	0.007		
10		28.85	0.015		
0		14.40	0.008		
-10		32.45	0.017		
-20		33.42	0.018		
-30		34.59	0.018		
20	Maximum Voltage	21.72	0.012		
20	BEP	16.31	0.009		


HSDPA Band 4 /1740MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	19.55	0.010	Within Authorized Band	PASS
40		19.66	0.010		
30		18.69	0.010		
20		36.31	0.019		
10		13.04	0.007		
0		32.59	0.017		
-10		13.71	0.007		
-20		35.35	0.019		
-30		19.92	0.011		
20	Maximum Voltage	22.17	0.012		
20	BEP	12.78	0.007		

HSUPA Band 4 /1740MHz					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	13.34	0.007	Within Authorized Band	PASS
40		21.75	0.012		
30		18.27	0.010		
20		20.87	0.011		
10		18.35	0.010		
0		34.86	0.019		
-10		27.52	0.015		
-20		27.70	0.015		
-30		34.73	0.018		
20	Maximum Voltage	21.09	0.011		
20	BEP	14.81	0.008		


1. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.




A6. SPURIOUS EMISSIONS AT ANTENNA TERMINALS




WCDMA_Band 2_Low




WCDMA_Band 2_Middle




WCDMA_Band 2_High



HSDPA_Band 2_Low



HSDPA_Band 2_Middle




HSDPA_Band 2_High




HSUPA_Band 2_Low




HSUPA_Band 2_Middle




HSUPA_Band 2_High




WCDMA Band 4 Low




WCDMA Band 4 Middle




WCDMA Band 4 High




HSDPA Band 4 Low



HSDPA_Band 4_Middle




HSDPA_Band 4_High




HSUPA_Band 4_Low




HSUPA_Band 4_Middle




HSUPA_Band 4_High




WCDMA_Band 5_Low



WCDMA_Band 5_Middle




WCDMA_Band 5_High




HSDPA_Band 5_Low




HSDPA_Band 5_Middle




HSDPA_Band 5_High



HSUPA Band 5 Low




HSUPA Band 5 Middle




HSUPA_Band 5_High



A7. BAND EDGE



WCDMA_Band 2_Low




WCDMA_Band 2_Low




WCDMA_Band 2_High




WCDMA_Band 2_High



HSDPA_Band 2_Low




HSDPA_Band 2_Low



HSDPA_Band 2_High




HSDPA_Band 2_High



HSUPA_Band 2_Low




HSUPA_Band 2_Low



HSUPA_Band 2_High




HSUPA_Band 2_High



WCDMA_Band 4_Low



WCDMA_Band 4_Low



WCDMA_Band 4_High



WCDMA_Band 4_High



HSDPA_Band 4_Low



HSDPA_Band 4_Low



HSDPA_Band 4_High



HSDPA_Band 4_High



HSUPA_Band 4_Low



HSUPA_Band 4_Low



HSUPA_Band 4_High



HSUPA_Band 4_High



WCDMA_Band 5_Low



WCDMA_Band 5_High



HSDPA_Band 5_Low



HSDPA_Band 5_High



HSUPA_Band 5_Low



HSUPA_Band 5_High



A8. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

Note: (1) Spurious emissions which are attenuated by more than 20dB below the permissible value for frequency below 1000MHz.

(2) Above 3.5GHz amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value

(3) Test is divided into three directions, X/Y/Z. X pattern for the worst.

WCDMA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.28	-41.40	9.40	4.75	-36.75	-13.00	-23.75	H
2479.70	-40.17	10.60	8.39	-37.96	-13.00	-24.96	H
3305.80	-32.30	12.00	11.79	-32.09	-13.00	-19.09	H
1652.40	-44.44	9.40	4.75	-39.79	-13.00	-26.79	V
2479.54	-43.98	10.60	8.39	-41.77	-13.00	-28.77	V
3305.64	-43.48	12.00	11.79	-43.27	-13.00	-30.27	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.87	-41.36	9.40	4.75	-36.71	-13.00	-23.71	H
2509.66	-39.77	10.60	8.39	-37.56	-13.00	-24.56	H
3346.40	-31.87	12.00	11.79	-31.66	-13.00	-18.66	H
1673.26	-44.00	9.40	4.75	-39.35	-13.00	-26.35	V
2509.55	-44.54	10.60	8.39	-42.33	-13.00	-29.33	V
3346.20	-43.30	12.00	11.79	-43.09	-13.00	-30.09	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1693.20	-41.13	9.40	4.75	-36.48	-13.00	-23.48	H
2539.55	-39.25	10.60	8.39	-37.04	-13.00	-24.04	H
3386.06	-31.83	12.00	11.79	-31.62	-13.00	-18.62	H
1693.37	-44.52	9.40	4.75	-39.87	-13.00	-26.87	V
2539.16	-45.24	10.60	8.39	-43.03	-13.00	-30.03	V
3386.30	-43.51	12.00	11.79	-43.30	-13.00	-30.30	V



HSUPA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.27	-40.40	9.40	4.75	-35.75	-13.00	-22.75	H
2479.66	-39.36	10.60	8.39	-37.15	-13.00	-24.15	H
3305.82	-31.76	12.00	11.79	-31.55	-13.00	-18.55	H
1652.24	-43.36	9.40	4.75	-38.71	-13.00	-25.71	V
2479.70	-45.13	10.60	8.39	-42.92	-13.00	-29.92	V
3305.74	-43.97	12.00	11.79	-43.76	-13.00	-30.76	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1673.09	-40.59	9.40	4.75	-35.94	-13.00	-22.94	H
2509.44	-39.91	10.60	8.39	-37.70	-13.00	-24.70	H
3346.34	-31.41	12.00	11.79	-31.20	-13.00	-18.20	H
1673.04	-43.21	9.40	4.75	-38.56	-13.00	-25.56	V
2509.77	-45.18	10.60	8.39	-42.97	-13.00	-29.97	V
3346.45	-43.29	12.00	11.79	-43.08	-13.00	-30.08	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1693.67	-40.45	9.40	4.75	-35.80	-13.00	-22.80	H
2539.53	-40.54	10.60	8.39	-38.33	-13.00	-25.33	H
3386.23	-32.17	12.00	11.79	-31.96	-13.00	-18.96	H
1693.52	-44.33	9.40	4.75	-39.68	-13.00	-26.68	V
2539.41	-44.87	10.60	8.39	-42.66	-13.00	-29.66	V
3386.28	-42.58	12.00	11.79	-42.37	-13.00	-29.37	V



HSDPA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.08	-40.93	9.40	4.75	-36.28	-13.00	-23.28	H
2479.51	-39.78	10.60	8.39	-37.57	-13.00	-24.57	H
3305.49	-32.31	12.00	11.79	-32.10	-13.00	-19.10	H
1652.31	-43.64	9.40	4.75	-38.99	-13.00	-25.99	V
2479.54	-45.00	10.60	8.39	-42.79	-13.00	-29.79	V
3305.50	-42.90	12.00	11.79	-42.69	-13.00	-29.69	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1673.20	-41.06	9.40	4.75	-36.41	-13.00	-23.41	H
2509.49	-40.02	10.60	8.39	-37.81	-13.00	-24.81	H
3346.36	-30.91	12.00	11.79	-30.70	-13.00	-17.70	H
1673.12	-44.63	9.40	4.75	-39.98	-13.00	-26.98	V
2509.54	-44.67	10.60	8.39	-42.46	-13.00	-29.46	V
3346.21	-43.34	12.00	11.79	-43.13	-13.00	-30.13	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1693.60	-41.46	9.40	4.75	-36.81	-13.00	-23.81	H
2539.36	-40.16	10.60	8.39	-37.95	-13.00	-24.95	H
3386.22	-32.16	12.00	11.79	-31.95	-13.00	-18.95	H
1693.58	-44.30	9.40	4.75	-39.65	-13.00	-26.65	V
2539.37	-44.45	10.60	8.39	-42.24	-13.00	-29.24	V
3385.86	-42.73	12.00	11.79	-42.52	-13.00	-29.52	V



WCDMA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3704.41	-33.72	12.60	12.93	-34.05	-13.00	-21.05	H
5557.52	-35.41	13.10	17.11	-39.42	-13.00	-26.42	H
7409.86	-32.77	11.50	22.20	-43.47	-13.00	-30.47	H
3704.12	-35.81	12.60	12.93	-36.14	-13.00	-23.14	V
5557.26	-35.03	13.10	17.11	-39.04	-13.00	-26.04	V
7409.61	-32.06	11.50	22.20	-42.76	-13.00	-29.76	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3760.05	-34.37	12.60	12.93	-34.70	-13.00	-21.70	H
5639.91	-34.43	13.10	17.11	-38.44	-13.00	-25.44	H
7520.23	-33.17	11.50	22.20	-43.87	-13.00	-30.87	H
3760.15	-35.48	12.60	12.93	-35.81	-13.00	-22.81	V
5640.32	-35.21	13.10	17.11	-39.22	-13.00	-26.22	V
7519.96	-32.84	11.50	22.20	-43.54	-13.00	-30.54	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3815.39	-33.92	12.60	12.93	-34.25	-13.00	-21.25	H
5722.31	-35.12	13.10	17.11	-39.13	-13.00	-26.13	H
7630.24	-33.50	11.50	22.20	-44.20	-13.00	-31.20	H
3815.69	-35.74	12.60	12.93	-36.07	-13.00	-23.07	V
5722.27	-35.01	13.10	17.11	-39.02	-13.00	-26.02	V
7630.10	-33.19	11.50	22.20	-43.89	-13.00	-30.89	V



HSUPA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3704.32	-33.77	12.60	12.93	-34.10	-13.00	-21.10	H
5557.37	-34.75	13.10	17.11	-38.76	-13.00	-25.76	H
7409.56	-32.62	11.50	22.20	-43.32	-13.00	-30.32	H
3704.17	-35.52	12.60	12.93	-35.85	-13.00	-22.85	V
5557.42	-34.77	13.10	17.11	-38.78	-13.00	-25.78	V
7409.78	-32.01	11.50	22.20	-42.71	-13.00	-29.71	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3760.13	-33.84	12.60	12.93	-34.17	-13.00	-21.17	H
5639.83	-35.09	13.10	17.11	-39.10	-13.00	-26.10	H
7519.94	-33.50	11.50	22.20	-44.20	-13.00	-31.20	H
3759.89	-36.01	12.60	12.93	-36.34	-13.00	-23.34	V
5640.29	-34.61	13.10	17.11	-38.62	-13.00	-25.62	V
7520.02	-32.42	11.50	22.20	-43.12	-13.00	-30.12	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3815.48	-33.64	12.60	12.93	-33.97	-13.00	-20.97	H
5722.09	-34.38	13.10	17.11	-38.39	-13.00	-25.39	H
7630.24	-32.88	11.50	22.20	-43.58	-13.00	-30.58	H
3815.62	-35.33	12.60	12.93	-35.66	-13.00	-22.66	V
5722.15	-33.88	13.10	17.11	-37.89	-13.00	-24.89	V
7630.22	-31.87	11.50	22.20	-42.57	-13.00	-29.57	V



HSDPA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3704.04	-34.78	12.60	12.93	-35.11	-13.00	-22.11	H
5557.33	-34.55	13.10	17.11	-38.56	-13.00	-25.56	H
7409.81	-33.26	11.50	22.20	-43.96	-13.00	-30.96	H
3704.03	-35.97	12.60	12.93	-36.30	-13.00	-23.30	V
5557.39	-34.76	13.10	17.11	-38.77	-13.00	-25.77	V
7409.75	-32.55	11.50	22.20	-43.25	-13.00	-30.25	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.83	-33.57	12.60	12.93	-33.90	-13.00	-20.90	H
5640.25	-34.12	13.10	17.11	-38.13	-13.00	-25.13	H
7520.20	-32.81	11.50	22.20	-43.51	-13.00	-30.51	H
3760.07	-35.39	12.60	12.93	-35.72	-13.00	-22.72	V
5640.32	-34.15	13.10	17.11	-38.16	-13.00	-25.16	V
7520.26	-32.78	11.50	22.20	-43.48	-13.00	-30.48	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3815.61	-34.41	12.60	12.93	-34.74	-13.00	-21.74	H
5722.42	-35.43	13.10	17.11	-39.44	-13.00	-26.44	H
7630.20	-33.33	11.50	22.20	-44.03	-13.00	-31.03	H
3815.43	-35.44	12.60	12.93	-35.77	-13.00	-22.77	V
5722.49	-35.00	13.10	17.11	-39.01	-13.00	-26.01	V
7629.98	-31.93	11.50	22.20	-42.63	-13.00	-29.63	V



WCDMA Band 4: (30-20000)MHz							
The Worst Test Results for Channel 1313/1712.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3424.92	-33.76	12.90	12.05	-32.91	-13.00	-19.91	H
5137.79	-34.02	12.80	16.27	-37.49	-13.00	-24.49	H
6849.94	-32.29	12.30	20.13	-40.12	-13.00	-27.12	H
3424.84	-34.83	12.90	12.05	-33.98	-13.00	-20.98	V
5137.51	-34.83	12.80	16.27	-38.30	-13.00	-25.30	V
6850.30	-31.91	12.30	20.13	-39.74	-13.00	-26.74	V
The Worst Test Results for Channel 1450/1740.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3479.56	-34.58	12.90	12.05	-33.73	-13.00	-20.73	H
5219.79	-34.58	12.80	16.27	-38.05	-13.00	-25.05	H
6959.63	-32.48	12.30	20.13	-40.31	-13.00	-27.31	H
3479.97	-35.60	12.90	12.05	-34.75	-13.00	-21.75	V
5219.62	-34.32	12.80	16.27	-37.79	-13.00	-24.79	V
6959.92	-32.60	12.30	20.13	-40.43	-13.00	-27.43	V
The Worst Test Results for Channel 1512/1752.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3504.44	-34.19	12.90	12.05	-33.34	-13.00	-20.34	H
5256.94	-34.17	12.80	16.27	-37.64	-13.00	-24.64	H
7009.13	-33.30	12.30	20.13	-41.13	-13.00	-28.13	H
3504.69	-34.71	12.90	12.05	-33.86	-13.00	-20.86	V
5257.14	-34.88	12.80	16.27	-38.35	-13.00	-25.35	V
7009.34	-32.61	12.30	20.13	-40.44	-13.00	-27.44	V



HSUPA Band 4: (30-20000)MHz							
The Worst Test Results for Channel 1313/1712.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3424.96	-34.36	12.90	12.05	-33.51	-13.00	-20.51	H
5137.73	-34.23	12.80	16.27	-37.70	-13.00	-24.70	H
6850.39	-32.64	12.30	20.13	-40.47	-13.00	-27.47	H
3424.80	-34.74	12.90	12.05	-33.89	-13.00	-20.89	V
5137.62	-35.12	12.80	16.27	-38.59	-13.00	-25.59	V
6849.95	-31.88	12.30	20.13	-39.71	-13.00	-26.71	V
The Worst Test Results for Channel 1450/1740.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3479.59	-34.24	12.90	12.05	-33.39	-13.00	-20.39	H
5219.71	-35.04	12.80	16.27	-38.51	-13.00	-25.51	H
6959.81	-32.32	12.30	20.13	-40.15	-13.00	-27.15	H
3479.76	-35.78	12.90	12.05	-34.93	-13.00	-21.93	V
5219.59	-34.10	12.80	16.27	-37.57	-13.00	-24.57	V
6959.98	-32.41	12.30	20.13	-40.24	-13.00	-27.24	V
The Worst Test Results for Channel 1512/1752.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3504.66	-33.97	12.90	12.05	-33.12	-13.00	-20.12	H
5256.87	-34.92	12.80	16.27	-38.39	-13.00	-25.39	H
7009.41	-33.53	12.30	20.13	-41.36	-13.00	-28.36	H
3504.78	-35.85	12.90	12.05	-35.00	-13.00	-22.00	V
5256.75	-34.21	12.80	16.27	-37.68	-13.00	-24.68	V
7009.35	-32.04	12.30	20.13	-39.87	-13.00	-26.87	V



HSDPA Band 4: (30-20000)MHz							
The Worst Test Results for Channel 1313/1712.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3424.88	-33.51	12.90	12.05	-32.66	-13.00	-19.66	H
5137.59	-34.99	12.80	16.27	-38.46	-13.00	-25.46	H
6849.94	-33.02	12.30	20.13	-40.85	-13.00	-27.85	H
3424.84	-35.15	12.90	12.05	-34.30	-13.00	-21.30	V
5137.78	-34.46	12.80	16.27	-37.93	-13.00	-24.93	V
6850.30	-31.76	12.30	20.13	-39.59	-13.00	-26.59	V
The Worst Test Results for Channel 1450/1740.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3479.88	-34.39	12.90	12.05	-33.54	-13.00	-20.54	H
5219.69	-34.70	12.80	16.27	-38.17	-13.00	-25.17	H
6959.68	-32.72	12.30	20.13	-40.55	-13.00	-27.55	H
3479.57	-35.89	12.90	12.05	-35.04	-13.00	-22.04	V
5219.64	-35.20	12.80	16.27	-38.67	-13.00	-25.67	V
6959.92	-31.86	12.30	20.13	-39.69	-13.00	-26.69	V
The Worst Test Results for Channel 1512/1752.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3504.33	-33.45	12.90	12.05	-32.60	-13.00	-19.60	H
5257.20	-34.94	12.80	16.27	-38.41	-13.00	-25.41	H
7009.23	-32.69	12.30	20.13	-40.52	-13.00	-27.52	H
3504.37	-35.33	12.90	12.05	-34.48	-13.00	-21.48	V
5257.12	-35.06	12.80	16.27	-38.53	-13.00	-25.53	V
7009.25	-33.09	12.30	20.13	-40.92	-13.00	-27.92	V



APPENDIX-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

*****END OF THE REPORT*****

