

RADIO TEST REPORT

FCC ID: 2AXDW-PD9

Product: PuduBot
Trade Mark: PUDU
Model No.: PD9
Family Model: PDH
Report No.: S21101800608001
Issue Date: Dec 16, 2021

Prepared for

SHENZHEN PUDU TECHNOLOGY CO., LTD.
Room 501, Building A, Block 1, Phase 1, Shenzhen International
Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China
518057

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website: <http://www.ntek.org.cn>

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	4
2	SUMMARY OF TEST RESULTS.....	5
3	FACILITIES AND ACCREDITATIONS	6
3.1	FACILITIES.....	6
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	6
3.3	MEASUREMENT UNCERTAINTY	6
4	GENERAL DESCRIPTION OF EUT	7
5	DESCRIPTION OF TEST MODES	10
6	SETUP OF EQUIPMENT UNDER TEST	12
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	12
6.2	SUPPORT EQUIPMENT.....	13
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	14
7	TEST REQUIREMENTS.....	16
7.1	CONDUCTED EMISSIONS TEST	16
7.1.1	Applicable Standard	16
7.1.2	Test Configuration	16
7.1.3	Test Procedure	16
7.1.4	Test Results	16
7.1.5	Test Results	17
7.2	RADIATED SPURIOUS EMISSION	21
7.2.1	Applicable Standard	21
7.2.2	Conformance Limit	21
7.2.3	Measuring Instruments	22
7.2.4	Test Configuration	22
7.2.5	Test Procedure	23
7.2.6	Test Results	24
7.3	NUMBER OF HOPPING CHANNEL	35
7.3.1	Applicable Standard	35
7.3.2	Conformance Limit	35
7.3.3	Measuring Instruments	35
7.3.4	Test Setup	35
7.3.5	Test Procedure	35
7.3.6	Test Results	35
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT	36
7.4.1	Applicable Standard	36
7.4.2	Conformance Limit	36
7.4.3	Measuring Instruments	36
7.4.4	Test Setup	36
7.4.5	Test Procedure	36
7.4.6	Test Results	36
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME)	37
7.5.1	Applicable Standard	37
7.5.2	Conformance Limit	37
7.5.3	Measuring Instruments	37
7.5.4	Test Setup	37
7.5.5	Test Procedure	37
7.5.6	Test Results	37
7.6	20DB BANDWIDTH TEST	38
7.6.1	Applicable Standard	38
7.6.2	Conformance Limit	38

7.6.3	Measuring Instruments	38
7.6.4	Test Setup	38
7.6.5	Test Procedure	38
7.6.6	Test Results	38
7.7	PEAK OUTPUT POWER	39
7.7.1	Applicable Standard	39
7.7.2	Conformance Limit	39
7.7.3	Measuring Instruments	39
7.7.4	Test Setup	39
7.7.5	Test Procedure	39
7.7.6	Test Results	39
7.8	CONDUCTED BAND EDGE MEASUREMENT	40
7.8.1	Applicable Standard	40
7.8.2	Conformance Limit	40
7.8.3	Measuring Instruments	40
7.8.4	Test Setup	40
7.8.5	Test Procedure	40
7.8.6	Test Results	40
7.9	SPURIOUS RF CONDUCTED EMISSION	41
7.9.1	Applicable Standard	41
7.9.2	Conformance Limit	41
7.9.3	Measuring Instruments	41
7.9.4	Test Setup	41
7.9.5	Test Procedure	41
7.9.6	Test Results	41
7.10	ANTENNA APPLICATION	42
7.10.1	Antenna Requirement	42
7.10.2	Result	42
7.11	FREQUENCY HOPPING SYSTEM (FHSS) EQUIPMENT REQUIREMENTS	43
8	TEST RESULTS	44
	MODULE 2:	44
8.1.1	DWELL TIME	44
8.1.2	MAXIMUM CONDUCTED OUTPUT POWER	49
8.1.3	OCCUPIED CHANNEL BANDWIDTH	54
8.1.4	CARRIER FREQUENCIES SEPARATION	64
8.1.5	NUMBER OF HOPPING CHANNEL	69
8.1.6	BAND EDGE	70
8.1.7	CONDUCTED RF SPURIOUS EMISSION	83
	MODULE 1:	93
8.1.8	DWELL TIME	93
8.1.9	MAXIMUM CONDUCTED OUTPUT POWER	98
8.1.10	OCCUPIED CHANNEL BANDWIDTH	103
8.1.11	CARRIER FREQUENCIES SEPARATION	113
8.1.12	NUMBER OF HOPPING CHANNEL	118
8.1.13	BAND EDGE	119
8.1.14	CONDUCTED RF SPURIOUS EMISSION	132

1 TEST RESULT CERTIFICATION

Applicant's name	SHENZHEN PUDU TECHNOLOGY CO., LTD.
Address	Room 501, Building A, Block 1, Phase 1, Shenzhen International Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China 518057
Manufacturer's Name	SHENZHEN PUDU TECHNOLOGY CO., LTD.
Address	Room 501, Building A, Block 1, Phase 1, Shenzhen International Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China 518057
Product description	
Product name	PuduBot
Model and/or type reference	PD9
Family Model	PDH

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	Complied


This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : Oct 25, 2021 ~ Dec 14, 2021

Testing Engineer : 
(Allen Liu)

Authorized Signatory : 
(Alex Li)

2 SUMMARY OF TEST RESULTS**FCC Part15 (15.247), Subpart C**

Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(1)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.

CAB identifier: CN0074

FCC- Accredited : Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(>6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^{\circ}\text{C}$
8	Humidity	$\pm 2\%$

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	PuduBot
Trade Mark	PUDU
FCC ID	2AXDW-PD9
Model No.	PD9
Family Model	PDH
Model Difference	All models are the same circuit and RF module, except the model name.
Module	1. ESP32 2. AP6398SV
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Bluetooth Version	BT V4.2
Number of Channels	79 Channels
Antenna Type	FPCB antenna
Antenna Gain	5.56dBi(Module 1) 5.41dBi(Module 2)
Power supply	☒ DC supply: Battery 1#: Model: 7S6P SDI 18650 26J DC 25.41V, 15.6Ah Battery 2#: Model: Pudu 7S5P 71NR19/66-5 DC 25.2V, 15.5Ah
	☒ Adapter supply: Adapter 1# : Model: HK120A-CF Input: 100-240V~50/60Hz 3.0A Max Output: 29.4V---8.0A Adapter 2# : Model: FY2903500 Input: 100-240V~50/60Hz 1.5A 150VA Output: 29.0V---3.5A 101.5W

HW Version	B03
SW Version	9.1.0.6

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Revision History

[illegible]

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for $\pi/4$ -DQPSK modulation; 3Mbps for 8-DPSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
...	...
39	2441
40	2442
...	...
77	2479
78	2480

Note: $f_c = 2402\text{MHz} + k \times 1\text{MHz}$ $k=0$ to 78

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission	
Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases	
Final Test Mode	Description
Mode 1	normal link mode
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

For Conducted Test Cases	
Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)
Mode 5	Hopping mode


Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

This EUT has three modules, module 2 supports Bluetooth, WIFI2.4G / 5G, module 2 has two antennas, Antenna 1 supports Bluetooth, WIFI2.4G / 5G, Antenna 2 supports WIFI2.4G / 5G. The module 1 only supports Bluetooth , WIFI 2.4G. The module 1 has only one antenna. module 3 only supports WCDMA/LTE. The module 3 has only one antenna. Antenna 4 supports WCDMA/LTE.

6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
AE-1	Adapter	N/A	HK120A-CF	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.2m
C-2	RF Cable	YES	NO	0.1m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.
- (4) During the battery power test, the battery is fully charged.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2021.04.27	2022.04.26	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2021.07.01	2022.06.30	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2021.07.01	2022.06.30	1 year
4	Test Receiver	R&S	ESPI7	101318	2021.04.27	2022.04.26	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2021.03.29	2022.03.28	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2021.03.29	2022.03.28	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2021.11.07	2022.11.06	1 year
9	Amplifier	EMC	EMC051835SE	980246	2021.07.01	2022.06.30	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2021.11.07	2022.11.06	1 year
11	Power Meter	DARE	RPR3006W	15I00041SN084	2021.07.01	2022.06.30	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2019.08.06	2022.08.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2019.08.06	2022.08.05	3 year
16	Filter	TRILTHIC	2400MHz	29	2021.07.01	2022.06.30	1 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2021.04.27	2022.04.26	1 year
2	LISN	R&S	ENV216	101313	2021.04.27	2022.04.26	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2021.04.27	2022.04.26	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard


According to FCC Part 15.207(a)

Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.2 Test Configuration



7.1.3 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.4 Test Results

Pass


7.1.5 Test Results

EUT:	PuduBot	Model Name :	PD9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 29.4V from Adapter AC 120V/60Hz	Test Mode:	Mode 1-Module 2

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1620	45.81	9.71	55.52	65.36	-9.84	QP
0.1620	35.94	9.71	45.65	55.36	-9.71	AVG
0.2300	39.15	9.63	48.78	62.45	-13.67	QP
0.2300	28.62	9.63	38.25	52.45	-14.20	AVG
0.4697	26.00	9.64	35.64	56.52	-20.88	QP
0.4697	16.72	9.64	26.36	46.52	-20.16	AVG
1.9818	24.15	9.76	33.91	56.00	-22.09	QP
1.9818	13.80	9.76	23.56	46.00	-22.44	AVG
5.8818	40.60	9.69	50.29	60.00	-9.71	QP
5.8818	30.33	9.69	40.02	50.00	-9.98	AVG
14.5777	34.91	9.82	44.73	60.00	-15.27	QP
14.5777	24.43	9.82	34.25	50.00	-15.75	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	PuduBot	Model Name :	PD9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 29.4V from Adapter AC 120V/60Hz	Test Mode:	Mode 1-Module 2

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	44.07	9.63	53.70	65.78	-12.08	QP
0.1539	33.73	9.63	43.36	55.78	-12.42	AVG
0.1900	41.89	9.63	51.52	64.03	-12.51	QP
0.1900	31.62	9.63	41.25	54.03	-12.78	AVG
0.2580	35.98	9.65	45.63	61.49	-15.86	QP
0.2580	25.49	9.65	35.14	51.49	-16.35	AVG
2.1739	25.58	9.67	35.25	56.00	-20.75	QP
2.1739	15.69	9.67	25.36	46.00	-20.64	AVG
5.7538	38.28	9.79	48.07	60.00	-11.93	QP
5.7538	28.42	9.79	38.21	50.00	-11.79	AVG
14.2538	35.51	9.74	45.25	60.00	-14.75	QP
14.2538	25.62	9.74	35.36	50.00	-14.64	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	PuduBot	Model Name :	PD9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 29.4V from Adapter AC 120V/60Hz	Test Mode:	Mode 1-Module 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1500	49.71	9.73	59.44	65.99	-6.55	QP
0.1500	27.12	9.73	36.85	55.99	-19.14	AVG
0.2060	44.11	9.63	53.74	63.36	-9.62	QP
0.2060	35.39	9.63	45.02	53.36	-8.34	AVG
0.3379	33.59	9.63	43.22	59.25	-16.03	QP
0.3379	26.02	9.63	35.65	49.25	-13.60	AVG
2.1060	22.27	9.75	32.02	56.00	-23.98	QP
2.1060	14.37	9.75	24.12	46.00	-21.88	AVG
5.6740	39.10	9.68	48.78	60.00	-11.22	QP
5.6740	25.24	9.68	34.92	50.00	-15.08	AVG
14.0580	39.63	9.81	49.44	60.00	-10.56	QP
14.0580	30.76	9.81	40.57	50.00	-9.43	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	PuduBot	Model Name :	PD9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 29.4V from Adapter AC 120V/60Hz	Test Mode:	Mode 1-Module 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1500	48.48	9.63	58.11	65.99	-7.88	QP
0.1500	26.46	9.63	36.09	55.99	-19.90	AVG
0.1740	47.48	9.63	57.11	64.76	-7.65	QP
0.1740	37.39	9.63	47.02	54.76	-7.74	AVG
0.2300	41.00	9.64	50.64	62.45	-11.81	QP
0.2300	30.61	9.64	40.25	52.45	-12.20	AVG
2.2340	23.24	9.67	32.91	56.00	-23.09	QP
2.2340	16.45	9.67	26.12	46.00	-19.88	AVG
5.6100	38.84	9.78	48.62	60.00	-11.38	QP
5.6100	24.84	9.78	34.62	50.00	-15.38	AVG
14.1580	38.34	9.75	48.09	60.00	-11.91	QP
14.1580	30.07	9.75	39.82	50.00	-10.18	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (μV/m)	300
0.490~1.705	24000/F(KHz)	20 log (μV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54


Remark : 1. Emission level in dBuV/m=20 log (μV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz:
Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz:
Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

■ Spurious Emission below 1GHz (30MHz to 1GHz)


All the modulation modes have been tested, and the worst result was report as below:

EUT:	PuduBot	Model Name :	PD9
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1- Module 2
Test Voltage :	DC 25.41V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	59.6492	19.45	11.48	30.93	40.00	-9.07	QP
V	109.7960	17.76	17.37	35.13	43.50	-8.37	QP
V	164.9073	11.85	17.96	29.81	43.50	-13.69	QP
V	219.8447	13.61	17.37	30.98	46.00	-15.02	QP
V	256.5210	11.36	21.44	32.80	46.00	-13.20	QP
V	350.4768	10.49	23.73	34.22	46.00	-11.78	QP

Remark:


Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	109.7960	12.68	17.37	30.05	43.50	-13.45	QP
H	167.8241	12.10	17.46	29.56	43.50	-13.94	QP
H	185.1379	12.26	16.69	28.95	43.50	-14.55	QP
H	264.7456	10.56	21.37	31.93	46.00	-14.07	QP
H	292.0581	12.73	21.50	34.23	46.00	-11.77	QP
H	345.5951	11.38	23.49	34.87	46.00	-11.13	QP

Remark:

Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit




EUT:	PuduBot	Model Name :	PD9
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1- Module 1
Test Voltage :	DC 25.41V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	109.7960	12.39	17.37	29.76	43.50	-13.74	QP
V	167.8242	12.45	17.46	29.91	43.50	-13.59	QP
V	184.4898	12.39	16.72	29.11	43.50	-14.39	QP
V	271.3245	11.71	21.46	33.17	46.00	-12.83	QP
V	290.0172	13.62	21.65	35.27	46.00	-10.73	QP
V	349.2500	14.55	23.69	38.24	46.00	-7.76	QP

Remark:


Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	60.2801	20.68	11.40	32.08	40.00	-7.92	QP
H	109.7960	20.44	17.37	37.81	43.50	-5.69	QP
H	164.9074	12.61	17.96	30.57	43.50	-12.93	QP
H	219.8448	13.50	17.37	30.87	46.00	-15.13	QP
H	263.8190	12.55	21.44	33.99	46.00	-12.01	QP
H	343.1800	11.78	23.36	35.14	46.00	-10.86	QP

Remark:

Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Module 2:

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(GFSK)--Above 1G									
4804.214	64.36	5.21	35.59	44.30	60.86	74.00	-13.14	Pk	Vertical
4804.214	41.47	5.21	35.59	44.30	37.97	54.00	-16.03	AV	Vertical
7206.265	60.01	6.48	36.27	44.60	58.16	74.00	-15.84	Pk	Vertical
7206.265	43.60	6.48	36.27	44.60	41.75	54.00	-12.25	AV	Vertical
4804.109	61.56	5.21	35.55	44.30	58.02	74.00	-15.98	Pk	Horizontal
4804.109	42.92	5.21	35.55	44.30	39.38	54.00	-14.62	AV	Horizontal
7206.224	63.29	6.48	36.27	44.52	61.52	74.00	-12.48	Pk	Horizontal
7206.224	47.75	6.48	36.27	44.52	45.98	54.00	-8.02	AV	Horizontal
Mid Channel (2441 MHz)(GFSK)--Above 1G									
4882.396	63.22	5.21	35.66	44.20	59.89	74.00	-14.11	Pk	Vertical
4882.396	42.53	5.21	35.66	44.20	39.20	54.00	-14.80	AV	Vertical
7323.241	60.04	7.10	36.50	44.43	59.21	74.00	-14.79	Pk	Vertical
7323.241	47.17	7.10	36.50	44.43	46.34	54.00	-7.66	AV	Vertical
4882.108	62.34	5.21	35.66	44.20	59.01	74.00	-14.99	Pk	Horizontal
4882.108	49.61	5.21	35.66	44.20	46.28	54.00	-7.72	AV	Horizontal
7323.132	61.71	7.10	36.50	44.43	60.88	74.00	-13.12	Pk	Horizontal
7323.132	41.92	7.10	36.50	44.43	41.09	54.00	-12.91	AV	Horizontal
High Channel (2480 MHz)(GFSK)-- Above 1G									
4960.397	66.34	5.21	35.52	44.21	62.86	74.00	-11.14	Pk	Vertical
4960.397	42.86	5.21	35.52	44.21	39.38	54.00	-14.62	AV	Vertical
7440.201	61.66	7.10	36.53	44.60	60.69	74.00	-13.31	Pk	Vertical
7440.201	44.72	7.10	36.53	44.60	43.75	54.00	-10.25	AV	Vertical
4960.225	68.41	5.21	35.52	44.21	64.93	74.00	-9.07	Pk	Horizontal
4960.225	47.13	5.21	35.52	44.21	43.65	54.00	-10.35	AV	Horizontal
7440.298	60.84	7.10	36.53	44.60	59.87	74.00	-14.13	Pk	Horizontal
7440.298	44.67	7.10	36.53	44.60	43.70	54.00	-10.30	AV	Horizontal

Note:

- (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
- (2)All other emissions more than 20dB below the limit.

Module 1:

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(GFSK)--Above 1G									
4804.214	64.39	5.21	35.59	44.30	60.89	74.00	-13.11	Pk	Vertical
4804.214	41.36	5.21	35.59	44.30	37.86	54.00	-16.14	AV	Vertical
7206.265	59.95	6.48	36.27	44.60	58.10	74.00	-15.90	Pk	Vertical
7206.265	45.17	6.48	36.27	44.60	43.32	54.00	-10.68	AV	Vertical
4804.109	61.94	5.21	35.55	44.30	58.40	74.00	-15.60	Pk	Horizontal
4804.109	44.07	5.21	35.55	44.30	40.53	54.00	-13.47	AV	Horizontal
7206.224	62.61	6.48	36.27	44.52	60.84	74.00	-13.16	Pk	Horizontal
7206.224	48.51	6.48	36.27	44.52	46.74	54.00	-7.26	AV	Horizontal
Mid Channel (2441 MHz)(GFSK)--Above 1G									
4882.396	64.15	5.21	35.66	44.20	60.82	74.00	-13.18	Pk	Vertical
4882.396	42.92	5.21	35.66	44.20	39.59	54.00	-14.41	AV	Vertical
7323.241	61.16	7.10	36.50	44.43	60.33	74.00	-13.67	Pk	Vertical
7323.241	46.67	7.10	36.50	44.43	45.84	54.00	-8.16	AV	Vertical
4882.108	60.96	5.21	35.66	44.20	57.63	74.00	-16.37	Pk	Horizontal
4882.108	48.79	5.21	35.66	44.20	45.46	54.00	-8.54	AV	Horizontal
7323.132	60.33	7.10	36.50	44.43	59.50	74.00	-14.50	Pk	Horizontal
7323.132	41.82	7.10	36.50	44.43	40.99	54.00	-13.01	AV	Horizontal
High Channel (2480 MHz)(GFSK)-- Above 1G									
4960.397	67.12	5.21	35.52	44.21	63.64	74.00	-10.36	Pk	Vertical
4960.397	43.18	5.21	35.52	44.21	39.70	54.00	-14.30	AV	Vertical
7440.201	61.62	7.10	36.53	44.60	60.65	74.00	-13.35	Pk	Vertical
7440.201	45.67	7.10	36.53	44.60	44.70	54.00	-9.30	AV	Vertical
4960.225	67.69	5.21	35.52	44.21	64.21	74.00	-9.79	Pk	Horizontal
4960.225	46.72	5.21	35.52	44.21	43.24	54.00	-10.76	AV	Horizontal
7440.298	61.61	7.10	36.53	44.60	60.64	74.00	-13.36	Pk	Horizontal
7440.298	44.58	7.10	36.53	44.60	43.61	54.00	-10.39	AV	Horizontal

Note:

- (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
- (2)All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Allen Liu

Module 2:

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
1Mbps(GFSK)-Non-hopping									
2310.00	57.32	2.97	27.80	43.80	44.29	74	-29.71	Pk	Horizontal
2310.00	44.98	2.97	27.80	43.80	31.95	54	-22.05	AV	Horizontal
2310.00	58.90	2.97	27.80	43.80	45.87	74	-28.13	Pk	Vertical
2310.00	43.68	2.97	27.80	43.80	30.65	54	-23.35	AV	Vertical
2390.00	57.85	3.14	27.21	43.80	44.40	74	-29.60	Pk	Vertical
2390.00	43.54	3.14	27.21	43.80	30.09	54	-23.91	AV	Vertical
2390.00	56.78	3.14	27.21	43.80	43.33	74	-30.67	Pk	Horizontal
2390.00	42.64	3.14	27.21	43.80	29.19	54	-24.81	AV	Horizontal
2483.50	59.12	3.58	27.70	44.00	46.40	74	-27.60	Pk	Vertical
2483.50	42.81	3.58	27.70	44.00	30.09	54	-23.91	AV	Vertical
2483.50	59.55	3.58	27.70	44.00	46.83	74	-27.17	Pk	Horizontal
2483.50	43.63	3.58	27.70	44.00	30.91	54	-23.09	AV	Horizontal
1Mbps(GFSK)-hopping									
2310.00	52.32	2.97	27.80	43.80	39.29	74.00	-34.71	Pk	Vertical
2310.00	42.31	2.97	27.80	43.80	29.28	54.00	-24.72	AV	Vertical
2310.00	52.65	2.97	27.80	43.80	39.62	74.00	-34.38	Pk	Horizontal
2310.00	41.05	2.97	27.80	43.80	28.02	54.00	-25.98	AV	Horizontal
2390.00	52.09	3.14	27.21	43.80	38.64	74.00	-35.36	Pk	Vertical
2390.00	44.37	3.14	27.21	43.80	30.92	54.00	-23.08	AV	Vertical
2390.00	50.78	3.14	27.21	43.80	37.33	74.00	-36.67	Pk	Horizontal
2390.00	43.88	3.14	27.21	43.80	30.43	54.00	-23.57	AV	Horizontal
2483.50	53.67	3.58	27.70	44.00	40.95	74.00	-33.05	Pk	Vertical
2483.50	40.18	3.58	27.70	44.00	27.46	54.00	-26.54	AV	Vertical
2483.50	52.62	3.58	27.70	44.00	39.90	74.00	-34.10	Pk	Horizontal
2483.50	41.54	3.58	27.70	44.00	28.82	54.00	-25.18	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

Module 1:

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preampl Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
1Mbps(GFSK)-Non-hopping									
2310.00	57.70	2.97	27.80	43.80	44.67	74	-29.33	Pk	Horizontal
2310.00	43.68	2.97	27.80	43.80	30.65	54	-23.35	AV	Horizontal
2310.00	60.02	2.97	27.80	43.80	46.99	74	-27.01	Pk	Vertical
2310.00	42.36	2.97	27.80	43.80	29.33	54	-24.67	AV	Vertical
2390.00	57.83	3.14	27.21	43.80	44.38	74	-29.62	Pk	Vertical
2390.00	42.94	3.14	27.21	43.80	29.49	54	-24.51	AV	Vertical
2390.00	56.81	3.14	27.21	43.80	43.36	74	-30.64	Pk	Horizontal
2390.00	43.78	3.14	27.21	43.80	30.33	54	-23.67	AV	Horizontal
2483.50	58.04	3.58	27.70	44.00	45.32	74	-28.68	Pk	Vertical
2483.50	42.19	3.58	27.70	44.00	29.47	54	-24.53	AV	Vertical
2483.50	59.74	3.58	27.70	44.00	47.02	74	-26.98	Pk	Horizontal
2483.50	42.17	3.58	27.70	44.00	29.45	54	-24.55	AV	Horizontal
1Mbps(GFSK)-hopping									
2310.00	51.98	2.97	27.80	43.80	38.95	74.00	-35.05	Pk	Vertical
2310.00	43.60	2.97	27.80	43.80	30.57	54.00	-23.43	AV	Vertical
2310.00	53.62	2.97	27.80	43.80	40.59	74.00	-33.41	Pk	Horizontal
2310.00	44.62	2.97	27.80	43.80	31.59	54.00	-22.41	AV	Horizontal
2390.00	53.82	3.14	27.21	43.80	40.37	74.00	-33.63	Pk	Vertical
2390.00	43.30	3.14	27.21	43.80	29.85	54.00	-24.15	AV	Vertical
2390.00	54.99	3.14	27.21	43.80	41.54	74.00	-32.46	Pk	Horizontal
2390.00	42.04	3.14	27.21	43.80	28.59	54.00	-25.41	AV	Horizontal
2483.50	51.72	3.58	27.70	44.00	39.00	74.00	-35.00	Pk	Vertical
2483.50	42.35	3.58	27.70	44.00	29.63	54.00	-24.37	AV	Vertical
2483.50	52.58	3.58	27.70	44.00	39.86	74.00	-34.14	Pk	Horizontal
2483.50	41.95	3.58	27.70	44.00	29.23	54.00	-24.77	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 3260MHz-18000MHz

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Allen Liu

Module 2:

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Reading Level	Cable Loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	61.57	4.04	29.57	44.70	50.48	74	-23.52	Pk	Vertical
3260	57.15	4.04	29.57	44.70	46.06	54	-7.94	AV	Vertical
3260	62.64	4.04	29.57	44.70	51.55	74	-22.45	Pk	Horizontal
3260	58.30	4.04	29.57	44.70	47.21	54	-6.79	AV	Horizontal
3332	65.36	4.26	29.87	44.40	55.09	74	-18.91	Pk	Vertical
3332	53.70	4.26	29.87	44.40	43.43	54	-10.57	AV	Vertical
3332	63.98	4.26	29.87	44.40	53.71	74	-20.29	Pk	Horizontal
3332	53.70	4.26	29.87	44.40	43.43	54	-10.57	AV	Horizontal
17797	44.81	10.99	43.95	43.50	56.25	74	-17.75	Pk	Vertical
17797	32.44	10.99	43.95	43.50	43.88	54	-10.12	AV	Vertical
17788	45.49	11.81	43.69	44.60	56.39	74	-17.61	Pk	Horizontal
17788	31.08	11.81	43.69	44.60	41.98	54	-12.02	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

Module 1:

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Reading Level	Cable Loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	61.90	4.04	29.57	44.70	50.81	74	-23.19	Pk	Vertical
3260	57.63	4.04	29.57	44.70	46.54	54	-7.46	AV	Vertical
3260	61.43	4.04	29.57	44.70	50.34	74	-23.66	Pk	Horizontal
3260	58.40	4.04	29.57	44.70	47.31	54	-6.69	AV	Horizontal
3332	65.93	4.26	29.87	44.40	55.66	74	-18.34	Pk	Vertical
3332	53.25	4.26	29.87	44.40	42.98	54	-11.02	AV	Vertical
3332	64.10	4.26	29.87	44.40	53.83	74	-20.17	Pk	Horizontal
3332	52.99	4.26	29.87	44.40	42.72	54	-11.28	AV	Horizontal
17797	43.74	10.99	43.95	43.50	55.18	74	-18.82	Pk	Vertical
17797	32.31	10.99	43.95	43.50	43.75	54	-10.25	AV	Vertical
17788	45.05	11.81	43.69	44.60	55.95	74	-18.05	Pk	Horizontal
17788	31.42	11.81	43.69	44.60	42.32	54	-11.68	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

7.3 NUMBER OF HOPPING CHANNEL

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and ANSI C63.10-2013

7.3.2 Conformance Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.3.6 Test Results

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 5(1Mbps)	Test By:	Allen Liu

Test data reference attachment.

7.4 HOPPING CHANNEL SEPARATION MEASUREMENT

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.4.2 Conformance Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Measurement Bandwidth or Channel Separation

RBW: Start with the RBW set to approximately 3% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.4.6 Test Results

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

7.5.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and ANSI C63.10-2013

7.5.2 Conformance Limit

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.4

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW $\geq$ 1MHz

VBW $\geq$ RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Measure the maximum time duration of one single pulse.

Set the EUT for DH5, DH3 and DH1 packet transmitting.

Measure the maximum time duration of one single pulse.

7.5.6 Test Results

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.6 20DB BANDWIDTH TEST

7.6.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.6.2 Conformance Limit

No limit requirement.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.6.6 Test Results

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.7 PEAK OUTPUT POWER

7.7.1 Applicable Standard

According to FCC Part 15.247(b)(1) and ANSI C63.10-2013

7.7.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.5.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.7.6 Test Results

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.6.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

7.8.6 Test Results

EUT:	PuduBot	Model No.:	PD9
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2 /Mode4/ Mode 5	Test By:	Allen Liu

Test data reference attachment.

7.9 SPURIOUS RF CONDUCTED EMISSION

7.9.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013.

7.9.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.4 Test Setup

Please refer to Section 6.1 of this test report.

7.9.5 Test Procedure

Establish an emission level by using the following procedure:

- Set the center frequency and span to encompass frequency range to be measured.
 - Set the RBW = 100 kHz.
 - Set the VBW $\geq [3 \times \text{RBW}]$.
 - Detector = peak.
 - Sweep time = auto couple.
 - Trace mode = max hold.
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum amplitude level.
- Then the limit shall be attenuated by at least 20 dB relative to the maximum amplitude level in 100 kHz.

7.9.6 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

Test data reference attachment.

7.10 ANTENNA APPLICATION

7.10.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.10.2 Result

The EUT antenna is permanent attached FPCB antenna (Gain: 5.41dBi(Module 2), 5.56dBi(Module 1)). It comply with the standard requirement.

7.11 FREQUENCY HOPPING SYSTEM (FHSS) EQUIPMENT REQUIREMENTS

7.11.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. (g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section. (h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

7.11.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule. This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock. Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for FCC Part 15.247 rule.

7.11.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below: Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.


8 TEST RESULTS

MODULE 2:


8.1.1 DWELL TIME

Condition	Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	0.381	121.92	31600	400	Pass
NVNT	1-DH3	2441	1.635	261.6	31600	400	Pass
NVNT	1-DH5	2441	2.888	308.053	31600	400	Pass
NVNT	2-DH1	2441	0.387	123.84	31600	400	Pass
NVNT	2-DH3	2441	1.625	260	31600	400	Pass
NVNT	2-DH5	2441	2.888	308.053	31600	400	Pass
NVNT	3-DH1	2441	0.387	123.84	31600	400	Pass
NVNT	3-DH3	2441	1.625	260	31600	400	Pass
NVNT	3-DH5	2441	2.872	306.347	31600	400	Pass


Dwell NVNT 1-DH1 2441MHz




Dwell NVNT 1-DH3 2441MHz




Dwell NVNT 1-DH5 2441MHz




Dwell NVNT 2-DH1 2441MHz




Dwell NVNT 2-DH3 2441MHz




Dwell NVNT 2-DH5 2441MHz




Dwell NVNT 3-DH1 2441MHz



Dwell NVNT 3-DH3 2441MHz




Dwell NVNT 3-DH5 2441MHz




8.1.2 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant 1	6.285	30	Pass
NVNT	1-DH5	2441	Ant 1	6.948	30	Pass
NVNT	1-DH5	2480	Ant 1	7.01	30	Pass
NVNT	2-DH5	2402	Ant 1	8.319	21	Pass
NVNT	2-DH5	2441	Ant 1	8.853	21	Pass
NVNT	2-DH5	2480	Ant 1	9.518	21	Pass
NVNT	3-DH5	2402	Ant 1	8.667	21	Pass
NVNT	3-DH5	2441	Ant 1	9.106	21	Pass
NVNT	3-DH5	2480	Ant 1	9.79	21	Pass


Power NVNT 1-DH5 2402MHz Ant1




Power NVNT 1-DH5 2441MHz Ant1




Power NVNT 1-DH5 2480MHz Ant1




Power NVNT 2-DH5 2402MHz Ant1




Power NVNT 2-DH5 2441MHz Ant1




Power NVNT 2-DH5 2480MHz Ant1




Power NVNT 3-DH5 2402MHz Ant1



Power NVNT 3-DH5 2441MHz Ant1



Power NVNT 3-DH5 2480MHz Ant1




8.1.3 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	Ant 1	0.8951	0.928	Pass
NVNT	1-DH5	2441	Ant 1	0.8911	0.968	Pass
NVNT	1-DH5	2480	Ant 1	0.8871	0.942	Pass
NVNT	2-DH5	2402	Ant 1	1.1948	1.348	Pass
NVNT	2-DH5	2441	Ant 1	1.2048	1.354	Pass
NVNT	2-DH5	2480	Ant 1	1.1968	1.35	Pass
NVNT	3-DH5	2402	Ant 1	1.1968	1.298	Pass
NVNT	3-DH5	2441	Ant 1	1.2108	1.316	Pass
NVNT	3-DH5	2480	Ant 1	1.1988	1.302	Pass

OBW NVNT 1-DH5 2402MHz Ant1




-20 dB BW NVNT 1-DH5 2402MHz Ant1



OBW NVNT 1-DH5 2441MHz Ant1



-20 dB BW NVNT 1-DH5 2441MHz Ant1



OBW NVNT 1-DH5 2480MHz Ant1



-20 dB BW NVNT 1-DH5 2480MHz Ant1




OBW NVNT 2-DH5 2402MHz Ant1




-20 dB BW NVNT 2-DH5 2402MHz Ant1




OBW NVNT 2-DH5 2441MHz Ant1




-20 dB BW NVNT 2-DH5 2441MHz Ant1



OBW NVNT 2-DH5 2480MHz Ant1



-20 dB BW NVNT 2-DH5 2480MHz Ant1



OBW NVNT 3-DH5 2402MHz Ant1




-20 dB BW NVNT 3-DH5 2402MHz Ant1



OBW NVNT 3-DH5 2441MHz Ant1




-20 dB BW NVNT 3-DH5 2441MHz Ant1



OBW NVNT 3-DH5 2480MHz Ant1




-20 dB BW NVNT 3-DH5 2480MHz Ant1




8.1.4 CARRIER FREQUENCIES SEPARATION

Condition	Mode	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	2402.167	2403.166	0.999	0.928	Pass
NVNT	1-DH5	2440.981	2441.983	1.002	0.968	Pass
NVNT	1-DH5	2479.155	2480.157	1.002	0.942	Pass
NVNT	2-DH5	2401.933	2402.935	1.002	0.899	Pass
NVNT	2-DH5	2441.164	2442.166	1.002	0.903	Pass
NVNT	2-DH5	2479.158	2480.16	1.002	0.9	Pass
NVNT	3-DH5	2401.933	2402.935	1.002	0.865	Pass
NVNT	3-DH5	2441.161	2442.16	0.999	0.877	Pass
NVNT	3-DH5	2479.152	2480.154	1.002	0.868	Pass


CFS NVNT 1-DH5 2402MHz




CFS NVNT 1-DH5 2441MHz




CFS NVNT 1-DH5 2480MHz




CFS NVNT 2-DH5 2402MHz




CFS NVNT 2-DH5 2441MHz




CFS NVNT 2-DH5 2480MHz




CFS NVNT 3-DH5 2402MHz



CFS NVNT 3-DH5 2441MHz




CFS NVNT 3-DH5 2480MHz



8.1.5 NUMBER OF HOPPING CHANNEL

Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH5	79	15	Pass


Hopping No. NVNT 1-DH5 2402MHz




8.1.6 BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant 1	No-Hopping	-46.64	-20	Pass
NVNT	1-DH5	2402	Ant 1	Hopping	-46.22	-20	Pass
NVNT	1-DH5	2480	Ant 1	No-Hopping	-49.46	-20	Pass
NVNT	1-DH5	2480	Ant 1	Hopping	-48.94	-20	Pass
NVNT	2-DH5	2402	Ant 1	No-Hopping	-46.49	-20	Pass
NVNT	2-DH5	2402	Ant 1	Hopping	-45.49	-20	Pass
NVNT	2-DH5	2480	Ant 1	No-Hopping	-48.27	-20	Pass
NVNT	2-DH5	2480	Ant 1	Hopping	-48.28	-20	Pass
NVNT	3-DH5	2402	Ant 1	No-Hopping	-47.58	-20	Pass
NVNT	3-DH5	2402	Ant 1	Hopping	-46.1	-20	Pass
NVNT	3-DH5	2480	Ant 1	No-Hopping	-47.2	-20	Pass
NVNT	3-DH5	2480	Ant 1	Hopping	-49.06	-20	Pass

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission




Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission




8.1.7 CONDUCTED RF SPURIOUS EMISSION

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant 1	-55.79	-20	Pass
NVNT	1-DH5	2441	Ant 1	-60.89	-20	Pass
NVNT	1-DH5	2480	Ant 1	-61.26	-20	Pass
NVNT	2-DH5	2402	Ant 1	-59.52	-20	Pass
NVNT	2-DH5	2441	Ant 1	-60.46	-20	Pass
NVNT	2-DH5	2480	Ant 1	-63.21	-20	Pass
NVNT	3-DH5	2402	Ant 1	-60.21	-20	Pass
NVNT	3-DH5	2441	Ant 1	-59.15	-20	Pass
NVNT	3-DH5	2480	Ant 1	-62.29	-20	Pass

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission




MODULE 1:


8.1.8 DWELL TIME

Condition	Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	0.375	120	31600	400	Pass
NVNT	1-DH3	2441	1.625	260	31600	400	Pass
NVNT	1-DH5	2441	2.88	307.2	31600	400	Pass
NVNT	2-DH1	2441	0.372	119.04	31600	400	Pass
NVNT	2-DH3	2441	1.62	259.2	31600	400	Pass
NVNT	2-DH5	2441	2.88	307.2	31600	400	Pass
NVNT	3-DH1	2441	0.372	119.04	31600	400	Pass
NVNT	3-DH3	2441	1.635	261.6	31600	400	Pass
NVNT	3-DH5	2441	2.888	308.053	31600	400	Pass


Dwell NVNT 1-DH1 2441MHz




Dwell NVNT 1-DH3 2441MHz




Dwell NVNT 1-DH5 2441MHz




Dwell NVNT 2-DH1 2441MHz




Dwell NVNT 2-DH3 2441MHz




Dwell NVNT 2-DH5 2441MHz




Dwell NVNT 3-DH1 2441MHz



Dwell NVNT 3-DH3 2441MHz




Dwell NVNT 3-DH5 2441MHz




8.1.9 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant 1	5.863	30	Pass
NVNT	1-DH5	2441	Ant 1	7.029	30	Pass
NVNT	1-DH5	2480	Ant 1	5.879	30	Pass
NVNT	2-DH5	2402	Ant 1	8.037	21	Pass
NVNT	2-DH5	2441	Ant 1	9.4	21	Pass
NVNT	2-DH5	2480	Ant 1	8.022	21	Pass
NVNT	3-DH5	2402	Ant 1	8.487	21	Pass
NVNT	3-DH5	2441	Ant 1	9.547	21	Pass
NVNT	3-DH5	2480	Ant 1	8.503	21	Pass


Power NVNT 1-DH5 2402MHz Ant1




Power NVNT 1-DH5 2441MHz Ant1



Power NVNT 1-DH5 2480MHz Ant1



Power NVNT 2-DH5 2402MHz Ant1



Power NVNT 2-DH5 2441MHz Ant1

