

RF Exposure Evaluation Report

Product : Pudu GW1
Trade mark : 
Model/Type reference : PGCG01
Serial Number : N/A
Report Number : EED32O80417303
FCC ID : 2AXDW-PGCG01
Date of Issue : Jul. 29, 2022
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Test result : PASS

Prepared for:

SHENZHEN PUDU TECHNOLOGY CO., LTD.

Room 501, Building A, Block 1, Phase 1, Shenzhen International Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, 518057, China

Prepared by:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District,

Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Frazer Li

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

Jul. 29, 2022



Check No.: 4858240322

2 Version

Version No.	Date	Description
00	Jul. 29, 2022	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	6
4.5 DEVIATION FROM STANDARDS.....	6
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
5 RF EXPOSURE EVALUATION.....	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	8

4 General Information

4.1 Client Information

Applicant:	SHENZHEN PUDU TECHNOLOGY CO., LTD.
Address of Applicant:	Room 501, Building A, Block 1, Phase 1, Shenzhen International Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, 518057, China
Manufacturer:	SHENZHEN PUDU TECHNOLOGY CO., LTD.
Address of Manufacturer:	Room 501, Building A, Block 1, Phase 1, Shenzhen International Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, 518057, China
Factory:	SHENZHEN WABONY ELECTRONIC CO., LTD.
Address of Factory:	Floor 1-5, Building 12#. An Tuo Shan High Tech Park, Xin Sha Road, Sha Er community, Sha Jing Street, Bao An District, Shenzhen, P.R.C

4.2 General Description of EUT

Product Name:	Pudu GW1
Model No.:	PGCG01
Trade mark:	
EUT Supports Radios application:	2.4GHz WiFi and 2.4GHz wireless

4.3 Product Specification subjective to this standard

Frequency Range:	2.4G WiFi:IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz 2.4G FHSS: 2466MHz to 2480MHz
Modulation Type:	2.4G WiFi: IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM,QPSK,BPSK) 2.4G FHSS: CCK
Test Power Grade:	Default
Test Software of EUT:	2.4G WiFi: EspRFTTestTool_v2.8_Manual.exe 2.4G FHSS: LoRaGatewaySettings.exe
Antenna Type	External antenna
Antenna Gain	2.4G WiFi: 5.4dBi 2.4G FHSS: ANT1: 5.4dBi; ANT2: 5.4dBi; ANT3: 5.4dBi; ANT4: 5.4dBi

Function :	☒ SISO ☐ 2x2 MIMO ☐ 3x3 MIMO ☐ 4x4MIMO	
Power Supply:	Adapter:	AC 100-120V~50/60Hz,0.4A Max
Test Voltage:	AC 230V/50Hz	
Max Conducted Peak Output Power:	2.4G WIFI:23.94dBm; 2.4G FHSS:5.24dBm	
	The Max Conducted Peak Output Power data refer to the report EED32O80417301, EED32O80417302	
Sample Received Date:	Jun. 24, 2022	
Sample tested Date:	Jun. 24, 2022 to Jul. 20, 2022	
Remark: Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. The product has 4 same modules of 2.4G FHSS,they are module A,module B,module C and module D.And module A used antenna 1,module B used antenna 2,module C used antenna 3 and module D used antenna 4.All modules were tested.		

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and

d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20 \text{ cm}$ into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm^2

1)Maximum tune-up Power

2.4G WiFi:

Test Mode	Antenna	Frequency [MHz]	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power(dBm)
11B	Ant1	2412	21.48	21.00 ± 1	22.00
		2437	21.45	21.00 ± 1	22.00
		2462	20.98	21.00 ± 1	22.00
11G	Ant1	2412	23.67	23.00 ± 1	24.00
		2437	23.84	23.00 ± 1	24.00
		2462	23.38	23.00 ± 1	24.00
11N20SI SO	Ant1	2412	23.77	23.00 ± 1	24.00
		2437	23.94	23.00 ± 1	24.00
		2462	23.44	23.00 ± 1	24.00
11N40SI SO	Ant1	2422	23.66	23.00 ± 1	24.00
		2437	23.10	23.00 ± 1	24.00
		2452	23.87	23.00 ± 1	24.00

2.4G FHSS:

Test Mode	Antenna	Frequency[MHz]	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power(dBm)
TX	Ant1	2466	4.33	4.50±1	5.50
	Ant2	2466	4.26	4.50±1	5.50
	Ant3	2466	5.14	4.50±1	5.50
	Ant4	2466	5.10	4.50±1	5.50
	Ant1	2473	4.24	4.50±1	5.50
	Ant2	2473	4.23	4.50±1	5.50
	Ant3	2473	5.00	4.50±1	5.50
	Ant4	2473	5.24	4.50±1	5.50
	Ant1	2480	4.26	4.50±1	5.50
	Ant2	2480	4.18	4.50±1	5.50
	Ant3	2480	5.02	4.50±1	5.50
	Ant4	2480	5.24	4.50±1	5.50

2)Calculation
①For SISO:
2.4G WIFI:

Maximum tune-up Power(dBm)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
24.00	251.19	3.467	20	0.1733	1

2.4G FHSS ANT1:

Maximum tune-up Power(dBm)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
5.50	3.548	3.467	20	0.0024	1

2.4G FHSS ANT2:

Maximum tune-up Power(dBm)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
5.50	3.548	3.467	20	0.0024	1

2.4G FHSS ANT3:

Maximum tune-up Power(dBm)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
5.50	3.548	3.467	20	0.0024	1

2.4G FHSS ANT4:

Maximum tune-up Power(dBm)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
5.50	3.548	3.467	20	0.0024	1

Result: compliant

②For SUM:

$$\text{SUM}=0.1733+0.0024+0.0024+0.0024+0.0024=0.1829<1$$

Result: compliant

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***