

FCC RADIO TEST REPORT

FCC ID: 2AXDW-PNT

Product: KettyBot

Trade Mark: PUDU

Model No.: PNT

Family Model: N/A

Report No.: S21060901210004

Issue Date: 09 Jul. 2021

Prepared for

SHENZHEN PUDU TECHNOLOGY CO., LTD.
Room 501, Building A, Block 1, Phase 1, Shenzhen International
Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China
518057

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : SHENZHEN PUDU TECHNOLOGY CO., LTD.

Address : Room 501, Building A, Block 1, Phase 1, Shenzhen International
Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China 518057

Manufacturer's Name : SHENZHEN PUDU TECHNOLOGY CO., LTD.

Address : Room 501, Building A, Block 1, Phase 1, Shenzhen International
Inno Valley, Dashi 1st Road, Nanshan District, Shenzhen, China 518057

Product description

Product name : KettyBot

Model and/or type reference : PNT

Family Model : N/A

Standards : FCC Part15.407

Test procedure ANSI C63.10-2013 and KDB 789033 D02 General UNII Test Procedures
New Rules v02r01
FCC KDB 662911 D01 Multiple Transmitter Output v02r01
KDB 905462 D03 Client Without DFS New Rules v01r02
KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests 09 Jun. 2021 ~ 08 Jul. 2021

Date of Issue 09 Jul. 2021

Test Result **Pass**

Testing Engineer :



(Allen Liu)

Authorized Signatory :



(Alex Li)

Table of Contents

	Page
1. SUMMARY OF TEST RESULTS	7
1.1 FACILITIES AND ACCREDITATIONS	8
1.2 MEASUREMENT UNCERTAINTY	8
1 . GENERAL INFORMATION	9
1.1 GENERAL DESCRIPTION OF EUT	9
1.2 DESCRIPTION OF TEST MODES	12
1.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
1.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	14
1.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	15
2 . EMC EMISSION TEST	17
2.1 CONDUCTED EMISSION MEASUREMENT	17
2.1.1 APPLICABLE STANDARD	17
2.1.2 CONFORMANCE LIMIT	17
2.1.3 TEST CONFIGURATION	17
2.1.4 TEST PROCEDURE	17
2.2 RADIATED EMISSION MEASUREMENT	26
2.2.1 APPLICABLE STANDARD	26
2.2.2 CONFORMANCE LIMIT	26
2.2.3 MEASURING INSTRUMENTS	26
2.2.4 TEST CONFIGURATION	27
2.2.5 TEST PROCEDURE	28
2.2.6 TEST RESULTS (9KHZ – 30 MHZ)	29
2.2.7 TEST RESULTS (30MHZ – 1GHZ)	30
2.2.8 TEST RESULTS (1GHZ-18GHZ)	38
2.2.10 TEST RESULTS (18GHZ-40GHZ)	46
3 . POWER SPECTRAL DENSITY TEST	57
3.1 APPLIED PROCEDURES / LIMIT	57
3.2 TEST PROCEDURE	58
3.3 DEVIATION FROM STANDARD	58
3.4 TEST SETUP	58
3.5 EUT OPERATION CONDITIONS	58
3.6 TEST RESULTS	59
4 . 26DB & 99% EMISSION BANDWIDTH	60
4.1 APPLIED PROCEDURES / LIMIT	60
4.2 TEST PROCEDURE	60
4.3 EUT OPERATION CONDITIONS	61
4.4 TEST RESULTS	61

Table of Contents

	Page
5 . MINIMUM 6 DB BANDWIDTH	62
5.1 APPLIED PROCEDURES / LIMIT	62
5.2 TEST PROCEDURE	62
5.3 DEVIATION FROM STANDARD	62
5.4 TEST SETUP	62
5.5 EUT OPERATION CONDITIONS	62
5.6 TEST RESULTS	63
6 . MAXIMUM CONDUCTED OUTPUT POWER	64
6.1 PPLIED PROCEDURES / LIMIT	64
6.2 TEST RESULTS	66
7 . OUT OF BAND EMISSIONS	67
7.1 APPLICABLE STANDARD	67
7.2 TEST PROCEDURE	67
7.3 DEVIATION FROM STANDARD	68
7.4 TEST SETUP	68
7.5 EUT OPERATION CONDITIONS	68
7.6 TEST RESULTS	69
8. FREQUENCY STABILITY MEASUREMENT	70
8.1 LIMIT	70
8.2 TEST PROCEDURES	70
8.3 TEST SETUP LAYOUT	70
8.4 EUT OPERATION DURING TEST	70
8.5 TEST RESULTS	71
9. DYNAMIC FREQUENCY SELECTION(DFS)	83
9.1 APPLICABILITY OF DFS REQUIREMENTS	83
9.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE MONITORING	83
9.3 DFS RESPONSE REQUIREMENT VALUES	84
9.4 SHORT PULSE RADAR TEST WAVEFORMS	84
9.5 CALIBRATION SETUP AND DFS TEST RESULTS	85
9.6 CONDUCTED CALIBRATION SETUP	85
9.7 RADAR WAVEFORM CALIBRATION RESULT	86
9.8 IN-SERVICE MONITORING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD	87
9.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST	88

Table of Contents

	Page
10. ANTENNA REQUIREMENT	89
10.1 STANDARD REQUIREMENT	89
10.2 EUT ANTENNA	89

Revision History

[illegible]

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4) 15.407(b)(8)(9)	Spurious Radiated Emissions	PASS	
15.407 (a)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)	Maximum Conducted Output Power	PASS	
15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4)	Band Edge	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.407(g)	Frequency Stability Measurement	PASS	
15.407(h)	Dynamic Frequency Selection(DFS)	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	(Note 3)

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) This device operates with a duty cycle greater than 99%
- (3) The product is a client device, and the data transmission is limited by the AP.
When the information to be sent is missing or the operation fails,
the device will automatically stop sending and directly connect to the AP correctly again.

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier: CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^{\circ}\text{C}$
8	Humidity	$\pm 2\%$

1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

Equipment	KettyBot		
Trade Mark	PUDU		
Model Name	PNT		
Family Model	N/A		
Model Difference	N/A		
FCC ID	2AXDW-PNT		
Product Description	Mode Supported	☒ 802.11a ☒ 802.11n(HT20) ☒ 802.11n(HT40) ☒ 802.11ac(HT20) ☒ 802.11ac(HT40) ☒ 802.11ac(HT80)	
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT20): NSS1, MCS0-MCS8 802.11ac(VHT40/VHT80):NSS1, MCS0-MCS9	
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM	
	Operating Frequency Range	☒ U-NII-1: 5150 MHz ~5250MHz ☒ U-NII-2A: 5250MHz~5350MHz ☒ U-NII-2C: 5470MHz~5725MHz ☒ U-NII-3: 5725 MHz ~5850 MHz	
	Function:	☐ Outdoor AP ☐ Indoor AP ☐ Fixed P2P ☒ Client	
	DFS type:	☐ master devices ☐ Slave devices with radar detection ☒ Slave devices without radar detection	
	Support TPC	☐ YES ☒ NO	
	Antenna Type	Main Antenna 2: FPCB antenna AUX Antenna 3: FPCB antenna	
	Antenna Gain	Antenna 2: 3.5dBi Antenna 3: 3.5dBi	
	Smart system	☒ SISO for 802.11a/n/ac ☒ MIMO for 802.11n/ac	
	Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.		
	Ratings	DC 25.55V from battery	
	Adapter	☒ Adapter 1 supply: Model: FY29008000 Input: 100-240V~50/60Hz 3A 300VA Output: 29.0V---8.0A 232.0W	
	Battery	Model:7S8P DC 25.55V, 25600mAh	
Connecting I/O Port(s)	Please refer to the User's Manual		
HW Version	B00		
SW Version	9.1.0.6		

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- Frequency and Channel list:

Band	20MHz		40MHz		80MHz	
	Channel	Frequency	Channel	Frequency	Channel	Frequency
U-NII-1	36	5180 MHz	38	5190 MHz	42	5210 MHz
	40	5200 MHz	46	5230 MHz	-	-
	44	5220 MHz				
	48	5240 MHz				
U-NII-2A	52	5260 MHz	54	5270 MHz	58	5290 MHz
	56	5280 MHz	62	5310 MHz		
	60	5300 MHz				
	64	5320 MHz				
U-NII-2C	100	5500 MHz	102	5510 MHz	106	5530 MHz
	104	5520 MHz	110	5550 MHz	122	5610 MHz
	108	5540 MHz	118	5590 MHz		
	112	5560 MHz	126	5630 MHz		
	116	5580 MHz	134	5670 MHz		
	120	5600 MHz				
	124	5620 MHz				
	128	5640 MHz				
	132	5660 MHz				
	136	5680 MHz				
	140	5700 MHz				
U-NII-3	149	5745 MHz	151	5755 MHz	155	5775 MHz
	153	5765 MHz	159	5795 MHz		
	157	5785 MHz				
	161	5805 MHz				
	165	5825 MHz				

Table for Filed Antenna

Antenna	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	FPCB antenna	IPEX	3.5	Wifi Antenna
2	N/A	N/A	FPCB antenna	IPEX	3.5	Wifi Antenna

This module 2 supports Bluetooth, WIFI2.4G / 5G, module 2 has two antennas, 1 antenna supports Bluetooth, WIFI2.4G / 5G, 2 antenna supports WIFI2.4G / 5G.

The module 2 for 5G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
802.11a	1TX, 1RX
802.11n/ac	1TX/2TX, 1RX/2RX

For power measurements: Directional gain= G_{ANT} + Array Gain=3.5dBi + 0 = 3.5dBi

For power spectral density (PSD) measurements: Directional gain= G_{ANT} + Array Gain=3.5dBi + 3.01 = 6.51dBi

Note: G_{ANT} means antenna gain for the same gain in dBi.

For power spectral density (PSD) measurements: Array Gain = $10\log(N_{ANT}/N_{SS})$ dB.

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements:

N_{ANT} = number of transmit antennas and

N_{SS} = number of spatial streams. (Assume $N_{SS} = 1$ unless you have specific information to the contrary.)

1.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n/ ac 20 CH36/ CH40/ CH48/CH52/CH56/CH64/CH100/CH120/CH140/CH149/ CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46/CH54/CH62/CH102/CH118/CH134/CH151/ CH159
Mode 4	802.11ac80 CH42/CH58/CH106/CH122/CH155


For Conducted Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n/ ac 20 CH36/ CH40/ CH48/CH52/CH56/CH64/CH100/CH120/CH140/CH149/ CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46/CH54/CH62/CH102/CH118/CH134/CH151/ CH159
Mode 4	802.11ac80 CH42/CH58/CH106/CH122/CH155

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

1.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

1.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
AE-1	Adapter	N/A	FY29008000	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	Power Cable	NO	NO	1.2m	
C-2	RF Cable	YES	NO	0.1m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) During the battery power test, the battery is fully charged.

1.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2021.04.27	2022.04.26	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2020.07.13	2021.07.12	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2020.07.13	2021.07.12	1 year
4	Test Receiver	R&S	ESPI7	101318	2021.04.27	2022.04.26	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2021.03.29	2022.03.28	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2021.03.29	2022.03.28	1 year
8	Amplifier	EMC	EMC051835SE	980246	2020.07.13	2021.07.12	1 year
9	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2020.11.19	2021.11.18	1 year
10	Power Meter	DARE	RPR3006W	15I00041SN084	2020.07.13	2021.07.12	1 year
11	USB RF Power Sensor	DARE	RPR3006W	15I00041SN084	2020.07.13	2021.07.12	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2020.07.13	2021.07.12	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	High Test Cable(1G-40GHz)	N/A	R-04	N/A	2019.08.06	2022.08.05	3 year
16	Filter	TRILTHIC	2400MHz	29	2021.04.27	2022.04.26	1 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A
18	Low Noise Amplifier	B&Z	BZ-P540-550850-452727	16476-11729	2021.04.27	2022.04.26	1 year
19	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2020.11.19	2021.11.18	1 year
20	Thermal Chamber	Ten Billion	TTC-B3C	TBN-960502	2021.04.27	2022.04.26	1 year

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2021.04.27	2022.04.26	1 year
2	LISN	R&S	ENV216	101313	2021.04.27	2022.04.26	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2021.04.27	2022.04.26	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

2. EMC EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

2.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

2.1.3 TEST CONFIGURATION



2.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.3019	42.89	9.54	52.43	60.19	-7.76	QP
0.3019	33.12	9.54	42.66	50.19	-7.53	AVG
0.4899	37.88	9.55	47.43	56.17	-8.74	QP
0.4899	28.47	9.55	38.02	46.17	-8.15	AVG
0.7096	37.73	9.55	47.28	56.00	-8.72	QP
0.7096	27.93	9.55	37.48	46.00	-8.52	AVG
1.2980	37.55	9.56	47.11	56.00	-8.89	QP
1.2980	28.46	9.56	38.02	46.00	-7.98	AVG
2.1419	38.82	9.58	48.40	56.00	-7.60	QP
2.1419	29.87	9.58	39.45	46.00	-6.55	AVG
4.8658	37.08	9.62	46.70	56.00	-9.30	QP
4.8658	27.82	9.62	37.44	46.00	-8.56	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.3019	42.10	9.53	51.63	60.19	-8.56	QP
0.3019	32.80	9.53	42.33	50.19	-7.86	AVG
0.4939	37.40	9.54	46.94	56.10	-9.16	QP
0.4939	28.48	9.54	38.02	46.10	-8.08	AVG
0.7137	37.23	9.54	46.77	56.00	-9.23	QP
0.7137	27.91	9.54	37.45	46.00	-8.55	AVG
1.1060	36.53	9.55	46.08	56.00	-9.92	QP
1.1060	28.47	9.55	38.02	46.00	-7.98	AVG
1.2980	37.56	9.55	47.11	56.00	-8.89	QP
1.2980	28.14	9.55	37.69	46.00	-8.31	AVG
2.9219	37.53	9.59	47.12	56.00	-8.88	QP
2.9219	26.99	9.59	36.58	46.00	-9.42	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.3G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.3019	40.89	9.54	50.43	60.19	-9.76	QP
0.3019	31.48	9.54	41.02	50.19	-9.17	AVG
0.7096	38.23	9.55	47.78	56.00	-8.22	QP
0.7096	29.01	9.55	38.56	46.00	-7.44	AVG
0.9100	37.61	9.56	47.17	56.00	-8.83	QP
0.9100	28.09	9.56	37.65	46.00	-8.35	AVG
1.2980	36.55	9.56	46.11	56.00	-9.89	QP
1.2980	27.13	9.56	36.69	46.00	-9.31	AVG
2.1419	39.32	9.58	48.90	56.00	-7.10	QP
2.1419	28.89	9.58	38.47	46.00	-7.53	AVG
2.3380	38.20	9.58	47.78	56.00	-8.22	QP
2.3380	28.40	9.58	37.98	46.00	-8.02	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.3G)

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.3019	41.60	9.53	51.13	60.19	-9.06	QP
0.3019	33.12	9.53	42.65	50.19	-7.54	AVG
0.5140	36.69	9.54	46.23	56.00	-9.77	QP
0.5140	27.91	9.54	37.45	46.00	-8.55	AVG
0.9180	37.81	9.55	47.36	56.00	-8.64	QP
0.9180	28.47	9.55	38.02	46.00	-7.98	AVG
1.1060	38.53	9.55	48.08	56.00	-7.92	QP
1.1060	29.11	9.55	38.66	46.00	-7.34	AVG
1.2980	39.06	9.55	48.61	56.00	-7.39	QP
1.2980	29.59	9.55	39.14	46.00	-6.86	AVG
6.0339	39.23	9.63	48.86	60.00	-11.14	QP
6.0339	30.11	9.63	39.74	50.00	-10.26	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.6G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.3019	40.39	9.54	49.93	60.19	-10.26	QP
0.3019	29.82	9.54	39.36	50.19	-10.83	AVG
0.4899	36.88	9.55	46.43	56.17	-9.74	QP
0.4899	27.90	9.55	37.45	46.17	-8.72	AVG
1.2980	38.05	9.56	47.61	56.00	-8.39	QP
1.2980	28.77	9.56	38.33	46.00	-7.67	AVG
1.6895	37.97	9.58	47.55	56.00	-8.45	QP
1.6895	29.11	9.58	38.69	46.00	-7.31	AVG
1.9455	36.89	9.58	46.47	56.00	-9.53	QP
1.9455	27.90	9.58	37.48	46.00	-8.52	AVG
4.8658	39.08	9.62	48.70	56.00	-7.30	QP
4.8658	29.40	9.62	39.02	46.00	-6.98	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.6G)

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.3019	41.60	9.53	51.13	60.19	-9.06	QP
0.3019	32.80	9.53	42.33	50.19	-7.86	AVG
0.5140	37.69	9.54	47.23	56.00	-8.77	QP
0.5140	29.01	9.54	38.55	46.00	-7.45	AVG
1.1060	38.03	9.55	47.58	56.00	-8.42	QP
1.1060	28.03	9.55	37.58	46.00	-8.42	AVG
1.2980	39.06	9.55	48.61	56.00	-7.39	QP
1.2980	28.94	9.55	38.49	46.00	-7.51	AVG
2.3340	38.70	9.57	48.27	56.00	-7.73	QP
2.3340	29.17	9.57	38.74	46.00	-7.26	AVG
6.0339	39.23	9.63	48.86	60.00	-11.14	QP
6.0339	29.06	9.63	38.69	50.00	-11.31	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.3019	40.39	9.54	49.93	60.19	-10.26	QP
0.3019	29.91	9.54	39.45	50.19	-10.74	AVG
0.4899	39.88	9.55	49.43	56.17	-6.74	QP
0.4899	30.19	9.55	39.74	46.17	-6.43	AVG
0.7096	37.23	9.55	46.78	56.00	-9.22	QP
0.7096	28.47	9.55	38.02	46.00	-7.98	AVG
1.2940	37.30	9.56	46.86	56.00	-9.14	QP
1.2940	28.29	9.56	37.85	46.00	-8.15	AVG
2.1419	38.82	9.58	48.40	56.00	-7.60	QP
2.1419	29.16	9.58	38.74	46.00	-7.26	AVG
4.8658	36.58	9.62	46.20	56.00	-9.80	QP
4.8658	29.71	9.62	39.33	46.00	-6.67	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	KettyBot	Model Name. :	PNT
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 29V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.3019	41.60	9.53	51.13	60.19	-9.06	QP
0.3019	32.79	9.53	42.32	50.19	-7.87	AVG
0.5100	37.94	9.54	47.48	56.00	-8.52	QP
0.5100	28.48	9.54	38.02	46.00	-7.98	AVG
0.7137	37.73	9.54	47.27	56.00	-8.73	QP
0.7137	28.15	9.54	37.69	46.00	-8.31	AVG
1.1060	36.53	9.55	46.08	56.00	-9.92	QP
1.1060	28.89	9.55	38.44	46.00	-7.56	AVG
1.2980	37.06	9.55	46.61	56.00	-9.39	QP
1.2980	27.50	9.55	37.05	46.00	-8.95	AVG
2.3340	36.70	9.57	46.27	56.00	-9.73	QP
2.3340	27.12	9.57	36.69	46.00	-9.31	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



2.2 RADIATED EMISSION MEASUREMENT

2.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(d) and 15.209

2.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(7): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

2.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

2.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



2.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

2.2.6 TEST RESULTS (9KHZ – 30 MHZ)

EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure:	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


2.2.7 TEST RESULTS (30MHZ – 1GHZ)

EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX(5.2G)- 802.11ac40 (Low CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	59.8588	24.16	5.42	29.58	40.00	-10.42	QP
V	107.1337	16.52	11.26	27.78	43.50	-15.72	QP
V	126.3285	17.60	12.11	29.71	43.50	-13.79	QP
V	150.0107	21.63	12.57	34.20	43.50	-9.30	QP
V	199.2855	21.72	9.56	31.28	43.50	-12.22	QP
V	308.9125	20.90	15.08	35.98	46.00	-10.02	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	127.2176	17.52	12.15	29.67	43.50	-13.83	QP
H	150.0107	17.02	12.57	29.59	43.50	-13.91	QP
H	162.0414	17.56	12.01	29.57	43.50	-13.93	QP
H	261.0581	19.50	15.20	34.70	46.00	-11.30	QP
H	459.1143	16.18	19.36	35.54	46.00	-10.46	QP
H	787.8513	14.34	24.97	39.31	46.00	-6.69	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX(5.3G)- 802.11n40 (Middle CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	59.8588	22.16	5.42	27.58	40.00	-12.42	QP
V	126.3285	15.60	12.11	27.71	43.50	-15.79	QP
V	150.0107	22.13	12.57	34.70	43.50	-8.80	QP
V	191.7450	20.06	9.98	30.04	43.50	-13.46	QP
V	308.9125	21.90	15.08	36.98	46.00	-9.02	QP
V	552.8831	13.67	21.47	35.14	46.00	-10.86	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	127.2176	16.52	12.15	28.67	43.50	-14.83	QP
H	150.0107	17.02	12.57	29.59	43.50	-13.91	QP
H	261.0581	16.50	15.20	31.70	46.00	-14.30	QP
H	451.1349	17.16	19.42	36.58	46.00	-9.42	QP
H	625.0778	13.60	22.85	36.45	46.00	-9.55	QP
H	827.4932	15.00	25.70	40.70	46.00	-5.30	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX(5.6G)- 802.11n20 (Low CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	59.8588	23.66	5.42	29.08	40.00	-10.92	QP
V	126.3285	15.60	12.11	27.71	43.50	-15.79	QP
V	150.0107	20.63	12.57	33.20	43.50	-10.30	QP
V	308.9125	20.40	15.08	35.48	46.00	-10.52	QP
V	552.8831	13.17	21.47	34.64	46.00	-11.36	QP
V	827.4932	11.28	25.70	36.98	46.00	-9.02	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	127.2176	17.52	12.15	29.67	43.50	-13.83	QP
H	150.0107	17.52	12.57	30.09	43.50	-13.41	QP
H	261.0581	16.00	15.20	31.20	46.00	-14.80	QP
H	451.1349	15.66	19.42	35.08	46.00	-10.92	QP
H	625.0778	12.10	22.85	34.95	46.00	-11.05	QP
H	827.4932	13.50	25.70	39.20	46.00	-6.80	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX(5.8G) - 802.11ac40 (Low CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	59.8588	21.16	5.42	26.58	40.00	-13.42	QP
V	107.1337	15.52	11.26	26.78	43.50	-16.72	QP
V	126.3285	15.60	12.11	27.71	43.50	-15.79	QP
V	150.0107	21.13	12.57	33.70	43.50	-9.80	QP
V	193.0945	20.20	9.97	30.17	43.50	-13.33	QP
V	308.9125	21.40	15.08	36.48	46.00	-9.52	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	127.2176	17.52	12.15	29.67	43.50	-13.83	QP
H	150.0107	18.02	12.57	30.59	43.50	-12.91	QP
H	226.8934	17.12	11.70	28.82	46.00	-17.18	QP
H	265.6757	18.39	14.95	33.34	46.00	-12.66	QP
H	451.1349	17.16	19.42	36.58	46.00	-9.42	QP
H	827.4932	15.00	25.70	40.70	46.00	-5.30	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Note: All modes have been tested, just the the worst mode has been recorded in the report.

2.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX(5.2G) - 802.11ac20 _5190~5230MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G									
Vertical	3694.68	61.97	5.94	35.40	44.00	59.31	74.00	-14.69	Pk
Vertical	3694.68	42.79	5.94	35.40	44.00	40.13	54.00	-13.87	AV
Vertical	10360.73	58.94	8.46	39.75	44.50	62.65	68.20	-5.55	Pk
Vertical	15540.80	61.47	10.12	38.80	44.10	66.29	74.00	-7.71	Pk
Vertical	15540.80	40.15	10.12	38.80	42.70	46.37	54.00	-7.63	AV
Horizontal	3713.58	63.85	5.94	35.18	44.00	60.97	74.00	-13.03	Pk
Horizontal	3713.58	44.25	5.94	35.18	44.00	41.37	54.00	-12.63	AV
Horizontal	10361.05	59.34	8.46	38.71	44.50	62.01	68.20	-6.19	Pk
Horizontal	15540.96	57.92	10.12	38.38	44.10	62.32	74.00	-11.68	Pk
Horizontal	15540.96	41.38	10.12	38.38	44.10	45.78	54.00	-8.22	AV
middle Channel (5200 MHz)-Above 1G									
Vertical	3624.71	59.09	6.48	36.35	44.05	57.87	74.00	-16.13	Pk
Vertical	3624.71	43.51	6.48	36.35	44.05	42.29	54.00	-11.71	AV
Vertical	10400.67	60.41	8.47	37.88	44.51	62.25	68.20	-5.95	Pk
Vertical	15600.73	60.63	10.12	38.80	44.10	65.45	74.00	-8.55	Pk
Vertical	15600.73	40.08	10.12	38.80	42.70	46.30	54.00	-7.70	AV
Horizontal	4202.72	58.77	6.48	36.37	44.05	57.57	74.00	-16.43	Pk
Horizontal	4202.72	45.44	6.48	36.37	44.05	44.24	54.00	-9.76	AV
Horizontal	10400.72	61.91	8.47	38.64	44.50	64.52	68.20	-3.68	Pk
Horizontal	15601.09	60.49	10.12	38.38	44.10	64.89	74.00	-9.11	Pk
Horizontal	15601.09	41.70	10.12	38.38	44.10	46.10	54.00	-7.90	AV

High Channel (5240 MHz)-Above 1G

Vertical	4598.28	64.43	7.10	37.24	43.50	65.27	74.00	-8.73	Pk
Vertical	4598.28	43.83	7.10	37.24	43.50	44.67	54.00	-9.33	AV
Vertical	10480.81	60.64	8.46	37.68	44.50	62.28	68.20	-5.92	Pk
Vertical	15720.73	62.02	10.12	38.80	44.10	66.84	74.00	-7.16	Pk
Vertical	15720.73	40.80	10.12	38.80	42.70	47.02	54.00	-6.98	AV
Horizontal	4589.84	61.71	7.10	37.24	43.50	62.55	74.00	-11.45	Pk
Horizontal	4589.84	41.98	7.10	37.24	43.50	42.82	54.00	-11.18	AV
Horizontal	10481.17	62.67	8.46	38.57	44.50	65.20	68.20	-3.00	Pk
Horizontal	15720.76	60.24	10.12	38.38	44.10	64.64	74.00	-9.36	Pk
Horizontal	15720.76	43.56	10.12	38.38	44.10	47.96	54.00	-6.04	AV

Note:"802.11ac20(5G)" mode is the worst mode. PK value is lower than the Average value limit, So average didn't record.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value
has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX(5.3G) - 802.11ac40 _5260~5320MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G									
Vertical	4633.83	63.49	5.44	35.40	44.00	60.34	74.00	-13.66	Pk
Vertical	4633.83	44.97	5.74	35.40	44.00	42.11	54.00	-11.89	AV
Vertical	10520.70	60.92	8.26	39.75	44.50	64.43	68.20	-3.77	Pk
Vertical	15780.92	62.25	10.12	38.80	44.10	67.07	74.00	-6.93	Pk
Vertical	15780.92	41.12	9.62	38.80	42.70	46.84	54.00	-7.16	AV
Horizontal	4366.73	65.64	5.57	35.18	44.00	62.38	74.00	-11.62	Pk
Horizontal	4366.73	44.90	5.74	35.18	44.00	41.82	54.00	-12.18	AV
Horizontal	10520.84	60.71	8.38	38.71	44.50	63.30	68.20	-4.90	Pk
Horizontal	15780.92	58.86	9.88	38.38	44.10	63.02	74.00	-10.98	Pk
Horizontal	15780.92	41.86	9.94	38.38	44.10	46.08	54.00	-7.92	AV
middle Channel (5280 MHz)-Above 1G									
Vertical	4122.92	60.30	6.08	36.35	44.05	58.68	74.00	-15.32	Pk
Vertical	4122.92	43.93	6.39	36.35	44.05	42.62	54.00	-11.38	AV
Vertical	10560.77	61.04	8.28	37.88	44.51	62.69	68.20	-5.51	Pk
Vertical	15840.94	62.77	9.79	38.8	44.10	67.25	74.00	-6.75	Pk
Vertical	15840.94	40.92	9.70	38.8	42.70	46.72	54.00	-7.28	AV
Horizontal	3870.06	60.04	6.11	36.37	44.05	58.47	74.00	-15.53	Pk
Horizontal	3870.06	47.35	6.27	36.37	44.05	45.94	54.00	-8.06	AV
Horizontal	10561.32	56.46	8.33	38.64	44.50	58.93	68.20	-9.27	Pk
Horizontal	15840.95	61.54	9.99	38.38	44.10	65.81	74.00	-8.19	Pk
Horizontal	15840.95	42.16	9.81	38.38	44.10	46.25	54.00	-7.75	AV

High Channel (5320 MHz)-Above 1G									
Vertical	5367.10	63.72	6.96	37.24	43.50	64.42	74.00	-9.58	Pk
Vertical	5367.10	44.72	7.07	37.24	43.50	45.52	54.00	-8.48	AV
Vertical	10641.16	63.11	8.14	37.68	44.50	64.43	74.00	-9.57	Pk
Vertical	10641.16	42.83	8.35	37.68	44.50	44.36	54.00	-9.64	AV
Vertical	15960.99	61.91	10.11	38.8	44.10	66.71	74.00	-7.29	Pk
Vertical	15960.99	40.19	9.64	38.8	42.70	45.94	54.00	-8.06	AV
Horizontal	5437.17	62.69	7.05	37.24	43.50	63.48	74.00	-10.52	Pk
Horizontal	5437.17	42.96	7.05	37.24	43.50	43.75	54.00	-10.25	AV
Horizontal	10640.82	61.89	8.20	38.57	44.50	64.16	74.00	-9.84	Pk
Horizontal	10640.82	44.64	8.03	38.57	44.50	46.74	54.00	-7.26	AV
Horizontal	15961.46	61.61	9.81	38.38	44.10	65.71	74.00	-8.29	Pk
Horizontal	15961.46	44.64	9.96	38.38	44.10	48.88	54.00	-5.12	AV

Note: ANT 1 802.11ac40(5G) mode is the worst mode. PK value is lower than the Average value limit, So average didn't record.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value
has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX(5.6G) - 802.11ac20 _5500~5700MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G									
Vertical	5433.60	65.28	5.61	35.40	44.00	62.29	74.00	-11.71	Pk
Vertical	5433.60	46.11	5.76	35.40	44.00	43.27	54.00	-10.73	AV
Vertical	11000.83	61.05	8.24	39.75	44.50	64.54	74.00	-9.46	Pk
Vertical	11000.83	42.91	8.35	39.75	44.50	46.51	54.00	-7.49	AV
Vertical	16500.99	52.04	10.05	38.80	44.10	56.79	68.20	-11.41	Pk
Horizontal	5127.05	61.57	5.78	35.18	44.00	58.53	74.00	-15.47	Pk
Horizontal	5127.05	43.52	5.66	35.18	44.00	40.37	54.00	-13.63	AV
Horizontal	11000.90	59.25	8.22	38.71	44.50	61.68	74.00	-12.32	Pk
Horizontal	11000.90	42.61	8.14	38.71	44.50	44.96	54.00	-9.04	AV
Horizontal	16501.05	57.74	10.04	38.38	44.10	62.06	68.20	-6.14	Pk
Middle Channel (5600 MHz)-Above 1G									
Vertical	4933.83	63.71	6.29	36.35	44.05	62.29	74.00	-11.71	Pk
Vertical	4933.83	45.27	6.24	36.35	44.05	43.81	54.00	-10.19	AV
Vertical	11201.16	60.92	8.24	37.88	44.51	62.54	74.00	-11.46	Pk
Vertical	11201.16	45.55	8.13	37.88	44.51	47.04	54.00	-6.96	AV
Vertical	16801.03	59.72	9.71	38.80	44.10	64.13	68.20	-4.07	Pk
Horizontal	4766.90	61.50	6.44	36.37	44.05	60.26	74.00	-13.74	Pk
Horizontal	4766.90	44.44	6.13	36.37	44.05	42.90	54.00	-11.10	AV
Horizontal	11201.03	61.89	8.31	38.64	44.50	64.34	74.00	-9.66	Pk
Horizontal	11201.03	44.13	8.04	38.64	44.50	46.31	54.00	-7.69	AV
Horizontal	16800.91	58.10	10.09	38.38	44.10	62.47	68.20	-5.73	Pk

High Channel (5700 MHz)-Above 1G

Vertical	5647.91	62.22	6.79	37.24	43.50	62.75	68.20	-5.45	Pk
Vertical	11400.87	61.47	8.10	37.68	44.50	62.75	74.00	-11.25	Pk
Vertical	11400.87	42.82	8.23	37.68	44.50	44.23	54.00	-9.77	AV
Vertical	17101.12	56.73	9.70	38.80	44.10	61.13	68.20	-7.07	Pk
Horizontal	5433.84	61.08	6.74	37.24	43.50	61.56	74.00	-12.44	Pk
Horizontal	5433.84	42.95	6.74	37.24	43.50	43.43	54.00	-10.57	AV
Horizontal	11401.01	60.57	8.25	38.57	44.50	62.89	74.00	-11.11	Pk
Horizontal	11401.01	42.48	8.35	38.57	44.50	44.90	54.00	-9.10	AV
Horizontal	17101.16	59.67	9.70	38.38	44.10	63.65	68.20	-4.55	Pk

Note: "802.11ac20(5G)" mode is the worst mode. PK value is lower than the Average value limit, So average didn't record.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX (5.8G) -- 802.11n20_5745~5825MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G									
Vertical	5123.09	64.24	5.94	35.40	44.00	61.58	74.00	-12.42	Pk
Vertical	5123.09	45.95	5.94	35.40	44.00	43.29	54.00	-10.71	AV
Vertical	11491.18	60.57	8.46	39.75	44.50	64.28	74.00	-9.72	Pk
Vertical	11491.18	43.82	8.46	39.75	44.50	47.53	54.00	-6.47	AV
Vertical	17236.23	52.55	10.12	38.80	44.10	57.37	68.20	-10.83	Pk
Horizontal	5167.18	60.05	5.94	35.18	44.00	57.17	68.20	-11.03	Pk
Horizontal	11491.05	59.50	8.46	38.71	44.50	62.17	74.00	-11.83	Pk
Horizontal	11491.05	42.90	8.46	38.71	44.50	45.57	54.00	-8.43	AV
Horizontal	17236.05	51.89	10.12	38.38	44.10	56.29	68.20	-11.91	Pk
middle Channel (5785 MHz)-Above 1G									
Vertical	5433.98	63.16	6.48	36.35	44.05	61.94	74.00	-12.06	Pk
Vertical	5433.98	43.51	6.48	36.35	44.05	42.29	54.00	-11.71	AV
Vertical	11570.99	61.02	8.47	37.88	44.51	62.86	74.00	-11.14	Pk
Vertical	11570.99	43.58	8.47	37.88	44.51	45.42	54.00	-8.58	AV
Vertical	17356.42	56.28	10.12	38.80	44.10	61.10	68.20	-7.10	Pk
Horizontal	4867.18	60.47	6.48	36.37	44.05	59.27	74.00	-14.73	Pk
Horizontal	4867.18	43.32	6.48	36.37	44.05	42.12	54.00	-11.88	AV
Horizontal	11570.86	63.21	8.47	38.64	44.50	65.82	74.00	-8.18	Pk
Horizontal	11570.86	44.45	8.47	38.64	44.50	47.06	54.00	-6.94	AV
Horizontal	17356.07	57.04	10.12	38.38	44.10	61.44	68.20	-6.76	Pk

High Channel (5825 MHz)-Above 1G									
Vertical	5243.90	62.26	7.10	37.24	43.50	63.10	68.20	-5.10	Pk
Vertical	11651.84	61.97	8.46	37.68	44.50	63.61	74.00	-10.39	Pk
Vertical	11651.84	43.36	8.46	37.68	44.50	45.00	54.00	-9.00	AV
Vertical	17473.16	58.83	10.12	38.80	44.10	63.65	68.20	-4.55	Pk
Horizontal	5284.71	60.49	7.10	37.24	43.50	61.33	68.20	-6.87	Pk
Horizontal	11652.09	60.54	8.46	38.57	44.50	63.07	74.00	-10.93	Pk
Horizontal	11652.09	42.09	8.46	38.57	44.50	44.62	54.00	-9.38	AV
Horizontal	17474.10	58.45	10.12	38.38	44.10	62.85	68.20	-5.35	Pk

Note:"802.11n20(5G)" mode is the worst mode. PK value is lower than the Average value limit, So average didn't record.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


2.2.10 TEST RESULTS (18GHz-40GHz)

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX (5.2G)-802.11ac40 5190MHz~5230MHz; TX (5.3G)-802.11n40 5270MHz~5310MHz; TX (5.6G)-802.11n20 5500MHz~5700MHz; TX (5.8G)-802.11ac40 5755MHz~5795MHz		

All the modulation modes have been tested, and the worst result was report as below:


Low Channel (5190 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39769.14	39.32	20.09	44.07	43.48	60	68.2	8.2	Peak
39767.06	27.62	20.09	44.04	43.48	48.27	54	5.73	AVG


Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39769.536	36.32	20.09	44.07	43.48	57	68.2	11.2	Peak
39769.355	27.62	20.09	44.04	43.48	48.27	54	5.73	AVG


High Channel (5230 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
35628.12	41.09	19.11	42.73	44.61	58.32	68.2	9.88	Peak
35596.736	31.66	19.11	42.73	44.61	48.89	54	5.11	AVG

Vertical




Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39769.466	37.42	20.09	44.07	43.48	58.1	68.2	10.1	Peak
39769.466	25.65	20.09	44.04	43.48	46.3	54	7.7	AVG

Note: 802.11ac40 MIMO mode is the worst mode.


Low Channel (5270 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark
39176.22	38.95	19.98	43.84	44.62	58.15	68.2	10.05	Peak
39176.22	30.15	19.98	43.84	44.62	49.35	54	4.65	AVG


Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark
39385.83	39.23	20.01	44.06	42.69	60.61	68.2	7.59	Peak
39385.83	28.99	20.01	44.06	42.69	50.37	54	3.63	AVG


High Channel (5310 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39176.93	39.15	19.98	43.84	44.62	58.35	68.2	9.85	Peak
39176.93	30.87	19.98	43.84	44.62	50.07	54	3.93	AVG

Vertical




Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39369.164	36.03	20.01	44.06	42.69	57.41	68.2	10.79	Peak
39369.164	27.69	20.01	44.06	42.69	49.07	54	4.93	AVG

Note:802.11n40 MIMO mode is the worst mode.


Low Channel (5500 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39696.427	37.42	20.09	44.07	43.48	58.1	68.2	10.1	Peak
39653.171	29.42	20.07	44.06	43.48	50.07	54	3.93	AVG


Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
36575.631	37.5	19.16	42.61	41.56	57.71	68.2	10.49	Peak
36575.631	27.6	19.16	42.61	41.56	47.81	54	6.19	AVG


High Channel (5700 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark
35794.49	37.83	19.17	42.63	42.74	56.89	68.2	11.31	Peak
35763.408	29.2	19.14	42.61	42.71	48.24	54	5.76	AVG

Vertical




Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark
39816.723	38.84	20.09	42.63	43.48	58.08	68.2	10.12	Peak
39804.008	30.91	20.09	42.61	43.48	50.13	54	3.87	AVG

Note: 802.11n20 MIMO mode is the worst mode.


Low Channel (5755 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39669.974	38.63	20.09	44.16	43.48	59.4	68.2	8.8	Peak
39669.974	29.66	20.09	44.16	43.48	50.43	54	3.57	AVG


Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39731.332	37.72	20.06	44.07	43.21	58.64	68.2	9.56	Peak
39731.332	28.69	20.06	44.07	43.21	49.61	54	4.39	AVG


High Channel (5795 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark
35628.284	39.68	19.11	42.63	43.48	57.94	68.2	10.26	Peak
35635.908	30.23	19.12	42.63	43.48	48.5	54	5.5	AVG

Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark
39821.753	38.57	20.1	44.1	43.22	59.55	68.2	8.65	Peak
39821.753	29.45	20.1	44.1	43.22	50.43	54	3.57	AVG

Note: 802.11ac40 MIMO mode is the worst mode.

2.2.10 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX (5.2G)-802.11ac20 5150MHz~5250MHz,		

All the modulation modes have been tested, The report just record the worst data mode.

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
5.2G WIFI-802.11ac20 Mode									
4500	56.55	5.2	35.6	44.2	53.15	74	-20.85	Pk	Horizontal
4500	47.55	5.2	35.6	44.2	44.15	54	-9.85	AV	Horizontal
4500	59.5	5.2	35.6	44.2	56.1	74	-17.9	Pk	Horizontal
4500	46.52	5.2	35.6	44.2	43.12	54	-10.88	AV	Horizontal
5150	70.51	5.36	35.66	44.22	67.31	74	-6.69	Pk	Horizontal
5150	80.18	5.36	35.66	44.22	76.98	54	22.98	AV	Horizontal
5150	57.18	5.36	35.66	44.22	53.98	74	-20.02	Pk	Vertical
5150	79.97	5.36	35.66	44.22	76.77	54	22.77	AV	Vertical
5350	65.84	5.68	35.68	44.22	62.98	74	-11.02	Pk	Vertical
5350	47.47	5.68	35.68	44.22	44.61	54	-9.39	AV	Vertical
5350	61.22	5.68	35.68	44.22	58.36	74	-15.64	Pk	Horizontal
5350	45.93	5.68	35.68	44.22	43.07	54	-10.93	AV	Horizontal

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11ac20 " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX (5.3G)-802.11ac40 5250MHz~5350MHz,		

All the modulation modes have been tested, The report just record the worst data mode.

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel (5320 MHz)-Above 1G									
Vertical	5350.00	66.36	6.96	37.24	43.50	67.06	74.00	-6.94	Pk
Vertical	5350.00	44.35	7.07	37.24	43.50	45.16	54.00	-8.84	AV
Horizontal	5350.00	67.05	7.05	37.24	43.50	67.84	74.00	-6.16	Pk
Horizontal	5350.00	46.66	7.05	37.24	43.50	47.45	54.00	-6.55	AV

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11ac40 " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

EUT :	KettyBot	Model Name. :	PNT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX (5.6G)-802.11ac20 5470MHz~5725MHz,		

All the modulation modes have been tested, The report just record the worst data mode.

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G									
Vertical	5460.00	68.36	5.61	35.40	44.00	65.37	74.00	-8.63	Pk
Vertical	5460.00	51.33	5.76	35.40	44.00	48.49	54.00	-5.51	AV
Horizontal	5460.00	63.25	5.78	35.18	44.00	60.21	74.00	-13.79	Pk
Horizontal	5460.00	48.36	5.66	35.18	44.00	45.20	54.00	-8.80	AV

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11ac20 " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

3. POWER SPECTRAL DENSITY TEST

3.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)

For the band 5.15-5.25 GHz,

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

- (3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:


- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

3.3 DEVIATION FROM STANDARD

No deviation.

3.4 TEST SETUP



3.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6 TEST RESULTS

EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz), Band 2C (5470-5725MHz), Band 3 (5745-5825MHz)		

Refer to section 1.1 of this report:

Band1&Band2A&Band2C For 802.11n/ac 5GHz has MIMO mode. Directional gain=6.51dbi
 $6.51\text{dbi} > 6.0\text{dbi}$ so power spectral density limit = $11 - (6.51 - 6) = 10.49\text{dBm}$

Band3 For 802.11n/ac 5GHz has MIMO mode. Directional gain=3.5dbi
 $6.51\text{dbi} > 6.0\text{dbi}$ so power spectral density limit = $30 - (6.51 - 6) = 29.49\text{dBm}$

Test data reference attachment.

4. 26DB & 99% EMISSION BANDWIDTH

4.1 APPLIED PROCEDURES / LIMIT


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

4.2 TEST PROCEDURE

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.4 TEST RESULTS

EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz), Band 2C(5470-5725MHz), Band 3(5725-5850MHz)		

Test data reference attachment.

5. MINIMUM 6 DB BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

5.2 TEST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX (5G) Mode Frequency Band 3 (5725-5850MHz)		

Test data reference attachment.

6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5250~5350	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5470~5725	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5725~5850	1W


6.2 TEST PROCEDURE

- Method PM is Measurement using an RF average power meter. The procedure for this method is as follows:
 - a) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
 - b) If the transmitter does not transmit continuously, measure the duty cycle D of the transmitter output signal as described in 12.2.
 - c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
 - d) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle {e.g., $[10 \log (1 / 0.25)]$, if the duty cycle is 25%}.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.2 TEST RESULTS

EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX (5G) Mode Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz) Band 2C, (5470-5725MHz), Band 3 (5725-5850MHz)		

Refer to section 1.1 of this report:

Band1&Band2A&Band2C For 802.11n/ac 5GHz has MIMO mode. Directional gain=3.5dbi
3.5dbi<6.0dbi so conducted power limit= 24dBm

Band3 For 802.11n/ac 5GHz has MIMO mode. Directional gain=3.5dbi
3.5dbi<6.0dbi so conducted power limit= 30.00dBm

Test data reference attachment.

7. OUT OF BAND EMISSIONS

7.1 APPLICABLE STANDARD

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

7.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot


the graph with marking the highest point and edge frequency.

5. Repeat above procedures until all measured frequencies were complete.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

EUT :	KettyBot	Model Name :	PNT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V

Test data reference attachment.

8. Frequency Stability Measurement


8.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

8.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11 specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^\circ\text{C} \sim 70^\circ\text{C}$.

8.3 TEST SETUP LAYOUT



8.4 EUT OPERATION DURING TEST

1. The EUT was programmed to be in continuously un-modulation transmitting mode.
2. The module has two antennas, and the worst data is Antenna 1, only shown Antenna 1 Plot.

8.5 TEST RESULTS

EUT :	KettyBot	Model Name. :	PNT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5180.0247	5180	0.0247	-4.7683
		V max (V)	28.98	5180.0165	5180	0.0165	-3.1853
		V min (V)	21.42	5180.0136	5180	0.0136	-2.6255
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5180.0113	5180	0.0113	-2.1815
		T (°C)	-10	5180.0117	5180	0.0117	-2.2587
		T (°C)	0	5180.0255	5180	0.0255	-4.9228
		T (°C)	10	5180.0138	5180	0.0138	-2.6641
		T (°C)	20	5180.0122	5180	0.0122	-2.3552
		T (°C)	30	5180.0136	5180	0.0136	-2.6255
		T (°C)	40	5180.0119	5180	0.0119	-2.2973
		T (°C)	50	5180.0145	5180	0.0145	-2.7992
		T (°C)	60	5180.0163	5180	0.0163	-3.1467
		T (°C)	70	5180.0119	5180	0.0119	-2.2973
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5200.0159	5200	0.0159	-3.0577
		V max (V)	28.98	5200.0117	5200	0.0117	-2.2500
		V min (V)	21.42	5200.0135	5200	0.0135	-2.5962
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5200.0336	5200	0.0336	-6.4615
		T (°C)	-10	5200.0148	5200	0.0148	-2.8462
		T (°C)	0	5200.0336	5200	0.0336	-6.4615
		T (°C)	10	5200.0231	5200	0.0231	-4.4423
		T (°C)	20	5200.0159	5200	0.0159	-3.0577
		T (°C)	30	5200.0146	5200	0.0146	-2.8077
		T (°C)	40	5200.0205	5200	0.0205	-3.9423
		T (°C)	50	5200.0197	5200	0.0197	-3.7885
		T (°C)	60	5200.0154	5200	0.0154	-2.9615
		T (°C)	70	5200.0147	5200	0.0147	-2.8269
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5240.0141	5240	0.0141	-2.6908
		V max (V)	28.98	5240.0198	5240	0.0198	-3.7786
		V min (V)	21.42	5240.0181	5240	0.0181	-3.4542
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5240.0138	5240	0.0138	-2.6336
		T (°C)	-10	5240.0180	5240	0.0180	-3.4351
		T (°C)	0	5240.0178	5240	0.0178	-3.3969
		T (°C)	10	5240.0253	5240	0.0253	-4.8282
		T (°C)	20	5240.0149	5240	0.0149	-2.8435
		T (°C)	30	5240.0171	5240	0.0171	-3.2634
		T (°C)	40	5240.0201	5240	0.0201	-3.8359
		T (°C)	50	5240.0189	5240	0.0189	-3.6069
		T (°C)	60	5240.0151	5240	0.0151	-2.8817
		T (°C)	70	5240.0135	5240	0.0135	-2.5763
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	KettyBot	Model Name. :	PNT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX Frequency Band 2A (5250-5350MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5260MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5260.01761	5260	0.01761	-3.3479
		V max (V)	28.98	5260.01581	5260	0.01581	-3.0057
		V min (V)	21.42	5260.02121	5260	0.02121	-4.0323
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5260MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5260.00691	5260	0.00691	-1.3137
		T (°C)	-10	5260.02451	5260	0.02451	-4.6597
		T (°C)	0	5260.00821	5260	0.00821	-1.5608
		T (°C)	10	5260.01631	5260	0.01631	-3.1008
		T (°C)	20	5260.00761	5260	0.00761	-1.4468
		T (°C)	30	5260.00961	5260	0.00961	-1.8270
		T (°C)	40	5260.01611	5260	0.01611	-3.0627
		T (°C)	50	5260.00791	5260	0.00791	-1.5038
		T (°C)	60	5260.02421	5260	0.02421	-4.6027
		T (°C)	70	5260.02261	5260	0.02261	-4.2985
Limits				Within 5250-5350MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5280MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5280.01161	5280	0.01161	-2.1989
		V max (V)	28.98	5280.01141	5280	0.01141	-2.1610
		V min (V)	21.42	5280.01261	5280	0.01261	-2.3883
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5280MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5280.01821	5280	0.01821	-3.4489
		T (°C)	-10	5280.01691	5280	0.01691	-3.2027
		T (°C)	0	5280.01071	5280	0.01071	-2.0284
		T (°C)	10	5280.01161	5280	0.01161	-2.1989
		T (°C)	20	5280.01171	5280	0.01171	-2.2178
		T (°C)	30	5280.00971	5280	0.00971	-1.8390
		T (°C)	40	5280.01821	5280	0.01821	-3.4489
		T (°C)	50	5280.01231	5280	0.01231	-2.3314
		T (°C)	60	5280.01411	5280	0.01411	-2.6723
		T (°C)	70	5280.00871	5280	0.00871	-1.6496
Limits				Within 5250-5350MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5320MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5320.02521	5320	0.02521	-4.7387
		V max (V)	28.98	5320.02041	5320	0.02041	-3.8365
		V min (V)	21.42	5320.01811	5320	0.01811	-3.4041
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5320MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5320.01341	5320	0.01341	-2.5207
		T (°C)	-10	5320.01201	5320	0.01201	-2.2575
		T (°C)	0	5320.01441	5320	0.01441	-2.7086
		T (°C)	10	5320.00761	5320	0.00761	-1.4305
		T (°C)	20	5320.00721	5320	0.00721	-1.3553
		T (°C)	30	5320.01311	5320	0.01311	-2.4643
		T (°C)	40	5320.02511	5320	0.02511	-4.7199
		T (°C)	50	5320.01651	5320	0.01651	-3.1034
		T (°C)	60	5320.00951	5320	0.00951	-1.7876
		T (°C)	70	5320.02321	5320	0.02321	-4.3628
Limits				Within 5250-5350MHz			
Result				Complies			

EUT :	KettyBot	Model Name. :	PNT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX Frequency Band 2C (5470-5725MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5500.00599	5500	0.00599	-1.0891
		V max (V)	28.98	5500.00436	5500	0.00436	-0.7927
		V min (V)	21.42	5500.00205	5500	0.00205	-0.3727
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5500.00408	5500	0.00408	-0.7418
		T (°C)	-10	5500.01099	5500	0.01099	-1.9982
		T (°C)	0	5500.00459	5500	0.00459	-0.8345
		T (°C)	10	5500.00472	5500	0.00472	-0.8582
		T (°C)	20	5500.00697	5500	0.00697	-1.2673
		T (°C)	30	5500.00399	5500	0.00399	-0.7255
		T (°C)	40	5500.00336	5500	0.00336	-0.6109
		T (°C)	50	5500.00127	5500	0.00127	-0.2309
		T (°C)	60	5500.00396	5500	0.00396	-0.7200
		T (°C)	70	5500.00667	5500	0.00667	-1.2127
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5600.00746	5600	0.00746	-1.3321
		V max (V)	28.98	5600.00925	5600	0.00925	-1.6518
		V min (V)	21.42	5600.00862	5600	0.00862	-1.5393
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5600.01027	5600	0.01027	-1.8339
		T (°C)	-10	5600.00404	5600	0.00404	-0.7214
		T (°C)	0	5600.00385	5600	0.00385	-0.6875
		T (°C)	10	5600.00854	5600	0.00854	-1.5250
		T (°C)	20	5600.01106	5600	0.01106	-1.9750
		T (°C)	30	5600.00473	5600	0.00473	-0.8446
		T (°C)	40	5600.00786	5600	0.00786	-1.4036
		T (°C)	50	5600.00803	5600	0.00803	-1.4339
		T (°C)	60	5600.01167	5600	0.01167	-2.0839
		T (°C)	70	5600.00602	5600	0.00602	-1.0750
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5700.00749	5700	0.00749	-1.3140
		V max (V)	28.98	5700.00916	5700	0.00916	-1.6070
		V min (V)	21.42	5700.01098	5700	0.01098	-1.9263
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5700.01018	5700	0.01018	-1.7860
		T (°C)	-10	5700.00514	5700	0.00514	-0.9018
		T (°C)	0	5700.00399	5700	0.00399	-0.7000
		T (°C)	10	5700.00283	5700	0.00283	-0.4965
		T (°C)	20	5700.00880	5700	0.00880	-1.5439
		T (°C)	30	5700.01043	5700	0.01043	-1.8298
		T (°C)	40	5700.00667	5700	0.00667	-1.1702
		T (°C)	50	5700.00249	5700	0.00249	-0.4368
		T (°C)	60	5700.00474	5700	0.00474	-0.8316
		T (°C)	70	5700.00469	5700	0.00469	-0.8228
Limits				Within 5470-5725MHz			
Result				Complies			

EUT :	KettyBot	Model Name. :	PNT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 25.55V
Test Mode :	TX Frequency(5745-5850MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5745.01766	5745	0.01766	-3.0732
		V max (V)	28.98	5745.01204	5745	0.01204	-2.0965
		V min (V)	21.42	5745.01903	5745	0.01903	-3.3119
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5745.02005	5745	0.02005	-3.4894
		T (°C)	-10	5745.01840	5745	0.01840	-3.2036
		T (°C)	0	5745.01195	5745	0.01195	-2.0797
		T (°C)	10	5745.01362	5745	0.01362	-2.3705
		T (°C)	20	5745.01119	5745	0.01119	-1.9472
		T (°C)	30	5745.01244	5745	0.01244	-2.1651
		T (°C)	40	5745.01671	5745	0.01671	-2.9085
		T (°C)	50	5745.01635	5745	0.01635	-2.8456
		T (°C)	60	5745.01494	5745	0.01494	-2.6008
		T (°C)	70	5745.01280	5745	0.01280	-2.2278
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5785.01048	5785	0.01048	-1.8123
		V max (V)	28.98	5785.01512	5785	0.01512	-2.6143
		V min (V)	21.42	5785.01304	5785	0.01304	-2.2546
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5785.01111	5785	0.01111	-1.9212
		T (°C)	-10	5785.01328	5785	0.01328	-2.2961
		T (°C)	0	5785.01637	5785	0.01637	-2.8295
		T (°C)	10	5785.00946	5785	0.00946	-1.6354
		T (°C)	20	5785.01419	5785	0.01419	-2.4537
		T (°C)	30	5785.01085	5785	0.01085	-1.8763
		T (°C)	40	5785.00842	5785	0.00842	-1.4550
		T (°C)	50	5785.01262	5785	0.01262	-2.1815
		T (°C)	60	5785.01594	5785	0.01594	-2.7551
		T (°C)	70	5785.01572	5785	0.01572	-2.7180
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	25.55	5825.01118	5825	0.01118	-1.9201
		V max (V)	28.98	5825.01429	5825	0.01429	-2.4530
		V min (V)	21.42	5825.01985	5825	0.01985	-3.4079
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	25.55	T (°C)	-20	5825.00954	5825	0.00954	-1.6385
		T (°C)	-10	5825.01507	5825	0.01507	-2.5873
		T (°C)	0	5825.01138	5825	0.01138	-1.9545
		T (°C)	10	5825.00852	5825	0.00852	-1.4622
		T (°C)	20	5825.00941	5825	0.00941	-1.6162
		T (°C)	30	5825.01720	5825	0.01720	-2.9529
		T (°C)	40	5825.01541	5825	0.01541	-2.6459
		T (°C)	50	5825.00948	5825	0.00948	-1.6278
		T (°C)	60	5825.01683	5825	0.01683	-2.8892
		T (°C)	70	5825.01392	5825	0.01392	-2.3891
Limits				Within 5745-5850MHz			
Result				Complies			

Note: antenna 1 is the worst case.

9. DYNAMIC FREQUENCY SELECTION(DFS)

9.1 APPLICABILITY OF DFS REQUIREMENTS

EUT is client and operates as client without radar detection function.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes
Client Beacon Test	N/A	Yes	Yes

Additional requirements for devices with multiple bandwidth modes	Operational Mode	
	Master or Client With Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required

Note

Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

9.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE MONITORING

Maximum Transmit Power	Value (see notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note 3: EIRP is based on the highest antenna gain.

9.3 DFS RESPONSE REQUIREMENT VALUES

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the 99% power bandwidth See Note 3.

Note 1: The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar Burst generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate Channel changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

9.4 SHORT PULSE RADAR TEST WAVEFORMS

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	60%	30
1	1	Test A Test B	$\text{Roundup}\left(\frac{1}{360} \cdot \frac{19 \cdot 10^6}{\text{PRI}_{\text{min}}}\right)$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a

Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.


If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B. The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.

9.5 CALIBRATION SETUP AND DFS TEST RESULTS

Radar Waveform Calibration Procedure

- 1) A 50 ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to place of the master
- 2) The interference Radar Detection Threshold Level is $-62\text{dBm} - 2\text{dBi} + 1\text{dB} = -63\text{dBm}$ that had been taken into account the output power range and antenna gain.
- 3) The following equipment setup was used to calibrate the conducted radar waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz. The spectrum analyzer had offset -1.0dB to compensate RF cable loss 1.0dB.
- 4) The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was $-62\text{dBm} - 2\text{dBi} + 1\text{dB} = -63\text{dBm}$. Capture the spectrum analyzer plots on short pulse radar waveform.

9.6 CONDUCTED CALIBRATION SETUP



Wireless AP	Manufacturer	LINKSYS LLC
	Model NO.	WRT32X
	FCC ID	Q87-WRT3200ACM


9.7 RADAR WAVEFORM CALIBRATION RESULT

Test data reference attachment.

9.8 IN-SERVICE MONITORING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD

TEST CONFIGURATION:

Setup for Client with injection at the Master



TEST PROCEDURE:

1. The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device
3. A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
4. EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is Streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
5. When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom In 600ms plot of the Short Pulse Radar Type
7. Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell(0.3ms) = S(12000ms) / B(4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C(ms) = N \times Dwell(0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
8. Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

TEST MODE:

Please refer to the clause 2.2

**9.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND
NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST**

Test data reference attachment.

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

This EUT has three modules, module 2 supports Bluetooth, WIFI2.4G / 5G, module 2 has two antennas, Antenna 1 supports Bluetooth, WIFI2.4G / 5G, Antenna 2 supports WIFI2.4G / 5G. The module 1 only supports Bluetooth , WIFI 2.4G. The module 1 has only one antenna. module 3 only supports WCDMA/LTE. The module 3 has only one antenna. Antenna 4 supports WCDMA/LTE.

The module 2 for 5G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
802.11a	1TX, 1RX
802.11n/ac	1TX/2TX, 1RX/2RX

For 5GHz mode, Antenna 1,2 are transmitting, each with the same directional gain.

For power measurements: Directional gain= $G_{ANT} + \text{Array Gain} = 3.5\text{dBi} + 0 = 3.5\text{dBi}$

For power spectral density (PSD) measurements: Directional gain= $G_{ANT} + \text{Array Gain} = 3.5\text{dBi} + 3.01 = 6.51\text{dBi}$

Note: G_{ANT} means antenna gain for the same gain in dBi.

For power spectral density (PSD) measurements: $\text{Array Gain} = 10\log(N_{ANT}/N_{SS})\text{dB}$.

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths

For power measurements: with $N_{ANT} \geq 5$.

N_{ANT} = number of transmit antennas and

N_{SS} = number of spatial streams. (Assume $N_{SS} = 1$ unless you have specific information to the contrary.)

The antenna is permanently fixed, It complies with the standard requirement.

END OF REPORT