



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20200800933E-02

Applicant: Huizhou Zhihang Technology Co.,Ltd.

Address of Applicant: 3/F,building a, Dabang Science Park, Yuechang village, Xinxu Town, Huiyang District, Huizhou City

Equipment Under Test (EUT):

EUT Name: mouse

Model No.: TL-180

Brand Name: N/A

FCC ID: 2AXET-TL180

Standards: 47 CFR Part 1.1307

47 CFR Part 1.1310

KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2020-08-27

Date of Test: 2020-08-27 to 2020-09-09

Date of Issue: 2020-09-09

Test Result: **PASS***

***In the configuration tested, the EUT complied with the standards specified above**

Tested By:

Tiny You

(Tiny You)

Reviewed By:

Sheek . Luo

(Sheek Luo)

Approved By:

Jack Ai



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200800933E-01	Rev.01	Initial report	2020-09-09

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 RF EXPOSURE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits	5
4.2 EUT RF EXPOSURE EVALUATION	6

3 General Information

3.1 Client Information

Applicant:	Huizhou Zhihang Technology Co.,Ltd.
Address of Applicant:	3/F,building a, Dabang Science Park, Yuechang village, Xinxu Town, Huiyang District, Huizhou City
Manufacturer:	Huizhou Zhihang Technology Co.,Ltd.
Address of Manufacturer:	3/F,building a, Dabang Science Park, Yuechang village, Xinxu Town, Huiyang District, Huizhou City
Factory:	Huizhou Zhihang Technology Co.,Ltd.
Address of Factory:	3/F,building a, Dabang Science Park, Yuechang village, Xinxu Town, Huiyang District, Huizhou City

3.2 General Description of EUT

Product Name:	mouse
Model No.:	TL-180
Trade Mark:	N/A
Hardware Version:	V1.3
Software Version:	V68
Frequency Range:	2402MHz ~ 2480MHz
Modulation Type:	GFSK
Number of Channels:	40 (declared by the client)
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	-2.10dBi
Power Supply:	1*AA battery, DC 1.5V

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.2 EUT RF Exposure Evaluation

1) For 2.4G

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^2/30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, $-10^{((\text{dB}\mu\text{V}/\text{m})/20)/10^6}$,

d = measurement distance in meters (m)---3m,

$$\text{So pt} = (\text{E} \times \text{d})^2/30 / \text{gt}$$

The worst case (refer to report CQASZ20200700685E-01) is below:

Antenna polarization: Horizontal		
Frequency (MHz)	Level (dB μ V/m)	Polarization
2402	92.96	Peak
2402	89.28	Average

For 2402MHz wireless:

Field strength = 92.96dB μ V/m @3m

Ant. gain -2.1dBi; so Ant numeric gain=0.62

$$\text{So pt} = \{[10^{(92.96/20)/10^6} \times 3]^2/30 / 0.62\} \times 1000\text{mW} = 0.962\text{mW}$$

$$\text{So } (0.962\text{mW}/5\text{mm}) \times \sqrt{2.402\text{GHz}} = 0.3,$$

0.3<3.0 for 1-g SAR

So the SAR report is not required.