



FCC RADIO TEST REPORT

FCC ID : 2AXFL-4269
Equipment : Digital Media Receiver
Model Name : H6Y2A5
Applicant : Orthoclase Feldspar LLC
1202 NE McClain Road
Bentonville, AR 72712
Standard : FCC Part 15 Subpart C §15.247

The product was received on May 11, 2021 and testing was started from May 26, 2021 and completed on Jun. 25, 2021. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sportun International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	5
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement	17
3.4 Conducted Band Edges and Spurious Emission Measurement	22
3.5 Radiated Band Edges and Spurious Emission Measurement	28
3.6 AC Conducted Emission Measurement.....	32
3.7 Antenna Requirements.....	34
4 List of Measuring Equipment	35
5 Uncertainty of Evaluation.....	37
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.247(a)(2)	6dB Bandwidth	Pass
3.1	2.1049	99% Occupied Bandwidth	Reporting only
3.2	15.247(b)(3)	Output Power	Pass
3.3	15.247(e)	Power Spectral Density	Pass
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass
3.6	15.207	AC Conducted Emission	Pass
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Alan Liu

Report Producer: Cindy Liu



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Digital Media Receiver
Model Name	H6Y2A5
FCC ID	2AXFL-4269
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE

Remark: The above EUT's information was declared by manufacturer.

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	Bluetooth – LE (1Mbps): 7.90 dBm / 0.0062 W Bluetooth – LE (2Mbps): 7.80 dBm / 0.0060 W
99% Occupied Bandwidth	Bluetooth – LE (1Mbps): 1.033 MHz Bluetooth – LE (2Mbps): 2.054 MHz
Antenna Type / Gain	PCB Folded Dipole Antenna type with gain 4.2 dBi
Type of Modulation	Bluetooth LE : GFSK

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	Sportun International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sportun Site No. TH02-HY, CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sportun International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sportun Site No. 03CH15-HY (TAF Code: 3786)
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Y plane as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
Radiated Test Cases	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
AC Conducted Emission	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Remark: For Radiated Test Cases, the tests were performed with Adapter	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth - LE Tx Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Speaker	JAWBONE	MINIJAMBOX	N/A	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth controller	N/A	N/A	2AVZA-2374	N/A	N/A

Note: The removable plastic fixtures are used for verification during test.

2.5 EUT Operation Test Setup

The RF test items, utility “Compliance tool 1.0.1.4” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
6. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth


Please refer to Appendix A.

<1Mbps>





<2Mbps>






3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<2Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




3.3.6 Test Result of Power Spectral Density Plots (100kHz)

<1Mbps>






<2Mbps>






3.3.7 Test Result of Power Spectral Density Plots (3kHz)

<1Mbps>





<2Mbps>



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots

<1Mbps>




<2Mbps>






3.4.6 Test Result of Conducted Spurious Emission Plots


<1Mbps>








<2Mbps>







3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.



3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1 GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and be reported.
7. For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and be reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jul. 14, 2020	May 26, 2021~Jun. 15, 2021	Jul. 13, 2021	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	41912 & 05	30MHz~1GHz	Feb. 08, 2021	May 26, 2021~Jun. 15, 2021	Feb. 07, 2022	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 28, 2020	May 26, 2021~Jun. 15, 2021	Dec. 27, 2021	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-01620	1GHz~18GHz	Nov. 03, 2020	May 26, 2021~Jun. 15, 2021	Nov. 02, 2021	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	18GHz~40GHz	Dec. 02, 2020	May 26, 2021~Jun. 15, 2021	Dec. 01, 2021	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	1710001800 055006	1GHz~18GHz	May 06, 2021	May 26, 2021~Jun. 15, 2021	May 05, 2022	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY53270195	1GHz~26.5GHz	Aug. 21, 2020	May 26, 2021~Jun. 15, 2021	Aug. 20, 2021	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	0600789	18-40GHz	Oct. 27, 2020	May 26, 2021~Jun. 15, 2021	Oct. 26, 2021	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20MHz~8.4GHz	Nov. 02, 2020	May 26, 2021~Jun. 15, 2021	Nov. 01, 2021	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY50180136	3Hz~44GHz	May 07, 2021	May 26, 2021~Jun. 15, 2021	May 06, 2022	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 26, 2021~Jun. 15, 2021	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 26, 2021~Jun. 15, 2021	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24 (k5)	RK-000451	N/A	N/A	May 26, 2021~Jun. 15, 2021	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104, 102E	MY36980/4, MY9838/4PE ,508405/2E	30MHz~18G	Nov. 16, 2020	May 26, 2021~Jun. 15, 2021	Nov. 15, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz-40GHz	Feb. 22, 2021	May 26, 2021~Jun. 15, 2021	Feb. 21, 2022	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz-40GHz	Feb. 22, 2021	May 26, 2021~Jun. 15, 2021	Feb. 21, 2022	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz~30MHz	Mar. 11, 2021	May 26, 2021~Jun. 15, 2021	Mar. 10, 2022	Radiation (03CH15-HY)
Filter	Wainwright	WLJ4-1000-15 30-6000-40ST	SN4	1.53GHz Low Pass Filter	Jul. 03, 2020	May 26, 2021~Jun. 15, 2021	Jul. 02, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WPKX12-2700-3000-18000-60ST	SN4	3GHz High Pass Filter	Sep. 16, 2020	May 26, 2021~Jun. 15, 2021	Sep. 15, 2021	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 25, 2021	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 30, 2020	Jun. 25, 2021	Nov. 29, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 18, 2020	Jun. 25, 2021	Nov. 17, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 01, 2020	Jun. 25, 2021	Nov. 30, 2021	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 25, 2021	N/A	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Feb. 25, 2021	Jun. 25, 2021	Feb. 24, 2022	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 31, 2020	Jun. 25, 2021	Dec. 30, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 03, 2021	May 28, 2021~Jun. 17, 2021	Mar. 02, 2022	Conducted (TH02-HY)
Power Sensor	DARE	RPR3006W	16I00054SN O10	10MHz~6GHz	Dec. 16, 2020	May 28, 2021~Jun. 17, 2021	Dec. 15, 2021	Conducted (TH02-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz ~ 40GHz	Jul. 22, 2020	May 28, 2021~Jun. 17, 2021	Jul. 21, 2021	Conducted (TH02-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2021	May 28, 2021~Jun. 17, 2021	Mar. 16, 2022	Conducted (TH02-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	2.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.9 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Peter Liao / Hank Hsu				Temperature:	21~25		°C
Test Date:	2021/5/28~2021/6/17				Relative Humidity:	51~54		%

<u>TEST RESULTS DATA</u> <u>6dB and 99% Occupied Bandwidth</u>								
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.031	0.682	0.50	Pass
BLE	1Mbps	1	19	2440	1.031	0.684	0.50	Pass
BLE	1Mbps	1	39	2480	1.033	0.688	0.50	Pass

<u>TEST RESULTS DATA</u> <u>Average Power Table</u>										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	7.90	30.00	4.20	12.10	36.00	Pass
BLE	1Mbps	1	19	2440	7.90	30.00	4.20	12.10	36.00	Pass
BLE	1Mbps	1	39	2480	7.70	30.00	4.20	11.90	36.00	Pass

<u>TEST RESULTS DATA</u> <u>Peak Power Density</u>									
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.81	-7.52	4.20	8.00	Pass
BLE	1Mbps	1	19	2440	6.44	-7.84	4.20	8.00	Pass
BLE	1Mbps	1	39	2480	6.92	-7.42	4.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.054	1.180	0.50	Pass
BLE	2Mbps	1	19	2440	2.054	1.176	0.50	Pass
BLE	2Mbps	1	39	2480	2.054	1.176	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	7.80	30.00	4.20	12.00	36.00	Pass
BLE	2Mbps	1	19	2440	7.80	30.00	4.20	12.00	36.00	Pass
BLE	2Mbps	1	39	2480	7.70	30.00	4.20	11.90	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	6.71	-11.24	4.20	8.00	Pass
BLE	2Mbps	1	19	2440	6.55	-11.39	4.20	8.00	Pass
BLE	2Mbps	1	39	2480	6.83	-11.13	4.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	40~50%

EUT Information

Report NO : 120234-01
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	34.68	55.88	21.20	L1	OFF	19.5
0.152250	49.47	---	65.88	16.41	L1	OFF	19.5
0.235500	---	32.42	52.25	19.83	L1	OFF	19.5
0.235500	36.29	---	62.25	25.96	L1	OFF	19.5
0.366000	---	27.51	48.59	21.08	L1	OFF	19.5
0.366000	30.41	---	58.59	28.18	L1	OFF	19.5
0.498750	---	31.26	46.02	14.76	L1	OFF	19.7
0.498750	35.05	---	56.02	20.97	L1	OFF	19.7
2.861250	---	24.19	46.00	21.81	L1	OFF	19.9
2.861250	25.33	---	56.00	30.67	L1	OFF	19.9
20.343750	---	27.98	50.00	22.02	L1	OFF	20.4
20.343750	30.32	---	60.00	29.68	L1	OFF	20.4

EUT Information

Report NO : 120234-01
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	33.91	55.88	21.97	N	OFF	19.5
0.152250	48.35	---	65.88	17.53	N	OFF	19.5
0.233250	---	33.33	52.33	19.00	N	OFF	19.5
0.233250	36.45	---	62.33	25.88	N	OFF	19.5
0.366000	---	27.62	48.59	20.97	N	OFF	19.6
0.366000	30.43	---	58.59	28.16	N	OFF	19.6
0.498750	---	31.09	46.02	14.93	N	OFF	19.7
0.498750	34.50	---	56.02	21.52	N	OFF	19.7
2.613750	---	24.20	46.00	21.80	N	OFF	20.0
2.613750	25.59	---	56.00	30.41	N	OFF	20.0
21.252750	---	27.97	50.00	22.03	N	OFF	20.6
21.252750	30.51	---	60.00	29.49	N	OFF	20.6



Appendix C. Radiated Spurious Emission

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.1~25.6°C
		Relative Humidity :	46~64%

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak	Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2388.435	55.77	-18.23	74	42.58	27.55	16.56	30.92	258	337	P	H	
		2366.91	45.77	-8.23	54	32.54	27.63	16.53	30.93	258	337	A	H	
	*	2402	110.35	-	-	97.18	27.5	16.58	30.91	258	337	P	H	
	*	2402	109.69	-	-	96.52	27.5	16.58	30.91	258	337	A	H	
		2378.775	55.88	-18.12	74	42.68	27.58	16.54	30.92	217	354	P	V	
		2358.405	45.69	-8.31	54	32.44	27.67	16.51	30.93	217	354	A	V	
	*	2402	110.87	-	-	97.7	27.5	16.58	30.91	217	354	P	V	
	*	2402	110.34	-	-	97.17	27.5	16.58	30.91	217	354	A	V	
BLE CH 19 2440MHz		2380.08	55.54	-18.46	74	42.33	27.58	16.55	30.92	253	337	P	H	
		2380.88	45.88	-8.12	54	32.67	27.58	16.55	30.92	253	337	A	H	
	*	2440	111.63	-	-	98.39	27.5	16.64	30.9	253	337	P	H	
	*	2440	110.94	-	-	97.7	27.5	16.64	30.9	253	337	A	H	
		2484.79	55.75	-18.25	74	42.49	27.43	16.71	30.88	253	337	P	H	
		2494.78	45.66	-8.34	54	32.39	27.41	16.73	30.87	253	337	A	H	
		2382.48	55.27	-18.73	74	42.07	27.57	16.55	30.92	238	360	P	V	
		2357.52	46.02	-7.98	54	32.77	27.67	16.51	30.93	238	360	A	V	
	*	2440	112.87	-	-	99.63	27.5	16.64	30.9	238	360	P	V	
	*	2440	112.27	-	-	99.03	27.5	16.64	30.9	238	360	A	V	
		2497.93	55.36	-18.64	74	42.1	27.4	16.73	30.87	238	360	P	V	
		2484.88	45.98	-8.02	54	32.72	27.43	16.71	30.88	238	360	A	V	



BLE CH 39 2480MHz	*	2480	113.7	-	-	100.44	27.44	16.7	30.88	252	334	P	H
	*	2480	113.15	-	-	99.89	27.44	16.7	30.88	252	334	A	H
		2483.76	62.86	-11.14	74	49.6	27.43	16.71	30.88	252	334	P	H
		2483.52	47.93	-6.07	54	34.67	27.43	16.71	30.88	252	334	A	H
	*	2480	113.83	-	-	100.57	27.44	16.7	30.88	232	358	P	V
	*	2480	113.29	-	-	100.03	27.44	16.7	30.88	232	358	A	V
		2484.96	63.12	-10.88	74	49.86	27.43	16.71	30.88	232	358	P	V
		2483.6	48.6	-5.4	54	35.34	27.43	16.71	30.88	232	358	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	41.66	-32.34	74	59.36	31.1	10.05	58.85	100	0	P	H
		18000	60.76	-13.24	74	50.11	49	18.89	57.24	300	247	P	H
		18000	50.87	-3.13	54	40.22	49	18.89	57.24	300	247	A	H
		4804	39.9	-34.1	74	57.6	31.1	10.05	58.85	100	0	P	V
		17985	59.69	-14.31	74	49.35	48.73	18.88	57.27	100	128	P	V
		17985	49.79	-4.21	54	39.45	48.73	18.88	57.27	100	128	A	V
BLE CH 19 2440MHz		4880	42.5	-31.5	74	60.26	31.04	10.11	58.91	100	0	P	H
		7320	46.41	-27.59	74	56.2	36.3	12.32	58.41	100	0	P	H
		18000	60.74	-13.26	74	50.09	49	18.89	57.24	100	31	P	H
		18000	50.72	-3.28	54	40.07	49	18.89	57.24	100	31	A	H
		4880	40.53	-33.47	74	58.29	31.04	10.11	58.91	100	0	P	V
		7320	46.01	-27.99	74	55.8	36.3	12.32	58.41	100	0	P	V
		18000	60.51	-13.49	74	49.86	49	18.89	57.24	100	21	P	V
		18000	50.49	-3.51	54	39.84	49	18.89	57.24	100	21	A	V
BLE CH 39 2480MHz		4960	42.59	-31.41	74	60.18	31.22	10.17	58.98	100	0	P	H
		7440	48.13	-25.87	74	57.64	36.3	12.39	58.2	100	0	P	H
		18000	60.82	-13.18	74	50.17	49	18.89	57.24	300	247	P	H
		18000	50.9	-3.1	54	40.25	49	18.89	57.24	300	247	A	H
		4960	42.55	-31.45	74	60.14	31.22	10.17	58.98	100	0	P	V
		7440	47	-27	74	56.51	36.3	12.39	58.2	100	0	P	V
		18000	59.61	-14.39	74	48.96	49	18.89	57.24	100	126	P	V
		18000	49.64	-4.36	54	38.99	49	18.89	57.24	100	126	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2387.07	55.65	-18.35	74	42.46	27.55	16.56	30.92	297	339	P	H
		2375.52	44.95	-9.05	54	31.73	27.6	16.54	30.92	297	339	A	H
	*	2402	109.54	-	-	96.37	27.5	16.58	30.91	297	339	P	H
	*	2402	107.98	-	-	94.81	27.5	16.58	30.91	297	339	A	H
		2384.34	56.43	-17.57	74	43.24	27.56	16.55	30.92	270	3	P	V
		2315.25	44.89	-9.11	54	31.63	27.77	16.44	30.95	270	3	A	V
	*	2402	110.71	-	-	97.54	27.5	16.58	30.91	270	3	P	V
	*	2402	109.19	-	-	96.02	27.5	16.58	30.91	270	3	A	V
BLE CH 19 2440MHz		2353.36	55.01	-18.99	74	41.75	27.69	16.5	30.93	287	339	P	H
		2358.32	45.2	-8.8	54	31.95	27.67	16.51	30.93	287	339	A	H
	*	2440	112.07	-	-	98.83	27.5	16.64	30.9	287	339	P	H
	*	2440	110.49	-	-	97.25	27.5	16.64	30.9	287	339	A	H
		2485.42	55	-19	74	41.74	27.43	16.71	30.88	287	339	P	H
		2497.12	45.11	-8.89	54	31.84	27.41	16.73	30.87	287	339	A	H
		2369.52	55.44	-18.56	74	42.21	27.62	16.53	30.92	260	359	P	V
		2373.84	45.15	-8.85	54	31.93	27.6	16.54	30.92	260	359	A	V
	*	2440	112.21	-	-	98.97	27.5	16.64	30.9	260	359	P	V
	*	2440	110.69	-	-	97.45	27.5	16.64	30.9	260	359	A	V
		2493.79	54.86	-19.14	74	41.59	27.41	16.73	30.87	260	359	P	V
		2486.05	44.85	-9.15	54	31.59	27.43	16.71	30.88	260	359	A	V



BLE CH 39 2480MHz	*	2480	109.27	-	-	96.01	27.44	16.7	30.88	250	337	P	H
	*	2480	107.6	-	-	94.34	27.44	16.7	30.88	250	337	A	H
		2483.96	59.3	-14.7	74	46.04	27.43	16.71	30.88	250	337	P	H
		2483.52	50	-4	54	36.74	27.43	16.71	30.88	250	337	A	H
	*	2480	110.25	-	-	96.99	27.44	16.7	30.88	257	359	P	V
	*	2480	108.77	-	-	95.51	27.44	16.7	30.88	257	359	A	V
		2484	60.96	-13.04	74	47.7	27.43	16.71	30.88	257	359	P	V
		2483.52	50.7	-3.3	54	37.44	27.43	16.71	30.88	257	359	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	42.39	-31.61	74	60.09	31.1	10.05	58.85	100	0	P	H
		18000	60.46	-13.54	74	49.81	49	18.89	57.24	300	258	P	H
		18000	50.56	-3.44	54	39.91	49	18.89	57.24	300	258	A	H
		4804	40.38	-33.62	74	58.08	31.1	10.05	58.85	100	0	P	V
		18000	60.74	-13.26	74	50.09	49	18.89	57.24	100	123	P	V
		18000	50.75	-3.25	54	40.1	49	18.89	57.24	100	123	A	V
BLE CH 19 2440MHz		4880	41.44	-32.56	74	59.2	31.04	10.11	58.91	100	0	P	H
		7320	45.53	-28.47	74	55.32	36.3	12.32	58.41	100	0	P	H
		17985	60.67	-13.33	74	50.33	48.73	18.88	57.27	300	247	P	H
		17985	50.72	-3.28	54	40.38	48.73	18.88	57.27	300	247	A	H
		4880	39.42	-34.58	74	57.18	31.04	10.11	58.91	100	0	P	V
		7320	47.41	-26.59	74	57.2	36.3	12.32	58.41	100	0	P	V
		18000	60.48	-13.52	74	49.83	49	18.89	57.24	100	132	P	V
		18000	50.56	-3.44	54	39.91	49	18.89	57.24	100	132	A	V
BLE CH 39 2480MHz		4960	43.44	-30.56	74	61.03	31.22	10.17	58.98	100	0	P	H
		7440	48.16	-25.84	74	57.67	36.3	12.39	58.2	100	0	P	H
		18000	60.08	-13.92	74	49.43	49	18.89	57.24	300	247	P	H
		18000	50.17	-3.83	54	39.52	49	18.89	57.24	300	247	A	H
		4960	41.68	-32.32	74	59.27	31.22	10.17	58.98	100	0	P	V
		7440	48.83	-25.17	74	58.34	36.3	12.39	58.2	100	0	P	V
		18000	59.98	-14.02	74	49.33	49	18.89	57.24	100	129	P	V
		18000	50.19	-3.81	54	39.54	49	18.89	57.24	100	129	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above 18GHz

2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE(2M) CH 39 2480MHz SHF		21496	39.07	-34.93	74	43.78	38.3	11.69	54.7	150	0	P	H	
		21568	38.56	-35.44	74	43.2	38.31	11.75	54.7	150	0	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line. 3. Super High Frequency (SHF)													



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
2.4GHz BLE LF		119.24	28.44	-15.06	43.5	42.02	17.41	1.56	32.55	-	-	P	H	
		267.65	25	-21	46	35.61	19.5	2.32	32.43	-	-	P	H	
		576.11	30.45	-15.55	46	33.86	25.82	3.31	32.54	-	-	P	H	
		703.18	39.78	-6.22	46	42.23	26.4	3.6	32.45	100	0	P	H	
		711.91	38.63	-7.37	46	40.9	26.56	3.62	32.45	-	-	P	H	
		729.37	35.44	-10.56	46	36.91	27.31	3.67	32.45	-	-	P	H	
		30.97	26.34	-13.66	40	33.95	24.21	0.68	32.5	-	-	P	V	
		121.18	25.07	-18.43	43.5	38.67	17.38	1.57	32.55	-	-	P	V	
		455.83	28.97	-17.03	46	35.25	23.27	2.88	32.43	-	-	P	V	
		576.11	30.77	-15.23	46	34.18	25.82	3.31	32.54	-	-	P	V	
		711.91	37.56	-8.44	46	39.83	26.56	3.62	32.45	-	-	P	V	
		885.54	39.24	-6.76	46	37.95	28.86	4.13	31.7	100	0	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A) (H/V)	
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB μ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) - Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB μ V) - 35.86 (dB)

= 55.45 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) - Limit Line(dB μ V/m)

= 55.45(dB μ V/m) - 74(dB μ V/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB μ V) - 35.86 (dB)

= 43.54 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) - Limit Line(dB μ V/m)

= 43.54(dB μ V/m) - 54(dB μ V/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.1~25.6°C
		Relative Humidity :	46~64%

Note symbol


-L	Low channel location
-R	High channel location





<1Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)














BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
Horizontal		Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_I5_1620 HORIZONTAL : R8W:1000.000kHz VBW:3.0000Hz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 HORIZONTAL : R8W:1000.000kHz VBW:3.0000Hz SWT:Auto</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
Vertical		Fundamental
Peak	 <p>Level (dBuV/m)</p> <p>Date: 2021-06-11</p> <p>PEAK_BE_74</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_I5_1620 VERTICAL : R8W:1000.000kHz VBW:3.0000Hz SWT:Auto</p>	Left blank
Avg.	 <p>Level (dBuV/m)</p> <p>Date: 2021-06-11</p> <p>Avg_BE_54</p> <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL : R8W:1000.000kHz VBW:3.0000Hz SWT:Auto</p>	Left blank










2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)












<2Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)














BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
Horizontal		Fundamental
Peak	 <p>Level (dBuV/m)</p> <p>Date: 2021-06-11</p> <p>PEAK_BE_74</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_I5_1620 HORIZONTAL : R8W:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	 <p>Level (dBuV/m)</p> <p>Date: 2021-06-11</p> <p>AVG_BE_54</p> <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 HORIZONTAL : R8W:1000.000kHz VBW:1.000kHz SWT:Auto</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
Vertical		Fundamental
Peak	 <p>Level (dBuV/m)</p> <p>Date: 2021-06-11</p> <p>PEAK_BE_74</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_I5_1620 VERTICAL : R8W:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	 <p>Level (dBuV/m)</p> <p>Date: 2021-06-11</p> <p>Avg_BE_54</p> <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL : R8W:1000.000kHz VBW:1000kHz SWT:Auto</p>	Left blank










2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)










Emission above 18GHz


2.4GHz BLE (SHF)






Emission below 1GHz

2.4GHz BLE (LF)



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth –LE for 1Mbps	61.06	381	2.62	3kHz	2.14
Bluetooth –LE for 2Mbps	56.80	1065	0.94	1kHz	2.46



—————THE END—————