

IWS Global Pty Ltd

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING- FUYL Tower Pro Control Door, Models: ELE-00368-01

REPORT NUMBER

104360835MPK-011B

ISSUE DATE

August 11, 2020

REVISED DATE

November 17, 2020

PAGES

10

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)**

Report Number: 104360835MPK-011B

Project Number: G104360835

Report Issue Date: August 11, 2020

Product Designation: FUYL Tower Pro Control Door

Model Tested: ELE-00368-01

FCC ID: 2AXFV-ELE0036801

IC: 26455-ELE0036801

to

47CFR 2.1091

RSS-102 Issue 5

for

IWS Global Pty Ltd

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

IWS Global Pty Ltd
29 Oxleigh Drive
Magala WA 6090, Australia

Report prepared by:



Hung Huynh / Project Engineer

Report reviewed by:



Krishna Vemuri / EMC Manager

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 104360835MPK-011B	
Equipment Under Test:	FUYL Tower Pro Control Door
Trade Name:	IWS Global Pty Ltd
Model(s) Tested:	ELE-00368-01
Applicant:	IWS Global Pty Ltd
Contact:	Jeff Cross
Address:	IWS Global Pty Ltd 29 Oxleigh Drive Magala WA 6090
Country:	Australia
Tel. Number:	61892097900
Email:	jeff.c@pclocs.com.au
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

TABLE OF CONTENTS

1.0	<i>RF Exposure Summary.....</i>	5
2.0	<i>RF Exposure Limits</i>	5
3.0	<i>Test Results (Mobile Configuration)</i>	7
Appendix A:	<i>Power Density Calculation.....</i>	9
4.0	<i>Document History</i>	10

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	$0.73/f$	-	6**
1.1-10	$87/f^{0.5}$	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142/f^{0.3417}$	$0.008335/f^{0.3417}$	$0.02619/f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158/f^{0.5}$	$4.21 \times 10^{-4}/f^{0.5}$	$6.67 \times 10^{-5}/f$	$616000/f^{1.2}$
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The FUYL Tower Pro Control Door, Model: ELE-00368-01 consists of three radios: RFID, Bluetooth Low Energy, 2.4 GHz WiFi, and 5GHz WiFi.

3.3 Maximum RF Power

Frequency Range (MHz)	Peak FS @10m (dBμV/m)	Note
13.56	29.95	FS measurement was taken from Report # 104360835MPK-001

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
2402-2480	10.47	1.59	As declared by the client the EUT consists of an approved Bluetooth Low Energy, 2.4 GHz WiFi, and 5GHz WiFi module under FCC ID: COF-WMBACBM25 & IC: 10293A-WMBACBM25
2412-2462	24.66	1.59	
5180-5825	22.58	2.23	

¹As declared by the manufacturer.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for RFID

Frequency Range (MHz)	Peak FS @10m (dBμV/m)	Peak FS @20 cm* (dBμV/m)	Peak FS @20 cm (V/m)	RSS Limit (V/m)	FCC Limit (V/m)	Results
13.56	29.95	97.90	0.08	27.46	60.77	Complies

* Distance Correction Factor was used.

3.4.2 RF Exposure calculation for Bluetooth Low Energy & 2.4 GHz WiFi

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	MPE Ratio	Sum of MPE Ratios
2402-2480	12.06	16.07	0.0032	1	0.0032	0.0871
2412-2462	26.25	421.69	0.0839	1	0.0839	

Note: Antenna gains below 0 are considered as 0dBi.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	MPE Ratio	Sum of MPE Ratios
2402-2480	12.06	16.07	0.0320	5.41	0.0059	0.1612
2412-2462	26.25	421.69	0.8389	5.40	0.1553	

Note: Antenna gains below 0 are considered as 0dBi.

3.4.2 RF Exposure calculation for Bluetooth Low Energy & 5 GHz WiFi

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	MPE Ratio	Sum of MPE Ratios
2402-2480	12.06	16.07	0.0032	1	0.0032	0.0634
5180-5825	24.81	302.69	0.0602	1	0.0602	

Note: Antenna gains below 0 are considered as 0dBi.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	MPE Ratio	Sum of MPE Ratios
2402-2480	12.06	16.07	0.0320	5.41	0.0059	0.0675
5180-5825	24.81	302.69	0.6022	9.77	0.0616	

Note: Antenna gains below 0 are considered as 0dBi.

The summation of the MPE ratio is less than 1, therefore, the EUT complies for the MPE requirement of simultaneous transmission.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0/ G104360835	HH	KV	August 11, 2020	Original document
1.1/ G104360835	HH	KV	November 17, 2020	Update page 7 with approved radio IC ID information.