

**Dreame Trading (Tianjin) Co.,Ltd.**

# RF TEST REPORT

**Report Type:**

FCC Part 15.247 & ISED RSS-247 RF report

**Model:**

RLS5-WH1, RLS5-WH2

**REPORT NUMBER:**

200801009SHA-001

**ISSUE DATE:**

Oct 13, 2020

**DOCUMENT CONTROL NUMBER:**

TTRF15.247-03\_V1 © 2018 Intertek



**Applicant:** Dreame Trading (Tianjin) Co.,Ltd.  
Room 2112-1-1, South District, Finance and Trade Center, No.6975  
Yazhou Road, Dongjiang Bonded Port Area, Tianjin Pilot Free Trade  
Zone, 300463 Tianjin, China

**Manufacturer:** Dreame Trading (Tianjin) Co.,Ltd.  
Room 2112-1-1, South District, Finance and Trade Center, No.6975  
Yazhou Road, Dongjiang Bonded Port Area, Tianjin Pilot Free Trade  
Zone, 300463 Tianjin, China

**Manufacturing site:** Suzhou Kaifa Electronics Co., Ltd.  
Comprehensive Free Zone, West Zone. No.200 Suhong Middle Rd.  
SIP, Suzhou, P.R. China

**FCC ID:** 2AXGD-RLS5

**IC:** 26444-RLS5

## SUMMARY:

<b>The equipment complies with the requirements according to the following standard(s) or Specification:</b>
<b>47CFR Part 15 (2019):</b> Radio Frequency Devices (Subpart C)
<b>ANSI C63.10 (2013):</b> American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
<b>RSS-247 Issue 2 (February 2017):</b> Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
<b>RSS-Gen Issue 5 (April 2018):</b> General Requirements for Compliance of Radio Apparatus

## PREPARED BY:

*Teddy Yin*

Project Engineer  
Teddy Yin

## REVIEWED BY:

*Daniel Zhao*

Reviewer  
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

## Content

<b>REVISION HISTORY.....</b>	<b>5</b>
<b>MEASUREMENT RESULT SUMMARY .....</b>	<b>6</b>
<b>1 GENERAL INFORMATION .....</b>	<b>7</b>
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....	7
1.2 TECHNICAL SPECIFICATION .....	7
1.3 DESCRIPTION OF TEST FACILITY .....	9
<b>2 TEST SPECIFICATIONS.....</b>	<b>10</b>
2.1 STANDARDS OR SPECIFICATION .....	10
2.2 MODE OF OPERATION DURING THE TEST.....	10
2.3 TEST SOFTWARE LIST .....	11
2.4 TEST PERIPHERALS LIST .....	11
2.5 TEST ENVIRONMENT CONDITION:.....	11
2.6 INSTRUMENT LIST .....	12
2.7 MEASUREMENT UNCERTAINTY .....	13
<b>3 MINIMUM 6DB BANDWIDTH.....</b>	<b>14</b>
3.1 LIMIT .....	14
3.2 MEASUREMENT PROCEDURE .....	14
3.3 TEST CONFIGURATION .....	14
3.4 TEST RESULTS OF MINIMUM 6DB BANDWIDTH .....	14
<b>4 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P.....</b>	<b>15</b>
4.1 LIMIT .....	15
4.2 MEASUREMENT PROCEDURE .....	15
4.3 TEST CONFIGURATION .....	15
4.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER.....	15
<b>5 POWER SPECTRUM DENSITY .....</b>	<b>16</b>
5.1 LIMIT .....	16
5.2 MEASUREMENT PROCEDURE .....	16
5.3 TEST CONFIGURATION .....	17
5.4 TEST RESULTS OF POWER SPECTRUM DENSITY .....	17
<b>6 EMISSION OUTSIDE THE FREQUENCY BAND .....</b>	<b>18</b>
6.1 LIMIT .....	18
6.2 MEASUREMENT PROCEDURE .....	18
6.3 TEST CONFIGURATION .....	19
6.4 THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND.....	19
<b>7 RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS.....</b>	<b>20</b>
7.1 LIMIT .....	20
7.2 MEASUREMENT PROCEDURE .....	20
7.3 TEST CONFIGURATION .....	22
7.4 TEST RESULTS OF RADIATED EMISSIONS .....	24
<b>8 POWER LINE CONDUCTED EMISSION.....</b>	<b>30</b>
8.1 LIMIT .....	30
8.2 TEST CONFIGURATION .....	30
8.3 MEASUREMENT PROCEDURE .....	31

**TEST REPORT**

8.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION..... 32

**9 OCCUPIED BANDWIDTH ..... 34**

9.1 LIMIT ..... 34

9.2 MEASUREMENT PROCEDURE ..... 34

9.3 TEST CONFIGURATION ..... 34

9.4 THE RESULTS OF OCCUPIED BANDWIDTH ..... 34

**10 ANTENNA REQUIREMENT ..... 35**

**APPENDIX A: TEST RESULTS ..... 36**

## Revision History

Report No.	Version	Description	Issued Date
200801009SHA-001	Rev. 01	Initial issue of report	Oct 13, 2020

## Measurement result summary

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	RSS-247 Issue 2 Clause 5.2	Pass
Maximum conducted output power and e.i.r.p.	15.247(b)(3)	RSS-247 Issue 2 Clause 5.4	Pass
Power spectrum density	15.247(e)	RSS-247 Issue 2 Clause 5.2	Pass
Emission outside the frequency band	15.247(d)	RSS-247 Issue 2 Clause 5.5	Pass
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	RSS-Gen Issue 5 Clause 8.9&8.10	Pass
Power line conducted emission	15.207(a)	RSS-Gen Issue 5 Clause 8.8	Pass
Occupied bandwidth	-	RSS-Gen Issue 5 Clause 6.6	Tested
Antenna requirement	15.203	-	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	Robot vacuum cleaner
Type/Model:	RLS5-WH1, RLS5-WH2
Description of EUT:	The EUT is automatically battery-powered cleaner and dry pick up for household indoor use only. Both models contain the same WIFI modular and the same PCBs. The difference is the model name and some motors. RLS5-WH1 was tested for conducted testing, RLS5-WH1 and RLS5-WH2 were tested for radiated testing. And the worst data is listed in the report.
Rating:	14.4VDC Docking Station (RCS0) Input:100-240V~, 50/60Hz, 0.5A Output:19.8VDC, 1A
EUT type:	<input type="checkbox"/> Table top <input checked="" type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	Aug 12, 2020
Date of test:	Aug 12~Sep 3, 2020

### 1.2 Technical Specification

Frequency Range:	2412MHz ~ 2462MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40: OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Channel Number:	11 Channels for 802.11b, 802.11g and 802.11n(HT20) 7 Channels for 802.11n(HT40)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7 IEEE 802.11n-HT40: Up to MCS7
Channel Separation:	5 MHz

### 1.3 Antenna information

Antenna No.	Model	Antenna type	Antenna Gain	Note
1	/	Internal	3.83dBi	

Mode	Tx/Rx Function	Beamforming function	CDD function
802.11b	1Tx/1Rx	NO	NO
802.11g	1Tx/1Rx	NO	NO
802.11n(HT20)	1Tx/1Rx	NO	NO
802.11n(HT40)	1Tx/1Rx	NO	NO

**TEST REPORT****1.4 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

## 2 TEST SPECIFICATIONS

### 2.1 Standards or specification

47CFR Part 15 (2019)  
 ANSI C63.10 (2013)  
 KDB 558074 D01(v05r02)  
 RSS-247 Issue 2 (February 2017)  
 RSS-Gen Issue 5 (April 2018)

### 2.2 Mode of operation during the test

While testing transmitting mode of EUT, the continuously transmission was applied by following software.

Software name	Manufacturer	Version	Supplied by
putty	/	/	Manufacturer

The lowest, middle and highest channel were tested as representatives.

Frequency Band (MHz)	Mode	Lowest (MHz)	Middle (MHz)	Highest (MHz)
2400-2483.5	802.11b	2412	2437	2462
	802.11g	2412	2437	2462
	802.11n(HT20)	2412	2437	2462
	802.11n(HT40)	2422	2437	2452

#### Data rate VS Power:

The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases. After this pre-scan, we choose the following table of the data rate as the worst case.

Frequency Band (MHz)	Mode	Worst case data rate
2400-2483.5	802.11b	1Mbps
	802.11g	6Mbps
	802.11n(HT20)	MCS0
	802.11n(HT40)	MCS0

The EUT will use two types antenna, and there have the following test mode:

Radiated test mode:

Mode 1: EUT transmitted signal with internal antenna;

Conducted test mode:

Mode 2: EUT transmitted signal from PCBA RF port connected to SPA directly;

We have verified all test modes, and choose the worst mode 1 for radiated test and mode 2 for conducted test as representatively to list the results in this report.

### 2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

### 2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Laptop computer	HP ProBook 6470b	100-240V AC, 50/60Hz
2	Charger	NER700-DS	Input: 100-240V AC, 50/60Hz Output: DC 16.9V, 2A

### 2.5 Test environment condition:

Test items	Temperature	Humidity
Minimum 6dB Bandwidth	22°C	55% RH
Maximum conducted output power and e.i.r.p.		
Power spectrum density		
Emission outside the frequency band		
Occupied bandwidth		
Radiated Emissions in restricted frequency bands	22°C	55% RH
Power line conducted emission	22°C	55% RH

## 2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCS 30	EC 2107	2021-07-14
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2020-11-10
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2021-01-13
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2020-09-16
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2020-09-24
<input checked="" type="checkbox"/>	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC5262	2021-06-11
<input checked="" type="checkbox"/>	Horn antenna	R&S	HF 906	EC 3049	2021-01-17
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross	-	EC 3048	2021-07-31
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2021-03-16
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3481	2021-01-05
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3442	2021-01-05

## 2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

### 3 Minimum 6dB bandwidth

Test result: Pass


#### 3.1 Limit

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.2 Measurement Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 3.3 Test Configuration



#### 3.4 Test Results of Minimum 6dB bandwidth

Please refer to Appendix A

## 4 Maximum conducted output power and e.i.r.p.

**Test result:** Pass

### 4.1 Limit


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

### 4.2 Measurement Procedure

The EUT was tested according to DTS test procedure of “KDB558074 D01v05r02 15.247 Meas Guidance” (clause 8.3.2.2) for compliance requirements.

### 4.3 Test Configuration



### 4.4 Test Results of Maximum conducted output power

Please refer to Appendix A

## 5 Power spectrum density

**Test result:** Pass

### 5.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.


If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and  $8 + (6 - \text{antenna gain} - \text{beam forming gain})$ .

### 5.2 Measurement Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to  $1.5 \times$  DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times$  RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 5.3 Test Configuration



### 5.4 Test Results of Power spectrum density

Please refer to Appendix A

**TEST REPORT**

## 6 Emission outside the frequency band

**Test result:** Pass

### 6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

### 6.2 Measurement Procedure

#### Reference level measurement

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq 3 \times$  RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

#### Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq 3 \times$  RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

### 6.3 Test Configuration



### 6.4 The results of Emission outside the frequency band

Please refer to Appendix A

## 7 Radiated Emissions in restricted frequency bands

Test result: Pass

### 7.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

### 7.2 Measurement Procedure

#### For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters (0.1 meters for floor-standing device) above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**TEST REPORT****For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) or 0.1 meters (for floor-standing device) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or  $3 \times \text{RBW}$  (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported

### 7.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



**For Radiated emission above 1GHz:**



**TEST REPORT**

**7.4 Test Results of Radiated Emissions**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


The worst waveform from 30MHz to 1000MHz is listed as below:

Model: RLS5-WH1

Horizontal



Vertical



## TEST REPORT


### Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.00	22.00	19.40	40.00	18.00	PK
H	199.12	23.60	10.90	40.00	16.40	PK
H	335.19	33.90	15.80	47.00	13.10	QP
H	480.98	32.70	19.20	47.00	14.30	QP
H	527.64	32.70	20.00	47.00	14.30	PK
H	751.18	34.60	22.20	47.00	12.40	PK
V	142.75	25.90	12.40	40.00	14.10	PK
V	191.34	30.10	10.70	40.00	9.90	PK
V	335.19	35.30	15.80	47.00	11.70	QP
V	480.98	32.40	19.20	47.00	14.60	QP
V	650.10	30.60	21.20	47.00	16.40	PK
V	751.18	32.60	22.20	47.00	14.40	PK

Note: The worst test result (30MHz to 1GHz) of 802.11b channel L (2412MHz) was chosen to list in the report as representative.


Model: RLS5-WH2

### Horizontal



## TEST REPORT

### Vertical



### Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.00	22.80	19.40	40.00	17.20	PK
H	191.34	28.20	10.70	40.00	11.80	PK
H	335.19	33.20	15.80	47.00	13.80	QP
H	480.98	36.20	19.20	47.00	10.80	PK
H	650.10	31.60	21.20	47.00	15.40	PK
H	751.18	33.20	22.20	47.00	13.80	PK
V	142.75	26.30	12.40	40.00	13.70	PK
V	191.34	30.50	10.70	40.00	9.50	PK
V	335.19	37.40	15.80	47.00	9.60	PK
V	383.79	37.60	17.10	47.00	9.40	PK
V	550.96	30.90	20.30	47.00	16.10	PK
V	961.12	33.50	24.20	47.00	13.50	PK

Note: The worst test result (30MHz to 1GHz) of 802.11b channel L (2412MHz) was chosen to list in the report as representative.

**TEST REPORT**

**Test result above 1GHz:**

The emission was conducted from 1GHz to 25GHz

802.11b

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H/V	2390.00	52.38	31.2	74	21.62	PK
	H/V	2390.00	43.39	31.2	54	10.61	AV
	H/V	4824.00	56.46	2.7	74	17.54	PK
	H/V	4824.00	52.61	2.7	54	1.39	AV
M	H/V	4874.00	54.83	2.67	74	19.17	PK
	H/V	4874.00	50.75	2.67	54	3.25	AV
H	H/V	2483.50	52.61	31.19	74	21.39	PK
	H/V	2483.50	43.87	31.19	54	10.13	AV
	H/V	4924.00	56.28	2.77	74	17.72	PK
	H/V	4924.00	52.39	2.77	54	1.61	AV

802.11g

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H/V	2390.00	51.86	31.2	74	22.14	PK
	H/V	2390.00	42.79	31.2	54	11.21	AV
	H/V	4824.00	52.84	2.7	74	21.16	PK
	H/V	4824.00	47.91	2.7	54	6.09	AV
M	H/V	4874.00	50.27	2.67	74	23.73	PK
	H/V	4874.00	46.44	2.67	54	7.56	AV
H	H/V	2483.50	51.65	31.19	74	22.35	PK
	H/V	2483.50	42.42	31.19	54	11.58	AV
	H/V	4924.00	51.61	2.77	74	22.39	PK
	H/V	4924.00	47.82	2.77	54	6.18	AV

**TEST REPORT**

802.11n(HT20)

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H/V	2390.00	52.05	31.2	74	21.95	PK
	H/V	2390.00	42.86	31.2	54	11.14	AV
	H/V	4824.00	55.26	2.7	74	18.74	PK
	H/V	4824.00	51.34	2.7	54	2.66	AV
M	H/V	4874.00	53.72	2.67	74	20.28	PK
	H/V	4874.00	48.88	2.67	54	5.12	AV
H	H/V	2483.50	52.57	31.19	74	21.43	PK
	H/V	2483.50	43.69	31.19	54	10.31	AV
	H/V	4924.00	54.74	2.77	74	19.26	PK
	H/V	4924.00	49.63	2.77	54	4.37	AV

802.11n(HT40)

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2390.00	60.47	31.2	74	13.53	PK
	H	2390.00	52.38	31.2	54	1.62	AV
	H	4844.00	53.81	2.9	74	20.19	PK
	H	4844.00	48.64	2.9	54	5.36	AV
M	H	4874.00	52.75	2.67	74	21.25	PK
	H	4874.00	47.39	2.67	54	6.61	AV
H	H	2483.50	61.73	31.19	74	12.27	PK
	H	2483.50	52.48	31.19	54	1.52	AV
	H	4904.00	53.16	2.73	74	20.84	PK
	H	4904.00	48.05	2.73	54	5.95	AV

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.  
 2. Corrected Reading = Original Receiver Reading + Correct Factor  
 3. Margin = Limit - Corrected Reading

**TEST REPORT**

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,  
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,  
Limit = 40.00dBuV/m.  
Then Correct Factor =  $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$ ;  
Corrected Reading =  $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$ ;  
Margin =  $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$ .

## 8 Power line conducted emission


Test result: Pass

### 8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### 8.2 Test Configuration



**TEST REPORT****8.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50  $\Omega$  LISN port (to which the EUT is connected), where permitted, terminated into a 50  $\Omega$  measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50  $\Omega$  measuring port is terminated by a measuring instrument having 50  $\Omega$  input impedance. All other ports are terminated in 50  $\Omega$  loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

**TEST REPORT**

**8.4 Test Results of Power line conducted emission**

**Charging mode**

**Test Curve:**




**Test Data:**

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.19	58.89	64.21	5.32	*	54.21	*
0.25	55.14	61.76	6.62	*	51.76	*
0.32	51.06	59.78	8.72	*	49.78	*
0.62	*	56.00	*	*	46.00	*
6.50	*	60.00	*	*	50.00	*
19.40	*	60.00	*	*	50.00	*

Note: \*means margin is more than 10dB.

## TEST REPORT

### Test Curve:



### Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.15	60.64	66.00	5.36	*	56.00	*
0.19	59.33	64.08	4.75	*	54.08	*
0.25	53.76	61.70	7.94	*	51.70	*
0.62	*	56.00	*	*	46.00	*
6.50	*	60.00	*	*	50.00	*
19.40	*	60.00	*	*	50.00	*

Note: \*means margin is more than 10dB.

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

## 9 Occupied Bandwidth

Test result: Tested

### 9.1 Limit


None

### 9.2 Measurement Procedure

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

### 9.3 Test Configuration



### 9.4 The results of Occupied Bandwidth

Please refer to Appendix A

## 10 Antenna requirement

**Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Result:**

EUT uses a permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

## TEST REPORT

### Appendix A: Test results


#### 1. RF Output Power


##### 1.1 Test Result and Data

WLAN Peak Output Power						
Mode	Test Frequency (MHz)	Ant	Max Power (dBm)	Limit (dBm)	EIRP (dBm)	Result
802.11b	2412	Ant0	12.83	30	16.66	Pass
802.11b	2437	Ant0	13.50	30	17.33	Pass
802.11b	2462	Ant0	14.10	30	17.93	Pass
802.11g	2412	Ant0	13.29	30	17.12	Pass
802.11g	2437	Ant0	13.86	30	17.69	Pass
802.11g	2462	Ant0	15.57	30	19.40	Pass
802.11n (HT20)	2412	Ant0	12.46	30	16.29	Pass
802.11n (HT20)	2437	Ant0	13.06	30	16.89	Pass
802.11n (HT20)	2462	Ant0	14.64	30	18.47	Pass
802.11n (HT40)	2422	Ant0	12.59	30	16.42	Pass
802.11n (HT40)	2437	Ant0	13.27	30	17.10	Pass
802.11n (HT40)	2452	Ant0	13.98	30	17.81	Pass

Conclusion: The maximum EIRP = 15.57dBm+3.83dBi = 19.40dBm = 0.087W which is lower than the limit of 4W listed in RSS-247.

##### 1.2 Test Plots







## 2. Minimum 6dB bandwidth


### 2.1 Test Result and Data


WLAN Occupied 6dB Bandwidth				
Mode	Test Frequency (MHz)	Ant	Occupied Bandwidth (MHz)	Result
802.11b	2412	Ant0	9.02	Pass
802.11b	2437	Ant0	9.06	Pass
802.11b	2462	Ant0	8.57	Pass
802.11g	2412	Ant0	16.37	Pass
802.11g	2437	Ant0	16.37	Pass
802.11g	2462	Ant0	16.38	Pass
802.11n (HT20)	2412	Ant0	17.57	Pass
802.11n (HT20)	2437	Ant0	17.57	Pass
802.11n (HT20)	2462	Ant0	17.58	Pass

## TEST REPORT

802.11n (HT40)	2422	Ant0	35.81	Pass
802.11n (HT40)	2437	Ant0	35.99	Pass
802.11n (HT40)	2452	Ant0	35.75	Pass

### 2.2 Test Plots






## TEST REPORT


### 3. Occupied Bandwidth

#### 3.1 Test Result and Data

WLAN 99% Occupied Bandwidth				
Mode	Test Frequency (MHz)	Ant	99% Occupied Bandwidth (MHz)	Result
802.11b	2412	Ant0	13.485	Pass
802.11b	2437	Ant0	13.492	Pass
802.11b	2462	Ant0	13.415	Pass
802.11g	2412	Ant0	16.963	Pass
802.11g	2437	Ant0	16.988	Pass
802.11g	2462	Ant0	16.977	Pass
802.11n (HT20)	2412	Ant0	17.904	Pass
802.11n (HT20)	2437	Ant0	17.906	Pass
802.11n (HT20)	2462	Ant0	17.868	Pass
802.11n (HT40)	2422	Ant0	36.473	Pass
802.11n (HT40)	2437	Ant0	36.574	Pass
802.11n (HT40)	2452	Ant0	36.530	Pass

#### 3.2 Test Plots







### 4. Power Spectral Density


#### 4.1 Test Result and Data


WLAN Peak Power Spectral Density						
Mode	Test Frequency (MHz)	Ant	PSD (dBm)	RBW (kHz)	Limit (dBm)	Result
802.11b	2412	Ant0	0.962	100	8	Pass
802.11b	2437	Ant0	1.095	100	8	Pass
802.11b	2462	Ant0	1.871	100	8	Pass
802.11g	2412	Ant0	-2.967	100	8	Pass
802.11g	2437	Ant0	-3.559	100	8	Pass
802.11g	2462	Ant0	-2.152	100	8	Pass
802.11n (HT20)	2412	Ant0	-5.519	100	8	Pass
802.11n (HT20)	2437	Ant0	-3.924	100	8	Pass
802.11n (HT20)	2462	Ant0	-2.406	100	8	Pass

## TEST REPORT

802.11n (HT40)	2422	Ant0	-6.665	100	8	Pass
802.11n (HT40)	2437	Ant0	-5.712	100	8	Pass
802.11n (HT40)	2452	Ant0	-4.904	100	8	Pass

### 4.2 Test Plots





**TEST REPORT**

5. Emission outside the frequency band

5.1 Test Result and Data

WLAN Transmitter Spurious Emission						
Mode	Test Frequency (MHz)	Ant	Plot No.	Frequency Range	Emission (dBm)	Result
802.11b	2412	Ant0	1	Reference Level	1.10	Pass
802.11b	2412	Ant0	2	Band Edge	-50.78	Pass
802.11b	2412	Ant0	3	30MHz~2310MHz	-55.52	Pass
802.11b	2412	Ant0	4	2500MHz~5000MHz	-39.26	Pass
802.11b	2412	Ant0	5	5000MHz~25000MHz	-41.81	Pass
802.11b	2437	Ant0	1	Reference Level	1.89	Pass
802.11b	2437	Ant0	2	Band Edge	-57.12	Pass
802.11b	2437	Ant0	3	30MHz~2310MHz	-57.29	Pass
802.11b	2437	Ant0	4	2500MHz~5000MHz	-38.64	Pass
802.11b	2437	Ant0	5	5000MHz~25000MHz	-42.34	Pass
802.11b	2462	Ant0	1	Reference Level	2.36	Pass
802.11b	2462	Ant0	2	Band Edge	-53.68	Pass
802.11b	2462	Ant0	3	30MHz~2310MHz	-56.30	Pass
802.11b	2462	Ant0	4	2500MHz~5000MHz	-38.80	Pass
802.11b	2462	Ant0	5	5000MHz~25000MHz	-40.26	Pass
802.11g	2412	Ant0	1	Reference Level	-3.20	Pass
802.11g	2412	Ant0	2	Band Edge	-43.11	Pass
802.11g	2412	Ant0	3	30MHz~2310MHz	-55.93	Pass
802.11g	2412	Ant0	4	2500MHz~5000MHz	-48.31	Pass
802.11g	2412	Ant0	5	5000MHz~25000MHz	-41.30	Pass
802.11g	2437	Ant0	1	Reference Level	-2.53	Pass
802.11g	2437	Ant0	2	Band Edge	-57.10	Pass
802.11g	2437	Ant0	3	30MHz~2310MHz	-55.21	Pass
802.11g	2437	Ant0	4	2500MHz~5000MHz	-48.43	Pass
802.11g	2437	Ant0	5	5000MHz~25000MHz	-42.21	Pass
802.11g	2462	Ant0	1	Reference Level	-1.26	Pass
802.11g	2462	Ant0	2	Band Edge	-51.88	Pass

**TEST REPORT**

802.11g	2462	Ant0	3	30MHz~2310MHz	-55.41	Pass
802.11g	2462	Ant0	4	2500MHz~5000MHz	-47.76	Pass
802.11g	2462	Ant0	5	5000MHz~25000MHz	-41.56	Pass
802.11n (HT20)	2412	Ant0	1	Reference Level	-4.12	Pass
802.11n (HT20)	2412	Ant0	2	Band Edge	-42.42	Pass
802.11n (HT20)	2412	Ant0	3	30MHz~2310MHz	-55.77	Pass
802.11n (HT20)	2412	Ant0	4	2500MHz~5000MHz	-50.17	Pass
802.11n (HT20)	2412	Ant0	5	5000MHz~25000MHz	-41.78	Pass
802.11n (HT20)	2437	Ant0	1	Reference Level	-3.41	Pass
802.11n (HT20)	2437	Ant0	2	Band Edge	-56.90	Pass
802.11n (HT20)	2437	Ant0	3	30MHz~2310MHz	-55.45	Pass
802.11n (HT20)	2437	Ant0	4	2500MHz~5000MHz	-49.76	Pass
802.11n (HT20)	2437	Ant0	5	5000MHz~25000MHz	-40.61	Pass
802.11n (HT20)	2462	Ant0	1	Reference Level	-2.36	Pass
802.11n (HT20)	2462	Ant0	2	Band Edge	-53.12	Pass
802.11n (HT20)	2462	Ant0	3	30MHz~2310MHz	-55.85	Pass
802.11n (HT20)	2462	Ant0	4	2500MHz~5000MHz	-48.95	Pass
802.11n (HT20)	2462	Ant0	5	5000MHz~25000MHz	-41.48	Pass
802.11n (HT40)	2422	Ant0	1	Reference Level	-6.58	Pass
802.11n (HT40)	2422	Ant0	2	Band Edge	-44.36	Pass
802.11n (HT40)	2422	Ant0	3	30MHz~2310MHz	-53.81	Pass
802.11n (HT40)	2422	Ant0	4	2500MHz~5000MHz	-49.73	Pass
802.11n (HT40)	2422	Ant0	5	5000MHz~25000MHz	-41.24	Pass
802.11n (HT40)	2437	Ant0	1	Reference Level	-6.25	Pass
802.11n (HT40)	2437	Ant0	2	Band Edge	-55.46	Pass
802.11n (HT40)	2437	Ant0	3	30MHz~2310MHz	-52.21	Pass
802.11n (HT40)	2437	Ant0	4	2500MHz~5000MHz	-49.48	Pass