

Meas.1 Body Plane with Top Edge 0mm on 0 Channel in Bluetooth mode with Ant 1

Date: 2025.08.30

Communication System Band: 1; Frequency: 2402 MHz; Duty Cycle: 1:1.309

Medium parameters used (interpolated): $f = 2402$ MHz; $\sigma = 1.721$ S/m; $\epsilon_r = 39.919$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.3°C Liquid Temperature: 21.1°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7664; ConvF(7.8, 7.8, 7.8); Calibrated: 2025.06.30;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2025.03.05
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1858
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch0/Area Scan (51x81x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.123 W/kg

Ch0/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.482 V/m; Power Drift = 0.08 dB


Peak SAR (extrapolated) = 0.708 W/kg

SAR(1 g) = 0.125 W/kg; SAR(10 g) = 0.034 W/kg

Smallest distance from peaks to all points 3 dB below = 7.5 mm

Ratio of SAR at M2 to SAR at M1 = 55.5%

Maximum value of SAR (measured) = 0.135 W/kg



0 dB = 0.135 W/kg

--BLANK BELOW--