

RF Exposure Evaluation

Test report
On Behalf of
Shenzhen Wofeng Outdoor Sports Co., Ltd.
For
Headphone
Model No.: OM BT01, OM BT02, OM BT03, OM BT04,
OMBT05 ,OMBT06, OM BT07

FCC ID: 2AXHJ-OMBTX

Prepared for : **Shenzhen Wofeng Outdoor Sports Co., Ltd.**
Room2203B, Building A, Yabao Road 1,Nankeng Community,
Bantian Street, Longgang District, Shenzhen, China

Prepared By : **Shenzhen HUAK Testing Technology Co., Ltd.**
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai
Street, Bao'an District, Shenzhen City, China

Date of Test: **Aug. 27, 2020 ~ Sep. 07, 2020**

Date of Report: **Sep. 07, 2020**

1 General Description of EUT

Product Name:	Headphone
Model/Type reference:	OM BT01
Serial Model:	OM BT02, OM BT03, OM BT04, OM BT05, OM BT06, OM BT07
Model Difference	All models have the same functionality, software and electronics, only model names may differ. Test sample model: OM BT01
Trade Mark	OutdoorMaster
FCC ID	2AXHJ-OMBTX
Hardware Version:	V1.0
Software Version:	V1.8
Version:	Supported EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79CH
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	0 dBi
Power supply:	DC 3.7V from battery

2 RF Exposure Compliance Requirement

2.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation

distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

3 EUT RF Exposure

GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-1.029	0±1	1	1.259	0.390	3.0
Middle (2441MHz)	-1.456	0±1	1	1.259	0.393	
Highest (2480MHz)	-2.148	-2±1	-1	0.794	0.250	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

π/4DQPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-0.002	0±1	1	1.259	0.390	3.0
Middle (2441MHz)	-0.364	0±1	1	1.259	0.393	
Highest (2480MHz)	-0.928	-1±1	0	1.000	0.315	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

8DPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	0.069	0±1	1	1.259	0.390	3.0
Middle (2441MHz)	-0.256	0±1	1	1.259	0.393	
Highest (2480MHz)	-0.946	-1±1	0	1.000	0.315	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: HK2009042435-E