

Antenna Specification

Product Model: Archer C86(US) 1.0

Version: 1.0

Date: 2022/10/19

Checked By: 宫新宇

TP-Link Corporation Limited
Room 901, 9/F. , New East Ocean Centre, 9 Science Museum
Road, Tsim Sha Tsui, Kowloon, Hong Kong

Index

I.	Antenna Distribution.....	3
II.	Electrical Characteristics	4
III.	Antenna Peak Gain.....	6
IV.	Antenna Radiation Pattern	7

I. Antenna Distribution

MR6500(EU) 2.0





II. Electrical Characteristics

Ant1	
Frequency	2400~2500MHz
Impedance	50Ohm
Antenna Type	Franklin
Antenna Gain	2.0dBi@2400~2500MHz
Radiation pattern	Omni-Directional

Ant2	
Frequency	5150~5850MHz
Impedance	50Ohm
Antenna Type	Franklin
Antenna Gain	3.0dBi@5150~5850MHz
Radiation pattern	Omni-Directional

Ant3	
Frequency	2400~2500MHz
Impedance	50Ohm
Antenna Type	Franklin
Antenna Gain	2.0dBi@2400~2500MHz
Radiation pattern	Omni-Directional

Ant4	
Frequency	5150~5850MHz
Impedance	50Ohm
Antenna Type	Franklin
Antenna Gain	3.0dBi@5150~5850MHz
Radiation pattern	Omni-Directional

Ant5	
Frequency	2400~2500MHz
Impedance	50Ohm
Antenna Type	Franklin
Antenna Gain	2.0dBi@2400~2500MHz
Radiation pattern	Omni-Directional

Ant6	
Frequency	5150~5850MHz
Impedance	50Ohm
Antenna Type	Franklin

Antenna Gain	3.0dBi@5150~5850MHz
Radiation pattern	Omni-Directional

III. Antenna Peak Gain

Ant1											
Freq (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain(dBi)	1.36	1.53	1.72	1.86	1.93	1.95	1.89	1.75	1.78	1.65	1.67

Ant2											
Freq (MHz)	5150	5200	5250	5300	5350	5400	5450	5500	5550	5600	5650
Gain(dBi)	2.32	2.45	2.89	2.55	2.37	2.67	2.34	2.44	2.65	2.79	2.92
Freq (MHz)	5700	5750	5800	5850							
Gain(dBi)	2.88	2.95	2.75	2.56							

Ant3											
Freq (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain(dBi)	1.42	1.61	1.66	1.9	1.97	1.91	1.77	1.68	1.78	1.62	1.67

Ant4											
Freq (MHz)	5150	5200	5250	5300	5350	5400	5450	5500	5550	5600	5650
Gain(dBi)	2.42	2.35	2.69	2.65	2.47	2.57	2.44	2.44	2.65	2.85	2.94
Freq (MHz)	5700	5750	5800	5850							
Gain(dBi)	2.78	2.85	2.73	2.55							

Ant5											
Freq (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain(dBi)	1.37	1.53	1.82	1.85	1.96	1.95	1.89	1.65	1.78	1.7	1.67

Ant6											
Freq (MHz)	5150	5200	5250	5300	5350	5400	5450	5500	5550	5600	5650
Gain(dBi)	2.52	2.45	2.8	2.55	2.47	2.72	2.54	2.44	2.69	2.72	2.88
Freq (MHz)	5700	5750	5800	5850							
Gain(dBi)	2.83	2.95	2.7	2.56							

IV. Antenna Radiation Pattern



