

FCC RF EXPOSURE REPORT


FCC ID: 2AXJ4EAP225V4

Project No. : 2108C221A
Equipment : AC1350 Wireless Dual Band Gigabit Ceiling Mount Access Point
Brand Name : tp-link
Test Model : EAP225
Series Model : N/A
Applicant : TP-Link Corporation Limited
Address : Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road,
Tsim Sha Tsui, Kowloon, Hong Kong
Manufacturer : TP-Link Corporation Limited
Address : Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road,
Tsim Sha Tsui, Kowloon, Hong Kong
Date of Receipt : Jan. 04, 2022
Date of Test : Jan. 05, 2022 ~ Feb. 23, 2022
Issued Date : Mar. 16, 2022
Report Version : R01
Test Sample : Engineering Sample No.: DG2022010453
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Antony Liang



Approved by : Chay Cai

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792

People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com



TESTING CERT #5123.02

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Mar. 08, 2022
R01	Revised the product name.	Mar. 16, 2022

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

BTL's Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

For 2.4GHz:

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	tp-link	EAP225 4.0	PIFA	N/A	3.98
2	tp-link	EAP225 4.0	PIFA	N/A	3.99
3	tp-link	EAP225 4.0	PIFA	N/A	3.99

Note:

- 1) This EUT supports CDD, and all antennas are not exactly the same, Directional gain = G_{ANT} +Array Gain. For power measurements, Array Gain=0dB ($N_{ANT} \leq 4$), so the Directional gain=3.99. For power spectral density measurements, $N_{ANT}=3$, $N_{SS} = 1$. So the Directional gain= G_{ANT} +Array Gain= $G_{ANT}+10\log(N_{ANT}/ N_{SS})$ dBi=3.99+10log(3/1)dBi=8.76. Then, the power spectral density limit is 8-(8.76-6)=5.24.
- 2) The antenna gain is provided by the manufacturer.

For 5GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	tp-link	EAP225 4.0	PIFA	N/A	4.95
2	tp-link	EAP225 4.0	PIFA	N/A	4.87

Note:

- 1) This EUT supports CDD, and all antennas are not equal, Directional gain = G_{ANT} +Array Gain. For power measurements, Array Gain=0dB ($N_{ANT} \leq 4$), so the Directional gain=4.95. For power spectral density measurements, $N_{ANT}=2$, $N_{SS} = 1$. So the Directional gain= G_{ANT} +Array Gain= $G_{ANT}+10\log(N_{ANT}/ N_{SS})$ dBi=4.95+10log(2/1)dBi=7.96. Then, the UNII-1 power spectral density limit is 17-(7.96-6)=15.04, the UNII-3 power spectral density limit is 30-(7.96-6)=28.04.
- 2) Beamforming gain = 3 dB. Then, Directional gain=3+4.95=7.95. Then, the Output Power limit is 30-(7.95-6)=28.05.
- 3) The antenna gain and beamforming gain are provided by the manufacturer.

Table for Antenna Configuration:
For 2.4GHz:

Operating Mode	TX Mode	3TX
IEEE 802.11b		V(Ant. 1 + Ant. 2 + Ant. 3)
IEEE 802.11g		V(Ant. 1 + Ant. 2 + Ant. 3)
IEEE 802.11n(HT20)		V(Ant. 1 + Ant. 2 + Ant. 3)
IEEE 802.11n(HT40)		V(Ant. 1 + Ant. 2 + Ant. 3)

For 5GHz:

For Non Beamforming:

Operating Mode	TX Mode	2TX
IEEE 802.11a		V (Ant. 1 + Ant. 2)
IEEE 802.11n(HT20)		V (Ant. 1 + Ant. 2)
IEEE 802.11n(HT40)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT20)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT40)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT80)		V (Ant. 1 + Ant. 2)

For Beamforming:

Operating Mode	TX Mode	2TX
IEEE 802.11n(HT20)		V (Ant. 1 + Ant. 2)
IEEE 802.11n(HT40)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT20)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT40)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT80)		V (Ant. 1 + Ant. 2)

3. TEST RESULTS

For 2.4GHz:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.99	2.5061	24.65	291.7427	0.14553	1	Complies

For 5GHz Non Beamforming:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
4.95	3.1261	22.70	186.2087	0.11586	1	Complies

For 5GHz Beamforming:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
7.95	6.2373	21.91	155.2387	0.19273	1	Complies

For the max simultaneous transmission MPE:

Ratio		Total	Limit of Ratio	Test Result
2.4GHz	5GHz			
0.14553	0.19273	0.33826	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

End of Test Report