

Product Number: 3101505257

Product Name: Antenna

TP-LINK®

TP-LINK®

Antenna Specification



Product Number: 3101505257

Product Name: Antenna

TP-LINK®

COPYRIGHT & TRADEMARKS

Specifications are subject to change without notice. **TP-LINK®** is a registered trademark of TP-LINK TECHNOLOGIES CO., LTD. Other brands and product names are trademarks or registered trademarks of their respective holders.

No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK TECHNOLOGIES CO., LTD. Copyright © 2011 TP-LINK TECHNOLOGIES CO., LTD. All rights reserved.

<http://www.tp-link.com>

Product Number: 3101505257

Product Name: Antenna

TP-LINK®

Specification for Approval

Date: _____

File No.: _____

Version: 1.0

Customer: _____ / _____

Customer P/N: _____ / _____

TP-LINK P/N: 3101505257

Description:

Antenna|2.4-2.5GHz|1.75 dBi|LP|Omni|2W|Weld|50mm|D1.13mm|H200|无|1273-JW050REV1.0|绿色|不防水|[自制/H200 贴壳天线]

TP-LINK Checked By:

Customer Approved By:

TP-LINK®

TP-LINK TECHNOLOGIES CO., LTD.

South Building, No.5 Keyuan Road,
Central Zone, Science & Technology Park,
Nanshan, Shenzhen, P. R. China

TEL: + 86 755 26612350


+ 86 755 26504400

[http:// www.tp-link.com](http://www.tp-link.com)

Table of Contents

1.	Specification	2
2.	Characteristics and Reliability Test.....	2
3.	Mechanical Drawing and Material Description	4
4.	RoHS Test Report	5
4.	Antenna S-Parameters Measurement Data	6
5.	Antenna Radiation Pattern Measurement Data	7
6.	Packing Drawing	错误!未定义书签。

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	2.4~2.5GHz
Impedance	50 Ohm
VSWR	≤ 2.0
Antenna Gain	1.75 dBi@2.4~2.5GHz
Max Input Power	≤ 2W
Polarization	Linear
Radiation pattern	Omni-Directional
B. Material & Mechanical Characteristics	
Material of Radiator	PCB(FR-4+Cu)
Cable Type	O.D. 1.13mm (Black)
Connector Type	Weld
Connector Pull Test	1.5 kg
C. Environmental Characteristics	
Operation Temperature	-10°C ~ +60°C
Storage Temperature	-40°C ~ +70°C

2. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements
C1	VSWR	Set DUT on Network Analyzer; make	Directive DUT specification

Product Number: 3101505257

Product Name: Antenna

TP-LINK®


		individual calibration to test	
C2	Antenna Gain	Set DUT on Antenna Chamber; make individual calibration to test	Directive DUT specification
M1	Vibration	MIL-STD-202G, 201 A Amplitude: 0.03 inch (0.76mm); Freq.: 10 to 55 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol. <=5%
M2	Random Drop	Height: 1.5 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol. <=5%
M3	Drop Test	Combine DUT with router; Height: 0.6 Meter; 1 direction; 3 times for the direction	1. No parts separated 2. Frequency Tol. <=5%
M4	Terminal- Pull Test	MIL-STD-202G, 211A, cond. A Holding with individual specification; force applied to axis of terminal	1. Directive DUT specification 2. Frequency Tol. <=5%
M5	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	SE-GS-90T Temp: 35°C; RH: 93%±3%; NaCl solution proportion: 1.026 ~ 1.041; Time: 12 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. <=5%
E2	Thermal Shock	1 Cycle: -20°C (30 minutes) to +70°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. <=5%
E3	Life (High Temp.)	MIL-STD-202G, 108A, cond. A Temp: 70°C; Time: 8 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. <=5%

Product Number: 3101505257

Product Name: Antenna

TP-LINK®

3. Mechanical Drawing and Material Description



Product Number: 3101505257


Product Name: Antenna



4. RoHS Test Report

N O .	Product Model	Constit uents	Material	Test Result for RoHS-corresponding Substance						PFOS	Halogen				Series No.	Date	Title	Test Agent	
				Cd	Pb	Hg	Cr(VI)	PBB s	PBD Es	PFOS	F	Cl	Br	I					
1	3120500035	Cable	Skin	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.		374000	N.D	N.D	N.D	RLSHD000593720060	2011/04/25	Cable	CTI	
			Isolated layer	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.		372000	N.D	N.D	N.D	RLSHD000593720060	2011/04/25	Cable	CTI	
			Mesh	N.D.	N.D.	N.D.	Negative								RLSHD000593720060	2011/04/25	Cable	CTI	
			Center Yarn	N.D.	N.D.	N.D.	Negative								RLSHD000593720060	2011/04/25	Cable	CTI	
3	2051501025	PCB	FR-4	N.D.	5	N.D.	N.D.	N.D.	N.D.		50mg/kg	50m g/kg	50m g/kg	50mg/ kg	NO.CANEC1512596206	2015/08/03	Sub	广州 SGS	

5. Antenna S-Parameters Measurement Data



以上驻波测试结果为天线配合 H200(US)整机的测试数据。


6. Antenna Radiation Pattern Measurement Data

Measurement Equipment Specification	
Microwave Chamber	ETS AMS-8923
Vector Network Analyzer	Agilent E5071C

2400~2500MHz

Freq. (GHz)	2.40	2.41	2.42	2.43	2.44	2.45	2.46	2.47	2.48	2.49	2.50
Effi. (%)	66.94	69.32	70.35	71.32	71.30	71.31	71.52	73.23	73.79	74.17	73.90
Gain (dBi)	0.91	1.26	1.46	1.57	1.60	1.65	1.65	1.69	1.75	1.78	1.76

Theta=90°



以上方向图测试结果为天线配合 H200(US)整机的测试数据。