

802.11g Out-of-Band Emissions - Ant 0

Channel 01 (2412MHz)

Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Spurious Emission



Channel 11 (2462MHz)

High Band Edge



Spurious Emission



802.11n-HT20 Out-of-Band Emissions - Ant 0

Channel 01 (2412MHz)

Low Band Edge



Spurious Emission




Channel 06 (2437MHz)

Spurious Emission



Channel 11 (2462MHz)

High Band Edge



Spurious Emission



802.11n-HT40 Out-of-Band Emissions - Ant 0

Channel 03 (2422MHz)

Low Band Edge

Spurious Emission



Channel 06 (2437MHz)

Spurious Emission



Channel 09 (2452MHz)

High Band Edge

Spurious Emission



802.11ax-HE20 Out-of-Band Emissions - Ant 0

Channel 01 (2412MHz)

Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Spurious Emission



Spurious Emission



High Band Edge




802.11ax-HE40 Out-of-Band Emissions - Ant 0

Channel 03 (2422MHz)

Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Spurious Emission



Channel 09 (2452MHz)

High Band Edge



Spurious Emission



802.11b Out-of-Band Emissions - Ant 1

Channel 01 (2412MHz)

Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Spurious Emission



Channel 11 (2462MHz)

High Band Edge



Spurious Emission



802.11g Out-of-Band Emissions - Ant 1

Channel 01 (2412MHz)

Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Spurious Emission



Channel 11 (2462MHz)

High Band Edge



Spurious Emission



802.11n-HT20 Out-of-Band Emissions - Ant 1

Channel 01 (2412MHz)

Low Band Edge



Spurious Emission




Channel 06 (2437MHz)

Spurious Emission



Channel 11 (2462MHz)

High Band Edge



Spurious Emission



802.11n-HT40 Out-of-Band Emissions - Ant 1

Channel 03 (2422MHz)

Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Spurious Emission



Channel 09 (2452MHz)

High Band Edge



Spurious Emission



802.11ax-HE20 Out-of-Band Emissions - Ant 1

Channel 01 (2412MHz)

Low Band Edge



Spurious Emission




Channel 06 (2437MHz)

Spurious Emission



Channel 11 (2462MHz)

High Band Edge




Spurious Emission



802.11ax-HE40 Out-of-Band Emissions - Ant 1

Channel 03 (2422MHz)

Low Band Edge



Spurious Emission




Channel 06 (2437MHz)

Spurious Emission



Channel 09 (2452MHz)

High Band Edge



Spurious Emission



7.6. Radiated Spurious Emission Measurement

7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

| FCC Part 15 Subpart C Paragraph 15.209 | | |
|--|--|-------------------------------|
| Frequency [MHz] | Field Strength [$\mu\text{V}/\text{m}$] | Measured Distance [Meters] |
| 0.009 - 0.490 | 2400/F (kHz) | 300 |
| 0.490 - 1.705 | 24000/F (kHz) | 30 |
| 1.705 - 30 | 30 | 30 |
| 30 - 88 | 100 | 3 |
| 88 - 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

7.6.2. Test Procedure Used

ANSI C63.10 Section 6.3 (General Requirements)

ANSI C63.10 Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 Section 6.6 (Standard test method above 1GHz)

7.6.3. Test Setting

Table 1 - RBW as a function of frequency

| Frequency | RBW |
|---------------|---------------|
| 9 ~ 150 kHz | 200 ~ 300 Hz |
| 0.15 ~ 30 MHz | 9 ~ 10 kHz |
| 30 ~ 1000 MHz | 100 ~ 120 kHz |
| > 1000MHz | 1MHz |

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.

If the EUT duty cycle is $< 98\%$, set $VBW \geq 1/T$. T is the minimum transmission duration.


4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

7.6.4. Test Setup

Below 1GHz Test Setup:




Above 1GHz Test Setup:



7.6.5. Test Result

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4825.000 | 40.87 | 3.64 | 44.51 | -29.49 | 74.00 | Peak |
| 2 | 8386.500 | 31.65 | 13.60 | 45.25 | -28.75 | 74.00 | Peak |
| 3 | * 11922.500 | 26.25 | 19.10 | 45.35 | -28.65 | 74.00 | Peak |

Note:

- "*" , means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4825.000 | 41.06 | 3.64 | 44.69 | -29.31 | 74.00 | Peak |
| 2 | 7545.000 | 30.87 | 13.05 | 43.92 | -30.08 | 74.00 | Peak |
| 3 | * 11778.000 | 26.67 | 19.42 | 46.09 | -27.91 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4876.000 | 40.06 | 3.73 | 43.79 | -30.21 | 74.00 | Peak |
| 2 | 7315.500 | 32.00 | 12.20 | 44.20 | -29.80 | 74.00 | Peak |
| 3 | * 11489.000 | 24.73 | 20.03 | 44.76 | -29.24 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4876.000 | 40.32 | 3.73 | 44.05 | -29.95 | 74.00 | Peak |
| 2 | 8148.500 | 30.78 | 13.50 | 44.28 | -29.72 | 74.00 | Peak |
| 3 | * 11914.000 | 25.61 | 19.11 | 44.72 | -29.28 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | * | 42.03 | 3.82 | 45.85 | -28.15 | 74.00 | Peak |
| 2 | | 33.23 | 12.50 | 45.73 | -28.27 | 74.00 | Peak |
| 3 | | 26.38 | 18.96 | 45.34 | -28.66 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | * 4927.000 | 41.51 | 3.82 | 45.33 | -28.67 | 74.00 | Peak |
| 2 | 8199.500 | 30.17 | 13.52 | 43.69 | -30.31 | 74.00 | Peak |
| 3 | 12169.000 | 26.39 | 18.75 | 45.13 | -28.87 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4825.000 | 38.27 | 3.64 | 41.90 | -32.10 | 74.00 | Peak |
| 2 | 11123.500 | 25.70 | 19.47 | 45.17 | -28.83 | 74.00 | Peak |
| 3 | * 15645.500 | 27.93 | 20.99 | 48.92 | -25.08 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4833.500 | 37.66 | 3.65 | 41.31 | -32.69 | 74.00 | Peak |
| 2 | 8318.500 | 29.95 | 13.57 | 43.53 | -30.47 | 74.00 | Peak |
| 3 | * 11880.000 | 26.05 | 19.19 | 45.24 | -28.76 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4876.000 | 39.76 | 3.73 | 43.48 | -30.52 | 74.00 | Peak |
| 2 | * 7315.500 | 35.50 | 12.20 | 47.69 | -26.31 | 74.00 | Peak |
| 3 | 11387.000 | 25.04 | 19.88 | 44.92 | -29.08 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4876.000 | 39.02 | 3.73 | 42.75 | -31.25 | 74.00 | Peak |
| 2 | 8157.000 | 29.95 | 13.50 | 43.45 | -30.55 | 74.00 | Peak |
| 3 | * 11846.000 | 25.99 | 19.27 | 45.25 | -28.75 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 7562.000 | 29.92 | 13.07 | 42.98 | -31.02 | 74.00 | Peak |
| 2 | 11948.000 | 26.26 | 19.04 | 45.30 | -28.70 | 74.00 | Peak |
| 3 | * 15747.500 | 28.75 | 20.74 | 49.49 | -24.51 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 8412.000 | 30.00 | 13.62 | 43.61 | -30.39 | 74.00 | Peak |
| 2 | 11922.500 | 25.81 | 19.10 | 44.91 | -29.09 | 74.00 | Peak |
| 3 | * 15824.000 | 28.30 | 20.55 | 48.84 | -25.16 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11n-HT20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4723.000 | 37.63 | 3.45 | 41.09 | -32.91 | 74.00 | Peak |
| 2 | 8293.000 | 30.35 | 13.56 | 43.91 | -30.09 | 74.00 | Peak |
| 3 | * 11999.000 | 26.03 | 18.92 | 44.95 | -29.05 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11n-HT20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 4825.000 | 38.66 | 3.64 | 42.30 | -31.70 | 74.00 | Peak |
| 2 | 8225.000 | 29.61 | 13.53 | 43.14 | -30.86 | 74.00 | Peak |
| 3 | * 11472.000 | 24.74 | 20.01 | 44.75 | -29.25 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11n-HT20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4884.500 | 39.27 | 3.74 | 43.02 | -30.98 | 74.00 | Peak |
| 2 | * 7315.500 | 35.60 | 12.20 | 47.80 | -26.20 | 74.00 | Peak |
| 3 | 11701.500 | 25.13 | 19.59 | 44.73 | -29.27 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11n-HT20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4876.000 | 39.96 | 3.73 | 43.69 | -30.31 | 74.00 | Peak |
| 2 | 7324.000 | 31.60 | 12.24 | 43.84 | -30.16 | 74.00 | Peak |
| 3 | * 8157.000 | 30.64 | 13.50 | 44.14 | -29.86 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11n-HT20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 5046.000 | 37.21 | 4.03 | 41.23 | -32.77 | 74.00 | Peak |
| 2 | 7698.000 | 29.49 | 13.18 | 42.67 | -31.33 | 74.00 | Peak |
| 3 | * 8208.000 | 30.03 | 13.52 | 43.55 | -30.45 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11n-HT20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 8267.500 | 29.73 | 13.55 | 43.28 | -30.72 | 74.00 | Peak |
| 2 | 12407.000 | 27.52 | 18.50 | 46.02 | -27.98 | 74.00 | Peak |
| 3 | * 15832.500 | 28.58 | 20.53 | 49.10 | -24.90 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2422MHz by 802.11n-HT40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 8369.500 | 30.30 | 13.60 | 43.90 | -30.10 | 74.00 | Peak |
| 2 | 11990.500 | 25.81 | 18.94 | 44.75 | -29.25 | 74.00 | Peak |
| 3 | * 15960.000 | 29.28 | 20.21 | 49.49 | -24.51 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2422MHz by 802.11n-HT40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 7536.500 | 29.95 | 13.05 | 42.99 | -31.01 | 74.00 | Peak |
| 2 | 8335.500 | 30.05 | 13.58 | 43.63 | -30.37 | 74.00 | Peak |
| 3 | * 11939.500 | 25.64 | 19.06 | 44.70 | -29.30 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11n-HT40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 5012.000 | 37.18 | 3.97 | 41.15 | -32.85 | 74.00 | Peak |
| 2 | 8318.500 | 29.69 | 13.57 | 43.27 | -30.73 | 74.00 | Peak |
| 3 | * 11302.000 | 25.15 | 19.75 | 44.89 | -29.11 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11n-HT40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 7477.000 | 30.13 | 12.91 | 43.05 | -30.95 | 74.00 | Peak |
| 2 | 8310.000 | 29.44 | 13.57 | 43.01 | -30.99 | 74.00 | Peak |
| 3 | * 11990.500 | 26.01 | 18.94 | 44.95 | -29.05 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2452MHz by 802.11n-HT40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 7621.500 | 29.09 | 13.12 | 42.21 | -31.79 | 74.00 | Peak |
| 2 | 8259.000 | 30.29 | 13.55 | 43.84 | -30.16 | 74.00 | Peak |
| 3 | * 11939.500 | 25.76 | 19.06 | 44.82 | -29.18 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2452MHz by 802.11n-HT40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 8352.500 | 30.30 | 13.59 | 43.89 | -30.11 | 74.00 | Peak |
| 2 | 11914.000 | 25.90 | 19.11 | 45.01 | -28.99 | 74.00 | Peak |
| 3 | * 15832.500 | 27.99 | 20.53 | 48.52 | -25.48 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11ax-HE20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4842.000 | 37.22 | 3.67 | 40.89 | -33.11 | 74.00 | Peak |
| 2 | 8361.000 | 30.02 | 13.59 | 43.61 | -30.39 | 74.00 | Peak |
| 3 | * 11472.000 | 24.64 | 20.01 | 44.65 | -29.35 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11ax-HE20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4825.000 | 38.08 | 3.64 | 41.72 | -32.28 | 74.00 | Peak |
| 2 | 8293.000 | 30.10 | 13.56 | 43.67 | -30.33 | 74.00 | Peak |
| 3 | * 11922.500 | 25.63 | 19.10 | 44.73 | -29.27 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11ax-HE20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4876.000 | 39.13 | 3.73 | 42.86 | -31.14 | 74.00 | Peak |
| 2 | * 7298.500 | 36.15 | 12.12 | 48.28 | -25.72 | 74.00 | Peak |
| 3 | 11854.500 | 25.32 | 19.25 | 44.57 | -29.43 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11ax-HE20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4876.000 | 37.63 | 3.73 | 41.35 | -32.65 | 74.00 | Peak |
| 2 | 8420.500 | 30.71 | 13.62 | 44.33 | -29.67 | 74.00 | Peak |
| 3 | * 11922.500 | 25.62 | 19.10 | 44.72 | -29.28 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11ax-HE20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 4774.000 | 37.81 | 3.54 | 41.35 | -32.65 | 74.00 | Peak |
| 2 | 7647.000 | 29.98 | 13.14 | 43.12 | -30.88 | 74.00 | Peak |
| 3 | * 11973.500 | 26.07 | 18.98 | 45.05 | -28.95 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11ax-HE20 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4842.000 | 37.11 | 3.67 | 40.77 | -33.23 | 74.00 | Peak |
| 2 | 7536.500 | 29.98 | 13.05 | 43.03 | -30.97 | 74.00 | Peak |
| 3 | * 12041.500 | 25.82 | 18.88 | 44.70 | -29.30 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2422MHz by 802.11ax-HE40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4765.500 | 37.40 | 3.53 | 40.93 | -33.07 | 74.00 | Peak |
| 2 | 8174.000 | 29.49 | 13.51 | 43.00 | -31.00 | 74.00 | Peak |
| 3 | * 11905.500 | 26.21 | 19.13 | 45.34 | -28.66 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2422MHz by 802.11ax-HE40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 4842.000 | 37.28 | 3.67 | 40.94 | -33.06 | 74.00 | Peak |
| 2 | 8301.500 | 30.42 | 13.57 | 43.98 | -30.02 | 74.00 | Peak |
| 3 | * 11395.500 | 25.03 | 19.89 | 44.92 | -29.08 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11ax-HE40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 4918.500 | 38.66 | 3.80 | 42.46 | -31.54 | 74.00 | Peak |
| 2 | * 7587.500 | 30.77 | 13.09 | 43.86 | -30.14 | 74.00 | Peak |
| 3 | 8259.000 | 29.76 | 13.55 | 43.31 | -30.69 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11ax-HE40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 7485.500 | 29.55 | 12.95 | 42.50 | -31.50 | 74.00 | Peak |
| 2 | 8259.000 | 30.61 | 13.55 | 44.15 | -29.85 | 74.00 | Peak |
| 3 | * 12024.500 | 26.24 | 18.89 | 45.14 | -28.86 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2452MHz by 802.11ax-HE40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 4816.500 | 36.53 | 3.62 | 40.15 | -33.85 | 74.00 | Peak |
| 2 | 8259.000 | 30.23 | 13.55 | 43.78 | -30.22 | 74.00 | Peak |
| 3 | * 11931.000 | 25.95 | 19.08 | 45.02 | -28.98 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2452MHz by 802.11ax-HE40 | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 8182.500 | 30.18 | 13.51 | 43.69 | -30.31 | 74.00 | Peak |
| 2 | 12024.500 | 25.89 | 18.89 | 44.78 | -29.22 | 74.00 | Peak |
| 3 | * 15662.500 | 27.99 | 20.95 | 48.94 | -25.06 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

The Result of Radiated Emission below 1GHz:

| | | | |
|-----------|---|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-13 |
| Factor | VULB 9162 (30MHz~8GHz) + 6dB Attenuator_2020 | Temp. / Humidity | 23.1°C/49.7% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V/60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 66.860 | 4.21 | 17.99 | 22.20 | -17.80 | 40.00 | Peak |
| 2 | 139.125 | 6.40 | 16.05 | 22.45 | -21.05 | 43.50 | Peak |
| 3 | 171.620 | 8.72 | 16.77 | 25.49 | -18.01 | 43.50 | Peak |
| 4 | 201.205 | 8.16 | 19.19 | 27.35 | -16.15 | 43.50 | Peak |
| 5 | 395.690 | 3.67 | 23.99 | 27.66 | -18.34 | 46.00 | Peak |
| 6 | * 805.030 | 0.01 | 30.60 | 30.61 | -15.39 | 46.00 | Peak |

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
- The amplitude of Radiated emissions (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

| | | | |
|-----------|--|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-13 |
| Factor | VULB 9162 (30MHz~8GHz) + 6dB Attenuator_2020 | Temp. / Humidity | 23.1°C/49.7% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V/60Hz |



| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 35.820 | 10.99 | 19.61 | 30.60 | -9.40 | 40.00 | Peak |
| 2 | * 45.520 | 9.65 | 21.83 | 31.48 | -8.52 | 40.00 | Peak |
| 3 | 81.895 | 15.67 | 14.83 | 30.50 | -9.50 | 40.00 | Peak |
| 4 | 139.610 | 15.46 | 16.04 | 31.50 | -12.00 | 43.50 | Peak |
| 5 | 144.460 | 13.48 | 16.01 | 29.49 | -14.01 | 43.50 | Peak |
| 6 | 951.500 | 0.16 | 32.18 | 32.34 | -13.66 | 46.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
- Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).
- The amplitude of Radiated emissions (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

7.7. Radiated Restricted Band Edge Measurement

7.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

| Frequency (MHz) | Frequency (MHz) | Frequency (MHz) | Frequency (GHz) |
|----------------------------|-----------------------|--------------------|--------------------|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| ¹ 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - 156.52525 | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.7 - 156.9 | 2690 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 162.0125 - 167.17 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 167.72 - 173.2 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 240 - 285 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 322 - 335.4 | 3600 - 4400 | (²) |
| 13.36 - 13.41 | -- | -- | -- |

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

| FCC Part 15 Subpart C Paragraph 15.209 Limits | | |
|---|--------------------------------|-------------------------------|
| Frequency [MHz] | Field Strength [μ V/m] | Measured Distance [Meters] |
| 0.009 - 0.490 | 2400/F (kHz) | 300 |
| 0.490 - 1.705 | 24000/F (kHz) | 30 |
| 1.705 - 30 | 30 | 30 |
| 30 - 88 | 100 | 3 |
| 88 - 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

7.7.2. Test Procedure Used

ANSI C63.10 Section 6.3 (General Requirements)

ANSI C63.10 Section 6.6 (Standard test method above 1GHz)

7.7.3. Test Setting


Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.
If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration.
4. Average Type = Voltage
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to stabilize

7.7.4. Test Setup



7.7.5. Test Result

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2365.048 | 27.57 | 32.11 | 59.68 | -14.32 | 74.00 | Peak |
| 2 | 2390.000 | 26.18 | 32.22 | 58.40 | -15.60 | 74.00 | Peak |
| 3 | * 2411.080 | 78.63 | 32.31 | 110.93 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2387.280 | 16.26 | 32.21 | 48.47 | -5.53 | 54.00 | Average |
| 2 | 2390.000 | 15.83 | 32.22 | 48.05 | -5.95 | 54.00 | Average |
| 3 | * 2411.304 | 74.54 | 32.31 | 106.84 | N/A | N/A | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 2385.656 | 31.35 | 32.20 | 63.55 | -10.45 | 74.00 | Peak |
| 2 | 2390.000 | 29.74 | 32.22 | 61.96 | -12.04 | 74.00 | Peak |
| 3 | * 2411.080 | 84.26 | 32.31 | 116.57 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 2385.264 | 21.44 | 32.20 | 53.64 | -0.36 | 54.00 | Average |
| 2 | 2390.000 | 18.88 | 32.22 | 51.10 | -2.90 | 54.00 | Average |
| 3 | * 2411.192 | 82.40 | 32.31 | 114.70 | N/A | N/A | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|----------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2376.310 | 26.40 | 32.16 | 58.56 | -15.44 | 74.00 | Peak |
| 2 | 2390.000 | 23.77 | 32.22 | 55.99 | -18.01 | 74.00 | Peak |
| 3 | * 2437.870 | 79.87 | 32.42 | 112.29 | N/A | N/A | Peak |
| 4 | 2483.500 | 23.62 | 32.61 | 56.23 | -17.77 | 74.00 | Peak |
| 5 | 2490.120 | 25.96 | 32.64 | 58.60 | -15.40 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1 | 2382.390 | 10.67 | 32.19 | 42.85 | -11.15 | 54.00 | Average |
| 2 | 2390.000 | 9.88 | 32.22 | 42.10 | -11.90 | 54.00 | Average |
| 3 | * 2437.775 | 77.47 | 32.42 | 109.89 | N/A | N/A | Average |
| 4 | 2483.500 | 9.38 | 32.61 | 41.99 | -12.01 | 54.00 | Average |
| 5 | 2492.210 | 9.81 | 32.65 | 42.46 | -11.54 | 54.00 | Average |

Note:

- "*" , means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1 | 2375.740 | 29.54 | 32.16 | 61.69 | -12.31 | 74.00 | Peak |
| 2 | 2390.000 | 26.65 | 32.22 | 58.87 | -15.13 | 74.00 | Peak |
| 3 | * 2437.870 | 87.44 | 32.42 | 119.86 | N/A | N/A | Peak |
| 4 | 2483.500 | 28.53 | 32.61 | 61.14 | -12.86 | 74.00 | Peak |
| 5 | 2484.515 | 29.18 | 32.61 | 61.80 | -12.20 | 74.00 | Peak |

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2437MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1 | 2388.660 | 15.96 | 32.21 | 48.18 | -5.82 | 54.00 | Average |
| 2 | 2390.000 | 15.58 | 32.22 | 47.79 | -6.21 | 54.00 | Average |
| 3 | * 2436.255 | 85.25 | 32.41 | 117.66 | N/A | N/A | Average |
| 4 | 2483.500 | 15.57 | 32.61 | 48.18 | -5.82 | 54.00 | Average |
| 5 | 2485.750 | 15.71 | 32.62 | 48.33 | -5.67 | 54.00 | Average |

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | * | 78.70 | 32.52 | 111.22 | N/A | N/A | Peak |
| 2 | | 26.70 | 32.61 | 59.31 | -14.69 | 74.00 | Peak |
| 3 | | 27.78 | 32.61 | 60.40 | -13.60 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | * 2461.192 | 76.80 | 32.52 | 109.31 | N/A | N/A | Average |
| 2 | 2483.500 | 16.03 | 32.61 | 48.64 | -5.36 | 54.00 | Average |
| 3 | 2486.680 | 16.89 | 32.62 | 49.51 | -4.49 | 54.00 | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | * | 83.94 | 32.52 | 116.47 | N/A | N/A | Peak |
| 2 | | 28.12 | 32.61 | 60.73 | -13.27 | 74.00 | Peak |
| 3 | | 30.19 | 32.62 | 62.81 | -11.19 | 74.00 | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2462MHz by 802.11b | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | * 2461.216 | 82.02 | 32.52 | 114.54 | N/A | N/A | Average |
| 2 | 2483.500 | 18.78 | 32.61 | 51.39 | -2.61 | 54.00 | Average |
| 3 | 2488.264 | 21.17 | 32.63 | 53.80 | -0.20 | 54.00 | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2390.000 | 34.59 | 32.22 | 66.81 | -7.19 | 74.00 | Peak |
| 2 | * 2408.336 | 75.98 | 32.30 | 108.28 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2390.000 | 16.72 | 32.22 | 48.94 | -5.06 | 54.00 | Average |
| 2 | * 2405.872 | 68.51 | 32.28 | 100.79 | N/A | N/A | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB/m) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|------------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2389.744 | 40.86 | 32.22 | 73.08 | -0.92 | 74.00 | Peak |
| 2 | 2390.000 | 40.31 | 32.22 | 72.53 | -1.47 | 74.00 | Peak |
| 3 | * 2416.904 | 82.63 | 32.33 | 114.96 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-08 |
| Factor | BBHA 9120D (1GHz~18GHz) _2021 | Temp. / Humidity | 23.2°C/47.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2412MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB/m) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------------|
| 1 | 2389.296 | 21.16 | 32.22 | 53.38 | -0.62 | 54.00 | Average |
| 2 | 2390.000 | 20.87 | 32.22 | 53.09 | -0.91 | 54.00 | Average |
| 3 | * 2407.048 | 74.51 | 32.29 | 106.80 | N/A | N/A | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2417MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1 | 2387.640 | 30.73 | 32.21 | 62.94 | -11.06 | 74.00 | Peak |
| 2 | 2390.000 | 27.39 | 32.22 | 59.61 | -14.39 | 74.00 | Peak |
| 3 | * 2421.960 | 77.55 | 32.35 | 109.90 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2417MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|----------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2387.580 | 13.20 | 32.21 | 45.40 | -8.60 | 54.00 | Average |
| 2 | 2390.000 | 12.87 | 32.22 | 45.09 | -8.91 | 54.00 | Average |
| 3 | * 2421.660 | 69.98 | 32.35 | 102.33 | N/A | N/A | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2417MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1 | 2388.120 | 38.55 | 32.21 | 70.76 | -3.24 | 74.00 | Peak |
| 2 | 2390.000 | 35.64 | 32.22 | 67.85 | -6.15 | 74.00 | Peak |
| 3 | * 2410.140 | 84.47 | 32.30 | 116.77 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2417MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|----------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2390.000 | 21.54 | 32.22 | 53.76 | -0.24 | 54.00 | Average |
| 2 | * 2415.600 | 76.47 | 32.33 | 108.80 | N/A | N/A | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2422MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dBμV) | C.F (dB) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1 | 2388.750 | 33.01 | 32.21 | 65.22 | -8.78 | 74.00 | Peak |
| 2 | 2390.000 | 30.25 | 32.22 | 62.47 | -11.53 | 74.00 | Peak |
| 3 | * 2424.375 | 79.03 | 32.36 | 111.39 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Horizontal | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2422MHz by 802.11g | Test Voltage | 120V / 60Hz |




| No | Frequency (MHz) | Reading (dB μ V) | C.F (dB) | Measurement (dB μ V/m) | Margin (dB) | Limit (dB μ V/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------------|----------|----------------------------|-------------|----------------------|-------------------|
| 1 | 2390.000 | 14.86 | 32.22 | 47.08 | -6.92 | 54.00 | Average |
| 2 | * 2426.313 | 70.29 | 32.37 | 102.66 | N/A | N/A | Average |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dB μ V/m) = Reading(dB μ V) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

| | | | |
|-----------|---------------------------------------|----------------------|--------------|
| EUT | AX3000 Whole Home Mesh Wi-Fi 6 System | Date of Test | 2021-12-24 |
| Factor | BBHA 9120D (1GHz~18GHz)_2021 | Temp. / Humidity | 22.9°C/50.2% |
| Polarity | Vertical | Site / Test Engineer | AC1 / Jay |
| Test Mode | Transmit at 2422MHz by 802.11g | Test Voltage | 120V / 60Hz |



| No | Frequency (MHz) | Reading (dBμV) | C.F (dB) | Measurement (dBμV/m) | Margin (dB) | Limit (dBμV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1 | 2388.063 | 38.49 | 32.21 | 70.70 | -3.30 | 74.00 | Peak |
| 2 | 2390.000 | 36.12 | 32.22 | 68.34 | -5.66 | 74.00 | Peak |
| 3 | * 2426.875 | 85.90 | 32.37 | 118.28 | N/A | N/A | Peak |

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.