



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No.:** CQASZ20200901007E-02

**Applicant:** Shenzhen HuaYuLianDaNetwork&Technology Co., Ltd

**Address of Applicant:** 4th Floor Building B, AnFeng Industrial Area, LianRun Road, DaLang Street, LongHua New District, Shenzhen City

**Equipment Under Test (EUT):**

**EUT Name:** BODY FAT SCALE

**Model No.:** TZ280, TZ280L, TZ290, TZ300

**Test Model No.:** TZ280

**Brand Name:** Tenswall, LeTaoCity, AROVA, Renwer, Sepoveda.

**FCC ID:** 2AXKM-TZ280

**Standards:** 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

**Date of Receipt:** 2020-09-10

**Date of Test:** 2020-09-10 to 2020-09-23

**Date of Issue:** 2020-09-23

**Test Result:** PASS\*

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

*Tiny You*  
( Tiny You )

**Reviewed By:**

*Sheek Luo*  
( Sheek Luo )

**Approved By:**

*Jack Ai*  
( Jack Ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200901007E-02	Rev.01	Initial report	2020-09-23

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits .....	5
4.1.3 EUT RF Exposure.....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen HuaYuLianDaNetwork&Technology Co., Ltd
Address of Applicant:	4th Floor Building B, AnFeng Industrial Area, LianRun Road, DaLang Street, LongHua New District, Shenzhen City
Manufacturer:	Shenzhen HuaYuLianDaNetwork&Technology Co., Ltd
Address of Manufacturer:	4th Floor Building B, AnFeng Industrial Area, LianRun Road, DaLang Street, LongHua New District, Shenzhen City
Factory:	Shenzhen HuaYuLianDaNetwork&Technology Co., Ltd
Address of Factory:	4th Floor Building B, AnFeng Industrial Area, LianRun Road, DaLang Street, LongHua New District, Shenzhen City

#### 3.2 General Description of EUT

Product Name:	BODY FAT SCALE
Model No.:	TZ280, TZ280L, TZ290, TZ300
Test Model No.:	TZ280
Trade Mark:	Tenswall, LeTaoCity, AROVA, Renwer, Sepoveda.
Hardware Version:	TZ280-V2.2
Software Version:	V2.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	FixFreqTester V1.0 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	2.6 dBi
EUT Power Supply:	2XAAA battery DC3V

Note:

Model No.: TZ280, TZ280L, TZ290, TZ300

Only the model TZ280 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 4.1.3 EUT RF Exposure

#### 1) For BLE

##### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)		(dBm)
Lowest(2402MHz)	2.99	2.0±1		3.0
Middle(2440MHz)	3.71	3.0±1		4.0
Highest(2480MHz)	4.41	3.5±1		4.5
				2.818

##### Worst case: GFSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	2.99	2.0±1	3.0	1.995	0.618	3.0
Middle (2440MHz)	3.71	3.0±1	4.0	2.512	0.785	
Highest (2480MHz)	4.41	3.5±1	4.5	2.818	0.888	

Conclusion: the calculated value  $\leq 3.0$ , SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200901007E-01