



RF Exposure Report

FCC ID: 2AXKN-RIFF

Applicant: Generation-S Private Limited

Address: 3 Ang Mo Kio ST 62 #06-08 Singapore 569139

Manufacturer: Generation-S Private Limited

Address: 3 Ang Mo Kio ST 62 #06-08 Singapore 569139

Product: Fender RIFF Bluetooth Speaker

Brand: Fender

Test Model(s): RIFF

Series Model(s): N/A

Test Date: Aug. 20, 2022~ Nov. 02, 2022

Issued Date: Nov. 03, 2022

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China

Test Firm Registration No.: 915896

Standards: FCC Part 2 (Section 2.1091); IEEE C95.1
KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Niny Zhang

Reviewed by :

Tanh Tan

Approved by :

Scott He



"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China](#)

Tel: [0769-83078199](tel:0769-83078199)

Web: www.hwa-hsing.com

E-Mail: customerservice.dg@hwa-hsing.com

Release
[Ver. 1.4](#)



Table of contents

Release control record	3
1 General Information	4
1.1 General Description of EUT	4
2 RF exposure limit.....	5
2.1 MPE calculation formula	5
3 Calculation result of maximum conducted power.....	6
Appendix – Information on the Testing Laboratories.....	7



HWA-HSING Test Report No.: 220805EL02-SE-US-01

Release control record

Issue No.	Reason for change	Date issued
220805EL02-SE-US-01	Original Release	Nov. 18, 2022



1 General Information

1.1 General Description of EUT

Product	Fender RIFF Bluetooth Speaker
Brand	RIFF
Test Model(s)	HS220823-01-13
Series Model(s)	N/A
Status of EUT	Engineering Prototype
Power Supply Rating	DC 15V/20V, 3A from USB or DC 7.2V from battery
Modulation Type	GFSK, π/4 DQPSK, 8DPSK for FHSS GFSK for DSSS
Transfer Rate	1/2/3Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	BT-LE: 40 FHSS: 79
Output Power (AVG)	FHSS: 6.15dBm BT-LE: 6.31dBm
Antenna Type	FPCB Antenna
Antenna Gain	2.95dBi Maximum peak Gain
Antenna Connector	I-PEX
Accessory Device	N/A
Cable Supplied	Type-c Charging Cable: 120cm, Unshielded, Detachable, No Core

Note:

1. Please refer to the EUT photo document (Reference No.: 220805EL02-1&-2) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



2 RF exposure limit

Limits for maximum permissible exposure (MPE)

Limits for general population / uncontrolled exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time (minutes)
300-1500	F/1500	30
1500-100,000	1.0	30

Note: F = Frequency in MHz

2.1 MPE calculation formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

Where:

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

Classification:

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.



3 Calculation result of maximum conducted power

The antennas provided to the EUT, please refer to the following table:

Function	Frequency Band	Antenna Gain (dBi)	Antenna Type	Transmit and Receive Chain	Maximum AVG Power(dBm)
FHSS	2400~2483.5MHz	2.95	FPCB	1TX,1RX	6.15
BT-LE	2400~2483.5MHz	2.95	FPCB	1TX,1RX	6.31

Frequency band (MHz)	Max power (mW)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
FHSS	4.121	2.95	20	0.001617	1.0
BT-LE	4.276	2.95	20	0.001678	1.0

Conclusion:

Therefore, the worst-case situation is 0.001678mW/cm², which is less than “1”. This confirmed that the device compliance with FCC 1.1310 MPE limit.



Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China](#)

Contact Tel: [0769-83078199](#)

Email: CustomerService.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---