



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247 TEST REPORT

For

Titanium Intelligent Solutions

275 Seventh Avenue Suite 713 New York, NY 10001, USA

FCC ID:2AXMT-750EXT

Report Type: Original Report	Product Name: IoT Gateway
Report Number: <u>RDG200729002-00A</u>	
Report Date: <u>2020-09-11</u>	
Reviewed By:	Ivan Cao Assistant manager 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	9
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	9
SUPPORT CABLE LIST AND DETAILS	9
CONFIGURATION OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	10
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	11
APPLICABLE STANDARD	11
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST DATA	16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST DATA	20
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST EQUIPMENT LIST AND DETAILS.....	29
TEST DATA	29
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43

TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA	44
FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST EQUIPMENT LIST AND DETAILS.....	45
TEST DATA	45
FCC §15.247(e) - POWER SPECTRAL DENSITY	54
APPLICABLE STANDARD	54
TEST PROCEDURE	54
TEST EQUIPMENT LIST AND DETAILS.....	54
TEST DATA	54

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	IoT Gateway
EUT Model:	TIS-750-EXT
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20) 2422-2452 MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	26.27 dBm
Modulation Type:	DSSS, OFDM
Rated Input Voltage:	DC 5V from USB port or DC 48V from PoE adapter
Serial Number:	RDG200729002-RF-S1
EUT Received Date:	2020.7.29
EUT Received Status:	Good

Note: the device contains a SRD certified module, FCC ID:SZV-TCM515U

Objective

This report is prepared on behalf of *Titanium Intelligent Solutions* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15E NII submissions with FCC ID:2AXMT-750EXT

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1,6,11. For 802.11n ht40 mode was tested with channel 3, 6, 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations. The device supports SISO in all modes, and MIMO in 802.11n modes, per pretest, MIMO mode was the worst mode for radiation test and reported.

The device was powered by USB adapter or PoE adapter, both mode were tested for 15B emission tests, and only the worst USB adapter mode was tested and reported in this report.

EUT Exercise Software


The software “Atheros Radio Test2” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:

Mode	Frequency (MHz)	Data Rate	Power level Setting	
			Chain 0	Chain 1
802.11 b	2412	1Mbps	21.5	20.5
	2437	1Mbps	21.5	20.5
	2462	1Mbps	21.5	20.5
802.11 g	2412	6Mbps	21	20
	2437	6Mbps	21	20
	2462	6Mbps	21	20
802.11n ht20	2412	MCS8	18	18
	2437	MCS8	18	18
	2462	MCS8	18	18
802.11n ht40	2422	MCS8	18	18
	2437	MCS8	18	18
	2452	MCS8	18	18

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	2.015	2.072	97.25
802.11n ht20	1.001	1.033	96.90
802.11n ht40	0.500	0.530	94.34

802.11b




Date: 7.SEP.2020 14:26:36

802.11g




Date: 7.SEP.2020 14:25:38

802.11n ht20



Date: 7.SEP.2020 14:30:16

802.11n ht40



Date: 7.SEP.2020 14:31:33

Equipment Modifications

No modification was made to the EUT.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1232
DELL	Laptop	PP11L	QDS-BRCM1012
HP	USB Flash Disk	8G	0078
Huawei	Adapter	HW-050200C3W	H33L5F4M6947

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.2	Adapter	EUT
RJ45 Cable	Yes	No	10	EUT	Laptop
RJ45 Cable	Yes	No	10	EUT	Laptop

Configuration of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
WLAN	2412-2462	2.3	1.70	27	501.19	20.00	0.17	1.0
WLAN	5150-5250	3	2.00	21	125.89	20.00	0.05	1.0
WLAN	5725-5850	3	2.00	18	63.10	20.00	0.03	1.0
SRD	902.875	1.0	1.26	<0	<1	20.00	<0.01	0.6

The WLAN 2.4G, 5G and SRD can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$=S_{2.4}/S_{limit-2.4}+ S_5/S_{limit-5}+ S_{SRD}/S_{limit-SRD}$$

$$=0.17/1+0.05/1+0.01/0.6$$

$$=0.24$$

$$< 1.0$$

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has 2 internal antenna for 2.4G WLAN and 1 internal antenna for 5G WLAN, fulfill the requirement of this section. Please refer to the EUT photos and below information:

Antenna	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
2.4G Chain 0	PCB	50	2.3 dBi/2.4-2.5GHz
2.4G Chain 1	PCB	50	2.3 dBi/2.4-2.5GHz
5G	FPC	50	3 dBi/5.15-5.85GHz

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase ("hot") line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF : voltage division factor of AMN

C_f : Correction Factor

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV 216	101614	2019-09-12	2020-09-12
R&S	EMI Test Receiver	ESCI	101121	2020-07-07	2021-07-07
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version 9.10.00	N/A	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	64 %
ATM Pressure:	100.1 kPa
Tester:	Barry Yang
Test Date:	2020-09-02


Test Mode: Transmitting

AC120 V, 60 Hz, Line:



Final Result



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.532440	---	34.52	46.00	11.48	9.000	L1	9.6
0.532440	42.68	---	56.00	13.32	9.000	L1	9.6
0.535103	---	34.32	46.00	11.68	9.000	L1	9.6
0.535103	42.65	---	56.00	13.35	9.000	L1	9.6
1.070335	37.05	---	56.00	18.95	9.000	L1	9.7
1.899401	38.80	---	56.00	17.20	9.000	L1	9.7
1.899401	---	31.33	46.00	14.67	9.000	L1	9.7
1.976720	38.68	---	56.00	17.32	9.000	L1	9.7
2.057187	---	31.95	46.00	14.05	9.000	L1	9.7
2.613633	---	31.03	46.00	14.97	9.000	L1	9.7
2.693029	---	30.95	46.00	15.05	9.000	L1	9.7
2.693029	38.29	---	56.00	17.71	9.000	L1	9.7

AC120 V, 60 Hz, Neutral:**Final Result**

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.532440	---	33.79	46.00	12.21	9.000	N	9.6
0.532440	39.41	---	56.00	16.59	9.000	N	9.6
0.535103	39.88	---	56.00	16.12	9.000	N	9.6
0.543169	---	34.76	46.00	11.24	9.000	N	9.6
0.758685	---	27.00	46.00	19.00	9.000	N	9.6
1.018261	33.31	---	56.00	22.69	9.000	N	9.6
1.070335	---	26.94	46.00	19.06	9.000	N	9.6
1.660095	34.25	---	56.00	21.75	9.000	N	9.6
1.744993	32.54	---	56.00	23.46	9.000	N	9.6
2.057187	---	26.58	46.00	19.42	9.000	N	9.6
2.295763	---	27.12	46.00	18.88	9.000	N	9.6
2.295763	35.21	---	56.00	20.79	9.000	N	9.6

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1GHz:****Above 1GHz:**

The radiated emission Below 1GHz tests were performed in the 10 meters chamber test site, above 1GHz tests were performed in the 3 meters chamber test site A, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
R&S	EMI Test Receiver	ESCI	100224	2019-09-12	2020-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2019-09-24	2020-09-24
Sonoma	Amplifier	310N	185914	2019-10-13	2020-10-13
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiation Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2017-12-06	2020-12-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2020-07-07	2021-07-07
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2020-06-27	2021-06-27
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2020-06-16	2021-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2020-06-16	2021-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	25.2 °C	29 °C
Relative Humidity:	39 %	45 %
ATM Pressure:	100.6 kPa	100.4 kPa
Tester:	Jackson Zhang	Bond Qin
Test Date:	2020-08-11	2020-08-25


Test Result: Compliance, please Refer to the following data

Test Mode: Transmitting


1) 30MHz-1GHz(802.11b mode Middle channel was the worst)

Horizontal:

80.0 dBuV/m



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	28.24	peak	-4.33	23.91	40.00	16.09
164.8300	32.87	peak	-9.51	23.36	43.50	20.14
324.8800	33.77	peak	-7.11	26.66	46.00	19.34
399.5700	35.37	peak	-5.29	30.08	46.00	15.92
480.0800	33.40	peak	-3.83	29.57	46.00	16.43
598.4200	37.31	peak	-1.42	35.89	46.00	10.11

Vertical:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	34.80	peak	-4.33	30.47	40.00	9.53
361.7400	31.21	peak	-6.05	25.16	46.00	20.84
553.8000	32.15	peak	-1.71	30.44	46.00	15.56
598.4200	45.12	QP	-1.42	43.70	46.00	2.30
650.8000	31.72	peak	-0.42	31.30	46.00	14.70
680.8700	31.69	peak	0.29	31.98	46.00	14.02

2) 1-25GHz:**802.11b Mode(Per pretest two chain ,Chain 0 was the worst):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	59.07	PK	H	28.12	1.81	0.00	89.00	N/A	N/A
2412.00	55.51	AV	H	28.12	1.81	0.00	85.44	N/A	N/A
2412.00	56.75	PK	V	28.12	1.81	0.00	86.68	N/A	N/A
2412.00	52.21	AV	V	28.12	1.81	0.00	82.14	N/A	N/A
2390.00	26.54	PK	H	28.08	1.80	0.00	56.42	74.00	17.58
2390.00	14.42	AV	H	28.08	1.80	0.00	44.30	54.00	9.70
4824.00	36.41	PK	H	32.95	3.19	25.62	46.93	74.00	27.07
4824.00	24.02	AV	H	32.95	3.19	25.62	34.54	54.00	19.46
7236.00	35.88	PK	H	35.81	4.77	25.64	50.82	74.00	23.18
7236.00	23.58	AV	H	35.81	4.77	25.64	38.52	54.00	15.48
1920.00	44.61	PK	H	26.96	1.67	26.03	47.21	74.00	26.79
1920.00	40.70	AV	H	26.96	1.67	26.03	43.30	54.00	10.70
Middle Channel: 2437 MHz									
2437.00	60.15	PK	H	28.17	1.82	0.00	90.14	N/A	N/A
2437.00	56.77	AV	H	28.17	1.82	0.00	86.76	N/A	N/A
2437.00	57.27	PK	V	28.17	1.82	0.00	87.26	N/A	N/A
2437.00	53.68	AV	V	28.17	1.82	0.00	83.67	N/A	N/A
4874.00	36.38	PK	H	33.05	3.26	25.65	47.04	74.00	26.96
4874.00	24.00	AV	H	33.05	3.26	25.65	34.66	54.00	19.34
7311.00	35.68	PK	H	36.01	4.64	25.71	50.62	74.00	23.38
7311.00	23.21	AV	H	36.01	4.64	25.71	38.15	54.00	15.85
1920.00	44.10	PK	H	26.96	1.67	26.03	46.70	74.00	27.30
1920.00	40.60	AV	H	26.96	1.67	26.03	43.20	54.00	10.80
High Channel: 2462 MHz									
2462.00	61.19	PK	H	28.22	1.83	0.00	91.24	N/A	N/A
2462.00	57.97	AV	H	28.22	1.83	0.00	88.02	N/A	N/A
2462.00	58.54	PK	V	28.22	1.83	0.00	88.59	N/A	N/A
2462.00	55.02	AV	V	28.22	1.83	0.00	85.07	N/A	N/A
2483.50	26.55	PK	H	28.27	1.84	0.00	56.66	74.00	17.34
2483.50	14.83	AV	H	28.27	1.84	0.00	44.94	54.00	9.06
4924.00	36.47	PK	H	33.15	3.27	25.65	47.24	74.00	26.76
4924.00	24.32	AV	H	33.15	3.27	25.65	35.09	54.00	18.91
7386.00	35.86	PK	H	36.20	4.51	25.79	50.78	74.00	23.22
7386.00	23.75	AV	H	36.20	4.51	25.79	38.67	54.00	15.33
1920.00	45.20	PK	H	26.96	1.67	26.03	47.80	74.00	26.20
1920.00	40.89	AV	H	26.96	1.67	26.03	43.49	54.00	10.51

802.11g Mode (Per pretest two chain ,Chain 0 was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	63.04	PK	H	28.12	1.81	0.00	92.97	N/A	N/A
2412.00	53.25	AV	H	28.12	1.81	0.00	83.18	N/A	N/A
2412.00	56.10	PK	V	28.12	1.81	0.00	86.03	N/A	N/A
2412.00	46.32	AV	V	28.12	1.81	0.00	76.25	N/A	N/A
2390.00	25.73	PK	H	28.08	1.80	0.00	55.61	74.00	18.39
2390.00	13.59	AV	H	28.08	1.80	0.00	43.47	54.00	10.53
4824.00	36.83	PK	H	32.95	3.19	25.62	47.35	74.00	26.65
4824.00	24.58	AV	H	32.95	3.19	25.62	35.10	54.00	18.90
7236.00	36.26	PK	H	35.81	4.77	25.64	51.20	74.00	22.80
7236.00	24.02	AV	H	35.81	4.77	25.64	38.96	54.00	15.04
1920.00	44.56	PK	H	26.96	1.67	26.03	47.16	74.00	26.84
1920.00	40.10	AV	H	26.96	1.67	26.03	42.70	54.00	11.30
Middle Channel: 2437 MHz									
2437.00	64.24	PK	H	28.17	1.82	0.00	94.23	N/A	N/A
2437.00	54.45	AV	H	28.17	1.82	0.00	84.44	N/A	N/A
2437.00	57.02	PK	V	28.17	1.82	0.00	87.01	N/A	N/A
2437.00	47.35	AV	V	28.17	1.82	0.00	77.34	N/A	N/A
4874.00	36.87	PK	H	33.05	3.26	25.65	47.53	74.00	26.47
4874.00	24.52	AV	H	33.05	3.26	25.65	35.18	54.00	18.82
7311.00	36.33	PK	H	36.01	4.64	25.71	51.27	74.00	22.73
7311.00	24.00	AV	H	36.01	4.64	25.71	38.94	54.00	15.06
1920.00	44.69	PK	H	26.96	1.67	26.03	47.29	74.00	26.71
1920.00	40.36	AV	H	26.96	1.67	26.03	42.96	54.00	11.04
High Channel: 2462 MHz									
2462.00	65.42	PK	H	28.22	1.83	0.00	95.47	N/A	N/A
2462.00	55.82	AV	H	28.22	1.83	0.00	85.87	N/A	N/A
2462.00	58.89	PK	V	28.22	1.83	0.00	88.94	N/A	N/A
2462.00	49.02	AV	V	28.22	1.83	0.00	79.07	N/A	N/A
2483.50	26.16	PK	H	28.27	1.84	0.00	56.27	74.00	17.73
2483.50	15.08	AV	H	28.27	1.84	0.00	45.19	54.00	8.81
4924.00	36.77	PK	H	33.15	3.27	25.65	47.54	74.00	26.46
4924.00	24.50	AV	H	33.15	3.27	25.65	35.27	54.00	18.73
7386.00	36.62	PK	H	36.20	4.51	25.79	51.54	74.00	22.46
7386.00	24.10	AV	H	36.20	4.51	25.79	39.02	54.00	14.98
1920.00	45.36	PK	H	26.96	1.67	26.03	47.96	74.00	26.04
1920.00	41.02	AV	H	26.96	1.67	26.03	43.62	54.00	10.38

802.11n ht20 Mode(MIMO was the worst):




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	60.96	PK	H	28.12	1.81	0.00	90.89	N/A	N/A
2412.00	50.77	AV	H	28.12	1.81	0.00	80.70	N/A	N/A
2412.00	56.59	PK	V	28.12	1.81	0.00	86.52	N/A	N/A
2412.00	46.41	AV	V	28.12	1.81	0.00	76.34	N/A	N/A
2390.00	26.05	PK	H	28.08	1.80	0.00	55.93	74.00	18.07
2390.00	13.62	AV	H	28.08	1.80	0.00	43.50	54.00	10.50
4824.00	36.02	PK	H	32.95	3.19	25.62	46.54	74.00	27.46
4824.00	23.58	AV	H	32.95	3.19	25.62	34.10	54.00	19.90
7236.00	35.45	PK	H	35.81	4.77	25.64	50.39	74.00	23.61
7236.00	23.21	AV	H	35.81	4.77	25.64	38.15	54.00	15.85
1920.00	44.25	PK	H	26.96	1.67	26.03	46.85	74.00	27.15
1920.00	40.36	AV	H	26.96	1.67	26.03	42.96	54.00	11.04
Middle Channel: 2437 MHz									
2437.00	61.40	PK	H	28.17	1.82	0.00	91.39	N/A	N/A
2437.00	51.02	AV	H	28.17	1.82	0.00	81.01	N/A	N/A
2437.00	56.97	PK	V	28.17	1.82	0.00	86.96	N/A	N/A
2437.00	46.52	AV	V	28.17	1.82	0.00	76.51	N/A	N/A
4874.00	36.21	PK	H	33.05	3.26	25.65	46.87	74.00	27.13
4874.00	24.00	AV	H	33.05	3.26	25.65	34.66	54.00	19.34
7311.00	35.78	PK	H	36.01	4.64	25.71	50.72	74.00	23.28
7311.00	23.54	AV	H	36.01	4.64	25.71	38.48	54.00	15.52
1920.00	43.69	PK	H	26.96	1.67	26.03	46.29	74.00	27.71
1920.00	39.85	AV	H	26.96	1.67	26.03	42.45	54.00	11.55
High Channel: 2462 MHz									
2462.00	62.16	PK	H	28.22	1.83	0.00	92.21	N/A	N/A
2462.00	51.89	AV	H	28.22	1.83	0.00	81.94	N/A	N/A
2462.00	57.62	PK	V	28.22	1.83	0.00	87.67	N/A	N/A
2462.00	47.21	AV	V	28.22	1.83	0.00	77.26	N/A	N/A
2483.50	26.11	PK	H	28.27	1.84	0.00	56.22	74.00	17.78
2483.50	14.01	AV	H	28.27	1.84	0.00	44.12	54.00	9.88
4924.00	36.25	PK	H	33.15	3.27	25.65	47.02	74.00	26.98
4924.00	24.02	AV	H	33.15	3.27	25.65	34.79	54.00	19.21
7386.00	35.89	PK	H	36.20	4.51	25.79	50.81	74.00	23.19
7386.00	23.58	AV	H	36.20	4.51	25.79	38.50	54.00	15.50
1920.00	44.36	PK	H	26.96	1.67	26.03	46.96	74.00	27.04
1920.00	40.10	AV	H	26.96	1.67	26.03	42.70	54.00	11.30

802.11n ht40 Mode(MIMO was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	60.86	PK	H	28.14	1.81	0.00	90.81	N/A	N/A
2422.00	50.64	AV	H	28.14	1.81	0.00	80.59	N/A	N/A
2422.00	57.84	PK	V	28.14	1.81	0.00	87.79	N/A	N/A
2422.00	47.58	AV	V	28.14	1.81	0.00	77.53	N/A	N/A
2390.00	25.76	PK	H	28.08	1.80	0.00	55.64	74.00	18.36
2390.00	13.42	AV	H	28.08	1.80	0.00	43.30	54.00	10.70
4844.00	36.02	PK	H	32.99	3.22	25.63	46.60	74.00	27.40
4844.00	23.98	AV	H	32.99	3.22	25.63	34.56	54.00	19.44
7266.00	35.78	PK	H	35.89	4.72	25.67	50.72	74.00	23.28
7266.00	23.59	AV	H	35.89	4.72	25.67	38.53	54.00	15.47
1920.00	43.96	PK	H	26.96	1.67	26.03	46.56	74.00	27.44
1920.00	39.58	AV	H	26.96	1.67	26.03	42.18	54.00	11.82
Middle Channel: 2437 MHz									
2437.00	60.96	PK	H	28.17	1.82	0.00	90.95	N/A	N/A
2437.00	50.75	AV	H	28.17	1.82	0.00	80.74	N/A	N/A
2437.00	57.95	PK	V	28.17	1.82	0.00	87.94	N/A	N/A
2437.00	47.68	AV	V	28.17	1.82	0.00	77.67	N/A	N/A
4874.00	36.03	PK	H	33.05	3.26	25.65	46.69	74.00	27.31
4874.00	24.00	AV	H	33.05	3.26	25.65	34.66	54.00	19.34
7311.00	35.87	PK	H	36.01	4.64	25.71	50.81	74.00	23.19
7311.00	23.62	AV	H	36.01	4.64	25.71	38.56	54.00	15.44
1920.00	44.25	PK	H	26.96	1.67	26.03	46.85	74.00	27.15
1920.00	39.87	AV	H	26.96	1.67	26.03	42.47	54.00	11.53
High Channel: 2452 MHz									
2452.00	61.77	PK	H	28.20	1.83	0.00	91.80	N/A	N/A
2452.00	51.22	AV	H	28.20	1.83	0.00	81.25	N/A	N/A
2452.00	58.35	PK	V	28.20	1.83	0.00	88.38	N/A	N/A
2452.00	48.02	AV	V	28.20	1.83	0.00	78.05	N/A	N/A
2483.50	26.58	PK	H	28.27	1.84	0.00	56.69	74.00	17.31
2483.50	14.79	AV	H	28.27	1.84	0.00	44.90	54.00	9.10
4904.00	36.21	PK	H	33.11	3.30	25.67	46.95	74.00	27.05
4904.00	24.12	AV	H	33.11	3.30	25.67	34.86	54.00	19.14
7356.00	35.98	PK	H	36.13	4.56	25.76	50.91	74.00	23.09
7356.00	23.75	AV	H	36.13	4.56	25.76	38.68	54.00	15.32
1920.00	45.20	PK	H	26.96	1.67	26.03	47.80	74.00	26.20
1920.00	40.21	AV	H	26.96	1.67	26.03	42.81	54.00	11.19




**Test plots(802.11g chain 0 high channel was the worst):
Horizontal:**

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2020-07-07	2021-07-07
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	27.3 °C
Relative Humidity:	65 %
ATM Pressure:	100.6 kPa
Test by:	Rita Huang
Test Date:	2020-09-07

Test Mode: Transmitting

Test Result: Compliant. Test only performed at chain 0. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.080	13.760	≥ 0.5
	Middle	2437	10.000	13.680	≥ 0.5
	High	2462	10.080	13.680	≥ 0.5
802.11g	Low	2412	15.200	16.800	≥ 0.5
	Middle	2437	13.920	16.800	≥ 0.5
	High	2462	15.040	16.640	≥ 0.5
802.11n ht20	Low	2412	15.200	17.440	≥ 0.5
	Middle	2437	15.120	17.440	≥ 0.5
	High	2462	15.200	17.440	≥ 0.5
802.11n ht40	Low	2422	33.600	36.320	≥ 0.5
	Middle	2437	32.480	36.320	≥ 0.5
	High	2452	32.480	36.320	≥ 0.5

802.11b Low Channel




Date: 7.SEP.2020 13:16:08

802.11b Middle Channel




Date: 7.SEP.2020 13:14:10

802.11b High Channel




Date: 7.SEP.2020 13:18:44

802.11g Low Channel




Date: 7.SEP.2020 13:36:55

802.11g Middle Channel




Date: 7.SEP.2020 13:35:40

802.11g High Channel




Date: 7.SEP.2020 13:33:42

802.11n ht20 Low Channel




Date: 7.SEP.2020 13:39:33

802.11n ht20 Middle Channel




Date: 7.SEP.2020 13:46:29

802.11n ht20 High Channel




Date: 7.SEP.2020 13:47:51

802.11n ht40 Low Channel




Date: 7.SEP.2020 14:01:47

802.11n ht40 Middle Channel




Date: 7.SEP.2020 14:06:03


802.11n ht40 High Channel



Date: 7.SEP.2020 14:16:47


99% Occupied Bandwidth:**802.11b Low Channel**

Date: 7.SEP.2020 13:16:17

802.11b Middle Channel


Date: 7.SEP.2020 13:14:19

802.11b High Channel




Date: 7.SEP.2020 13:11:37

802.11g Low Channel




Date: 7.SEP.2020 13:43:00

802.11g Middle Channel




Date: 7.SEP.2020 13:43:47

802.11g High Channel




Date: 7.SEP.2020 13:44:38

802.11n ht20 Low Channel




Date: 7.SEP.2020 13:39:46

802.11n ht20 Middle Channel




Date: 7.SEP.2020 13:46:41

802.11n ht20 High Channel




Date: 7.SEP.2020 13:48:04

802.11n ht40 Low Channel




Date: 7.SEP.2020 14:02:03

802.11n ht40 Middle Channel



Date: 7.SEP.2020 14:06:15

802.11n ht40 High Channel




Date: 7.SEP.2020 14:16:59

FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER**Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power Meter to test Peak output power, record the result as peak power.
5. Set the power meter to test average output power, record the result as average power.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2019-09-23	2020-09-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.3 °C
Relative Humidity:	65 %
ATM Pressure:	100.6 kPa
Test by:	Rita Huang
Test Date:	2020-09-07

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)			Limit (dBm)
			Chain 0	Chain 1	Total	
802.11b	Low	2412	22.49	22.10	/	30
	Middle	2437	22.75	21.95	/	30
	High	2462	22.54	21.47	/	30
802.11g	Low	2412	24.35	24.66	/	30
	Middle	2437	24.09	24.57	/	30
	High	2462	24.12	24.24	/	30
802.11n ht20	Low	2412	23.17	22.90	26.05	30
	Middle	2437	22.99	23.51	26.27	30
	High	2462	22.88	22.87	25.89	30
802.11n ht40	Low	2422	21.76	21.74	24.76	30
	Middle	2437	21.67	21.71	24.70	30
	High	2452	21.74	21.53	24.65	30

Note:

The maximum antenna gain is 2.3 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

So:

Directional gain = $G_{ANT} + \text{Array Gain} = 2.3 \text{ dBi} < 6 \text{ dBi}$

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2020-07-07	2021-07-07
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	27.3 °C
Relative Humidity:	65 %
ATM Pressure:	100.6 kPa
Test by:	Rita Huang
Test Date:	2020-09-07


Test mode: Transmitting
Test Result: Compliant. Please refer to following plots.
Chain 0

802.11b: Band Edge, Left Side




Date: 7.SEP.2020 13:16:56

802.11b: Band Edge, Right Side




Date: 7.SEP.2020 13:12:18

802.11g: Band Edge, Left Side




Date: 7.SEP.2020 13:38:06

802.11g: Band Edge, Right Side




Date: 7.SEP.2020 13:34:44

802.11n ht20 Band Edge, Left Side




Date: 7.SEP.2020 13:40:33

802.11n ht20 Band Edge, Right Side




Date: 7.SEP.2020 13:48:57

802.11n ht40: Band Edge, Left Side



Date: 7.SEP.2020 14:04:33


802.11n ht40 Band Edge, Right Side



Date: 7.SEP.2020 14:18:14


Chain 1

802.11b: Band Edge, Left Side




Date: 7.SEP.2020 11:57:22


802.11b: Band Edge, Right Side



Date: 7.SEP.2020 13:10:11


802.11g: Band Edge, Left Side

Date: 7.SEP.2020 13:27:44

802.11g: Band Edge, Right Side


Date: 7.SEP.2020 13:30:57

802.11n ht20 Band Edge, Left Side




Date: 7.SEP.2020 13:53:49

802.11n ht20 Band Edge, Right Side




Date: 7.SEP.2020 13:50:45

802.11n ht40: Band Edge, Left Side



Date: 7.SEP.2020 13:59:24

802.11n ht40 Band Edge, Right Side



Date: 7.SEP.2020 14:16:07

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2020-07-07	2021-07-07
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.3 °C
Relative Humidity:	65 %
ATM Pressure:	100.6 kPa
Test by:	Rita Huang
Test Date:	2020-09-07

Test Result: Compliance

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)
			Chain 0	Chain 1	Total	
802.11b	Low	2412	-3.86	-4.41	/	≤8
	Middle	2437	-4.70	-3.75	/	≤8
	High	2462	-4.77	-4.75	/	≤8
802.11g	Low	2412	-4.69	-4.70	/	≤8
	Middle	2437	-4.59	-5.29	/	≤8
	High	2462	-4.41	-5.39	/	≤8
802.11n ht20	Low	2412	-8.03	-6.02	-3.90	≤8
	Middle	2437	-8.09	-8.10	-5.08	≤8
	High	2462	-8.93	-8.06	-5.46	≤8
802.11n ht40	Low	2422	-10.88	-10.01	-7.41	≤8
	Middle	2437	-11.09	-10.70	-7.88	≤8
	High	2452	-10.41	-10.61	-7.50	≤8

Note 1: The maximum antenna gain is 2.3 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:


$$\text{Array Gain} = 10 \log(N_{\text{ANT}}/N_{\text{SS}}) \text{ dB.}$$

So:

$$\text{Directional gain} = G_{\text{ANT}} + \text{Array Gain} = 2.3\text{dBi} + 10 \cdot \log(2/1) = 5.3 \text{ dBi}$$


Chain 0

Power Spectral Density, 802.11b Low Channel




Date: 7.SEP.2020 13:16:46

Power Spectral Density, 802.11b Middle Channel




Date: 7.SEP.2020 13:14:43

Power Spectral Density, 802.11b High Channel




Date: 7.SEP.2020 13:19:00

Power Spectral Density, 802.11g Low Channel




Date: 7.SEP.2020 13:37:54

Power Spectral Density, 802.11g Middle Channel




Date: 7.SEP.2020 13:36:25

Power Spectral Density, 802.11g High Channel




Date: 7.SEP.2020 13:34:31

Power Spectral Density, 802.11n ht20 Low Channel




Date: 7.SEP.2020 13:40:20

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 7.SEP.2020 13:47:04

Power Spectral Density, 802.11n ht20 High Channel




Date: 7.SEP.2020 13:48:44

Power Spectral Density, 802.11n ht40 Low Channel




Date: 7.SEP.2020 14:03:04

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 7.SEP.2020 14:07:17


Power Spectral Density, 802.11n ht40 High Channel



Date: 7.SEP.2020 14:18:01


Chain 1

Power Spectral Density, 802.11b Low Channel




Date: 7.SEP.2020 11:57:08

Power Spectral Density, 802.11b Middle Channel




Date: 7.SEP.2020 13:08:25

Power Spectral Density, 802.11b High Channel




Date: 7.SEP.2020 13:21:50

Power Spectral Density, 802.11g Low Channel




Date: 7.SEP.2020 13:27:32

Power Spectral Density, 802.11g Middle Channel




Date: 7.SEP.2020 13:28:58

Power Spectral Density, 802.11g High Channel




Date: 7.SEP.2020 13:30:44

Power Spectral Density, 802.11n ht20 Low Channel




Date: 7.SEP.2020 13:53:36

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 7.SEP.2020 13:52:15

Power Spectral Density, 802.11n ht20 High Channel




Date: 7.SEP.2020 13:50:32

Power Spectral Density, 802.11n ht40 Low Channel




Date: 7.SEP.2020 13:59:08

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 7.SEP.2020 14:13:38

Power Spectral Density, 802.11n ht40 High Channel



Date: 7.SEP.2020 14:15:54

***** END OF REPORT *****