

TEST REPORT

Product : JSOM CONNECT
Trade mark : JABIL
Model/Type reference : CONNECT0402,
CONNECT0404,
CONNECT0408,
CONNECT0416
Serial Number : N/A
Report Number : EED32O81077801
FCC ID : 2AXNJ-JSOM-CN2
Date of Issue : Aug. 17, 2022
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

Jabil

10560 Dr M.L.K. Jr St N, St. Petersburg, Florida, United States

Prepared by:

**Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Frazer Li

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

Aug. 17, 2022



Check No.: 3935190722

2 Content

1 COVER PAGE	1
2 CONTENT	2
3 VERSION	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST CONFIGURATION	6
5.4 TEST ENVIRONMENT	7
5.5 DESCRIPTION OF SUPPORT UNITS	7
5.6 TEST LOCATION	7
5.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	8
6 EQUIPMENT LIST	9
7 TEST RESULTS AND MEASUREMENT DATA	11
7.1 ANTENNA REQUIREMENT	11
7.2 MAXIMUM CONDUCTED OUTPUT POWER	12
7.3 DTS BANDWIDTH	13
7.4 MAXIMUM POWER SPECTRAL DENSITY	14
7.5 BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSION	15
7.6 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	16
8 APPENDIX A	32
9 PHOTOGRAPHS OF TEST SETUP	33
10 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	35

3 Version

Version No.	Date	Description
00	Aug. 17, 2022	Original

4 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	N/A
DTS Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	PASS
Band Edge Measurements	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Radiated Spurious Emission & Restricted bands	47 CFR Part 15 Subpart C Section 15.205/15.209	PASS

Remark:

N/A:The product is powered by DC 3.3V,so it doesn't apply.

Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

Model No.: CONNECT0402, CONNECT0404, CONNECT0408, CONNECT0416

Only the model CONNECT0402 was tested,their electrical circuit design, layout, components used and internal wiring are identical.Only the flash memory size is different.

5 General Information

5.1 Client Information

Applicant:	Jabil
Address of Applicant:	10560 Dr M.L.K. Jr St N, St. Petersburg, Florida, United States
Manufacturer:	Jabil
Address of Manufacturer:	10560 Dr M.L.K. Jr St N, St. Petersburg, Florida, United States
Factory:	Jabil Precision Industry (Guangzhou) CO., LTD.
Address of Factory:	5th floor, Building C, No. 1199, Hulin Road, Huangpu District, Guangzhou, Guangdong (510700), China

5.2 General Description of EUT

Product Name:	JSOM CONNECT			
Model No.:	CONNECT0402, CONNECT0404, CONNECT0408, CONNECT0416			
Test Model No.:	CONNECT0402,			
Trade mark:	JABIL			
Product Type:	☐ Mobile ☐ Portable ☒ Fix Location			
Operation Frequency:	2402MHz~2480MHz			
Modulation Type:	GFSK			
Transfer Rate:	☒ 1Mbps ☒ 2Mbps			
Number of Channel:	40			
Antenna Type:	PCB antenna	PCB	Flex	FPC Self-adhesive
Antenna Gain:	4.97dBi	3.45dBi	4.03dBi	2.17dBi
Note:Only the maximum antenna gain was tested.				
Power Supply:	DC 3.3V			
Test Voltage:	DC 3.3V			
Sample Received Date:	Jul.19,2022			
Sample tested Date:	Jul.19,2022 to Aug. 08, 2022			

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

5.3 Test Configuration

EUT Test Software Settings:

Software:	RTLBTAPP.exe (manufacturer declare)			
EUT Power Grade:	Default (Power level is built-in set parameters and cannot be changed and selected)			
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.				
Test Mode	Modulation	Rate	Channel	Frequency(MHz)
Mode a	GFSK	1Mbps	CH0	2402
Mode b	GFSK	1Mbps	CH19	2440
Mode c	GFSK	1Mbps	CH39	2480
Mode d	GFSK	2Mbps	CH0	2402
Mode e	GFSK	2Mbps	CH19	2440
Mode f	GFSK	2Mbps	CH39	2480

5.4 Test Environment

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Conducted Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

5.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Netbook	DELL	Latitude 3490	FCC&CE	CTI

5.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

5.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

6 Equipment List

RF test system					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Communication test set	R&S	CMW500	107929	07-06-2022	07-05-2023
Signal Generator	R&S	SMBV100A	1407.6004K02- 262149-CV	09-30-2021	09-23-2022
Spectrum Analyzer	R&S	FSV40	101200	09-10-2021	08-25-2022
RF control unit(power unit)	MWRF-test	MW100-RFCB	MW220620CTI- 42	07-06-2022	07-05-2023
high-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	12-24-2021	12-23-2022
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	07-01-2022	06-15-2023

3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Due Date
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05/22/2022	05/21/2025
Receiver	R&S	ESCI7	100938-003	10/14/2021	10/13/2022
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/22/2022	05/21/2023
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	04/15/2021	04/14/2024
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-17-2021	04-16-2024
Preamplifier	Agilent	11909A	12-1	04-01-2022	03-31-2023


3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	Keysight	N9038A	MY57290136	03-01-2022	02-28-2023
Spectrum Analyzer	Keysight	N9020B	MY57111112	02-23-2022	02-22-2023
Spectrum Analyzer	Keysight	N9030B	MY57140871	02-23-2022	02-22-2023
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-28-2021	04-27-2024
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-15-2021	04-14-2024
Horn Antenna	ETS-LINDGREN	3117	57407	07-04-2021	07-03-2024
Preamplifier	EMCI	EMC184055SE	980597	04-20-2022	04-19-2023
Preamplifier	EMCI	EMC001330	980563	04-01-2022	03-31-2023
Preamplifier	JS Tonscend	980380	EMC051845SE	12-24-2021	12-23-2022
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	04-11-2022	04-10-2023
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2021	01-08-2024
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

7 Test results and Measurement Data


7.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	Please see Internal photos
The antenna is PCB antenna. The best case gain of the antenna is 4.97dBi.	


7.2 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set the RBW $\geq$ DTS bandwidth. b) Set VBW $\geq 3 \times$ RBW. c) Set span $\geq 3 \times$ RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.
Limit:	30dBm
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A


7.3 DTS Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10 2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
Limit:	$\geq 500 \text{ kHz}$
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

7.4 Maximum Power Spectral Density




Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set analyzer center frequency to DTS channel center frequency. b) Set the span to 1.5 times the DTS bandwidth. c) Set the RBW to $3 \text{ kHz} < \text{RBW} < 100 \text{ kHz}$. d) Set the VBW $> [3 \times \text{RBW}]$. e) Detector = peak. f) Sweep time = auto couple. g) Trace mode = max hold. h) Allow trace to fully stabilize. i) Use the peak marker function to determine the maximum amplitude level within the RBW. j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.
Limit:	$\leq 8.00 \text{ dBm}/3 \text{ kHz}$
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

7.5 Band Edge measurements and Conducted Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set RBW =100KHz. b) Set VBW = 300KHz. c) Sweep time = auto couple. d) Detector = peak. e) Trace mode = max hold. f) Allow trace to fully stabilize. g) Use peak marker function to determine the peak amplitude level.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Refer to clause 5.3
Test Results:	Refer to Appendix A

7.6 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					



Test Procedure:


- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

	horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Refer to clause 5.3
Test Results:	Pass

Radiated Spurious Emission below 1GHz:


During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case highest channel of GFSK 1M was recorded in the report.

Polarization: Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		55.6093	4.96	13.88	18.84	40.00	-21.16	QP	200	4
2		95.0929	5.02	13.37	18.39	43.50	-25.11	QP	200	129
3		223.7333	8.49	14.60	23.09	46.00	-22.91	QP	200	341
4		304.6099	6.32	17.35	23.67	46.00	-22.33	QP	100	160
5		515.4373	5.18	21.92	27.10	46.00	-18.90	QP	100	291
6	*	744.8660	8.50	25.48	33.98	46.00	-12.02	QP	200	210

Polarization: Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		49.8814	5.47	14.27	19.74	40.00	-20.26	QP	100	4
2		65.3431	11.47	11.70	23.17	40.00	-16.83	QP	100	140
3		98.1418	5.01	13.80	18.81	43.50	-24.69	QP	200	280
4		223.7333	8.14	14.60	22.74	46.00	-23.26	QP	200	340
5		378.5842	5.56	18.93	24.49	46.00	-21.51	QP	100	242
6	*	766.0571	8.04	25.83	33.87	46.00	-12.13	QP	100	252

Radiated Spurious Emission above 1GHz:

1M:

Mode:			BLE GFSK Transmitting			Channel:		2402 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1267.4267	0.98	40.69	41.67	74.00	32.33	Pass	H	PK
2	2053.3053	4.73	39.97	44.70	74.00	29.30	Pass	H	PK
3	4170.0780	-18.07	55.20	37.13	74.00	36.87	Pass	H	PK
4	5977.1985	-13.11	53.19	40.08	74.00	33.92	Pass	H	PK
5	8799.3866	-9.46	50.88	41.42	74.00	32.58	Pass	H	PK
6	12410.6274	-4.70	51.51	46.81	74.00	27.19	Pass	H	PK
7	1562.0562	1.98	40.22	42.20	74.00	31.80	Pass	V	PK
8	2124.1124	4.62	40.91	45.53	74.00	28.47	Pass	V	PK
9	4251.0834	-17.62	60.59	42.97	74.00	31.03	Pass	V	PK
10	6235.2157	-13.11	53.43	40.32	74.00	33.68	Pass	V	PK
11	8533.3689	-10.48	53.17	42.69	74.00	31.31	Pass	V	PK
12	12400.6267	-4.69	51.08	46.39	74.00	27.61	Pass	V	PK

Mode:			BLE GFSK Transmitting			Channel:		2440 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1147.4147	0.83	40.97	41.80	74.00	32.20	Pass	H	PK
2	2126.9127	4.59	44.40	48.99	74.00	25.01	Pass	H	PK
3	4259.0839	-17.55	56.90	39.35	74.00	34.65	Pass	H	PK
4	6379.2253	-12.87	53.70	40.83	74.00	33.17	Pass	H	PK
5	8929.3953	-8.99	51.56	42.57	74.00	31.43	Pass	H	PK
6	10280.4854	-6.59	51.02	44.43	74.00	29.57	Pass	H	PK
7	1294.6295	1.05	40.31	41.36	74.00	32.64	Pass	V	PK
8	2128.3128	4.57	41.00	45.57	74.00	28.43	Pass	V	PK
9	3986.0657	-18.92	59.76	40.84	74.00	33.16	Pass	V	PK
10	6392.2261	-12.86	55.25	42.39	74.00	31.61	Pass	V	PK
11	7889.3260	-10.96	52.39	41.43	74.00	32.57	Pass	V	PK
12	11816.5878	-6.06	52.64	46.58	74.00	27.42	Pass	V	PK

Mode:			BLE GFSK Transmitting			Channel:		2480 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1324.4324	1.14	40.63	41.77	74.00	32.23	Pass	H	PK
2	2002.7003	4.56	39.45	44.01	74.00	29.99	Pass	H	PK
3	3994.0663	-18.90	59.54	40.64	74.00	33.36	Pass	H	PK
4	5565.1710	-14.35	54.34	39.99	74.00	34.01	Pass	H	PK
5	7705.3137	-11.06	53.62	42.56	74.00	31.44	Pass	H	PK
6	11158.5439	-6.33	52.03	45.70	74.00	28.30	Pass	H	PK
7	1411.8412	1.40	40.25	41.65	74.00	32.35	Pass	V	PK
8	2127.1127	4.58	43.35	47.93	74.00	26.07	Pass	V	PK
9	4255.0837	-17.58	60.47	42.89	74.00	31.11	Pass	V	PK
10	7122.2748	-11.64	52.13	40.49	74.00	33.51	Pass	V	PK
11	9172.4115	-8.10	52.12	44.02	74.00	29.98	Pass	V	PK
12	12967.6645	-4.12	51.14	47.02	74.00	26.98	Pass	V	PK

2M:

Mode:			BLE GFSK Transmitting			Channel:		2402 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1393.8394	1.37	39.97	41.34	74.00	32.66	Pass	H	PK
2	2026.5027	4.64	39.48	44.12	74.00	29.88	Pass	H	PK
3	4868.1245	-16.21	53.98	37.77	74.00	36.23	Pass	H	PK
4	8080.3387	-10.78	51.13	40.35	74.00	33.65	Pass	H	PK
5	10835.5224	-6.28	51.67	45.39	74.00	28.61	Pass	H	PK
6	13178.6786	-3.23	50.57	47.34	74.00	26.66	Pass	H	PK
7	1341.6342	1.20	40.87	42.07	74.00	31.93	Pass	V	PK
8	2128.7129	4.57	43.30	47.87	74.00	26.13	Pass	V	PK
9	4265.0843	-17.51	60.13	42.62	74.00	31.38	Pass	V	PK
10	6039.2026	-13.03	52.85	39.82	74.00	34.18	Pass	V	PK
11	8276.3518	-10.96	52.04	41.08	74.00	32.92	Pass	V	PK
12	12485.6324	-4.81	51.15	46.34	74.00	27.66	Pass	V	PK

Mode:			BLE GFSK Transmitting			Channel:		2440 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1427.6428	1.41	40.70	42.11	74.00	31.89	Pass	H	PK
2	2130.5131	4.55	43.59	48.14	74.00	25.86	Pass	H	PK
3	3998.0665	-18.89	56.32	37.43	74.00	36.57	Pass	H	PK
4	6355.2237	-12.89	53.19	40.30	74.00	33.70	Pass	H	PK
5	8928.3952	-9.00	52.23	43.23	74.00	30.77	Pass	H	PK
6	13277.6852	-3.38	50.19	46.81	74.00	27.19	Pass	H	PK
7	1282.0282	1.01	41.21	42.22	74.00	31.78	Pass	V	PK
8	2125.3125	4.60	44.47	49.07	74.00	24.93	Pass	V	PK
9	4250.0833	-17.62	61.46	43.84	74.00	30.16	Pass	V	PK
10	6369.2246	-12.88	52.43	39.55	74.00	34.45	Pass	V	PK
11	8499.3666	-10.55	54.37	43.82	74.00	30.18	Pass	V	PK
12	14384.7590	0.97	46.61	47.58	74.00	26.42	Pass	V	PK

Mode:			BLE GFSK Transmitting			Channel:		2480 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1281.4281	1.01	41.80	42.81	74.00	31.19	Pass	H	PK
2	2129.5130	4.56	44.50	49.06	74.00	24.94	Pass	H	PK
3	4261.0841	-17.54	58.89	41.35	74.00	32.65	Pass	H	PK
4	6430.2287	-12.81	53.09	40.28	74.00	33.72	Pass	H	PK
5	10781.5188	-6.27	50.30	44.03	74.00	29.97	Pass	H	PK
6	14383.7589	0.95	47.05	48.00	74.00	26.00	Pass	H	PK
7	1166.8167	0.82	40.70	41.52	74.00	32.48	Pass	V	PK
8	1983.2983	4.46	39.73	44.19	74.00	29.81	Pass	V	PK
9	4811.1207	-16.23	55.04	38.81	74.00	35.19	Pass	V	PK
10	6846.2564	-12.14	53.03	40.89	74.00	33.11	Pass	V	PK
11	8527.3685	-10.50	56.67	46.17	74.00	27.83	Pass	V	PK
12	11922.5948	-5.70	51.52	45.82	74.00	28.18	Pass	V	PK

Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Restricted bands:

Test plot as follows:

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	1M		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	5.77	39.24	45.01	74.00	28.99	PASS	Horizontal	PK
2	2390.0000	5.77	28.69	34.46	54.00	19.54	PASS	Horizontal	AV

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	1M		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	5.77	39.43	45.20	74.00	28.80	PASS	Vertical	PK
2	2390.0000	5.77	28.25	34.02	54.00	19.98	PASS	Vertical	AV

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	1M		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5000	6.57	39.47	46.04	74.00	27.96	PASS	Horizontal	PK
2	2483.5000	6.57	28.52	35.09	54.00	18.91	PASS	Horizontal	AV

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	1M		

Test Graph




Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5000	6.57	38.96	45.53	74.00	28.47	PASS	Vertical	PK
2	2483.5000	6.57	28.32	34.89	54.00	19.11	PASS	Vertical	AV

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	2M		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	5.77	39.25	45.02	74.00	28.98	PASS	Horizontal	PK
2	2390.0000	5.77	27.96	33.73	54.00	20.27	PASS	Horizontal	AV

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	2M		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390.0000	5.77	38.64	44.41	74.00	29.59	PASS	Vertical	PK
2	2390.0000	5.77	28.10	33.87	54.00	20.13	PASS	Vertical	AV

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	2M		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5000	6.57	40.07	46.64	74.00	27.36	PASS	Horizontal	PK
2	2483.5000	6.57	29.37	35.94	54.00	18.06	PASS	Horizontal	AV

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	2M		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5000	6.57	39.25	45.82	74.00	28.18	PASS	Vertical	PK
2	2483.5000	6.57	27.74	34.31	54.00	19.69	PASS	Vertical	AV


Note:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading -Correct Factor
Correct Factor = Preamplifier Factor– Antenna Factor–Cable Factor

8 Appendix A


Refer to Appendix: Bluetooth LE of EED32O81077801

9 PHOTOGRAPHS OF TEST SETUP

Test model No.:CONNECT0402



Radiated spurious emission Test Setup-1(Below 1GHz)



Radiated spurious emission Test Setup-2(Above 1GHz)



**Radiated spurious emission Test Setup-3(Above 1GHz)
There are absorbing materials under the ground.**