

SSPN Safety System Products North AB

RF TEST REPORT

Report Type:

FCC Part 15.247 & ISED RSS-247 RF report

Model:

RB001

REPORT NUMBER:

220102003SHA-001

ISSUE DATE:

April 12, 2022

DOCUMENT CONTROL NUMBER:

TTRF15.247-02_V1 © 2018 Intertek



Applicant: SSPN Safety System Products North AB
Tullkammarv 14 S-439 31 Onsala Sweden

Manufacturer: SSPN Safety System Products North AB
Tullkammarv 14 S-439 31 Onsala Sweden

FCC ID: 2AXNQ2101A

IC: 27995-2101A

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2020): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-247 Issue 2 (February 2017): Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5 Amendment 1 (March 2019): General Requirements for Compliance of Radio Apparatus

PREPARED BY:**REVIEWED BY:**

Project Engineer
Erick Liu

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	5
MEASUREMENT RESULT SUMMARY	6
1 GENERAL INFORMATION	7
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7
1.2 TECHNICAL SPECIFICATION	7
1.3 DESCRIPTION OF TEST FACILITY	8
2 TEST SPECIFICATIONS.....	9
2.1 STANDARDS OR SPECIFICATION	9
2.2 MODE OF OPERATION DURING THE TEST.....	9
2.3 TEST SOFTWARE LIST	10
2.4 TEST PERIPHERALS LIST	10
2.5 TEST ENVIRONMENT CONDITION:.....	10
2.6 INSTRUMENT LIST	11
2.7 MEASUREMENT UNCERTAINTY	14
3 MINIMUM 6DB BANDWIDTH.....	15
3.1 LIMIT	15
3.2 MEASUREMENT PROCEDURE	15
3.3 TEST CONFIGURATION	15
3.4 TEST RESULTS OF MINIMUM 6DB BANDWIDTH	15
4 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P.....	16
4.1 LIMIT	16
4.2 MEASUREMENT PROCEDURE	16
4.3 TEST CONFIGURATION	17
4.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER.....	17
5 POWER SPECTRUM DENSITY	18
5.1 LIMIT	18
5.2 MEASUREMENT PROCEDURE	18
5.3 TEST CONFIGURATION	19
5.4 TEST RESULTS OF POWER SPECTRUM DENSITY	19
6 EMISSION OUTSIDE THE FREQUENCY BAND	20
6.1 LIMIT	20
6.2 MEASUREMENT PROCEDURE	20
6.3 TEST CONFIGURATION	21
6.4 THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND.....	21
7 RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS.....	22
7.1 LIMIT	22
7.2 MEASUREMENT PROCEDURE	22
7.3 TEST CONFIGURATION	24
7.4 TEST RESULTS OF RADIATED EMISSIONS	26
8 POWER LINE CONDUCTED EMISSION.....	38
8.1 LIMIT	38

TEST REPORT

8.2	TEST CONFIGURATION	38
8.3	MEASUREMENT PROCEDURE	39
8.4	TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....	40
9	OCCUPIED BANDWIDTH	42
9.1	LIMIT	42
9.2	MEASUREMENT PROCEDURE	42
9.3	TEST CONFIGURATION	42
9.4	THE RESULTS OF OCCUPIED BANDWIDTH.....	42
10	ANTENNA REQUIREMENT.....	43
APPENDIX A: TEST RESULTS		44
RF OUTPUT POWER.....		44
<i>Test Result and Data.....</i>		44
POWER SPECTRAL DENSITY		45
<i>Test Result and Data.....</i>		45
6dB BANDWIDTH		46
<i>Test Result and Data.....</i>		46
99% BANDWIDTH.....		47
<i>Test Result and Data.....</i>		47

Revision History

Report No.	Version	Description	Issued Date
220102003SHA-001	Rev. 01	Initial issue of report	April 12, 2022

Measurement result summary

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	RSS-247 Issue 2 Clause 5.2	Pass
Maximum conducted output power and e.i.r.p.	15.247(b)(3)	RSS-247 Issue 2 Clause 5.4	Pass
Power spectrum density	15.247(e)	RSS-247 Issue 2 Clause 5.2	Pass
Emission outside the frequency band	15.247(d)	RSS-247 Issue 2 Clause 5.5	Pass
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	RSS-Gen Issue 5 Clause 8.9&8.10	Pass
Power line conducted emission	15.207(a)	RSS-Gen Issue 5 Clause 8.8	Pass
Occupied bandwidth	-	RSS-Gen Issue 5 Clause 6.6	Tested
Antenna requirement	15.203	-	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Transceiver
Type/Model:	RB001
Description of EUT:	EUT is a wireless module, it has only one model.
Rating:	4.5-5.5V DC
Category of EUT:	Class B
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	November 30, 2021
Date of test:	November 30, 2021 – February 24, 2022

1.2 Technical Specification

Frequency Range:	2405-2480MHz
Type of Modulation:	O-QPSK
Channel Number:	16
Channel Separation:	5MHz
Antenna Information:	Antenna 1: Internal chip antenna, 4.0dBi max Antenna 2: External omni antenna, 3.0dBi max

Note:

1. This information is supplied by the applicant. Any change on this value would result in different test data / conclusion.
2. The internal antenna 1 and external omni antenna 2 are used in the same switch. After evaluation, all conducted tests were performed in the external antenna port.

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2020)

ANSI C63.10 (2013)

RSS-247 Issue 2 (February 2017)

RSS-Gen Issue 5 Amendment 1 (March 2019)

KDB 558074 D01 15.247 Meas Guidance v05r02

2.2 Mode of operation during the test

Three axes (X, Y, Z) were observed while the test receiver worked as “max hold” continuously and the highest reading among the whole test procedure was recorded. Compare with the test results that X axis is the worst case.

The channels were tested as representatives.

Frequency Band (MHz)				2405 ~ 2480			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	2405	15	2425	19	2445	23	2465
12	2410	16	2430	20	2450	24	2470
13	2415	17	2435	21	2455	25	2475
14	2420	18	2440	22	2460	26	2480

Data rate VS Power:

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

Test software and Power Setting parameter				
Test Software	SW0026-15v01pre10-RadioPerformanceMeterII			
Working Mode	Continuously transmission			
Test Channel	2405MHz	2440MHz	2475MHz	2480MHz
Power Setting	18	18	18	10

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

Radiated test mode: EUT transmitted signal with antenna;

Conducted test mode: EUT transmitted signal from RF port connected to SPA directly;

TEST REPORT

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Laptop computer	HP	-
2	DC regulated power supply	QJ3003H	-
3	Transceiver	S16LDRBCA20	-

2.5 Test environment condition:

Test items	Temperature	Humidity
Minimum 6dB Bandwidth	25°C	54% RH
Maximum conducted output power and e.i.r.p.		
Power spectrum density		
Emission outside the frequency band		
Occupied bandwidth		
Radiated Emissions in restricted frequency bands	24°C	52% RH
Power line conducted emission	25°C	54% RH

2.6 Instrument list

Conducted Emission/Disturbance Power/Tri-loop Test/CDN method					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESCS 30	EC 2107	2022-07-15
☒	A.M.N.	R&S	ESH2-Z5	EC 3119	2022-11-30
☐	A.M.N.	R&S	ENV 216	EC 3393	2022-07-04
☐	A.M.N.	R&S	ENV4200	EC 3558	2022-06-10
☐	Absorbing clamp	R&S	MDS 21	EC 2108	2022-06-19
☐	CDN	Frankonia	CDN M2M316	EC 5969	2023-03-15
☐	CDN	Schaffner	CDN M316	EC 2113-1	2022-07-16
☐	Attenuator	Weinschel	68-6-44	EC 3043-9	2023-02-05
☐	Tri-loop	Schwarzbeck	HXYZ 9170	EC 3384	2022-10-10
☐	Voltage Probe	Schwarzbeck	TK9420	EC 4888	2022-09-12
☐	Current probe	R&S	EZ-17	EC 3221	2023-03-15
☐	I.S.N.	FCC	FCC-TLISN -T2-02	EC 3754	2023-02-05
☐	I.S.N.	FCC	FCC-TLISN -T4-02	EC 3755	2023-02-05
☐	I.S.N.	FCC	FCC-TLISN -T8-02	EC 3756	2023-02-05
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2022-09-12
☒	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2022-06-10
☒	Pre-amplifier	R&S	AFS42- 00101800-25-S- 42	EC5262	2022-06-10
☐	Horn antenna	R&S	HF 906	EC 3049	2022-11-17
☒	Horn antenna	ETS	3117	EC 4792-1	2023-01-09
☐	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2022-07-09

TEST REPORT

☒	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2023-03-07
		EM TEST	NETWAVE-30-400	EC 5383-2	2022-06-19
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2023-03-05
☒	Power sensor	Agilent	U2021XA	EC 5338-1	2023-03-05
☒	Vector Signal Generator	Agilent	N5182B	EC 5175	2023-03-05
☒	Spectrum analyzer	R&S	CMW500	EC5944	2022-12-23
☒	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2023-03-05
☐	Mobile Test System	Litepoint	Iqxel	EC 5176	2023-01-09
☐	Test Receiver	R&S	ESCI 7	EC 4501	2022-09-12
Tet Site					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Shielded room	Zhongyu	-	EC 2838	2023-01-07
☐	Shielded room	Zhongyu	-	EC 2839	2023-01-14
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2022-07-31
☐	Fully-anechoic chamber	Albatross project	-	EC 3047	2022-07-31
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Spectrum analyzer	Agilent	E7402A	EC 2254	2022-07-15
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2023-02-28
☐	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 2122	2023-03-11
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 5198	2023-01-18
☐	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3326	2023-03-28

TEST REPORT

	Pressure meter	YM3	Shanghai Mengde	EC 3320	2021-07-01
---	----------------	-----	--------------------	---------	------------

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

3 Minimum 6dB bandwidth

Test result: Pass

3.1 Limit


For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2 Measurement Procedure

The minimum 6dB bandwidth is measured using the Spectrum Analyzer according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance" (clause 8.2) for compliance requirements.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.3 Test Configuration



3.4 Test Results of Minimum 6dB bandwidth

Please refer to Appendix A

4 Maximum conducted output power and e.i.r.p.

Test result: Pass

4.1 Limit


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands:
1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

4.2 Measurement Procedure

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 9.1.1) for compliance requirements.

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

TEST REPORT**4.3 Test Configuration****4.4 Test Results of Maximum conducted output power**

Please refer to Appendix A

TEST REPORT

5 Power spectrum density

Test result: Pass

5.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.


If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and $8 + (6 - \text{antenna gain} - \text{beam forming gain})$.

5.2 Measurement Procedure

The power output was tested according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance" (clause 10.2) for compliance requirements.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 Test Configuration



5.4 Test Results of Power spectrum density

Please refer to Appendix A

6 Emission outside the frequency band

Test result: Pass

6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

6.2 Measurement Procedure

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 11.0) for compliance requirements.

Reference level measurement

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq 3 \times$ RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

6.3 Test Configuration



6.4 The results of Emission outside the frequency band

Please refer to Appendix A

7 Radiated Emissions in restricted frequency bands

Test result: Pass

7.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

7.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%), peak detector or 3 x RBW (Duty cycle $\geq 98\%$), RMS detector, trace average for AV data measurement at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

7.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



For Radiated emission above 1GHz:




TEST REPORT

7.4 Test Results of Radiated Emissions


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

The worst waveform from 30MHz to 1000MHz is listed as below:

Horizontal



Vertical



TEST REPORT

Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	54.359	23.70	9.20	40.00	16.30	PK
H	192.009	38.20	11.20	43.50	5.30	PK
H	208.596	31.10	11.30	43.50	12.40	PK
H	663.910	31.10	22.40	46.00	14.90	PK
H	948.388	31.30	24.80	46.00	14.70	PK
V	54.168	32.60	9.30	40.00	7.40	PK
V	192.017	29.50	11.20	43.50	14.00	PK
V	619.555	22.90	22.10	46.00	23.10	PK
V	663.785	32.20	22.40	46.00	13.80	PK
V	948.427	32.60	24.80	46.00	13.40	PK

TEST REPORT


Test result above 1GHz:

The emission was conducted from 1GHz to 25GHz


Antenna 1:

Channel 11:

H




V




Channel 18:

H




V




TEST REPORT

Channel 25:

H




V




Channel 26:

H



V



TEST REPORT


CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
11	H	2405.00	32.60	105.40	Fundamental	/	PK
	H	2390.00	30.30	42.65	74.00	31.35	PK
	V	2390.00	30.30	41.72	74.00	32.28	PK
	H	7215.00	-1.50	44.70	74.00	29.30	PK
	V	7215.00	-1.50	48.80	74.00	25.20	PK
18	H	2440.00	32.70	105.40	Fundamental	/	PK
	H	7320.00	-1.10	46.60	74.00	27.40	PK
	V	7320.00	-1.10	50.30	74.00	23.70	PK
25	H	2475.00	32.70	105.50	Fundamental	/	PK
	H	2483.50	30.80	44.86	74.00	29.14	PK
	V	2483.50	30.80	42.64	74.00	31.36	PK
	H	7425.00	-0.80	41.80	74.00	32.20	PK
	V	7425.00	-0.80	42.70	74.00	31.30	PK
26	H	2480.00	32.70	99.20	Fundamental	/	PK
	H	2483.50	30.80	61.27	74.00	12.73	PK
	H	2483.50	30.80	52.71	54.00	1.29	AV
	V	2483.50	30.80	54.74	74.00	19.26	PK
	V	2483.50	30.80	44.21	54.00	9.79	AV
	H	7440.00	-0.80	41.10	74.00	32.90	PK
	V	7440.00	-0.80	41.70	74.00	32.30	PK

TEST REPORT


Antenna 2:

Channel 11:

H




V




TEST REPORT

Channel 18:

H




V




TEST REPORT

Channel 25:

H




V




TEST REPORT

Channel 26:

H



V



TEST REPORT

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
11	H	2405.00	32.60	105.40	Fundamental	/	PK
	H	2390.00	30.30	42.62	74.00	31.38	PK
	V	2390.00	30.30	42.10	74.00	31.90	PK
	H	7215.00	-1.50	43.70	74.00	30.30	PK
	V	7215.00	-1.50	45.20	74.00	28.80	PK
18	H	2440.00	32.70	105.40	Fundamental	/	PK
	H	7320.00	-1.10	42.60	74.00	31.40	PK
	V	7320.00	-1.10	48.30	74.00	25.70	PK
25	H	2475.00	32.70	103.90	Fundamental	/	PK
	H	2483.50	30.80	45.12	74.00	28.88	PK
	V	2483.50	30.80	42.50	74.00	31.50	PK
	H	7425.00	-0.80	45.20	74.00	28.80	PK
	V	7425.00	-0.80	45.00	74.00	29.00	PK
26	H	2480.00	32.70	96.00	Fundamental	/	PK
	H	2483.50	30.80	62.50	74.00	11.50	PK
	H	2483.50	30.80	52.62	54.00	1.38	AV
	V	2483.50	30.80	55.20	74.00	18.80	PK
	V	2483.50	30.80	45.30	54.00	8.70	AV
	H	7440.00	-0.80	40.60	74.00	33.40	PK
	V	7440.00	-0.80	41.50	74.00	32.50	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

8 Power line conducted emission


Test result: Pass

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

8.2 Test Configuration



8.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.


TEST REPORT

8.4 Test Results of Power line conducted emission


Test Condition: During the test, the module(EUT) is connected to the S16LDRBCA20 (host). The S16LDRBCA20 supplies 7-33V DC power from a DC source, and the DC source is connected to the LISN.
Test voltage: AC 120V, 60Hz

Test Curve:

L line:



N Line



TEST REPORT

Test Data:

No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1	262.500kHz	61.4	7.2	-54.1	-3.1	10.3	QP	L1
2	26.606MHz	60.0	21.5	-38.5	9.7	11.8	QP	L1
3	150.000kHz	66.0	29.1	-36.9	18.8	10.3	QP	N
4	1.235MHz	56.0	14.3	-41.7	3.7	10.6	QP	N
5	1.541MHz	56.0	14.3	-41.7	3.8	10.5	QP	N
6	19.896MHz	60.0	25.4	-34.6	14.1	11.3	QP	N

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Factor

3. Delta= Level - Limit

4. If the PK Level is lower than AV limit, the AV test can be elided.

Example: Assuming LISN Factor = 10.00dB, Cable Loss = 2.00dB,
Original Receiver Reading = 10.00dBuV, Limit = 66.00dBuV.
Then Factor = 10.00 + 2.00 = 12.00dB;
Level = 10dBuV + 12.00dB = 22.00dBuV;
Delta = 22.00dBuV - 66.00dBuV = -44.00dB.

9 Occupied Bandwidth

Test result: Tested

9.1 Limit

None


9.2 Measurement Procedure

The occupied bandwidth per RSS-Gen was measured using the Spectrum Analyzer.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

9.3 Test Configuration



9.4 The results of Occupied Bandwidth

Please refer to Appendix A

10 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:


EUT use of a permanently attached antenna and unique coupling to the intentional radiator, so it can comply with the provisions of this section.

Appendix A: Test results

RF Output Power


Test Result and Data

Maximum Output Power				
Test Frequency (MHz)	Power (dBm)	Antenna Gain	EIRP (dBm)	Result
2405	17.08	4.00	21.08	Pass
2440	18.88	4.00	22.88	Pass
2475	16.52	4.00	20.52	Pass
2480	8.82	4.00	12.82	Pass



Power Spectral Density Test Result and Data


Peak Power Spectral Density		
Test Frequency (MHz)	PSD (dBm/3kHz)	Result
2405	2.82	Pass
2440	5.37	Pass
2475	2.34	Pass
2480	-6.81	Pass



6dB BandWidth

Test Result and Data


Occupied 6dB Bandwidth			
Test Frequency (MHz)	Occupied Bandwidth (kHz)	Min Limit (kHz)	Result
2405	1588.7	500	Pass
2440	1588.8	500	Pass
2475	1608	500	Pass
2480	1633.1	500	Pass





99% BandWidth


Test Result and Data

99% Occupied Bandwidth		
Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	Result
2405	3.6229	Pass
2440	3.8216	Pass
2475	3.6728	Pass
2480	2.7859	Pass









***** END *****