



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

Changzhou Jutai Electronic Co., Ltd

No. 8 Longfa Road, Xinbei District, Changzhou, Jiangsu 213031 China

FCC ID: 2AXOG-JT-WIFI-001

Report Type: Original Report	Product Type: Controller
Test Engineer:	Chao Gao <i>Chao Gao</i>
Report Number:	RHZ200915001-00A
Report Date:	2020-10-19 Oscar Ye
Reviewed By:	EMC Manager <i>Oscar Ye</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	13
FCC §15.203 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
FACTOR & OVER LIMIT CALCULATION.....	16
TEST RESULTS SUMMARY	16
TEST DATA	16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER SETUP.....	20
TEST PROCEDURE	20
TEST RESULTS SUMMARY	20
TEST DATA	21
FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	39
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	46
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST DATA	48

FCC §15.247(e) - POWER SPECTRAL DENSITY	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Changzhou Jutai Electronic Co., Ltd
Tested Model	JT-WIFI-001
Product Type	Controller
Power Supply	DC 5-31V
RF Function:	2.4G Wi-Fi
Operating Band/Frequency:	2412-2462 MHz
Channel Number:	11
Channel Separation:	5 MHz
Modulation Type:	DSSS,OFDM
Antenna Type:	PCB antenna
*Maximum Antenna Gain:	3.0 dBi

Note: The antenna gain is provided by the applicant.

**All measurement and test data in this report was gathered from production sample serial number: 20200915001. (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-09-15.*

Objective

This report is prepared on behalf of *Changzhou Jutai Electronic Co., Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions' rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliant Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test tool: espRFTool


*Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data Rate	Channel	Power Level Setting
802.11b	1 Mbps	Low	0
		Middle	0
		High	0
802.11g	6 Mbps	Low	0
		Middle	0
		High	0
802.11n-HT20	MCS0	Low	0
		Middle	0
		High	0


Note: The power level setting was declared by the applicant.

Duty Cycle:


802.11b Mode Middle Channel



802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	100	/	/	0
802.11n-HT20	100	/	/	0

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
CZJUTAI	Adapter	JT-DC240V0500-F	/
/	Socket	/	/

External I/O Cable


Cable Description	Length(m)	From Port	To
Power Cable	1.0	Socket	AC Source
Power Cable	0.2	EUT	Adapter

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2019-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	2516	2020-01-17	2023-01-16
A.H.Systems, inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2019-12-14	2020-12-13
Agilent	Power Meter	N1912A	MY5000492	2019-11-18	2020-11-17
Agilent	Power Sensor	N1921A	MY54210024	2019-11-18	2020-11-17
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Changzhou Jutai Electronic Co., Ltd.	RF Cable	Changzhou Jutai Electronic Co., Ltd. C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2020-08-05	2021-08-04
Rohde & Schwarz	LISN	ENV216	3560655016	2019-12-14	2020-12-13
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2020-08-10	2021-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Target Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412~2462	3.0	2.0	21.0	125.89	20	0.0501	1.0
802.11g		3.0	2.0	24.5	281.84	20	0.1121	1.0
802.11n-HT20		3.0	2.0	24.5	281.84	20	0.1121	1.0

Note: The Tune-up output power was declared by the Manufacturer.

Conclusion: The device meets MPE at distance 20cm.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliant with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PCB antenna for Wi-Fi and the antenna gain is 3.0 dBi, the antenna was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter of the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over Limit of 7 dB means the emission is 7 dB above the limit. The equation for over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.


Test Data**Environmental Conditions**

Temperature:	24.6 °C
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa

The testing was performed by Chao Gao on 2020-10-13.


EUT operation mode: Transmitting in 802.11g mode low channel (worst case)

AC 120V/60 Hz, Line



		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.518	2.20	19.76	21.96	46.00	-24.04	Average
2	0.518	11.10	19.76	30.86	56.00	-25.14	QP
3	1.276	6.60	19.82	26.42	46.00	-19.58	Average
4	1.276	13.50	19.82	33.32	56.00	-22.68	QP
5	1.698	2.50	19.84	22.34	46.00	-23.66	Average
6	1.698	8.20	19.84	28.04	56.00	-27.96	QP
7	2.839	4.39	19.47	23.86	46.00	-22.14	Average
8	2.839	8.89	19.47	28.36	56.00	-27.64	QP
9	3.417	7.60	19.46	27.06	46.00	-18.94	Average
10	3.417	11.90	19.46	31.36	56.00	-24.64	QP
11	4.549	8.29	19.49	27.78	46.00	-18.22	Average
12	4.549	12.79	19.49	32.28	56.00	-23.72	QP

AC 120V/60 Hz, Neutral




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.521	8.10	19.76	27.86	46.00	-18.14	Average
2	0.521	17.30	19.76	37.06	56.00	-18.94	QP
3	1.249	5.80	19.82	25.62	46.00	-20.38	Average
4	1.249	12.30	19.82	32.12	56.00	-23.88	QP
5	1.707	7.70	19.84	27.54	46.00	-18.46	Average
6	1.707	14.20	19.84	34.04	56.00	-21.96	QP
7	2.839	9.69	19.47	29.16	46.00	-16.84	Average
8	2.839	15.19	19.47	34.66	56.00	-21.34	QP
9	3.399	12.70	19.46	32.16	46.00	-13.84	Average
10	3.399	17.50	19.46	36.96	56.00	-19.04	QP
11	4.549	12.99	19.49	32.48	46.00	-13.52	Average
12	4.549	17.89	19.49	37.38	56.00	-18.62	QP

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30MHz - 1GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV/m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**


Temperature:	25.5°C
Relative Humidity:	51 %
ATM Pressure:	101.5 kPa

The testing was performed by Chao Gao on 2020-10-15.

EUT operation mode: Transmitting

Spurious Emission Test:**30MHz-1GHz**

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case low channel of 802.11g mode in Z-axis of orientation was recorded.



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi Peak (dBμV/m)	Height (cm)	Polar (H/V)				
39.80	30.12	100	V	225.0	-17.1	40.00	9.88
149.92	24.51	100	V	146.0	-18.3	43.50	18.99
196.48	33.65	100	V	309.0	-17.7	43.50	9.85
207.35	30.82	100	V	209.0	-18.2	43.50	12.68
560.02	36.54	100	V	3.0	-11.7	46.00	9.46
799.98	40.96	100	H	117.0	-7.4	46.00	5.04

1GHz-18GHz:**802.11b Mode:**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412 MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1503.20	---	24.59	200	H	219.0	-16.3	54.00	29.41
1503.20	34.61	---	200	H	219.0	-16.3	74.00	39.39
3488.80	---	30.79	150	H	219.0	-8.8	54.00	23.21
3488.80	39.91	---	150	H	219.0	-8.8	74.00	34.09
4824.00	---	45.45	200	H	204.0	-5.5	54.00	8.55
4824.00	49.03	---	200	H	204.0	-5.5	74.00	24.97
7329.10	---	37.52	150	V	99.0	0.7	54.00	16.48
7329.10	46.24	---	150	V	99.0	0.7	74.00	27.76
13835.00	---	41.62	200	H	148.0	6.0	54.00	12.38
13835.00	51.53	---	200	H	148.0	6.0	74.00	22.47
17819.80	---	46.46	150	V	150.0	8.8	54.00	7.54
17819.80	55.25	---	150	V	150.0	8.8	74.00	18.75

Middle Channel: 2437 MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1421.60	---	24.31	200	H	310.0	-16.8	54.00	29.69
1421.60	32.76	---	200	H	310.0	-16.8	74.00	41.24
3507.50	---	30.69	200	V	108.0	-8.8	54.00	23.31
3507.50	39.61	---	200	V	108.0	-8.8	74.00	34.39
4874.00	---	42.15	200	V	161.0	-5.4	54.00	11.85
4874.00	49.57	---	200	V	161.0	-5.4	74.00	24.43
7925.80	---	38.44	200	V	82.0	1.7	54.00	15.56
7925.80	47.63	---	200	V	82.0	1.7	74.00	26.37
12354.30	---	39.78	150	H	311.0	3.2	54.00	14.22
12354.30	49.14	---	150	H	311.0	3.2	74.00	24.86
17449.20	---	44.43	200	H	103.0	8.7	54.00	9.57
17449.20	55.25	---	200	H	103.0	8.7	74.00	18.75

High Channel: 2462 MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1255.00	---	23.31	200	V	357.0	-17.7	54.00	30.69
1255.00	32.64	---	200	V	357.0	-17.7	74.00	41.36
3487.10	---	30.58	150	H	50.0	-8.9	54.00	23.42
3487.10	39.89	---	150	H	50.0	-8.9	74.00	34.11
4924.00	---	44.92	150	V	203.0	-5.3	54.00	9.08
4924.00	49.29	---	150	V	203.0	-5.3	74.00	24.71
7815.30	---	36.90	200	V	357.0	1.5	54.00	17.10
7815.30	47.08	---	200	V	357.0	1.5	74.00	26.92
11670.90	---	38.31	200	H	284.0	3.1	54.00	15.69
11670.90	48.15	---	200	H	284.0	3.1	74.00	25.85
17836.80	---	46.60	200	V	0.0	8.8	54.00	7.40
17836.80	55.11	---	200	V	0.0	8.8	74.00	18.89

802.11g Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2412 MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1255.00	---	23.30	150	H	129.0	-17.7	54.00	30.70
1255.00	33.40	---	150	H	129.0	-17.7	74.00	40.60
3357.90	---	30.63	200	V	315.0	-9.2	54.00	23.37
3357.90	38.31	---	200	V	315.0	-9.2	74.00	35.69
4824.00	---	40.00	150	V	205.0	-5.6	54.00	14.00
4824.00	46.41	---	150	V	205.0	-5.6	74.00	27.59
7879.90	---	38.10	150	V	166.0	1.6	54.00	15.90
7879.90	46.66	---	150	V	166.0	1.6	74.00	27.34
14702.00	---	42.79	150	H	237.0	6.0	54.00	11.21
14702.00	51.60	---	150	H	237.0	6.0	74.00	22.40
17920.10	---	46.36	150	V	141.0	8.8	54.00	7.64
17920.10	56.06	---	150	V	141.0	8.8	74.00	17.94

Middle Channel: 2437 MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1595.00	---	25.34	150	V	282.0	-16.0	54.00	28.66
1595.00	35.47	---	150	V	282.0	-16.0	74.00	38.53
3425.90	---	31.36	200	H	25.0	-9.0	54.00	22.64
3425.90	39.98	---	200	H	25.0	-9.0	74.00	34.02
4874.00	---	38.90	150	V	178.0	-5.4	54.00	15.10
4874.00	45.40	---	150	V	178.0	-5.4	74.00	28.60
7142.10	---	36.18	150	H	168.0	0.2	54.00	17.82
7142.10	46.28	---	150	H	165.0	0.2	74.00	27.72
10820.90	---	38.04	200	V	352.0	2.7	54.00	15.96
10820.90	48.06	---	200	V	352.0	2.7	74.00	25.94
17845.30	---	46.04	150	V	0.0	8.8	54.00	7.96
17845.30	54.80	---	150	V	0.0	8.8	74.00	19.20

High Channel: 2462 MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1426.70	---	24.30	200	H	270.0	-16.8	54.00	29.70
1426.70	33.34	---	200	H	270.0	-16.8	74.00	40.66
3657.10	---	29.45	200	H	86.0	-8.2	54.00	24.55
3657.10	38.81	---	200	H	86.0	-8.2	74.00	35.19
4924.00	---	36.89	150	V	213.0	-5.3	54.00	17.11
4924.00	46.77	---	150	V	213.0	-5.3	74.00	27.23
7842.50	---	38.48	150	H	333.0	1.6	54.00	15.52
7842.50	47.71	---	150	H	333.0	1.6	74.00	26.29
10251.40	---	37.53	200	V	15.0	2.1	54.00	16.47
10251.40	47.64	---	200	V	15.0	2.1	74.00	26.36
17789.20	---	45.52	200	H	155.0	8.8	54.00	8.48
17789.20	55.47	---	200	H	155.0	8.8	74.00	18.53

802.11n-HT20 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel : 2412 MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1557.60	34.46	---	150	V	256.0	-16.1	74.00	39.54
1557.60	---	24.81	150	V	256.0	-16.1	54.00	29.19
3432.70	39.95	---	150	V	152.0	-9.0	74.00	34.05
3432.70	---	31.45	150	V	152.0	-9.0	54.00	22.55
4824.00	47.48	---	200	H	148.0	-5.5	74.00	26.52
4824.00	---	39.86	200	H	148.0	-5.5	54.00	14.14
7236.00	46.84	---	200	V	328.0	0.5	74.00	27.16
7236.00	---	37.50	200	V	328.0	0.5	54.00	16.50
13952.30	51.96	---	200	V	5.0	6.1	74.00	22.04
13952.30	---	42.44	200	V	5.0	6.1	54.00	11.56
17775.60	55.85	---	150	H	152.0	8.8	74.00	18.15
17775.60	---	46.36	150	H	152.0	8.8	54.00	7.64

Middle Channel: 2437 MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1627.30	35.33	---	200	V	270.0	-15.9	74.00	38.67
1627.30	---	25.68	200	V	270.0	-15.9	54.00	28.32
3478.60	39.99	---	150	H	95.0	-8.9	74.00	34.01
3478.60	---	30.50	150	H	95.0	-8.9	54.00	23.50
4874.00	48.47	---	150	V	200.0	-5.4	74.00	25.53
4874.00	---	41.05	150	V	200.0	-5.4	54.00	12.95
7311.00	47.39	---	200	H	102.0	0.5	74.00	26.61
7311.00	---	37.67	200	H	102.0	0.5	54.00	16.33
14457.20	51.56	---	200	H	46.0	6.5	74.00	22.44
14457.20	---	42.26	200	H	46.0	6.5	54.00	11.74
17818.10	55.21	---	200	H	358.0	8.8	74.00	18.79
17818.10	---	46.49	200	H	358.0	8.8	54.00	7.51

High Channel : 2462 MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1574.60	---	25.90	150	V	296.0	-16.1	54.00	28.10
1574.60	37.28	---	150	V	296.0	-16.1	74.00	36.72
3456.50	---	30.84	200	H	339.0	-8.9	54.00	23.16
3456.50	40.19	---	200	H	339.0	-8.9	74.00	33.81
4924.00	---	37.65	150	V	190.0	-5.3	54.00	16.35
4924.00	46.53	---	150	V	190.0	-5.3	74.00	27.47
9738.00	---	38.06	200	H	139.0	2.0	54.00	15.94
9738.00	47.67	---	200	H	139.0	2.0	74.00	26.33
13840.10	---	41.98	200	H	89.0	6.0	54.00	12.02
13840.10	51.71	---	200	H	89.0	6.0	74.00	22.29
17841.90	---	46.51	200	V	350.0	8.8	54.00	7.49
17841.90	55.40	---	200	V	350.0	8.8	74.00	18.60

18GHz-25GHz:

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case low channel of 802.11g mode in Z-axis of orientation was recorded

Vertical

Date: 15.OCT.2020 20:09:15

Horizontal

Date: 15.OCT.2020 20:19:16

Restricted Bands Emissions Test:

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)**802.11b Mode:** (Pre-scan in the X, Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412 MHz								
2390.00	46.68	---	150.0	V	156.0	-2.9	74.00	27.32
2390.00	---	43.23	150.0	V	156.0	-2.9	54.00	10.77
High Channel: 2462 MHz								
2483.50	48.68	---	200.0	V	133.0	-2.5	74.00	25.32
2483.50	---	43.14	200.0	V	133.0	-2.5	54.00	10.86

802.11g Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412 MHz								
2390.00	48.40	---	200.0	V	140.0	-2.9	74.00	25.60
2390.00	---	44.44	200.0	V	140.0	-2.9	54.00	9.56
High Channel: 2462 MHz								
2483.50	49.05	---	150.0	V	262.0	-2.5	74.00	24.95
2483.50	---	44.93	150.0	V	262.0	-2.5	54.00	9.07

802.11n-HT20 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412 MHz								
2390.00	49.18	---	150.0	V	264.0	-2.9	74.00	24.82
2390.00	---	45.69	150.0	V	264.0	-2.9	54.00	8.31
High Channel: 2462 MHz								
2483.50	53.16	---	150.0	V	115.0	-2.5	74.00	20.84
2483.50	---	49.52	150.0	V	115.0	-2.5	54.00	4.48

Conducted Spurious Emissions at Antenna Port


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	25.5°C
Relative Humidity:	51 %
ATM Pressure:	101.5 kPa


The testing was performed by Chao Gao on 2020-10-15.

EUT operation mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
Low	2412	8.176	≥ 0.5
Middle	2437	8.176	≥ 0.5
High	2462	8.176	≥ 0.5
802.11g Mode			
Low	2412	15.271	≥ 0.5
Middle	2437	15.451	≥ 0.5
High	2462	15.451	≥ 0.5
802.11n-HT20 Mode			
Low	2412	15.511	≥ 0.5
Middle	2437	15.511	≥ 0.5
High	2462	15.511	≥ 0.5


802.11b Mode Low Channel




802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel




Delta 1 [T1] 0.89 dB
 RBW 100 kHz RF Att 30 dB
 Ref Lvl 30 dBm 15.45090180 MHz Unit dBm
 SWT 7.5 ms
 11 dB Offset
 -1.43 dBm
 2.42933467 GHz
 0.89 dB
 15.45090180 MHz
 -D1 5.68 dBm
 -D2 0.32 dBm
 1MAX
 Center 2.437 GHz 3 MHz/
 Span 30 MHz
 Date: 15.OCT.2020 17:34:43

Delta 1 [T1] 0.93 dB
 RBW 100 kHz RF Att 30 dB
 Ref Lvl 30 dBm 15.45090180 MHz SWT 7.5 ms Unit dBm


Center 2.462 GHz 3 MHz/ Span 30 MHz

Date: 15.OCT.2020 17:35:45


802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25.5°C
Relative Humidity:	51 %
ATM Pressure:	101.5 kPa

The testing was performed by Chao Gao on 2020-10-15.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
802.11b Mode				
Low	2412	20.85	30	Pass
Middle	2437	20.80	30	Pass
High	2462	20.56	30	Pass
802.11g Mode				
Low	2412	24.40	30	Pass
Middle	2437	24.04	30	Pass
High	2462	23.77	30	Pass
802.11n-HT20 Mode				
Low	2412	24.19	30	Pass
Middle	2437	23.81	30	Pass
High	2462	23.61	30	Pass

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data**Environmental Conditions**


Temperature:	25.5°C
Relative Humidity:	51 %
ATM Pressure:	101.5 kPa

The testing was performed by Chao Gao on 2020-10-15.


EUT operation mode: Transmitting

Test Result: Compliant


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side



802.11n-HT20 Mode Left Side



802.11n-HT20 Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine Compliant, and it is optional if the maximum conducted (average) output power was used to determine Compliant:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 * \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	25.5°C
Relative Humidity:	51 %
ATM Pressure:	101.5 kPa


The testing was performed by Chao Gao on 2020-10-15.

EUT operation mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b Mode			
Low	2412	-5.12	≤ 8
Middle	2437	-5.33	≤ 8
High	2462	-5.65	≤ 8
802.11g Mode			
Low	2412	-8.59	≤ 8
Middle	2437	-8.69	≤ 8
High	2462	-8.80	≤ 8
802.11n-HT20 mode			
Low	2412	-8.99	≤ 8
Middle	2437	-9.03	≤ 8
High	2462	-9.08	≤ 8


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******