

THE DUKE

BLUETOOTH SPEAKER WITH WIRELESS CHARGING

The DUKE has twin wireless charging pads and shares some of the audio drivers of the Drama Queen so it sounds amazing. Priced as a mid range option for a main room sideboard speaker it has a bold mellow sound quality. Equipped with the Bluetooth 5.1 it's performance will get you into the groove with its 4 drivers.

Finished in ebony veneer, the Duke has a black etched stainless steel grille and makes a stylish focal point for any room. Equipped with 2 x USB and 2 x Qi wireless charging, a volume limiter and built in security tether.



wireless charging



Bluetooth





THE DUKE

BLUETOOTH SPEAKER WITH TWIN WIRELESS CHARGING

Oliver Hemming

The DUKE has twin wireless charging pads and shares some of the audio drivers of the Drama Queen so it sounds amazing. Priced as a mid range option for a main room sideboard speaker it has a bold mellow sound quality. Equipped with the Bluetooth 5.1, it's performance will get you into the groove with its 4 drivers.

Finished in ebony veneer, the Duke has a black etched stainless steel grille and makes a stylish focal point for any room. Equipped with 2 x USB and 2 x Qi wireless charging, a volume limiter and built in security tether.



Qi
wireless charging

Model: DUESA

THE DUKE

BLUETOOTH SPEAKER WITH TWIN WIRELESS CHARGING
specifications

Model: DUESA

Brand: Oliver Hemming

Oliver Hemming

KEY FEATURES

2 x Qi Wireless charging

2 x usb C phone charging ports

Bluetooth 5.1

Volume limiter

Built in security tether



wireless charging

Bluetooth®

POWER SUPPLY & INPUTS

External power adapter

INPUT: 100-240V 50/60Hz 2A Max

OUTPUT: 18.0V 3A

CONTROLS

BT pairing

Volume + -

Pause / Play

CHARGING

2 x 10W Qi Wireless charging pad

2 x 5V / 2 amp USB C ports for phone charging

SIZE

W X H X D

300mm x 70mm x 120mm

12" x 3" x 5"

Nett Weight 2.2kg or 4.8Lbs

AUDIO

40W peak music power

2.1 Stereo

1 x 77.5mm rubber edge sub-woofers

1 x 52mm x 52mm midrange driver

1 x silk dome 20mm tweeters

1 x 120mm x 60mm passive radiator

SNR signal to noise ratio ≥ 85db

DSP enhanced bass technology

Frequency response: 35Hz -20,000Hz

Stainless steel facia grille, ebony veneer MDF cabinet

Class D stereo amplifier with ≤ 0.1% distortion @ 1W, 1KHz

Cabinet: MDF with ebony veneer

18V, 3A, 54W (110V / 220V) external AC adapter

FCC statement:

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: 1) this device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

--Reorient or relocate the receiving antenna.

--Increase the separation between the equipment and receiver.

--Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

--Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Radiation Exposure Statement

This device complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. During the operation of device a distance of 15 cm surrounding the device and 20 cm above the top surface of the device must be respected.