



FCS202508166W03

FCC RF Exposure

EUT Description: Wireless mouse

ModelNo.:MS039, MS033C, MS036, MS032

FCC ID: 2AXSU-MS039

Equipment type: Portable devices

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numericasimulation, is not required when the corresponding SAR Test Exclusion Thresholocondition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR testexclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance mm})] \cdot [f(\text{GHz})] < 3.0$ for 1-g SAR, and $s 7.5$ for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

conducted power (dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
-0.37	0.9183	2402	5	0.2846	3.0
-2.05	0.6237	2440	5	0.1949	3.0
-2.33	0.5848	2480	5	0.1842	3.0

2.4G

$EIRP = E_{\text{Meas}} + 20 \log(d_{\text{meas}}) - 104.7$

EIRP is the equivalent isotropically radiated power,

E_{Meas} in dBmis the field strength of the emission at the measurement distance, in dB u V/m

d_{meas} is the measurement distance, in m

Field strength(dBuV/m)	EIRP(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
96.42	1.26	1.3366	2405	5	0.4146	3.0
94.95	-0.21	0.9528	2440	5	0.2977	3.0
97.76	2.60	1.8197	2475	5	0.5726	3.0

Conclusion: No SAR is required