

**TEST REPORT**
Maximal Permissible Exposure [MPE]**Applicant Name:**EUCAST Co., Ltd.
(13595) 4th FL Sungok Bldg, 262,
Hwangsaeul-ro Bundang-Gu, Seongnam-si,
Gyeonggi-do, Korea**Date of Testing:**

11/01/2021 – 11/15/2021

Test Site/Location:PCTEST KOREA Lab. Yongin-si,
Gyeonggi-do, Korea**Test Report Serial No.:**

8K21102701-01-R2.2AXTR

FCC ID: 2AXTR-ECL4248-2401**APPLICANT:** EUCAST Co., Ltd.**Application Type:**

Certification

Model:

ECL4248-2401

EUT Type:

LTE Pico cell base station for CBRS

FCC Classification:

Citizens Band Category B Devices (CBD)

FCC Rule Part(s):

FCC Part 1 (§1.1310) and Part 2 (§2.1091)

Test Procedure(s):

KDB 447498 D01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Prepared by DuJin Kim
Test EngineerReviewed by Charles.Shin
Technical Manager

FCC: 2AXTR-ECL4248-2401	 PCTEST Proud to be part of element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS		Page 1 of 9

T A B L E O F C O N T E N T S

1.0	REVISION RECORD	3
2.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	4
2.1	Introduction	4
2.2	EUT Description	5
2.3	MPE Requirements Overview	6
2.4	Procedure	7
2.5	Results of RF exposure evaluation	8
3.0	CONCLUSION	9

FCC: 2AXTR-ECL4248-2401	 PCTEST Proud to be part of 	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS	Page 2 of 9	

1.0 REVISION RECORD

Issue Number	Issued Date	Revision History
8K21102701-01.2AXTR	11/15/2021	Initial Issue
8K21102701-01-R1.2AXTR	11/16/2021	Revision due to updated MPE table
8K21102701-01-R2.2AXTR	12/06/2021	Revision due to revised FCC Classification

FCC: 2AXTR-ECL4248-2401	 PCTEST Proud to be part of  element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS	Page 3 of 9	

2.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

2.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 2-1. Limits for Maximum Permissible Exposure (MPE)

FCC: 2AXTR-ECL4248-2401		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS	Page 4 of 9	

2.2 EUT Description

The Equipment Under Test (EUT) is the **EUCAST Co., Ltd. CBSD FCC ID: 2AXTR-ECL4248-2401**. The test data contained in this report pertains only to the emissions due to the EUT's LTE Band 48 operation in the CBRS band. Per FCC Part 96, this device is evaluated under Citizens Band Category B Devices (CBD).

This device supports the following conditional features:

EUT Type:	LTE Pico cell base station for CBRS		
Model Name:	ECL4248-2401		
Test Device Serial No.:	EE0F010021B010001		
Device Capabilities:	LTE		
Operating Band:	Band	Tx (Downlink)	Rx (Uplink)
	B48:	3550 MHz to 3700 MHz	3550 MHz to 3700 MHz
Supported Number of Carriers:	Max. 1 carrier		
Supported Modulation:	LTE: QPSK (E-TM 1.1), 16QAM (E-TM 3.2), 64QAM (E-TM 3.1)		
Supported Channel Bandwidth:	10MHz, 20MHz		
Maximum Output Power	10 MHz	29 dBm/Path	
	20 MHz	32 dBm/Path	
Number of Antenna ports	2		
Supported Configurations:	Single carrier		
Input Voltage:	-48 VDC		
Antenna Gain:	Max. 14 dBi		

Note

Actual antenna gain is 17dBi. And antenna cable loss as specified by the manufacture: 3dB (minimum) Therefore, the maximum antenna gain is 14dBi.

FCC: 2AXTR-ECL4248-2401		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS	Page 5 of 9	

2.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC KDB 447498 D01. These categories are fixed installation, mobile and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 46 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR §2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The **EUCAST Co., Ltd. CBSD FCC ID: 2AXTR-ECL4248-2401** is professionally installed on poles or walls in fixed locations. The device is a fixed mounted base station and MPE is evaluated to the General Population/Uncontrolled Exposure limits per 1.1310.

FCC: 2AXTR-ECL4248-2401		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS		Page 6 of 9

2.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each operating mode used in this product was initially measured with a spectrum analyzer and powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated for the safe distance which must be maintained during installation based on maximum power and antenna gain.

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

P_d = Power Density (mW/cm²)

P_{out} = output power to antenna (mW)

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator (cm)

FCC: 2AXTR-ECL4248-2401	 PCTEST® Proud to be part of element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS		Page 7 of 9

2.5 Results of RF exposure evaluation

LTE_Band 48_10MHz			Result
Frequency (MHz)	3550 – 3700	MHz	Pass
MPE Limit (W/m ²)	1.00	mW/m ²	
Distance (R)	100.20	cm	
Total MIMO Max measured Output power	32.00	dBm	
Total MIMO Max Output Power (P) (The Output Power scaled to maximum tune-up tolerance)	34.00	dBm	
Antenna Gain (G) Typical	14.00	dBi	
Power density (S)	0.50	mW/m ²	

Table 2-2. Calculated MPE Data for LTE_Band 48_10MHz

LTE_Band 48_20MHz			Result
Frequency (MHz)	3550 - 3700	MHz	Pass
MPE Limit (W/m ²)	1.00	mW/m ²	
Distance (R)	100.20	cm	
Total MIMO Max measured Output power	34.66	dBm	
Total MIMO Max Output Power (P) (The Output Power scaled to maximum tune-up tolerance)	37.00	dBm	
Antenna Gain (G) Typical	14.00	dBi	
Power density (S)	0.998	mW/m ²	

Table 2-3. Calculated MPE Data for LTE_Band 48_20MHz

FCC: 2AXTR-ECL4248-2401		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS		Page 8 of 9

3.0 CONCLUSION

The device meets the MPE Compliance requirements as specified in §2.1091 of the FCC Rules and Regulations with minimum safe distance of 100.2 cm for operation.

An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC: 2AXTR-ECL4248-2401	 Proud to be part of element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K21102701-01-R2.2AXTR	Test Dates: 11/01/2021 – 11/15/2021	EUT Type: LTE Pico cell base station for CBRS		Page 9 of 9