



## TEST REPORT

### Maximal Permissible Exposure [MPE]

**Applicant Name:**

EUCAST Co., Ltd.  
(13595) 4th FL Sungok Bldg, 262,  
Hwangsaewul-ro Bundang-Gu, Seongnam-si,  
Gyeonggi-do, Korea

**Date of Testing:**

06/27/2022 – 07/13/2022

**Test Site/Location:**

Element Lab., Suwon,  
Yongin-si, Gyeonggi-do, Korea

**Test Report Serial No.:**

8K22062201-01.2AXTR

<b>FCC ID:</b>	<b>2AXTR-EPL2248-1690</b>
<b>APPLICANT:</b>	<b>EUCAST Co., Ltd.</b>

**Application Type:** Certification

**Model:** EPL2248-1690

**EUT Type:** LTE portable base station

**FCC Classification:** Citizens Band Category B Devices (CBD)

**FCC Rule Part(s):** FCC Part 1 (§1.1310) and Part 2 (§2.1091)

**Test Procedure(s):** KDB 447498 D01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Prepared by DuJin Kim  
Test Engineer

Reviewed by Charles Shin  
Technical Manager

FCC ID: 2AXTR-EPL2248-1690		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 1 of 9

---

## T A B L E   O F   C O N T E N T S

---

1.0	REVISION RECORD .....	3
2.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....	4
2.1	Introduction .....	4
2.2	EUT Description .....	5
2.3	MPE Requirements Overview .....	6
2.4	Procedure .....	7
2.5	Results of RF exposure evaluation .....	8
3.0	CONCLUSION .....	9

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 2 of 9

## 1.0 REVISION RECORD

Issue Number	Issued Date	Revision History
8K22062201-01.2AXTR	07/13/2023	Initial Issue

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT	 EUCAST <sup>®</sup>	Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 3 of 9

## 2.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 2.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

**Table 2-1. Limits for Maximum Permissible Exposure (MPE)**

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 4 of 9

## 2.2 EUT Description

The Equipment Under Test (EUT) is the **EUCAST Co., Ltd. CBSD FCC ID: 2AXTR-EPL2248-1690**.

The test data contained in this report pertains only to the emissions due to the EUT's LTE Band 48 operation in the CBRS band. Per FCC Part 96, this device is evaluated under Citizens Band Category B Devices (CBD).

This device supports the following conditional features:

EUT Type:	LTE portable base station				
Model Name:	EPL2248-1690				
Test Device Serial No.:	EE0A010022300005				
Device Capabilities:	LTE				
Operating Band:	Band B48:	Operating Band: 3550 MHz to 3700 MHz	Band B48:		
Supported Number of Carriers:	Max. 1 carrier				
Supported Modulation:	QPSK (E-TM 1.1), 16QAM (E-TM 3.2), 64QAM (E-TM 3.1)				
Supported Channel Bandwidth:	10MHz, 20MHz				
Maximum Output Power	10 MHz	Maximum Output Power			
	20 MHz	32 dBm/Path			
Number of Antenna ports	2				
Supported Configurations:	Single carrier				
Input Voltage:	12VDC Battery, 24 VDC External power source				
Antenna Gain:	Max. 6 dBi				

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT	 EUCAST	Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 5 of 9

## 2.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC KDB 447498 D01. These categories are fixed installation, mobile and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 46 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR §2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The **EUCAST Co., Ltd. CBSD FCC ID: 2AXTR- EPL2248-1690** is professionally installed on poles or walls in fixed locations. The device is a fixed mounted base station and MPE is evaluated to the General Population/Uncontrolled Exposure limits per 1.1310.

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 6 of 9

## 2.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each operating mode used in this product was initially measured with a spectrum analyzer and powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated for the safe distance which must be maintained during installation based on maximum power and antenna gain.

### Friis Transmission Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

$P_d$  = Power Density (mW/cm<sup>2</sup>)

$\pi = 3.1416$

$P_{out}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

G = gain of antenna in linear scale

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 7 of 9

## 2.5 Results of RF exposure evaluation

LTE_Band 48_10MHz			Result
Frequency (MHz)	3550 – 3700	MHz	Pass
MPE Limit (W/m <sup>2</sup> )	1.00	mW/m <sup>2</sup>	
Distance (R)	40.00	cm	
Total MIMO Max measured Output power	31.61	dBm	
Total MIMO Max Output Power (P) (The Output Power scaled to maximum tune-up tolerance)	34.00	dBm	
Antenna Gain (G) Typical	6.00	dBi	
Power density (S)	<b>0.50</b>	mW/m <sup>2</sup>	

**Table 2-2. Calculated MPE Data for LTE\_Band 48\_10MHz**

LTE_Band 48_20MHz			Result
Frequency (MHz)	3550 - 3700	MHz	Pass
MPE Limit (W/m <sup>2</sup> )	1.00	mW/m <sup>2</sup>	
Distance (R)	40.00	cm	
Total MIMO Max measured Output power	34.35	dBm	
Total MIMO Max Output Power (P) (The Output Power scaled to maximum tune-up tolerance)	37.00	dBm	
Antenna Gain (G) Typical	6.00	dBi	
Power density (S)	<b>0.992</b>	mW/m <sup>2</sup>	

**Table 2-3. Calculated MPE Data for LTE\_Band 48\_20MHz**

Sample Calculation for 20MHz bandwidth maximum Output Power (P) :

Let us assume the following numbers:

- Rated conducted power: 32 dBm per port
- Maximum tune-up tolerance: +2 dB per port
- Scaled to the maximum tune-up tolerance power: 34dBm/port
- 10 times the base 10 logarithm of the power: 2511.88 mw
- Summed 2 TX MIMO Conducted Power linear sum: 2511.88 mw + 2511.88 mw = 5023.77mW
- 10 times the base 10 logarithm of the power P (5023.77 mW) is equal to 37 dBm.

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 8 of 9

## 3.0 CONCLUSION

The device meets the MPE Compliance requirements as specified in §2.1091 of the FCC Rules and Regulations with minimum safe distance of 40 cm for operation. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: 2AXTR-EPL2248-1690	 element	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 8K22062201-01.2AXTR	Test Dates: 06/27/2022 – 07/13/2022	EUT Type: LTE portable base station		Page 9 of 9