



**313 West 12800 South, Suite 311  
Draper, UT 84020  
(801) 260-4040**

## **Test Report**

### **Certification**

<b>FCC ID</b>	2AXWYERIKA
<b>Equipment Under Test</b>	ERIKA
<b>Test Report Serial No</b>	V055045_02
<b>Dates of Test</b>	November 3 – 4, 2020
<b>Report Issue Date</b>	November 17, 2020

<b>Test Specifications:</b>	<b>Applicant:</b>
FCC Part 15, Subpart C	Convergent Design, Inc. 4525 Northpark Dr. Colorado Springs, CO 80918 U.S.A.



## Certification of Engineering Report

This report has been prepared by VPI Laboratories, Inc. to document compliance of the device described below with the requirements of Federal Communications Commission (FCC) Part 15, Subpart C. This report may be reproduced in full. Partial reproduction of this report may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested.

<b>Applicant</b>	Convergent Design, Inc.
<b>Manufacturer</b>	Convergent Design, Inc.
<b>Brand Name</b>	Convergent Design
<b>Model Number</b>	ERIKA
<b>FCC ID</b>	2AXWYERIKA

On this 17<sup>th</sup> day of November 2020, I, individually and for VPI Laboratories, Inc., certify that the statements made in this engineering report are true, complete, and correct to the best of my knowledge, and are made in good faith.

Although NVLAP has accredited the VPI Laboratories, Inc. EMC testing facilities, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

VPI Laboratories, Inc.



Tested by: Norman P. Hansen



Reviewed by: Benjamin N. Antczak

<b>Revision History</b>		
<b>Revision</b>	<b>Description</b>	<b>Date</b>
01	Original Report Release	November 17, 2020
02	Photos Removed for Confidentiality	January 8, 2021

## Table of Contents

1	Client Information.....	5
1.1	Applicant.....	5
1.2	Manufacturer.....	5
2	Equipment Under Test (EUT).....	6
2.1	Identification of EUT.....	6
2.2	Description of EUT.....	6
2.3	EUT and Support Equipment.....	6
2.4	Interface Ports on EUT .....	7
2.5	Modification Incorporated/Special Accessories on EUT.....	7
2.6	Deviation from Test Standard.....	7
3	Test Specification, Methods and Procedures .....	8
3.1	Test Specification.....	8
3.2	Methods & Procedures.....	8
3.3	Test Procedure .....	12
4	Operation of EUT During Testing .....	13
4.1	Operating Environment.....	13
4.2	Operating Modes.....	13
4.3	EUT Exercise Software.....	13
5	Summary of Test Results .....	14
5.1	FCC Part 15, Subpart C .....	14
5.2	Result .....	14
6	Measurements, Examinations and Derived Results.....	15
6.1	General Comments.....	15
6.2	Test Results (ERIKA Receiver) .....	15
6.3	Test Results (ERIKA Microphone).....	25
7	Test Procedures and Test Equipment.....	34
7.1	Conducted Emissions at Mains Ports.....	34
7.2	Radiated Emissions .....	35
7.3	Equipment Calibration .....	37
7.4	Measurement Uncertainty .....	37
8	Photographs .....	38

## 1 Client Information

### 1.1 Applicant

<b>Company Name</b>	Convergent Design, Inc. 4525 Northpark Dr. Colorado Springs, CO 80918 U.S.A.
<b>Contact Name</b>	Michael Schell
<b>Title</b>	President

### 1.2 Manufacturer

<b>Company Name</b>	Convergent Design, Inc. 4525 Northpark Dr. Colorado Springs, CO 80918 U.S.A.
<b>Contact Name</b>	Michael Schell
<b>Title</b>	President

## 2 Equipment Under Test (EUT)

### 2.1 Identification of EUT

<b>Brand Name</b>	Convergent Design		
<b>Model Number</b>	ERIKA		
<b>Serial Number</b>	Microphone	50-1-0000066 & 50-1-0000128	
	Receiver	60-1-0000072 & 60-1-0000073	
<b>Dimensions (cm)</b>	Microphone	3.5 x 2 x 1	
	Receiver	3.75 x 2 x 0.8	

### 2.2 Description of EUT

The ERIKA is a wireless microphone system. The system is made up of a battery powered, wearable microphone and a USB powered receiver. The same PCB is used in each device with some components not filled depending on whether it is the microphone or the receiver. The microphone has a magnetic clasp for attachment to the speaker and is powered by a 3.7 V rechargeable battery. The microphone cannot transmit when charging. The receiver is powered by a USB port on the host device. Communication between the devices is by a 2.4 ISM band transceiver in each device using Nordic RF protocol at 2 Mbps. 37 channels are used in the hopping scheme with one used for advertising/pairing (channel 38 at 2426 MHz). The antenna used is a Johanson 2450T43B100 chip antenna with a maximum gain of 1.3 dBi, and a typical gain of -0.5 dBi.

Channel	Frequency (MHz)						
4	2404	24	2424	44	2444	64	2464
6	2406	26	2426	46	2446	66	2466
8	2408	28	2428	48	2448	68	2468
10	2410	30	2430	50	2450	70	2470
12	2412	32	2432	52	2452	72	2472
14	2414	34	2434	54	2454	74	2474
16	2416	36	2436	56	2456	76	2476
18	2418	38	2438	58	2458	78	2478
20	2420	40	2440	60	2460		
22	2422	42	2442	62	2462		

This report covers the circuitry of the devices subject to FCC Part 15, Subpart C. The circuitry of the device subject to FCC Subpart B was found to be compliant and is covered in VPI Laboratories, Inc. report V055043.

### 2.3 EUT and Support Equipment

The EUT and support equipment used during the test are listed below.

Brand Name Model Number Serial Number	Description	Name of Interface Ports / Interface Cables
BN: Convergent Design MN: ERIKA (Note 1) SN: See Table of 2.1	Wireless Microphone system	See Section 2.4
BN: Dell MN: Vostro SN: 43YLRP1	Computer	USB/USB A to USB C cable (Note 2)

Notes: (1) EUT

(2) Interface port connected to EUT (See Section 2.4)

The support equipment listed above was not modified in order to achieve compliance with this standard.

## 2.4 Interface Ports on EUT

Name of Ports	No. of Ports Fitted to EUT	Cable Description/Length
USB C	1	USB A to USB C cable/2 meters

## 2.5 Modification Incorporated/Special Accessories on EUT

There were no modifications or special accessories required to comply with the specification.

## 2.6 Deviation from Test Standard

There were no deviations from the test specification.

### 3 Test Specification, Methods and Procedures

#### 3.1 Test Specification

<b>Title</b>	FCC PART 15, Subpart C (47 CFR 15) 15.203, 15.207, and 15.247 Limits and methods of measurement of radio interference characteristics of radio frequency devices.
<b>Purpose of Test</b>	The tests were performed to demonstrate initial compliance

#### 3.2 Methods & Procedures

##### 3.2.1 §15.203 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

##### 3.2.2 §15.207 Conducted Limits

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50*	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

\*Decreases with the logarithm of the frequency.

Table 1: Limits for conducted emissions at mains ports of Class B ITE.

##### 3.2.3 §15.247 Operation within the bands 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz

- a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions.

- 1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400 – 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.
  - i. For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
  - ii. Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.
  - iii. Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels are used.
- 2) Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

b) The maximum peak output power of the intentional radiator shall not exceed the following:

- 1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- 2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

- 3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725 – 5850 MHz bands: 1 watt. As an alternative to a peak power measurement, compliance with the Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
- 4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

c) Operation with directional antenna gains greater than 6 dBi.

- 1) Fixed point-to-point operation:
  - i. Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
  - ii. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.
  - iii. Fixed, point-to-point operation, as used in paragraphs (b)(4)(i) and (b)(4)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.
- 2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400-2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
  - i. Different information must be transmitted to each receiver.

- ii. If the transmitter employs an antenna system that emits multiple directional beams but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna /antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
  - A. The directional gain shall be calculated as the sum of  $10 \log$  (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
  - B. A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.
- iii. If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.
- iv. Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned off, shall have an

average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4. The digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

- g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.
- h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.
- i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Note: Spread spectrum systems are sharing these bands on a noninterference basis with systems supporting critical Government requirements that have been allocated the usage of these bands, secondary only to ISM equipment operated under the provisions of Part 18 of this Chapter. Many of these Government systems are airborne radiolocation systems that emit a high EIRP which can cause interference to other users. Also, investigations of the effect of spread spectrum interference to U. S. Government operations in the 902-928 MHz band may require a future decrease in the power limits allowed for spread spectrum operation.

### 3.3 Test Procedure

VPI Laboratories, Inc. is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Lab Code: 100272-0, which is effective until September 30, 2021. VPI Laboratories, Inc. carries FCC Accreditation Designation Number US5263. VPI Laboratories main office is located at 313 W 12800 S, Suite 311, Draper, UT 84020. The testing was performed according to the procedures in ANSI C63.10-2013, KDB 558074, and 47 CFR Part 15.

## 4 Operation of EUT During Testing

### 4.1 Operating Environment

<b>Power Supply</b>	120 VAC/60 Hz to host receiver is powered from 5 VDC from host USB port to receiver Microphone is powered by a 3.7 VDC battery
---------------------	--

### 4.2 Operating Modes

The transmitter was tested on 3 orthogonal axes while in a constant transmit mode at the upper, middle, and lower channels. Power was set to +8 at 2 Mbps using Nordic nRF modulation. The voltage was varied as required by §15.31(e) with no change seen in transmitter characteristics.

### 4.3 EUT Exercise Software

Internal firmware was used to exercise the EUT. Nordic software on the computer was used to place the transceiver in the necessary test mode over the USB port.

## 5 Summary of Test Results

### 5.1 FCC Part 15, Subpart C

#### 5.1.1 Summary of Tests

Section	Environmental Phenomena	Frequency Range (MHz)	Result
15.203	Antenna Requirements	Structural requirement	Complied
15.207	Conducted Disturbance at Mains Ports	0.15 to 30	Complied
15.247(a)	Bandwidth Requirement	2400 to 2483.5	Complied
15.247(b)	Peak Output Power	2400 to 2483.5	Complied
15.247(d)	Spurious Emissions	0.009 - 25000	Complied
15.247(e)	Peak Power Spectral Density	2400 to 2483.5	Complied

### 5.2 Result

In the configuration tested, the EUT complied with the requirements of the specification.

## 6 Measurements, Examinations and Derived Results

### 6.1 General Comments

This section contains the test results only. Details of the test methods used and a list of the test equipment used during the measurements can be found in Section 7 of this report.

### 6.2 Test Results (ERIKA Receiver)

#### 6.2.1 §15.203 Antenna Requirements

The EUT uses a Johanson 2450AT43B100 chip antenna. The chip antenna has a maximum gain of 1.3 dBi. The antenna is soldered to the PCB and is not user replaceable.

#### Result

The EUT complied with the specification.

#### 6.2.2 Conducted Emissions at Mains Ports Data (Hot Lead)

Frequency (MHz)	AC Mains Lead	Detector	Measured Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
0.17	Hot Lead	Peak (Note 1)	45.1	55.0	-9.9
0.23	Hot Lead	Peak (Note 1)	47.5	52.5	-5.0
0.26	Hot Lead	Peak (Note 1)	43.8	51.5	-7.7
0.39	Hot Lead	Peak (Note 1)	37.7	48.1	-10.4
0.68	Hot Lead	Peak (Note 1)	36.6	46.0	-9.4
2.85	Hot Lead	Peak (Note 1)	35.0	46.0	-11.0
0.15	Neutral Lead	Peak (Note 1)	49.3	56.0	-6.7
0.22	Neutral Lead	Peak (Note 1)	45.7	52.9	-7.2
0.58	Neutral Lead	Peak (Note 1)	39.8	46.0	-6.2
0.64	Neutral Lead	Peak (Note 1)	38.1	46.0	-7.9
3.62	Neutral Lead	Peak (Note 1)	39.4	46.0	-6.6
3.78	Neutral Lead	Peak (Note 1)	40.4	46.0	-5.6

Note 1: The reference detector used for the measurements was Quasi-Peak or Peak and the data was compared to the average limit; therefore, the EUT was deemed to meet both the average and quasi-peak limits.

Note 2: The reference detector used for the measurements was quasi-peak and average and the data was compared to the respective limits.

#### Result


The EUT complied with the specification limit by a margin of 5.0 dB.

### 6.2.3 §15.247(a)(2) Emissions Bandwidth


Frequency (MHz)	Emissions 6 dB bandwidth (kHz)
2404	896
2440	917
2478	875

#### Result


In the configuration tested, the 6 dB bandwidth was greater than 500 kHz; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).



**Graph 1: Lowest Channel Bandwidth**



Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.4401 GHz	97.28 dBuV	
2-1	Peak	-511.0000 kHz	-5.87 dB	
3-2	Peak	917.0000 kHz	0.02 dB	

**Graph 2: Middle Channel Bandwidth**


Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.4781 GHz	96.23 dBuV	
2-1	Peak	-469.0000 kHz	-6.06 dB	
3-2	Peak	875.0000 kHz	0.15 dB	

**Graph 3: Highest Channel Bandwidth**


#### 6.2.4 §15.247(b)(3) Peak Output Power



The maximum peak RF power measured using radiated methods. The field strength measurements were converted to EIRP using the equation 1.1 of FCC KDB 412172. The antenna gain was then subtracted from the calculated EIRP to give a calculated conducted power and compared to the limit of 1 Watt. The antenna has a maximum gain of 1.3 dBi.

Frequency (MHz)	Measured Field Strength (dB $\mu$ V/m)	EIRP (mW)	EIRP (dBm)	Calculated Conducted Power (dBm)	Calculated Conducted Power (W)
2404	98.25	2.01	3.02	1.72	0.0015
2440	98.78	2.27	3.55	2.25	0.0017
2478	97.74	1.78	2.51	1.21	0.0013

#### Result

In the configuration tested, the RF peak output power was less than 1 Watt; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).





### 6.2.5 §15.247(d) Spurious Emissions

The frequency range from the lowest frequency generated or used in the device to the tenth harmonic of the highest fundamental emission was investigated to measure any radiated emissions. The following tables show measurements of any emission found. The noise floor was a minimum of 6 dB below the limit. The emissions in the restricted bands must meet the limits specified in §15.209. Tabular data for each of the spurious emissions is shown below for each of the units. Plots of the band edges are also shown. Note that all emissions seen are compared to the tighter limits of the restricted bands.

#### Result

All emissions in the restricted bands of §15.205 met the limits specified in §15.209; therefore, the EUT complies with the specification.

Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4808.0	Peak	Vertical	3.7	38.5	42.2	74.0	-31.8
4808.0	Average	Vertical	-6.8	38.5	31.7	54.0	-22.3
4808.0	Peak	Horizontal	4.2	38.5	42.7	74.0	-31.3
4808.0	Average	Horizontal	-5.7	38.5	32.8	54.0	-21.2
7212.0	Peak	Vertical	13.9	42.6	56.5	74.0	-17.5
7212.0	Average	Vertical	8.3	42.6	50.9	54.0	-3.1
7212.0	Peak	Horizontal	14.5	42.6	57.1	74.0	-16.9
7212.0	Average	Horizontal	9.4	42.6	52.0	54.0	-2.0
9616.0	Peak	Vertical	6.3	46.1	52.4	74.0	-21.6
9616.0	Average	Vertical	-4.6	46.1	41.5	54.0	-12.5
9616.0	Peak	Horizontal	6.0	46.1	52.1	74.0	-21.9
9616.0	Average	Horizontal	-4.7	46.1	41.4	54.0	-12.6
12020.0	Peak	Vertical	6.0	47.9	53.9	74.0	-20.1
12020.0	Average	Vertical	-4.7	47.9	43.2	54.0	-10.8
12020.0	Peak	Horizontal	6.7	47.9	54.6	74.0	-19.4
12020.0	Average	Horizontal	-5.0	47.9	42.9	54.0	-11.1

**Table 2: Transmitting at the Lowest Frequency**


Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4880.0	Peak	Vertical	2.9	38.6	41.5	74.0	-32.5
4880.0	Average	Vertical	-6.7	38.6	31.9	54.0	-22.1
4880.0	Peak	Horizontal	3.3	38.6	41.9	74.0	-32.1
4880.0	Average	Horizontal	-5.7	38.6	32.9	54.0	-21.1
7320.0	Peak	Vertical	14.8	42.9	57.7	74.0	-16.3

Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
7320.0	Average	Vertical	8.9	42.9	51.8	54.0	-2.2
7320.0	Peak	Horizontal	13.5	42.9	56.4	74.0	-17.6
7320.0	Average	Horizontal	8.5	42.9	51.4	54.0	-2.6
9760.0	Peak	Vertical	6.3	46.2	52.5	74.0	-21.5
9760.0	Average	Vertical	-4.4	46.2	41.8	54.0	-12.2
9760.0	Peak	Horizontal	6.3	46.2	52.5	74.0	-21.5
9760.0	Average	Horizontal	-4.3	46.2	41.9	54.0	-12.1
12200.0	Peak	Vertical	5.0	47.8	52.8	74.0	-21.2
12200.0	Average	Vertical	-5.9	47.8	41.9	54.0	-12.1
12200.0	Peak	Horizontal	5.2	47.8	53.0	74.0	-21.0
12200.0	Average	Horizontal	-5.5	47.8	42.3	54.0	-11.7


Table 3: Transmitting at the Middle Frequency

Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4956.0	Peak	Vertical	3.9	38.8	42.7	74.0	-31.3
4956.0	Average	Vertical	-4.9	38.8	33.9	54.0	-20.1
4956.0	Peak	Horizontal	5.5	38.8	44.3	74.0	-29.7
4956.0	Average	Horizontal	-5.0	38.8	33.8	54.0	-20.2
7434.0	Peak	Vertical	13.2	43.2	56.4	74.0	-17.6
7434.0	Average	Vertical	7.4	43.2	50.6	54.0	-3.4
7434.0	Peak	Horizontal	14.1	43.2	57.3	74.0	-16.7
7434.0	Average	Horizontal	9.3	43.2	52.5	54.0	-1.5
9912.0	Peak	Vertical	6.6	46.3	52.9	74.0	-21.1
9912.0	Average	Vertical	-4.8	46.3	41.5	54.0	-12.5
9912.0	Peak	Horizontal	5.1	46.3	51.4	74.0	-22.6
9912.0	Average	Horizontal	-4.9	46.3	41.4	54.0	-12.6
12390.0	Peak	Vertical	5.2	47.7	52.9	74.0	-21.1
12390.0	Average	Vertical	-5.6	47.7	42.1	54.0	-11.9
12390.0	Peak	Horizontal	5.9	47.7	53.6	74.0	-20.4
12390.0	Average	Horizontal	-5.5	47.7	42.2	54.0	-11.8

Table 4: Transmitting at the Highest Frequency



### Graph 7: Radiated Lower Band Edge Plot



### Graph 8: Radiated Upper Band Edge Plot


### 6.2.6 §15.247(e) Peak Power Spectral Density

The maximum peak 3 kHz spectral density measured using radiated methods. The field strength measurements were converted to EIRP using the equation 1.1 of FCC KDB 412172. The maximum antenna gain of 1.3 dBi was then subtracted from the calculated EIRP and was then compared to the limit of 8 dBm


Frequency (MHz)	Measured Field Strength (dB $\mu$ V/m)	EIRP (mW)	EIRP (dBm)	Calculated Conducted 3 kHz Power Spectral Density (dBm)
2404	85.72	0.112	-9.5	-10.8
2440	84.33	0.081	-10.9	-12.2
2478	84.04	0.076	-11.2	-12.5

### Result


The maximum peak power spectral density was less than the limit of 8 dBm; therefore, the EUT complies with the specification.



**Graph 9: Lowest Channel 3 kHz PSD Plot**



**Graph 10: Middle Channel 3 kHz PSD Plot**



**Graph 11: Highest Channel Output 3 kHz PSD Plot**

## 6.3 Test Results (ERIKA Microphone)

### 6.3.1 §15.203 Antenna Requirements

The EUT uses a Johanson 2450AT43B100 chip antenna. The chip antenna has a maximum gain of 1.3 dBi. The antenna is soldered to the PCB and is not user replaceable.

#### Result

The EUT complied with the specification.

### 6.3.2 Conducted Emissions at Mains Ports Data (Hot Lead)

The EUT is battery powered. The EUT will not transmit when the battery is charging.

#### Result


This requirement is not applicable to the ERIKA Microphone.

### 6.3.3 §15.247(a)(2) Emissions Bandwidth


Frequency (MHz)	Emissions 6 dB bandwidth (kHz)
2404	910
2440	896
2478	910

#### Result

In the configuration tested, the 6 dB bandwidth was greater than 500 kHz; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).




**Graph 12: Lowest Channel Bandwidth**



Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.4399 GHz	97.86 dBuV	
2-1	Peak	-315.0000 kHz	-6.11 dB	
3-2	Peak	896.0000 kHz	-0.16 dB	

**Graph 13: Middle Channel Bandwidth**



Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.4781 GHz	94.65 dBuV	
2-1	Peak	-504.0000 kHz	-5.97 dB	
3-2	Peak	910.0000 kHz	-0.21 dB	

**Graph 14: Highest Channel Bandwidth**


### 6.3.4 §15.247(b)(3) Peak Output Power

The maximum peak RF power measured using radiated methods. The field strength measurements were converted to EIRP using the equation 1.1 of FCC KDB 412172. The antenna gain was then subtracted from the calculated EIRP to give a calculated conducted power and compared to the limit of 1 Watt. The antenna has a maximum gain of 1.3 dBi.



Frequency (MHz)	Measured Field Strength (dB $\mu$ V/m)	EIRP (mW)	EIRP (dBm)	Calculated Conducted Power (dBm)	Calculated Conducted Power (W)
2404	98.45	2.10	3.22	1.92	0.0016
2440	99.11	2.44	3.88	2.58	0.0018
2478	97.08	1.53	1.85	0.35	0.0011

### Result

In the configuration tested, the RF peak output power was less than 1 Watt; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).



Graph 15: Lowest Channel Output Power Plot


**Graph 16: Middle Channel Output Power**

**Graph 17: Highest Channel Output Power Plot**

### 6.3.5 §15.247(d) Spurious Emissions

The frequency range from the lowest frequency generated or used in the device to the tenth harmonic of the highest fundamental emission was investigated to measure any radiated emissions. The following tables show measurements of any emission found. The noise floor was a minimum of 6 dB below the limit. The emissions in the restricted bands must meet the limits specified in §15.209. Tabular data for each of the spurious emissions is shown below for each of the units. Plots of the band edges are also shown. Note that all emissions seen are compared to the tighter limits of the restricted bands.

#### Result

All emissions in the restricted bands of §15.205 met the limits specified in §15.209; therefore, the EUT complies with the specification.

Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4808.0	Peak	Vertical	1.5	38.5	40.0	74.0	-34.0
4808.0	Average	Vertical	-7.3	38.5	31.2	54.0	-22.8
4808.0	Peak	Horizontal	3.5	38.5	42.0	74.0	-32.0
4808.0	Average	Horizontal	-6.7	38.5	31.8	54.0	-22.2
7212.0	Peak	Vertical	13.1	42.6	55.7	74.0	-18.3
7212.0	Average	Vertical	8.0	42.6	50.6	54.0	-3.4
7212.0	Peak	Horizontal	15.3	42.6	57.9	74.0	-16.1
7212.0	Average	Horizontal	10.3	42.6	52.9	54.0	-1.1
9616.0	Peak	Vertical	6.5	46.1	52.6	74.0	-21.4
9616.0	Average	Vertical	-4.3	46.1	41.8	54.0	-12.2
9616.0	Peak	Horizontal	6.8	46.1	52.9	74.0	-21.1
9616.0	Average	Horizontal	-3.2	46.1	42.9	54.0	-11.1
12020.0	Peak	Vertical	7.2	47.9	55.1	74.0	-18.9
12020.0	Average	Vertical	-2.4	47.9	45.5	54.0	-8.5
12020.0	Peak	Horizontal	7.2	47.9	55.1	74.0	-18.9
12020.0	Average	Horizontal	-2.9	47.9	45.0	54.0	-9.0

Table 5: Transmitting at the Lowest Frequency



Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4880.0	Peak	Vertical	3.9	38.6	42.5	74.0	-31.5
4880.0	Average	Vertical	-6.1	38.6	32.5	54.0	-21.5
4880.0	Peak	Horizontal	4.2	38.6	42.8	74.0	-31.2
4880.0	Average	Horizontal	-5.8	38.6	32.8	54.0	-21.2
7320.0	Peak	Vertical	12.3	42.9	55.2	74.0	-18.8
7320.0	Average	Vertical	6.2	42.9	49.1	54.0	-4.9

Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
7320.0	Peak	Horizontal	14.8	42.9	57.7	74.0	-16.3
7320.0	Average	Horizontal	8.6	42.9	51.5	54.0	-2.5
9760.0	Peak	Vertical	7.1	46.2	53.3	74.0	-20.7
9760.0	Average	Vertical	-4.8	46.2	41.4	54.0	-12.6
9760.0	Peak	Horizontal	7.0	46.2	53.2	74.0	-20.8
9760.0	Average	Horizontal	-3.7	46.2	42.5	54.0	-11.5
12200.0	Peak	Vertical	6.4	47.8	54.2	74.0	-19.8
12200.0	Average	Vertical	-4.0	47.8	43.8	54.0	-10.2
12200.0	Peak	Horizontal	7.3	47.8	55.1	74.0	-18.9
12200.0	Average	Horizontal	-3.5	47.8	44.3	54.0	-9.7

Table 6: Transmitting at the Middle Frequency

Frequency (MHz)	Detector	Antenna Polarity	Receiver Reading (dB $\mu$ V)	Correction Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4956.0	Peak	Vertical	4.2	38.8	43.0	74.0	-31.0
4956.0	Average	Vertical	-5.2	38.8	33.6	54.0	-20.4
4956.0	Peak	Horizontal	5.1	38.8	43.9	74.0	-30.1
4956.0	Average	Horizontal	-2.3	38.8	36.5	54.0	-17.5
7434.0	Peak	Vertical	13.5	43.2	56.7	74.0	-17.3
7434.0	Average	Vertical	8.8	43.2	52.0	54.0	-2.0
7434.0	Peak	Horizontal	17.5	43.2	60.7	74.0	-13.3
7434.0	Average	Horizontal	8.5	43.2	51.7	54.0	-2.3
9912.0	Peak	Vertical	6.6	46.3	52.9	74.0	-21.1
9912.0	Average	Vertical	-3.9	46.3	42.4	54.0	-11.6
9912.0	Peak	Horizontal	7.6	46.3	53.9	74.0	-20.1
9912.0	Average	Horizontal	-1.7	46.3	44.6	54.0	-9.4
12390.0	Peak	Vertical	5.4	47.7	53.1	74.0	-20.9
12390.0	Average	Vertical	-3.2	47.7	44.5	54.0	-9.5
12390.0	Peak	Horizontal	7.0	47.7	54.7	74.0	-19.3
12390.0	Average	Horizontal	-3.1	47.7	44.6	54.0	-9.4

Table 7: Transmitting at the Highest Frequency


**Graph 18: Radiated Lower Band Edge Plot**

**Graph 19: Radiated Upper Band Edge Plot**


### 6.3.6 §15.247(e) Peak Power Spectral Density

The maximum peak 3 kHz spectral density measured using radiated methods. The field strength measurements were converted to EIRP using the equation 1.1 of FCC KDB 412172. The maximum antenna gain of 1.3 dBi was then subtracted from the calculated EIRP and was then compared to the limit of 8 dBm


Frequency (MHz)	Measured Field Strength (dB $\mu$ V/m)	EIRP (mW)	EIRP (dBm)	Calculated Conducted 3 kHz Power Spectral Density (dBm)
2404	83.81	0.07	-11.4	-12.7
2440	86.31	0.13	-8.9	-10.2
2478	82.54	0.05	-12.7	-14.0

### Result


The maximum peak power spectral density was less than the limit of 8 dBm; therefore, the EUT complies with the specification.



Graph 20: Lowest Channel 3 kHz PSD Plot



**Graph 21: Middle Channel 3 kHz PSD Plot**



**Graph 22: Highest Channel Output 3 kHz PSD Plot**

## 7 Test Procedures and Test Equipment

### 7.1 Conducted Emissions at Mains Ports

The conducted emissions at mains and telecommunications ports from the EUT were measured using a spectrum analyzer with a quasi-peak adapter for peak, quasi-peak and average readings. The quasi-peak adapter uses a bandwidth of 9 kHz, with the spectrum analyzer's resolution bandwidth set at 100 kHz, for readings in the 150 kHz to 30 MHz frequency ranges.

The conducted emissions at mains ports measurements are performed in a screen room using a (50 Ω/50 μH) Line Impedance Stabilization Network (LISN).

Where mains flexible power cords are longer than 1 m, the excess cable is folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.


Where the EUT is a collection of devices with each device having its own power cord, the point of connection for the LISN is determined from the following rules:

- Each power cord, which is terminated in a mains supply plug, shall be tested separately.
- Power cords, which are not specified by the manufacturer to be connected via a host unit, shall be tested separately.
- Power cords which are specified by the manufacturer to be connected via a host unit or other power supplying equipment shall be connected to that host unit and the power cords of that host unit connected to the LISN and tested.
- Where a special connection is specified, the necessary hardware to effect the connection is supplied by the manufacturer for the testing purpose.
- When testing equipment with multiple mains cords, those cords not under test are connected to an artificial mains network (AMN) different than the AMN used for the mains cord under test.

For testing, desktop EUT are placed on a non-conducting table at least 0.8 meters from the metallic floor and placed 40 cm from the vertical coupling plane (copper plating in the wall behind EUT table). Floor standing equipment is placed directly on the earth grounded floor.

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	Hewlett Packard	8566B	V034141	05/12/2020	05/12/2021
Quasi-Peak Detector	Hewlett Packard	85650A	V033345	05/11/2020	05/11/2022
LISN	Teseq	NNB 51	V045406	08/20/2020	08/20/2021
Conductance Cable Wanship Upper Site	VPI Labs	Cable J	V034832	01/09/2020	01/09/2021
Filter	VPI Labs	47038	V047038	01/09/2020	01/09/2021
Test Software (AC)	VPI Labs	Revision 01	V035674	N/A	N/A

**Table 8: List of equipment used for conducted emissions testing at mains ports.**



**Figure 1: Conducted Emissions Test**

## 7.2 Radiated Emissions

The radiated emissions from the EUT were measured using a spectrum analyzer with a quasi-peak adapter for peak and quasi-peak readings.

A preamplifier with a fixed gain of 51 dB was used to increase the sensitivity of the measuring instrumentation. The quasi-peak adapter uses a bandwidth of 120 kHz, with the spectrum analyzer's resolution bandwidth set at 1 MHz, for readings in the 30 to 1000 MHz frequency ranges. For frequencies below 30 MHz, a 9 kHz resolution Bandwidth was used.

A loop antenna was used to measure frequencies below 30 MHz. A biconilog antenna was used to measure the frequency range of 30 to 1000 MHz, at a distance of 3 meters from the EUT. The readings obtained by these antennas are correlated to the levels obtained with a tuned dipole antenna by adding antenna factors. A double-ridged guide antenna was used to measure the emissions at frequencies above 1000 MHz at a distance of 3 and/or 1 meter from the EUT.

The configuration of the EUT was varied to find the maximum radiated emission. The EUT was connected to the peripherals listed in Section 2.3 via the interconnecting cables listed in Section 2.4. A technician manually manipulated these interconnecting cables to obtain worst-case radiated emissions. The EUT was rotated 360 degrees, and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission. Where there were multiple interface ports all of the same type, cables are either placed on all of the ports or cables added to these ports until the emissions do not increase by more than 2 dB.

Desktop EUT are measured on a non-conducting table 0.8 meters above the ground plane. For frequencies above 1000 MHz, the EUT is placed on a table 1.5 meters above the ground plane. The table is placed on a turntable, which is level with the ground plane. For equipment normally placed on floors, the equipment shall be placed directly on the turntable.

For radiated emissions testing that is performed at distances closer than the specified distance; an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer/Receiver	Rohde & Schwarz	ESU40	V033119	08/05/2020	08/05/2021
Spectrum Analyzer	Hewlett Packard	8566B	V034141	05/12/2020	05/12/2021
Quasi-Peak Detector	Hewlett Packard	85650A	V033345	05/11/2020	05/11/2022
Loop Antenna	EMCO	6502	V034216	02/11/2019	02/11/2021
Biconilog Antenna	EMCO	3142E-PA	V035736	06/24/2020	06/24/2022
Double Ridged Guide Antenna	EMCO	3115	V034194	03/09/2019	03/09/2021
Standard Gain Horn	ETS-Lindgren	3160-09	V034223	ICO	ICO
High Frequency Amplifier	Miteq	AFS4-001018000-35-10P-4	V033997	01/09/2020	01/09/2021
2.4 GHz Notch Filter	Micro-Tronics	BRM50702-03	V034213	01/09/2020	01/09/2021
6' High Frequency Cable	Microcoax	UFB197C-0-0720-000000	V033638	01/09/2020	01/09/2021
20' High Frequency Cable	Microcoax	UFB197C-1-3120-000000	V033979	01/09/2020	01/09/2021
3 Meter Radiated Emissions Cable Wanship Upper Site	Microcoax	UFB205A-0-4700-000000	V033639	01/09/2020	01/09/2021
Test Software (FCC)	VPI Labs	Revision 01	V035673	N/A	N/A

**Table 9: List of equipment used for radiated emissions testing.**




Figure 2: Radiated Emissions Test

### 7.3 Equipment Calibration

All applicable equipment is calibrated using either an independent calibration laboratory or VPI Laboratories, Inc. personnel at intervals defined in ANSI C63.4:2014 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

### 7.4 Measurement Uncertainty

Test	Uncertainty ( $\pm$ dB)	Confidence (%)
Conducted Emissions	2.8	95
Radiated Emission (9 kHz to 30 MHz)	3.3	95
Radiated Emissions (30 MHz to 1 GHz)	3.4	95
Radiated Emissions (1 GHz to 18 GHz)	5.0	95
Radiated Emissions (18 GHz to 40 GHz)	4.1	95

## 8 Photographs

Photographs are contained in a separate exhibit.

--- End of Report ---