



TEST REPORT

Applicant Name : ORAIMO TECHNOLOGY LIMITED
Address : FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG
Report Number : SZNS220914-41587E-RF-00A
FCC ID: 2AXYP-OPN-60D

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Audio Sunglasses
Model No.: OPN-60D
Multiple Model(s) No.: N/A
Trade Mark: oraimo
Date Received: 2022/09/14
Report Date: 2022/10/25

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Roger Ling

Roger Ling
EMC Engineer

Approved By:

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES.....	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC§15.247 (I), §1.1307 (B) (3) &§2.1093 – RF EXPOSURE	11
APPLICABLE STANDARD	11
FCC §15.203 – ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.205, §15.209 & §15.247(D) – RADIATED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	15
FACTOR & MARGIN CALCULATION	15
TEST DATA	15
FCC §15.247(A) (1)-CHANNEL SEPARATION TEST	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26
FCC §15.247(A) (1) – 20 DB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	28
FCC §15.247(A) (1) (III)-QUANTITY OF HOPPING CHANNEL TEST.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29

FCC §15.247(A) (1) (III) - TIME OF OCCUPANCY (DWELL TIME).....	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.247(B) (1) - PEAK OUTPUT POWER MEASUREMENT	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	31
FCC §15.247(D) - BAND EDGES TESTING.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
APPENDIX-FOR LEFT	33
APPENDIX A: 20dB EMISSION BANDWIDTH.....	33
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	37
APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER.....	41
APPENDIX D: CARRIER FREQUENCY SEPARATION	45
APPENDIX E: TIME OF OCCUPANCY	47
APPENDIX F: NUMBER OF HOPPING CHANNELS	57
APPENDIX G: BAND EDGE MEASUREMENTS	59
APPENDIX-FOR RIGHT.....	64
APPENDIX A: 20dB EMISSION BANDWIDTH.....	64
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	68
APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER.....	72
APPENDIX D: CARRIER FREQUENCY SEPARATION	76
APPENDIX E: TIME OF OCCUPANCY	78
APPENDIX F: NUMBER OF HOPPING CHANNELS	88
APPENDIX G: BAND EDGE MEASUREMENTS	90

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	SZNS220914-41587E-RF-00A	Original Report	2022/10/25

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	Bluetooth: 2402~2480MHz
Maximum conducted Peak output power	Bluetooth: 4.26dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification*	-0.01dBi for left; -0.57dBi for right (provided by the applicant)
Voltage Range	DC3.7V from battery or DC5V from USB Charging Port
Sample serial number	SZNS220914-41587E-RF-S1 for Radiated Emissions SZNS220914-41587E-RF-S2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
AC Line Conducted emission		2.72dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Two bluetooths, only one of them work, according to the receiving quality of the signal, and the two cannot work at the same time

EUT Exercise Software

“BT FCC Tool v2.24”* exercise software was used and the power level is 2 for left, 0 for right*. The software and power level was provided by the manufacturer.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (3) & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth & 99% Occupied Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

Not Applicable: the Bluetooth function cannot used when in charging.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated emission test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13
RF conducted test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/01/19	2023/01/18
Tonscend	RF Control Unit	JS0806-2	19G8060182	2021/10/26	2022/10/25
WEINSCHHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (3) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance

SAR-Based Exemption:

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum timeaveraged power or maximum time-averaged ERP, whichever is greater.

Per § 1.1307(b)(3)(i)(B), for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

For worst case:

Exemption limit:

For $f=2.48\text{GHz}$, $d=0.5\text{cm}$, the $P_{th}=2.72\text{mW}$

The higher of the available maximum time-averaged power or effective radiated power (ERP):

The antenna gain is -0.01dBi (-2.16dBd), $0\text{dBd}=2.15\text{dBi}$

The maximum tune-up conducted power is 4.3dBm (2.69mW), which less than $2.72\text{ mW}@2480\text{MHz}$ exemption limit

So the stand-alone SAR evaluation can be exempted.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has two internal antennas, which was permanently attached, the maximum antenna gain is -0.01dBi for left and -0.57dBi for right, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.


FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
Above 1 GHz	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	24~25.6 °C
Relative Humidity:	50~60 %
ATM Pressure:	101.0 kPa

The testing was performed by Level Li on 2022-10-14 for below 1GHz, Jeff Jiang on 2022-09-19 for above 1GHz

EUT operation mode: Transmitting


Note: Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded

For Left:

30MHz-1GHz: (worst case is GFSK Mode, high channel)

Note: When the test result of Peak was less than the limit of QP, just the peak value was recorded.


Horizontal:



Site : chamber
Condition: 3m HORIZONTAL
Job No. : SZNS220914-41587E-RF
Test Mode: BT
Note : Left

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	39.506	-10.46	28.35	17.89	40.00	-22.11	Peak
2	56.001	-10.18	28.36	18.18	40.00	-21.82	Peak
3	101.912	-11.58	28.97	17.39	43.50	-26.11	Peak
4	236.541	-10.95	27.79	16.84	46.00	-29.16	Peak
5	370.865	-7.30	27.54	20.24	46.00	-25.76	Peak
6	549.501	-4.03	28.00	23.97	46.00	-22.03	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220914-41587E-RF
 Test Mode: BT
 Note : Left

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	38.905	-10.61	28.16	17.55	40.00	-22.45	Peak
2	58.715	-10.17	31.52	21.35	40.00	-18.65	Peak
3	101.867	-11.58	37.57	25.99	43.50	-17.51	Peak
4	177.977	-12.97	27.88	14.91	43.50	-28.59	Peak
5	362.031	-7.62	27.67	20.05	46.00	-25.95	Peak
6	627.549	-2.22	27.47	25.25	46.00	-20.75	Peak

Above 1GHz: (worst case is GFSK Mode, DH5)

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(2402MHz)									
2310	68.59	PK	164	2.2	H	-7.24	61.35	74	-12.65
2310	37.72	AV	164	2.2	H	-7.24	30.48	54	-23.52
2310	68.66	PK	78	2.3	V	-7.24	61.42	74	-12.58
2310	37.79	AV	78	2.3	V	-7.24	30.55	54	-23.45
2390	69.50	PK	196	1.3	H	-7.22	62.28	74	-11.72
2390	38.63	AV	196	1.3	H	-7.22	31.41	54	-22.59
2390	69.24	PK	45	1.6	V	-7.22	62.02	74	-11.98
2390	38.37	AV	45	1.6	V	-7.22	31.15	54	-22.85
4804	62.32	PK	323	1.1	H	-3.51	58.81	74	-15.19
4804	31.45	AV	323	1.1	H	-3.51	27.94	54	-26.06
4804	59.92	PK	227	2.2	V	-3.51	56.41	74	-17.59
4804	29.05	AV	227	2.2	V	-3.51	25.54	54	-28.46
Middle Channel(2441MHz)									
4882	62.58	PK	198	1.5	H	-3.37	59.21	74	-14.79
4882	31.71	AV	198	1.5	H	-3.37	28.34	54	-25.66
4882	61.34	PK	103	2	V	-3.37	57.97	74	-16.03
4882	30.47	AV	103	2	V	-3.37	27.1	54	-26.90
High Channel(2480 MHz)									
2483.5	71.03	PK	293	2.4	H	-7.20	63.83	74	-10.17
2483.5	40.16	AV	293	2.4	H	-7.20	32.96	54	-21.04
2483.5	70.88	PK	16	1.8	V	-7.20	63.68	74	-10.32
2483.5	40.01	AV	16	1.8	V	-7.20	32.81	54	-21.19
2500	69.02	PK	130	2	H	-7.18	61.84	74	-12.16
2500	38.15	AV	130	2	H	-7.18	30.97	54	-23.03
2500	69.27	PK	307	2.3	V	-7.18	62.09	74	-11.91
2500	38.40	AV	307	2.3	V	-7.18	31.22	54	-22.78
4960	62.13	PK	334	1.6	H	-3.01	59.12	74	-14.88
4960	31.26	AV	334	1.6	H	-3.01	28.25	54	-25.75
4960	61.20	PK	190	1.1	V	-3.01	58.19	74	-15.81
4960	30.33	AV	190	1.1	V	-3.01	27.32	54	-26.68

Note:



Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level = Corrected Factor + Reading

Margin = Absolute Level - Limit

The other spurious emission which is in the noise floor level was not recorded.


When the test result of Peak was below the limit of average, just the Peak value was recorded.

1-18GHz**Pre-scan for Middle Channel****Horizontal:****Vertical:**


18-25GHz

Pre-scan for Middle Channel

Horizontal:



Vertical:




For Right:

30MHz-1GHz: (worst case is GFSK Mode, high channel)

Note: When the test result of Peak was less than the limit of QP, just the peak value was recorded.


Horizontal:



Site : chamber
Condition: 3m HORIZONTAL
Job No. : SZNS220914-41587E-RF
Test Mode: BT
Note : Right

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	38.786	-10.63	26.71	16.08	40.00	-23.92	Peak
2	56.543	-10.11	28.53	18.42	40.00	-21.58	Peak
3	101.867	-11.58	29.11	17.53	43.50	-25.97	Peak
4	184.895	-12.19	27.79	15.60	43.50	-27.90	Peak
5	342.729	-7.31	27.28	19.97	46.00	-26.03	Peak
6	933.498	1.77	29.03	30.80	46.00	-15.20	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220914-41587E-RF
 Test Mode: BT
 Note : Right

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	38.939	-10.60	28.34	17.74	40.00	-22.26	Peak
2	58.715	-10.17	31.63	21.46	40.00	-18.54	Peak
3	79.975	-16.79	32.54	15.75	40.00	-24.25	Peak
4	101.867	-11.58	37.27	25.69	43.50	-17.81	Peak
5	280.024	-9.58	27.62	18.04	46.00	-27.96	Peak
6	620.710	-2.51	27.89	25.38	46.00	-20.62	Peak

Above 1GHz: (worst case is GFSK Mode, DH5)

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(2402MHz)									
2310	68.73	PK	108	1.3	H	-7.24	61.49	74	-12.51
2310	37.89	AV	108	1.3	H	-7.24	30.65	54	-23.35
2310	68.56	PK	56	1.6	V	-7.24	61.32	74	-12.68
2310	37.72	AV	56	1.6	V	-7.24	30.48	54	-23.52
2390	69.30	PK	333	2.1	H	-7.22	62.08	74	-11.92
2390	38.46	AV	333	2.1	H	-7.22	31.24	54	-22.76
2390	69.49	PK	148	2	V	-7.22	62.27	74	-11.73
2390	38.65	AV	148	2	V	-7.22	31.43	54	-22.57
4804	68.39	PK	188	1.4	H	-3.51	64.88	74	-9.12
4804	37.55	AV	188	1.4	H	-3.51	34.04	54	-19.96
4804	66.29	PK	1	1.6	V	-3.51	62.78	74	-11.22
4804	35.45	AV	1	1.6	V	-3.51	31.94	54	-22.06
Middle Channel(2441MHz)									
4882	69.68	PK	89	1.7	H	-3.37	66.31	74	-7.69
4882	38.84	AV	89	1.7	H	-3.37	35.47	54	-18.53
4882	65.27	PK	155	1.5	V	-3.37	61.9	74	-12.10
4882	34.43	AV	155	1.5	V	-3.37	31.06	54	-22.94
High Channel(2480 MHz)									
2483.5	71.20	PK	51	2.3	H	-7.20	64	74	-10.00
2483.5	40.36	AV	51	2.3	H	-7.20	33.16	54	-20.84
2483.5	70.51	PK	328	1.3	V	-7.20	63.31	74	-10.69
2483.5	39.67	AV	328	1.3	V	-7.20	32.47	54	-21.53
2500	68.31	PK	346	2.4	H	-7.18	61.13	74	-12.87
2500	37.47	AV	346	2.4	H	-7.18	30.29	54	-23.71
2500	68.55	PK	115	1.1	V	-7.18	61.37	74	-12.63
2500	37.71	AV	115	1.1	V	-7.18	30.53	54	-23.47
4960	70.41	PK	273	1.1	H	-3.01	67.40	74	-6.60
4960	39.57	AV	273	1.1	H	-3.01	36.56	54	-17.44
4960	66.20	PK	223	2.5	V	-3.01	63.19	74	-10.81
4960	35.36	AV	223	2.5	V	-3.01	32.35	54	-21.65

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level = Corrected Factor + Reading

Margin = Absolute Level - Limit


The other spurious emission which is in the noise floor level was not recorded.

When the test result of Peak was below the limit of average, just the Peak value was recorded.


1-18GHz

Pre-scan for High Channel

Horizontal:




Vertical:




18-25GHz

Pre-scan for High Channel

Horizontal:



Vertical:



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST


Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.2

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.



Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2022-10-11.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure


Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data**Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2022-10-11.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.3

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

**Test Data****Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2022-10-11.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

**Test Data****Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2022-10-11.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT


Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.5

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2022-10-11.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(d) - BAND EDGES TESTING


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.6 & Clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2022-10-11 and 2022-10-24.


EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


APPENDIX-For Left**Appendix A: 20dB Emission Bandwidth
Test Result**

Test Mode	Antenna	Channel	20db EBW[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.96	---	---
		2441	0.97	---	---
		2480	0.98	---	---
2DH1	Ant1	2402	1.21	---	---
		2441	1.22	---	---
		2480	1.22	---	---
3DH1	Ant1	2402	1.21	---	---
		2441	1.22	---	---
		2480	1.22	---	---

Test Graphs




2DH1_Ant1_2402




Date: 11.OCT.2022 19:57:21

2DH1_Ant1_2441




Date: 11.OCT.2022 19:58:59

2DH1_Ant1_2480




Date: 11.OCT.2022 20:00:05

3DH1_Ant1_2402




Date: 11.OCT.2022 20:24:00

3DH1_Ant1_2441



Date: 11.OCT.2022 20:27:14

3DH1_Ant1_2480




Date: 11.OCT.2022 20:28:09


**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.905	---	---
		2441	0.911	---	---
		2480	0.914	---	---
2DH1	Ant1	2402	1.136	---	---
		2441	1.142	---	---
		2480	1.142	---	---
3DH1	Ant1	2402	1.118	---	---
		2441	1.121	---	---
		2480	1.127	---	---

Test Graphs








**Appendix C: Maximum conducted Peak output power
Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	3.15	≤20.97	PASS
		2441	2.97	≤20.97	PASS
		2480	3.02	≤20.97	PASS
2DH1	Ant1	2402	3.10	≤20.97	PASS
		2441	2.92	≤20.97	PASS
		2480	2.97	≤20.97	PASS
3DH1	Ant1	2402	3.13	≤20.97	PASS
		2441	2.95	≤20.97	PASS
		2480	2.99	≤20.97	PASS

Test Graphs



2DH1_Ant1_2402



2DH1_Ant1_2441



2DH1_Ant1_2480



3DH1_Ant1_2402



Date: 11.OCT.2022 20:24:27

3DH1_Ant1_2441



Date: 11.OCT.2022 20:27:31

3DH1_Ant1_2480



Date: 11.OCT.2022 20:28:36

**Appendix D: Carrier frequency separation
Test Result**

Test Mode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	1.003	≥0.653	PASS
2DH1	Ant1	Hop	1.003	≥0.813	PASS
3DH1	Ant1	Hop	1.000	≥0.813	PASS

Test Graphs



**Appendix E: Time of occupancy
Test Result**


Test Mode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.37	320	0.118	≤0.4	PASS
DH3	Ant1	Hop	1.61	160	0.258	≤0.4	PASS
DH5	Ant1	Hop	2.85	110	0.314	≤0.4	PASS
2DH1	Ant1	Hop	0.38	320	0.122	≤0.4	PASS
2DH3	Ant1	Hop	1.62	170	0.275	≤0.4	PASS
2DH5	Ant1	Hop	2.86	110	0.315	≤0.4	PASS
3DH1	Ant1	Hop	0.38	320	0.122	≤0.4	PASS
3DH3	Ant1	Hop	1.62	160	0.259	≤0.4	PASS
3DH5	Ant1	Hop	2.86	110	0.315	≤0.4	PASS


Note 1: A period time= $0.4 \times 79 = 31.6(S)$, Result=BurstWidth*Totalhops


Note 2: Totalhops=Hopping Number in $3.16s \times 10$


Note 3: Hopping Number in $3.16s$ =Total of highest signals in $3.16s$ (Second high signals were other channel)


Test Graphs
























**Appendix F: Number of hopping channels
Test Result**

Test Mode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	≥15	PASS
2DH1	Ant1	Hop	79	≥15	PASS
3DH1	Ant1	Hop	79	≥15	PASS

Test Graphs




Appendix G: Band edge measurements


Test Graphs




DH1_Ant1_Low_Hop_2402




DH1_Ant1_High_Hop_2480



2DH1_Ant1_Low_2402




2DH1_Ant1_High_2480




Date: 11.OCT.2022 20:00:25

2DH1_Ant1_Low_Hop_2402




Date: 11.OCT.2022 20:21:15

2DH1_Ant1_High_Hop_2480




Date: 11.OCT.2022 20:20:47

3DH1 Ant1 Low 2402




Date: 11.OCT.2022 20:24:20

3DH1 Ant1 High 2480




Date: 11.OCT.2022 20:28:29

3DH1 Ant1 Low Hop 2402




Date: 11.OCT.2022 20:30:58




APPENDIX-For Right**Appendix A: 20dB Emission Bandwidth
Test Result**

Test Mode	Antenna	Channel	20db EBW[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.94	---	---
		2441	0.94	---	---
		2480	0.94	---	---
2DH1	Ant1	2402	1.22	---	---
		2441	1.22	---	---
		2480	1.22	---	---
3DH1	Ant1	2402	1.22	---	---
		2441	1.22	---	---
		2480	1.22	---	---

Test Graphs




2DH1_Ant1_2402




Date: 11.OCT.2022 18:49:32

2DH1_Ant1_2441




Date: 11.OCT.2022 18:50:59

2DH1_Ant1_2480




Date: 11.OCT.2022 18:51:52

3DH1_Ant1_2402




Date: 11.OCT.2022 19:02:41

3DH1_Ant1_2441



Date: 11.OCT.2022 19:03:50

3DH1_Ant1_2480



Date: 11.OCT.2022 19:04:48


**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.890	---	---
		2441	0.890	---	---
		2480	0.893	---	---
2DH1	Ant1	2402	1.136	---	---
		2441	1.142	---	---
		2480	1.136	---	---
3DH1	Ant1	2402	1.124	---	---
		2441	1.121	---	---
		2480	1.118	---	---

Test Graphs




2DH1_Ant1_2402




Date: 11.OCT.2022 18:49:43

2DH1_Ant1_2441




Date: 11.OCT.2022 18:51:10

2DH1_Ant1_2480




Date: 11.OCT.2022 18:52:03


3DH1_Ant1_2402



3DH1_Ant1_2441



3DH1_Ant1_2480



**Appendix C: Maximum conducted Peak output power
Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	3.68	≤20.97	PASS
		2441	3.88	≤20.97	PASS
		2480	4.26	≤20.97	PASS
2DH1	Ant1	2402	3.67	≤20.97	PASS
		2441	3.85	≤20.97	PASS
		2480	4.25	≤20.97	PASS
3DH1	Ant1	2402	3.81	≤20.97	PASS
		2441	4.02	≤20.97	PASS
		2480	4.24	≤20.97	PASS

Test Graphs



2DH1_Ant1_2402



2DH1_Ant1_2441



2DH1_Ant1_2480



3DH1_Ant1_2402



3DH1_Ant1_2441



3DH1_Ant1_2480



**Appendix D: Carrier frequency separation
Test Result**

Test Mode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	1.006	≥ 0.627	PASS
2DH1	Ant1	Hop	1.003	≥ 0.813	PASS
3DH1	Ant1	Hop	1.003	≥ 0.813	PASS

Test Graphs



**Appendix E: Time of occupancy
Test Result**


Test Mode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.37	330	0.122	≤0.4	PASS
DH3	Ant1	Hop	1.61	160	0.258	≤0.4	PASS
DH5	Ant1	Hop	2.85	120	0.342	≤0.4	PASS
2DH1	Ant1	Hop	0.38	320	0.122	≤0.4	PASS
2DH3	Ant1	Hop	1.62	160	0.259	≤0.4	PASS
2DH5	Ant1	Hop	2.86	110	0.315	≤0.4	PASS
3DH1	Ant1	Hop	0.38	330	0.125	≤0.4	PASS
3DH3	Ant1	Hop	1.62	170	0.275	≤0.4	PASS
3DH5	Ant1	Hop	2.86	110	0.315	≤0.4	PASS


Note 1: A period time= $0.4 \times 79 = 31.6(S)$, Result=BurstWidth*Totalhops


Note 2: Totalhops=Hopping Number in $3.16s \times 10$


Note 3: Hopping Number in $3.16s$ =Total of highest signals in $3.16s$ (Second high signals were other channel)


Test Graphs
























**Appendix F: Number of hopping channels
Test Result**


Test Mode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	≥15	PASS
2DH1	Ant1	Hop	79	≥15	PASS
3DH1	Ant1	Hop	79	≥15	PASS

Test Graphs




Appendix G: Band edge measurements

Test Graphs




DH1_Ant1_Low_Hop_2402




Date: 11.OCT.2022 18:45:09

DH1_Ant1_High_Hop_2480




Date: 11.OCT.2022 18:46:15

2DH1_Ant1_Low_2402




Date: 11.OCT.2022 18:49:52

2DH1_Ant1_High_2480




Date: 11.OCT.2022 18:52:12

2DH1_Ant1_Low_Hop_2402




Date: 11.OCT.2022 18:59:40

2DH1_Ant1_High_Hop_2480




Date: 11.OCT.2022 18:59:15

3DH1_Ant1_Low_2402




Date: 11.OCT.2022 19:03:01

3DH1_Ant1_High_2480




Date: 11.OCT.2022 19:05:08

3DH1_Ant1_Low_Hop_2402



Date: 24.OCT.2022 22:35:45



***** END OF REPORT *****