

FCC Part 15C&RSS-247 TEST REPORT

FCC ID:2AY2I-2130XI

IC: 27035-2130XI

Product : Amplifier
Model Name : Connect 2130Xi
Brand : elipson
Report No. : NCT25010088-3

Prepared for

AV Industry

309 Avenue du Général De Gaulle, 94500 Champigny Sur Marne, France

Prepared by

Shenzhen NCT Testing Technology Co., Ltd.

**A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District,
Shenzhen, People's Republic of China**

TEL: 400-8868-419

FAX: 86-755-27790922

1 TEST RESULT CERTIFICATION

Applicant : AV Industry

Address : 309 Avenue du Général De Gaulle, 94500 Champigny Sur Marne, France

Manufacturer : AV Industry

Address : 309 Avenue du Général De Gaulle, 94500 Champigny Sur Marne, France

Product name : Amplifier

Model name : Connect 2130Xi

Additional model : N/A

Standards : FCC CFR47 Part 15 Section 15.247
RSS-247 Issue 3, August 2023
RSS-Gen Issue 5, Amendment 2, February, 2021

Test procedure : ANSI C63.10:2013

Date of test : Oct. 08, 2024 to Mar. 06, 2025

Date of Issue : Mar. 11, 2025

This device described above has been tested by NCT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NCT, this document may be altered or revised by NCT, personal only, and shall be noted in the revision of the document.

Test Engineer:



Keven Wu / Engineer

Technical Manager:



Henry Wang / Manager



Contents

Page

1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF E.U.T.	6
3.2 CHANNEL LIST	7
3.3 TEST SITE	8
3.4 TEST SETUP CONFIGURATION	9
3.5 TEST MODE	9
4 EQUIPMENT DURING TEST	10
4.1 EQUIPMENTS LIST	10
4.2 MEASUREMENT UNCERTAINTY	12
4.3 DESCRIPTION OF SUPPORT UNITS	12
5 CONDUCTED EMISSION	13
5.1 E.U.T. OPERATION	13
5.2 EUT SETUP	13
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
5.4 MEASUREMENT PROCEDURE	14
5.5 CONDUCTED EMISSION LIMIT	14
5.6 MEASUREMENT DESCRIPTION	14
5.7 CONDUCTED EMISSION TEST RESULT	14
6 RADIATED SPURIOUS EMISSIONS	17
6.1 EUT OPERATION	17
6.2 TEST SETUP	18
6.3 SPECTRUM ANALYZER SETUP	19
6.4 TEST PROCEDURE	20
6.5 SUMMARY OF TEST RESULTS	21
7 CONDUCT BAND EDGE AND SPURIOUS EMISSIONS MEASUREMENT	28
7.1 TEST PROCEDURE	28
7.2 TEST RESULT	29

8 6DB&99% BANDWIDTH MEASUREMENT	34
8.1 TEST PROCEDURE	34
8.2 TEST RESULT	34
9 MAXIMUM PEAK OUTPUT POWER	39
9.1 TEST PROCEDURE	39
9.2 TEST RESULT	40
10 POWER SPECTRAL DENSITY	41
10.1 TEST PROCEDURE	41
10.2 TEST RESULT	41
11 ANTENNA APPLICATION	50
11.1 ANTENNA REQUIREMENT	50
11.2 RESULT	50
12 TEST SETUP AND EUT PHOTOS	51

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	FCC part 15.207 RSS-Gen 8.8	PASS
Radiated Spurious Emissions	FCC part 15.205/15.209 RSS-Gen §6.13	PASS
Conducted Spurious Emission	FCC part 15.205/15.209 RSS-Gen 8.9	PASS
Band edge	FCC part 15.247(d) RSS-247 5.5	PASS
6dB&99% Bandwidth	FCC part 15.247 (a)(2) RSS-247 5.2(a) RSS-Gen section 6.7	PASS
Maximum Peak Output Power	FCC part 15.247 (b)(3) RSS-247 5.4(d)	PASS
Power Spectral Density	FCC part 15.247 (e) RSS-247 5.2(b)	PASS
Antenna Requirement	FCC part 15.203/15.247 (c) RSS-Gen 6.8	PASS

Remark:

"N/A" denotes test is not applicable in this Test Report.

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Amplifier
Model Name	:	Connect 2130Xi
Sample ID	:	241119082
HVIN	:	Connect 2130Xi
Sample(s) Status:	:	Engineer sample
Series Model	:	N/A
Model Different.:	:	N/A
Specification	:	802.11b/g/n20
Operation Frequency	:	2412-2462MHz for 802.11 b/g/n (HT20);
Number of Channel	:	11 channels for 802.11 b/g/n (HT20);
Type of Modulation	:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n(HT20): DSSS (CCK, DQPSK,DBPSK)+OFDM+OFAMA (QPSK, BPSK, 16-QAM, 64-QAM)
Antenna installation	:	External Antenna
Antenna Gain	:	2.15dBi
Power supply	:	AC100-240V 50/60Hz
Hardware Version	:	CONNECT2130XI_V1_L6A
Software Version	:	CONNECT2130XI_1.0
Remark : the Antenna gain is provided by customer from Antenna spec. and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.		

3.2 Channel List

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; ;were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

3.3 Test Site

Site Description

EMC Lab. : Accredited by CNAS, 2022-09-27

The certificate is valid until 2028.01.07

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2017)

The Certificate Registration Number is L8251

Designation Number: CN1347

Test Firm Registration Number: 894804

Accredited by A2LA, June 14, 2023

The Certificate Registration Number is 6837.01

Accredited by Industry Canada, November 09, 2018


The Conformity Assessment Body Identifier is CN0150

Company Number: 30806

Name of Firm : Shenzhen NCT Testing Technology Co., Ltd.

Site Location : A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

3.4 Test Setup Configuration



3.5 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	CMD.exe
Power level setup	21

4 Equipment During Test

4.1 Equipments List

Conducted emission Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	944 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESPI	101604	Rohde & Schwarz	2024/6/17	2025/6/16
LISN	ENV 216	102796	Rohde & Schwarz	2024/6/17	2025/6/16
LISN	VN1-13S	004023	CRANAGE	2024/6/17	2025/6/16
Cable	RG223-1500MM	NA	RG	2024/6/17	2025/6/16

Radiated emission & Radio Frequency Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESCI	101178	Rohde & Schwarz	2024/6/17	2025/6/16
Spectrum Analyze (10Hz-26.5GHz)	N9020A	MY50510202	Agilent	2024/6/17	2025/6/16
Amplifi (30MHz-1GHz)	BBV 9743 B	00374	SCHNARZBECK	2023/3/19	2025/3/18
Bilog Antenna (30MHz-1GHz)	VULB9162	00473	SCHNARZBECK	2023/3/19	2025/3/18
Horn antenna (1GHz-18GHz)	BBHA 9120 D	02622	SCHNARZBECK	2024/6/17	2025/6/16
Pream plifier (1GHz-18GHz)	BBV 9718D	0024	SCHNARZBECK	2024/6/17	2025/6/16
Spectrum Analyze (1GHz-40GHz)	FSV 40	100952	Rohde & Schwarz	2024/6/17	2025/6/16
Pream plifier (18GHz-40GHz)	BBV 9721	0056	SCHNWARZBEC K	2023/3/19	2025/3/18
Pream plifier (15GHz-40GHz)	BBV 9718D	0024	SCHNARZBECK	2024/6/17	2025/6/16
Broadband Antenna (15GHz-40GHz)	SAS-574	588	A.H.System	2024/6/17	2025/6/16

Loop Antenna (9KHz-30MHz)	FMZB1519B	014	SCHNARZBECK	2024/6/17	2025/6/16
Amplifier (9KHz-30MHz)	CVP 9222 C	00109	SCHNARZBECK	2024/6/17	2025/6/16
MXG Signal Analyzer	N9020A	101178	RS	2024/6/17	2025/6/16
MXG Vector Signal Generator	N5182A	MY50510202	Agilent	2024/6/17	2025/6/16
MXG Analog Signal Generator	N5181A	00374	SCHWARZBECK	2024/6/17	2025/6/16
Power Sensor	TR1029-2	00473	SCHNARZBECK	2024/6/17	2025/6/16
RF Swith	TR1029-1	02622	SCHNARZBECK	2024/6/17	2025/6/16
Cable	DA800- 4000MM	NA	DA	2024/6/17	2025/6/16
Cable	DA800- 11000MM	NA	DA	2024/6/17	2025/6/16

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	AUDIX	e3	6.120718
2	EMC radiation test system	AUDIX	e3	6.120718
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10 ⁻⁶
Bandwidth	± 1.5 x 10 ⁻⁶
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(9KHz~30MHz)	±4.51dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB
Radiated Emission(25GHz~40GHz)	±3.38dB
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	

4.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Amplifier	elipson	Connect 2130Xi	N/A	EUT
E-2	Notebook	lenovo	B40-80	MP07F6JD	Auxiliary

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

5 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207,RSS-Gen 8.8
Test Method : ANSI C63.10: 2013
Test Result : PASS
Frequency Range : 150kHz to 30MHz
Class/Severity : Class B


5.1 E.U.T. Operation

Operating Environment :

Temperature : 24.5 °C
Humidity : 51.3 % RH
Atmospheric Pressure : 101.11kPa


5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


5.7 Conducted Emission Test Result

Pass.

Please refer to the following pages.

All the modulation modes were tested the data of the worst mode (TX 802.11g Middle Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.156	24.69	10.90	35.59	55.67	-20.08	AVG	P
2 *	0.462	25.44	10.68	36.12	46.66	-10.54	AVG	P
3	0.480	32.86	10.65	43.51	56.34	-12.83	QP	P
4	0.549	33.89	10.67	44.56	56.00	-11.44	QP	P
5	0.707	32.30	10.82	43.12	56.00	-12.88	QP	P
6	0.774	18.94	10.85	29.79	46.00	-16.21	AVG	P
7	0.865	31.67	10.91	42.58	56.00	-13.42	QP	P
8	0.927	16.87	10.99	27.86	46.00	-18.14	AVG	P
9	1.009	31.40	11.13	42.53	56.00	-13.47	QP	P
10	1.387	16.59	11.09	27.68	46.00	-18.32	AVG	P
11	1.666	32.19	11.06	43.25	56.00	-12.75	QP	P
12	2.314	13.88	11.02	24.90	46.00	-21.10	AVG	P

Notes: 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Measurement Level = Reading level + Correct Factor

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.162	23.97	10.88	34.85	55.36	-20.51	AVG	P
2	0.396	33.87	10.76	44.63	57.94	-13.31	QP	P
3 *	0.462	26.36	10.70	37.06	46.66	-9.60	AVG	P
4	0.495	31.68	10.67	42.35	56.08	-13.73	QP	P
5	0.568	30.53	10.68	41.21	56.00	-14.79	QP	P
6	0.752	20.70	10.84	31.54	46.00	-14.46	AVG	P
7	0.774	34.37	10.86	45.23	56.00	-10.77	QP	P
8	0.927	17.07	11.00	28.07	46.00	-17.93	AVG	P
9	0.977	31.29	11.07	42.36	56.00	-13.64	QP	P
10	1.180	31.47	11.10	42.57	56.00	-13.43	QP	P
11	1.387	16.18	11.09	27.27	46.00	-18.73	AVG	P
12	1.855	15.44	11.04	26.48	46.00	-19.52	AVG	P

Notes: 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Measurement Level = Reading level + Correct Factor

6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247, RSS-Gen §6.13
Test Method : ANSI C63.10:2013
Test Result : PASS
Measurement Distance : 3m
Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$
Frequency (MHz)	Magnetic field strength (H-Field) (uA/m)		Measurement distance (m)	
0.009 ~ 0.490	$6.37/F$ (F in kHz)		300	
0.490 ~ 1.705	$63.7/F$ (F in kHz)		30	
1.705 ~ 30	0.08		30	

6.1 EUT Operation


Operating Environment :

Temperature: : 24.5°C
Humidity: : 52 % RH
Atmospheric Pressure: : 101.11kPa
Test Voltage : AC 120V/60Hz


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

Below 30MHz			
IF Bandwidth	:	10kHz	
Resolution Bandwidth	:	10kHz	
Video Bandwidth	:	10kHz	
30MHz ~ 1GHz			
Detector	:	PK	QP
Resolution Bandwidth	:	100kHz	120kHz
Video Bandwidth	:	300kHz	300kHz
Above 1GHz			
Detector	:	PK	AV
Resolution Bandwidth	:	1MHz	1MHz
Video Bandwidth	:	3MHz	10Hz

6.4 Test Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room

6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);
Limit line = Specific limits (dBuV) + distance extrapolation factor.

Test Frequency: 30MHz ~ 1GHz

All the modulation modes were tested the data of the worst mode (TX 802.11g Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following test plots:

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.437	7.37	13.04	20.41	40.00	-19.59	QP
2	64.659	5.84	10.55	16.39	40.00	-23.61	QP
3	141.330	13.82	9.63	23.45	43.50	-20.05	QP
4 *	197.893	25.52	12.07	37.59	43.50	-5.91	QP
5	248.552	14.47	12.99	27.46	46.00	-18.54	QP
6	478.846	8.70	18.15	26.85	46.00	-19.15	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38.346	7.19	13.34	20.53	40.00	-19.47	QP
2	77.865	6.52	11.83	18.35	40.00	-21.65	QP
3 *	170.793	17.80	16.04	33.84	43.50	-9.66	QP
4	197.200	22.79	10.47	33.26	43.50	-10.24	QP
5	248.552	13.57	12.92	26.49	46.00	-19.51	QP
6	528.246	8.29	19.16	27.45	46.00	-18.55	QP

Remark: Emission Level = Reading + Cable Loss + ANT Factor

All the modulation modes were tested the data of the worst mode (TX 802.11g Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Test Frequency: From 1GHz to 25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Low Channel:2412MHz									
V	4824.00	50.82	34.12	5.03	32.39	54.12	74	-19.88	PK
V	4824.00	40.69	34.12	5.03	32.39	43.99	54	-10.01	AV
V	7236.00	42.94	32.54	6.29	35.86	52.55	74	-21.45	PK
V	7236.00	32.85	32.54	6.29	35.86	42.46	54	-11.54	AV
V	9648.00	41.30	32.98	7.55	38.4	54.27	74	-19.73	PK
V	9648.00	30.56	32.98	7.55	38.4	43.53	54	-10.47	AV
V	12060.00	37.87	32.09	8.93	39	53.71	74	-20.29	PK
V	12060.00	29.33	32.09	8.93	39	45.17	54	-8.83	AV
H	4824.00	50.46	34.12	5.03	32.39	53.76	74	-20.24	PK
H	4824.00	40.94	34.12	5.03	32.39	44.24	54	-9.76	AV
H	7236.00	42.24	32.54	6.29	35.86	51.85	74	-22.15	PK
H	7236.00	33.45	32.54	6.29	35.86	43.06	54	-10.94	AV
H	9648.00	39.34	32.98	7.55	38.4	52.31	74	-21.69	PK
H	9648.00	30.91	32.98	7.55	38.4	43.88	54	-10.12	AV
H	12060.00	39.26	32.09	8.93	39	55.10	74	-18.90	PK
H	12060.00	29.30	32.09	8.93	39	45.14	54	-8.86	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Middle Channel:2437MHz									
V	4874.00	50.98	34.07	5.09	32.59	54.59	74	-19.41	PK
V	4874.00	41.32	34.07	5.09	32.59	44.93	54	-9.07	AV
V	7311.00	42.35	32.63	6.34	35.96	52.02	74	-21.98	PK
V	7311.00	31.37	32.63	6.34	35.96	41.04	54	-12.96	AV
V	9748.00	41.17	32.92	7.59	38.4	54.24	74	-19.76	PK
V	9748.00	32.36	32.92	7.59	38.4	45.43	54	-8.57	AV
V	12185.00	39.82	31.96	8.88	39.04	55.78	74	-18.22	PK
V	12185.00	29.66	31.96	8.88	39.04	45.62	54	-8.38	AV
H	4874.00	51.00	34.07	5.09	32.59	54.61	74	-19.39	PK
H	4874.00	42.14	34.07	5.09	32.59	45.75	54	-8.25	AV
H	7311.00	42.22	32.63	6.34	35.96	51.89	74	-22.11	PK
H	7311.00	33.90	32.63	6.34	35.96	43.57	54	-10.43	AV
H	9748.00	42.15	32.92	7.59	38.4	55.22	74	-18.78	PK
H	9748.00	30.56	32.92	7.59	38.4	43.63	54	-10.37	AV
H	12185.00	39.71	31.96	8.88	39.04	55.67	74	-18.33	PK
H	12185.00	29.61	31.96	8.88	39.04	45.57	54	-8.43	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
High Channel:2462MHz									
V	4924.00	50.24	34.02	5.15	32.8	54.17	74	-19.83	PK
V	4924.00	40.85	34.02	5.15	32.8	44.78	54	-9.22	AV
V	7386.00	42.89	32.71	6.4	36.05	52.63	74	-21.37	PK
V	7386.00	32.84	32.71	6.4	36.05	42.58	54	-11.42	AV
V	9848.00	41.56	32.86	7.62	38.4	54.72	74	-19.28	PK
V	9848.00	31.33	32.86	7.62	38.4	44.49	54	-9.51	AV
V	12310.00	38.71	31.82	8.84	39.08	54.81	74	-19.19	PK
V	12310.00	29.89	31.82	8.84	39.08	45.99	54	-8.01	AV
H	4924.00	51.14	34.02	5.15	32.8	55.07	74	-18.93	PK
H	4924.00	40.45	34.02	5.15	32.8	44.38	54	-9.62	AV
H	7386.00	43.01	32.71	6.4	36.05	52.75	74	-21.25	PK
H	7386.00	34.73	32.71	6.4	36.05	44.47	54	-9.53	AV
H	9848.00	40.59	32.86	7.62	38.4	53.75	74	-20.25	PK
H	9848.00	31.05	32.86	7.62	38.4	44.21	54	-9.79	AV
H	12310.00	39.28	31.82	8.84	39.08	55.38	74	-18.62	PK
H	12310.00	28.54	31.82	8.84	39.08	44.64	54	-9.36	AV

Note:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

All the modulation modes were tested the data of the worst mode (TX 802.11g Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Radiated Band Emission Measurement:

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detect or Type	Result
802.11g	Low Channel 2412MHz										
	H	2390.00	55.82	35.17	3.48	27.49	51.62	74	-22.38	PK	PASS
	H	2390.00	46.40	35.17	3.48	27.49	42.20	54	-11.80	AV	PASS
	H	2400.00	55.80	35.16	3.49	27.52	51.65	74	-22.35	PK	PASS
	H	2400.00	46.20	35.16	3.49	27.52	42.05	54	-11.95	AV	PASS
	V	2390.00	57.31	35.17	3.48	27.49	53.11	74	-20.89	PK	PASS
	V	2390.00	46.93	35.17	3.48	27.49	42.73	54	-11.27	AV	PASS
	V	2400.00	56.40	35.16	3.49	27.52	52.25	74	-21.75	PK	PASS
	V	2400.00	45.64	35.16	3.49	27.52	41.49	54	-12.51	AV	PASS
	High Channel 2462MHz										
	H	2483.50	56.86	35.11	3.56	27.75	53.06	74	-20.94	PK	PASS
	H	2483.50	45.44	35.11	3.56	27.75	41.64	54	-12.36	AV	PASS
	H	2500.00	57.37	35.1	3.57	27.8	53.64	74	-20.36	PK	PASS
	H	2500.00	47.34	35.1	3.57	27.8	43.61	54	-10.39	AV	PASS
	V	2483.50	56.12	35.11	3.56	27.75	52.32	74	-21.68	PK	PASS
	V	2483.50	45.84	35.11	3.56	27.75	42.04	54	-11.96	AV	PASS
	V	2500.00	56.04	35.1	3.57	27.8	52.31	74	-21.69	PK	PASS
	V	2500.00	47.12	35.1	3.57	27.8	43.39	54	-10.61	AV	PASS
Remark:											
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit											

7 Conduct Band Edge And Spurious Emissions Measurement

Test Requirement	:	FCC CFR47 Part 15 Section 15.247, RSS-247 § 5.5
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). RSS-247 § 5.5: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


7.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold


7.2 Test Result


Mode	Channel	Ant.	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
IEEE 802.11b	1	0	2398.40	-37.978	-15.14	-22.838	PASS
			2400.00	-41.615	-15.14	-26.475	PASS
			4824.20	-53.795	-15.14	-38.655	PASS
			7236.30	-54.762	-15.14	-39.622	PASS
			9637.80	-55.871	-15.14	-40.731	PASS
	6		21142.8	-42.785	-15.14	-27.645	PASS
			4874.18	-53.799	-14.55	-39.249	PASS
			7311.25	-54.609	-14.55	-40.059	PASS
			9735.21	-55.972	-14.55	-41.422	PASS
			21592.8	-43.148	-14.55	-28.598	PASS
	11		2483.50	-45.303	-14.03	-31.273	PASS
			4924.12	-53.301	-14.03	-39.271	PASS
			7387.41	-54.232	-14.03	-40.202	PASS
			9856.94	-54.172	-14.03	-40.142	PASS
			21179.0	-42.908	-14.03	-28.878	PASS
IEEE 802.11g	1		2398.92	-33.365	-17.88	-15.485	PASS
			2400.00	-34.562	-17.88	-16.682	PASS
			4841.10	-53.437	-17.88	-35.557	PASS
			7227.60	-55.022	-17.88	-37.142	PASS
			9636.60	-56.942	-17.88	-39.062	PASS
	6		21195.2	-43.145	-17.88	-25.265	PASS
			4878.55	-53.091	-17.3	-35.791	PASS
			7321.86	-55.079	-17.3	-37.779	PASS
			9759.56	-55.172	-17.3	-37.872	PASS
			21145.3	-43.492	-17.3	-26.192	PASS
	11		2483.50	-37.481	-16.72	-20.761	PASS
			4909.14	-52.781	-16.72	-36.061	PASS
			7387.41	-54.771	-16.72	-38.051	PASS
			9845.08	-55.502	-16.72	-38.782	PASS
			21181.5	-43.445	-16.72	-26.725	PASS
IEEE 802.11n_20	1		2398.27	-33.574	-17.91	-15.664	PASS
			2400.00	-36.581	-17.91	-18.671	PASS
			4832.40	-54.526	-17.91	-36.615	PASS
			7228.20	-54.908	-17.91	-36.998	PASS
			9649.10	-56.912	-17.91	-39.002	PASS
	6		21142.8	-43.509	-17.91	-25.599	PASS
			4885.42	-53.880	-17.52	-36.360	PASS
			7303.14	-53.255	-17.52	-35.735	PASS
			9762.68	-56.636	-17.52	-39.116	PASS
			21137.8	-43.585	-17.52	-26.065	PASS
	11		2483.50	-42.477	-17.01	-25.467	PASS
			4923.50	-54.162	-17.01	-37.152	PASS
			7388.03	-53.369	-17.01	-36.359	PASS
			9850.08	-55.563	-17.01	-38.553	PASS

		21720.8	-43.445	-17.01	-26.435	PASS
--	--	---------	---------	--------	---------	------









8 6dB&99% Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247, RSS-GEN § 6.7&RSS-247 § 5.2

Test Method : ANSI C63.10:2013

Test Limit Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1 Test Procedure

For 6dB Bandwidth Measurement

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz


For 99% Bandwidth Measurement


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1%-5% OBW, VBW $\geq$ 3RBW

8.2 Test Result

Mode	Channel	Ant.	Center Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	99% Bandwidth (MHz)	Result
IEEE 802.11b	1	0	2412	7.077	≥ 0.5	11.035	PASS
	6		2437	7.077		11.081	PASS
	11		2462	7.563		11.233	PASS
IEEE 802.11g	1		2412	15.49		16.538	PASS
	6		2437	14.07		16.516	PASS
	11		2462	15.16		16.414	PASS
IEEE 802.11n_20	1		2412	15.13		17.692	PASS
	6		2437	15.10		17.675	PASS
	11		2462	15.16		17.568	PASS

6 dB Bandwidth





99% Bandwidth