

## MAXIMUM PERMISSIBLE EXPOSURE

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

### EUT Specification

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>FCC ID</b>                     | 2AY2P-WMF72                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>EUT</b>                        | Advanced Wireless Multi-Format Presentation Switch                                                                                                                                                                                                                                                                                                                                                  |
| <b>Frequency band (Operating)</b> | <input type="checkbox"/> BT: 2.402GHz ~ 2.480GHz<br><input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input checked="" type="checkbox"/> RLAN: 5.180GHz ~ 5.240GHz<br><input type="checkbox"/> RLAN: 5.260GHz ~ 5.320GHz<br><input type="checkbox"/> RLAN: 5.500GHz ~ 5.700GHz<br><input checked="" type="checkbox"/> RLAN: 5.745GHz ~ 5.825GHz<br><input type="checkbox"/> Others: |
| <b>Device category</b>            | <input type="checkbox"/> Portable (<20cm separation)<br><input checked="" type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others _____                                                                                                                                                                                                                                      |
| <b>Exposure classification</b>    | <input type="checkbox"/> Occupational/Controlled exposure<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure                                                                                                                                                                                                                                                           |
| <b>Antenna diversity</b>          | <input type="checkbox"/> Single antenna<br><input checked="" type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input type="checkbox"/> Tx/Rx diversity                                                                                                                                                                      |
| <b>Antenna gain (Max)</b>         | Module 1:<br>WiFi 2.4G ANT1: 2.68dBi<br>WiFi 2.4G ANT2: 2.68dBi<br>WiFi 5.2G ANT1: 1.75dBi<br>WiFi 5.2G ANT2: 1.75dBi<br>WiFi 5.8G ANT1: 3.88dBi<br>WiFi 5.8G ANT2: 3.88dBi<br>Module 2:<br>WiFi 2.4G: 2.68dBi<br>WiFi 5.2G: 1.75dBi<br>WiFi 5.8G: 3.88dBi                                                                                                                                          |
| <b>Directional gain</b>           | Module 1:<br>WiFi 2.4G: 5.69dBi<br>WiFi 5.2G: 4.76dBi<br>WiFi 5.8G: 6.89dBi                                                                                                                                                                                                                                                                                                                         |

#### Shenzhen Anbotek Compliance Laboratory Limited

Address: Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hahqcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.  
 Tel: (86)0755-26066440 Email: service@anbotek.com



Hotline  
400-003-0500  
www.anbotek.com



## Evaluation applied

☒ MPE Evaluation☐ SAR Evaluation

## Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz)                                  | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|-------------------------------------------------------|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures         |                              |                              |                                    |              |
| 300-1500                                              | --                           | --                           | F/300                              | 6            |
| 1500-100000                                           | --                           | --                           | 5                                  | 6            |
| (B) Limits for General Population/Uncontrol Exposures |                              |                              |                                    |              |
| 300-1500                                              | --                           | --                           | F/1500                             | 30           |
| 1500-100000                                           | --                           | --                           | 1                                  | 30           |

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$ 

Where

 $P_d$  = Power density in mW/cm<sup>2</sup> $P_{out}$  = output power to antenna in Mw $G$  = gain of antenna in linear scale $\pi$  = 3.1416 $R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

| Operating Mode  | Maximum output power (dBm) | Tune up tolerance (dBm) | Max. Tune up Power (dBm) | Antenna Gain (dBi) | Power density at 20cm (mW/cm <sup>2</sup> ) | Power density Limits (mW/cm <sup>2</sup> ) |
|-----------------|----------------------------|-------------------------|--------------------------|--------------------|---------------------------------------------|--------------------------------------------|
| <b>Module 1</b> |                            |                         |                          |                    |                                             |                                            |
| WiFi 2.4G ANT1  | 14.33                      | 14.33 ±1                | 15.33                    | 2.68               | 0.0126                                      | 1                                          |
| WiFi 2.4G ANT2  | 14.77                      | 14.77 ±1                | 15.77                    | 2.68               | 0.0139                                      | 1                                          |
| WiFi 5.2G ANT1  | 15.29                      | 15.29 ±1                | 16.29                    | 1.75               | 0.0127                                      | 1                                          |
| WiFi 5.2G ANT2  | 15.54                      | 15.54 ±1                | 16.54                    | 1.75               | 0.0134                                      | 1                                          |
| WiFi 5.8G ANT1  | 12.45                      | 12.45 ±1                | 13.45                    | 3.88               | 0.0108                                      | 1                                          |
| WiFi 5.8G ANT2  | 13.06                      | 13.06 ±1                | 14.06                    | 3.88               | 0.0124                                      | 1                                          |
| <b>Module 2</b> |                            |                         |                          |                    |                                             |                                            |
| WiFi 2.4G       | 14.10                      | 14.10 ±1                | 15.10                    | 2.68               | 0.0119                                      | 1                                          |
| WiFi 5.2G       | 15.12                      | 15.12 ±1                | 16.12                    | 1.75               | 0.0122                                      | 1                                          |
| WiFi 5.8G       | 12.83                      | 12.83 ±1                | 13.83                    | 3.88               | 0.0117                                      | 1                                          |

## Shenzhen Anbotek Compliance Laboratory Limited

Address: Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hahqcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.  
Tel: (86) 0755-26066440 Email: service@anbotek.com



Hotline  
400-003-0500

www.anbotek.com



## No. Applicable Simultaneous Transmission

1. WiFi 2.4G ANT1 (Module 1) + WiFi 2.4G ANT2 (Module 1)
2. WiFi 2.4G ANT1 (Module 1) + WiFi 2.4G (Module 2)
3. WiFi 2.4G ANT1 (Module 1) + WiFi 5.2G (Module 2)
4. WiFi 2.4G ANT1 (Module 1) + WiFi 5.8G (Module 2)
5. WiFi 2.4G ANT2 (Module 1) + WiFi 2.4G (Module 2)
6. WiFi 2.4G ANT2 (Module 1) + WiFi 5.2G (Module 2)
7. WiFi 2.4G ANT2 (Module 1) + WiFi 5.8G (Module 2)
8. WiFi 2.4G ANT1 (Module 1) + WiFi 2.4G ANT2 (Module 1) + WiFi 2.4G (Module 2)
9. WiFi 2.4G ANT1 (Module 1) + WiFi 2.4G ANT2 (Module 1) + WiFi 5.2G (Module 2)
10. WiFi 2.4G ANT1 (Module 1) + WiFi 2.4G ANT2 (Module 1) + WiFi 5.8G (Module 2)
11. WiFi 5.2G ANT1 (Module 1) + WiFi 5.2G ANT2 (Module 1)
12. WiFi 5.2G ANT1 (Module 1) + WiFi 2.4G (Module 2)
13. WiFi 5.2G ANT1 (Module 1) + WiFi 5.2G (Module 2)
14. WiFi 5.2G ANT1 (Module 1) + WiFi 5.8G (Module 2)
15. WiFi 5.2G ANT2 (Module 1) + WiFi 2.4G (Module 2)
16. WiFi 5.2G ANT2 (Module 1) + WiFi 5.2G (Module 2)
17. WiFi 5.2G ANT2 (Module 1) + WiFi 5.8G (Module 2)
18. WiFi 5.2G ANT1 (Module 1) + WiFi 5.2G ANT2 (Module 1) + WiFi 2.4G (Module 2)
19. WiFi 5.2G ANT1 (Module 1) + WiFi 5.2G ANT2 (Module 1) + WiFi 5.2G (Module 2)
20. WiFi 5.2G ANT1 (Module 1) + WiFi 5.2G ANT2 (Module 1) + WiFi 5.8G (Module 2)
21. WiFi 5.8G ANT1 (Module 1) + WiFi 5.8G ANT2 (Module 1)
22. WiFi 5.8G ANT1 (Module 1) + WiFi 2.4G (Module 2)
23. WiFi 5.8G ANT1 (Module 1) + WiFi 5.2G (Module 2)
24. WiFi 5.8G ANT1 (Module 1) + WiFi 5.8G (Module 2)
25. WiFi 5.8G ANT2 (Module 1) + WiFi 2.4G (Module 2)
26. WiFi 5.8G ANT2 (Module 1) + WiFi 5.2G (Module 2)
27. WiFi 5.8G ANT2 (Module 1) + WiFi 5.8G (Module 2)
28. WiFi 5.8G ANT1 (Module 1) + WiFi 5.8G ANT2 (Module 1) + WiFi 2.4G (Module 2)
29. WiFi 5.8G ANT1 (Module 1) + WiFi 5.8G ANT2 (Module 1) + WiFi 5.2G (Module 2)
30. WiFi 5.8G ANT1 (Module 1) + WiFi 5.8G ANT2 (Module 1) + WiFi 5.8G (Module 2)

**The Maximum simultaneous transmission for WiFi 5.2G ANT1 (Module 1) + WiFi 2.4G ANT2 (Module 1) + WiFi 5.2G (Module 2):**

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= 0.0127/1 + 0.0139/1 + 0.0122/1$$

$$= 0.0388$$

$$< 1.0$$

Result: PASS.

## Shenzhen Anbotek Compliance Laboratory Limited

Address: Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park,  
Sanwei Community, Hahqcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China,  
Tel: (86)0755-26066440 Email: service@anbotek.com



Hotline  
400-003-0500

www.anbotek.com

