

# RF TEST REPORT

For

**Dongguan YEST Science&Technology CO., LTD**

**Product Name: Portable CD Boombox**

**Test Model(s).: CDB233BT**

**Report Reference No.** : DACE240822002RF001

**FCC ID** : 2AY38-CDB233BT

**Applicant's Name** : Dongguan YEST Science&Technology CO., LTD

**Address** : Room 301, No.33, Hehe Road, Xiangxi Village, Liaobu Town, Dongguan, Guangdong Province, China 523408

**Testing Laboratory** : Shenzhen DACE Testing Technology Co., Ltd.

**Address** : 102 Building H1 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China

**Test Specification Standard** : 47 CFR Part 15.247

**Date of Receipt** : August 22, 2024

**Date of Test** : August 22, 2024 to September 10, 2024

**Date of Issue** : September 10, 2024

**Result** : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample


## Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE240822002RF001	September 10, 2024

**NOTE1:**

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:



Ben Tang / Test Engineer

Supervised by:



Tom Chen / Project Engineer

Approved by:



Machael Mo / Manager

## CONTENTS

<b>1 TEST SUMMARY .....</b>	<b>5</b>
1.1 TEST STANDARDS .....	5
1.2 SUMMARY OF TEST RESULT .....	5
<b>2 GENERAL INFORMATION .....</b>	<b>6</b>
2.1 CLIENT INFORMATION .....	6
2.2 DESCRIPTION OF DEVICE (EUT) .....	6
2.3 DESCRIPTION OF TEST MODES .....	6
2.4 DESCRIPTION OF SUPPORT UNITS .....	6
2.5 EQUIPMENTS USED DURING THE TEST .....	7
2.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	9
2.7 IDENTIFICATION OF TESTING LABORATORY .....	9
2.8 ANNOUNCEMENT .....	9
<b>3 EVALUATION RESULTS (EVALUATION) .....</b>	<b>10</b>
3.1 ANTENNA REQUIREMENT .....	10
3.1.1 Conclusion: .....	10
<b>4 RADIO SPECTRUM MATTER TEST RESULTS (RF) .....</b>	<b>11</b>
4.1 CONDUCTED EMISSION AT AC POWER LINE .....	11
4.1.1 E.U.T. Operation: .....	11
4.1.2 Test Setup Diagram: .....	11
4.1.3 Test Data: .....	12
4.2 OCCUPIED BANDWIDTH .....	14
4.2.1 E.U.T. Operation: .....	14
4.2.2 Test Setup Diagram: .....	15
4.2.3 Test Data: .....	15
4.3 MAXIMUM CONDUCTED OUTPUT POWER .....	16
4.3.1 E.U.T. Operation: .....	16
4.3.2 Test Setup Diagram: .....	16
4.3.3 Test Data: .....	16
4.4 CHANNEL SEPARATION .....	17
4.4.1 E.U.T. Operation: .....	17
4.4.2 Test Setup Diagram: .....	17
4.4.3 Test Data: .....	17
4.5 NUMBER OF HOPPING FREQUENCIES .....	18
4.5.1 E.U.T. Operation: .....	18
4.5.2 Test Setup Diagram: .....	18
4.5.3 Test Data: .....	18
4.6 DWELL TIME .....	19
4.6.1 E.U.T. Operation: .....	19
4.6.2 Test Setup Diagram: .....	19
4.6.3 Test Data: .....	20
4.7 EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS .....	21
4.7.1 E.U.T. Operation: .....	21
4.7.2 Test Setup Diagram: .....	21
4.7.3 Test Data: .....	21
4.8 BAND EDGE EMISSIONS (RADIATED) .....	22
4.8.1 E.U.T. Operation: .....	22

4.8.2 Test Setup Diagram: .....	22
4.8.3 Test Data: .....	23
<b>4.9 EMISSIONS IN FREQUENCY BANDS (BELOW 1GHz) .....</b>	<b>27</b>
4.9.1 E.U.T. Operation: .....	28
4.9.2 Test Data: .....	28
<b>4.10 EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHz).....</b>	<b>30</b>
4.10.1 E.U.T. Operation: .....	31
4.10.2 Test Data: .....	31
<b>5 TEST SETUP PHOTOS .....</b>	<b>37</b>
<b>6 PHOTOS OF THE EUT .....</b>	<b>39</b>
<b>APPENDIX .....</b>	<b>48</b>
1. -20dB BANDWIDTH .....	49
2. 99% OCCUPIED BANDWIDTH .....	53
3. PEAK OUTPUT POWER .....	57
4. SPURIOUS EMISSIONS .....	61
5. BANDEdge .....	67
6. CARRIER FREQUENCIES SEPARATION (HOPPING) .....	76
7. NUMBER OF HOPPING CHANNEL (HOPPING) .....	80
8. DWELL TIME (HOPPING) .....	84

# 1 TEST SUMMARY

## 1.1 Test Standards

The tests were performed according to following standards:

**47 CFR Part 15.247:** Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

## 1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.247		47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	ANSI C63.10-2013 section 6.2	47 CFR 15.207(a)	Pass
Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2013, section 7.8.7 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2013, section 7.8.5 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(b)(1)	Pass
Channel Separation	47 CFR Part 15.247	ANSI C63.10-2013, section 7.8.2 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)	Pass
Number of Hopping Frequencies	47 CFR Part 15.247	ANSI C63.10-2013, section 7.8.3 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)(iii)	Pass
Dwell Time	47 CFR Part 15.247	ANSI C63.10-2013, section 7.8.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)(iii)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2013 section 7.8.8 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass

## 2 GENERAL INFORMATION

### 2.1 Client Information

**Applicant's Name** : Dongguan YEST Science&Technology CO., LTD  
**Address** : Room 301,No.33,Hehe Road, Xiangxi Village Liaobu Town Dongguan, Guangdong Province China 523408

**Manufacturer** : Dongguan YEST Science&Technology CO., LTD  
**Address** : Room 301,No.33,Hehe Road, Xiangxi Village Liaobu Town Dongguan, Guangdong Province China 523408

### 2.2 Description of Device (EUT)

Product Name:	Portable CD Boombox
Model/Type reference:	CDB233BT
Series Model:	CDB238BT,BT-9253,BT-9224,CD-X2A,CD-X2B,CD-X2C,W10,W12,W13,W14, W15,W16,W17,W18,X4,X5,X6,L1,L2,L3,L4,L5,T1,T2,T3,T4,T5,CR-1,CR-2,CR-3,CR-4,CR-5,C-01,C-02,C-03,PM10,PM11,PM22,PM24,PM25,PM30,PM31
Model Difference:	The product has many models, only the model name is different, and the other parts such as the circuit principle, pcb and electrical structure are the same.
Trade Mark:	RIPTUNES
Power Supply:	INPUT:120V~60Hz
Operation Frequency:	2402MHz to 2480MHz
Number of Channels:	79
Modulation Type:	GFSK, $\pi/4$ DQPSK
Antenna Type:	PCB
Antenna Gain:	-0.58dBi
Hardware Version:	V1.0
Software Version:	V1.0

### 2.3 Description of Test Modes

No	Title	Description
TM1	TX-GFSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.
TM2	TX-Pi/4DQPSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with Pi/4DQPSK modulation.
TM3	TX-GFSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation.,
TM4	TX-Pi/4DQPSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with Pi/4DQPSK modulation.

### 2.4 Description of Support Units

The EUT was tested as an independent device.

## 2.5 Equipments Used During The Test

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power absorbing clamp	SCHWARZ BECK	MESS-ELEKTRONIK	/	2024-03-25	2025-03-24
Electric Network	SCHWARZ BECK	CAT5 8158	CAT5 8158#207	/	/
Cable	SCHWARZ BECK	/	/	2024-03-20	2025-03-19
Pulse Limiter	SCHWARZ BECK	VTSD 9561-F Pulse limiter 10dB Ateennator	561-G071	2023-12-12	2024-12-11
50ΩCoaxial Switch	Anritsu	MP59B	M20531	/	/
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	ID:1164.6607K 03-102109-MH	2024-06-12	2025-06-11
L.I.S.N	R&S	ESH3-Z5	831.5518.52	2023-12-12	2024-12-11
L.I.S.N	SCHWARZ BECK	NSLK 8126	05055	2024-06-14	2025-06-13
Pulse Limiter	CYBERTEK	EM5010A	/	2023-09-27	2024-09-26
EMI test software	EZ -EMC	EZ	V1.1.42	/	/

### Channel Separation

### Number of Hopping Frequencies

### Dwell Time

### Emissions in non-restricted frequency bands

### Occupied Bandwidth

### Maximum Conducted Output Power

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	TACHOY	RTS-01	V1.0.0	/	/
High Pass filter	ZHINAN	OQHPP1-M1.5-18G-224	6210075	/	/
Power divider	MIDWEST	PWD-2533	SMA-79	2023-05-11	2026-05-10
RF Sensor Unit	Tachoy Information Technology(shenzhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2024-06-12	2025-06-11
Vector signal generator	Keysight	N5181A	MY48180415	2023-11-09	2024-11-08
Signal generator	Keysight	N5182A	MY50143455	2023-11-09	2024-11-08
Spectrum Analyzer	Keysight	N9020A	MY53420323	2023-12-12	2024-12-11

**Band edge emissions (Radiated)****Emissions in frequency bands (below 1GHz)****Emissions in frequency bands (above 1GHz)**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	/	MF-7802	/	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2022-04-05	2025-04-04
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2023-04-05	2025-04-04
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2024-06-14	2026-06-13
Cable(LF)#2	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(LF)#1	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2024-03-20	2025-03-19
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2024-03-20	2025-03-19
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2024-06-12	2025-06-11
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2024-06-12	2025-06-11
Wideband radio communication tester	R&S	CMW500	113410	2024-06-12	2025-06-11
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2024-06-12	2025-06-11
Horn Antenna	Sunol Sciences	DRH-118	A091114	2023-05-13	2025-05-12
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2023-05-21	2025-05-20

## 2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	±3.41dB
Occupied Bandwidth	±3.63%
RF conducted power	±0.733dB
Duty cycle	±3.1%
Conducted Spurious emissions	±1.98dB
Radiated Emission (Above 1GHz)	±5.46dB
Radiated Emission (Below 1GHz)	±5.79dB
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 2.7 Identification of Testing Laboratory

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102 Building H1 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

### Identification of the Responsible Testing Location

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102 Building H1 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
FCC Registration Number:	0032847402
Designation Number:	CN1342
Test Firm Registration Number:	778666
A2LA Certificate Number:	6270.01

## 2.8 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by DACE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

### 3 Evaluation Results (Evaluation)

#### 3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

##### 3.1.1 Conclusion:



## 4 Radio Spectrum Matter Test Results (RF)

#### 4.1 Conducted Emission at AC power line


Test Requirement:	Refer to 47 CFR 15.207(a). Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 ohms line impedance stabilization network (LISN).																	
Test Limit:	<table border="1"> <thead> <tr> <th>Frequency of emission (MHz)</th><th colspan="2">Conducted limit (dB<math>\mu</math>V)</th></tr> <tr> <th></th><th>Quasi-peak</th><th>Average</th></tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table>			Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)			Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)																	
	Quasi-peak	Average																
0.15-0.5	66 to 56*	56 to 46*																
0.5-5	56	46																
5-30	60	50																
	*Decreases with the logarithm of the frequency.																	
Test Method:	ANSI C63.10-2013 section 6.2																	
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices																	

#### 4.1.1 E.U.T. Operation:

## Operating Environment:

Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1, TM2				
Final test mode:	TM1				


#### 4.1.2 Test Setup Diagram:



#### 4.1.3 Test Data:


TM1 / Line / Band: 2400-2483.5 MHz / BW: 1 / CH: L

Power: AC120V60Hz



No.	Mk.	Freq.	Reading	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
			Level						
MHz		dBuV	dB	dBuV	dBuV	dB			
1		0.1740	0.60	10.12	10.72	54.76	-44.04		AVG
2	*	0.1860	19.06	10.12	29.18	64.21	-35.03		QP
3		0.6700	-2.51	10.09	7.58	46.00	-38.42		AVG
4		0.6900	8.04	10.10	18.14	56.00	-37.86		QP
5		1.6180	7.97	10.04	18.01	56.00	-37.99		QP
6		1.6300	-2.79	10.03	7.24	46.00	-38.76		AVG
7		7.5980	8.83	10.24	19.07	60.00	-40.93		QP
8		8.1420	-3.51	10.26	6.75	50.00	-43.25		AVG
9		12.8380	-4.17	10.42	6.25	50.00	-43.75		AVG
10		13.8940	7.46	10.46	17.92	60.00	-42.08		QP
11		23.7780	11.60	10.71	22.31	60.00	-37.69		QP
12		24.4940	-3.19	10.73	7.54	50.00	-42.46		AVG

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 1 / CH: L  
Power: AC120V60Hz



No.	Mk.	Freq.	Reading	Correct Factor	Measure- ment	Limit	Over		
			Level				dBuV	dB	Detector
1		0.1499	-0.08	10.13	10.05	56.00	-45.95	AVG	
2		0.1620	10.79	10.12	20.91	65.36	-44.45	QP	
3		0.3780	9.42	10.10	19.52	58.32	-38.80	QP	
4		0.4100	-1.49	10.09	8.60	47.65	-39.05	AVG	
5		1.0740	8.85	10.10	18.95	56.00	-37.05	QP	
6		1.1140	-2.48	10.11	7.63	46.00	-38.37	AVG	
7		2.1820	-4.09	10.01	5.92	46.00	-40.08	AVG	
8		2.3260	8.44	10.02	18.46	56.00	-37.54	QP	
9		8.1379	-3.38	10.26	6.88	50.00	-43.12	AVG	
10		8.3379	11.89	10.27	22.16	60.00	-37.84	QP	
11		27.1620	-1.29	10.88	9.59	50.00	-40.41	AVG	
12 *		28.1620	13.89	10.97	24.86	60.00	-35.14	QP	

## 4.2 Occupied Bandwidth


Test Requirement:	47 CFR 15.247(a)(1)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2013, section 7.8.7, For occupied bandwidth measurements, use the procedure in 6.9.2. KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	<p>a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.</p> <p>b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.</p> <p>c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than <math>[10 \log (\text{OBW}/\text{RBW})]</math> below the reference level. Specific guidance is given in 4.1.5.2.</p> <p>d) Steps a) through c) might require iteration to adjust within the specified tolerances.</p> <p>e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.</p> <p>f) Set detection mode to peak and trace mode to max hold.</p> <p>g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).</p> <p>h) Determine the “-xx dB down amplitude” using <math>[(\text{reference value}) - \text{xx}]</math>. Alternatively, this calculation may be made by using the marker-delta function of the instrument.</p> <p>i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).</p> <p>j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.</p> <p>k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).</p>

### 4.2.1 E.U.T. Operation:

#### Operating Environment:

Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1, TM2				
Final test mode:	TM1, TM2				

#### 4.2.2 Test Setup Diagram:



#### 4.2.3 Test Data:

Please Refer to Appendix for Details.


### 4.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(1)
Test Limit:	Refer to 47 CFR 15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Test Method:	ANSI C63.10-2013, section 7.8.5 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	<p>This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:</p> <p>a) Use the following spectrum analyzer settings:</p> <ol style="list-style-type: none"> <li>1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.</li> <li>2) RBW &gt; 20 dB bandwidth of the emission being measured.</li> <li>3) VBW <math>\geq</math> RBW.</li> <li>4) Sweep: Auto.</li> <li>5) Detector function: Peak.</li> <li>6) Trace: Max hold.</li> </ol> <p>b) Allow trace to stabilize.</p> <p>c) Use the marker-to-peak function to set the marker to the peak of the emission.</p> <p>d) The indicated level is the peak output power, after any corrections for external attenuators and cables.</p> <p>e) A plot of the test results and setup description shall be included in the test report.</p> <p>NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.</p>

#### 4.3.1 E.U.T. Operation:

Operating Environment:				
Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure:
Pretest mode:	TM1, TM2			
Final test mode:	TM1, TM2			

#### 4.3.2 Test Setup Diagram:



#### 4.3.3 Test Data:

Please Refer to Appendix for Details.


#### 4.4 Channel Separation

Test Requirement:	47 CFR 15.247(a)(1)
Test Limit:	Refer to 47 CFR 15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
Test Method:	ANSI C63.10-2013, section 7.8.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	<p>The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>a) Span: Wide enough to capture the peaks of two adjacent channels.</li> <li>b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.</li> <li>c) Video (or average) bandwidth (VBW) <math>\geq</math> RBW.</li> <li>d) Sweep: Auto.</li> <li>e) Detector function: Peak.</li> <li>f) Trace: Max hold.</li> <li>g) Allow the trace to stabilize.</li> </ul> <p>Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.</p>

##### 4.4.1 E.U.T. Operation:

Operating Environment:				
Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM3, TM4			
Final test mode:	TM3, TM4			

##### 4.4.2 Test Setup Diagram:



##### 4.4.3 Test Data:

Please Refer to Appendix for Details.


## 4.5 Number of Hopping Frequencies

Test Requirement:	47 CFR 15.247(a)(1)(iii)
Test Limit:	Refer to 47 CFR 15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	ANSI C63.10-2013, section 7.8.3 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	<p>The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.</li> <li>b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.</li> <li>c) VBW <math>\geq</math> RBW.</li> <li>d) Sweep: Auto.</li> <li>e) Detector function: Peak.</li> <li>f) Trace: Max hold.</li> <li>g) Allow the trace to stabilize.</li> </ul> <p>It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.</p>

### 4.5.1 E.U.T. Operation:

Operating Environment:				
Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM3, TM4			
Final test mode:	TM3, TM4			

### 4.5.2 Test Setup Diagram:



### 4.5.3 Test Data:

Please Refer to Appendix for Details.

## 4.6 Dwell Time


Test Requirement:	47 CFR 15.247(a)(1)(iii)
Test Limit:	Refer to 47 CFR 15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	ANSI C63.10-2013, section 7.8.4 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	<p>The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>a) Span: Zero span, centered on a hopping channel.</li> <li>b) RBW shall be <math>\leq</math> channel spacing and where possible RBW should be set <math>\gg 1 / T</math>, where T is the expected dwell time per channel.</li> <li>c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.</li> <li>d) Detector function: Peak.</li> <li>e) Trace: Max hold.</li> </ul> <p>Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.</p> <p>Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:</p> $(\text{Number of hops in the period specified in the requirements}) = (\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time})$ <p>The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.</p> <p>The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.</p>

### 4.6.1 E.U.T. Operation:

Operating Environment:				
Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM3, TM4			
Final test mode:	TM3, TM4			

### 4.6.2 Test Setup Diagram:





#### 4.6.3 Test Data:

Please Refer to Appendix for Details.


## 4.7 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2013 section 7.8.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers. Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

### 4.7.1 E.U.T. Operation:

Operating Environment:				
Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM1, TM2, TM3, TM4			
Final test mode:	TM1, TM2, TM3, TM4			

### 4.7.2 Test Setup Diagram:



### 4.7.3 Test Data:

Please Refer to Appendix for Details.


#### 4.8 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d). In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

##### 4.8.1 E.U.T. Operation:


Operating Environment:				
Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM1, TM2			
Final test mode:	TM1			

##### 4.8.2 Test Setup Diagram:



#### 4.8.3 Test Data:


TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L



#### Suspected Data List


NO.	Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2310.18	30.57	-11.73	74.00	43.43	150	294	Horizontal
2	2390.49	32.47	-11.47	74.00	41.53	150	322	Horizontal
3	2310.01	20.52	-11.73	54.00	33.48	150	61	Horizontal
4	2390.76	22.37	-11.47	54.00	31.63	150	322	Horizontal

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L

**Suspected Data List**


NO.	Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2310.31	30.16	-11.73	74.00	43.84	150	337	Vertical
2	2390.74	31.67	-11.47	74.00	42.33	150	127	Vertical
3	2310.48	20.77	-11.73	54.00	33.23	150	358	Vertical
4	2390.79	22.12	-11.47	54.00	31.88	150	116	Vertical

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: H

**Suspected Data List**

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2483.46	40.84	-11.18	74.00	33.16	150	315	Horizontal
2	2499.93	33.92	-11.12	74.00	40.08	150	310	Horizontal
3	2483.44	25.96	-11.18	54.00	28.04	150	315	Horizontal
4	2499.93	25.28	-11.12	54.00	28.72	150	304	Horizontal

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: H

**Suspected Data List**

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2483.61	35.69	-11.18	74.00	38.31	150	106	Vertical
2	2499.92	31.89	-11.12	74.00	42.11	150	213	Vertical
3	2483.58	23.02	-11.18	54.00	30.98	150	117	Vertical
4	2499.92	22.50	-11.12	54.00	31.50	150	106	Vertical

#### 4.9 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).			
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	
	0.009-0.490	2400/F(kHz)	300	
	0.490-1.705	24000/F(kHz)	30	
	1.705-30.0	30	30	
	30-88	100 **	3	
	88-216	150 **	3	
	216-960	200 **	3	
	Above 960	500	3	
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>				
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02			
Procedure:	<p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>h. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <p>1) For emission below 1GHz, through pre-scan found the worst case is the lowest</p>			

channel. Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor °C

Preamplifier Factor

3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.


#### 4.9.1 E.U.T. Operation:

Operating Environment:


Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1, TM2				
Final test mode:	TM1				

#### 4.9.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L



TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	96.0986	39.26	-9.12	30.14	43.50	-13.36	QP	100		P	
2 *	143.8295	37.44	-6.26	31.18	43.50	-12.32	QP	100		P	
3	191.7450	33.16	-8.70	24.46	43.50	-19.04	QP	100		P	
4	312.1794	32.78	-5.64	27.14	46.00	-18.86	QP	100		P	
5	408.9460	31.84	-3.16	28.68	46.00	-17.32	QP	100		P	
6	601.4265	33.31	0.31	33.62	46.00	-12.38	QP	100		P	

#### 4.10 Emissions in frequency bands (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c).`			
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	
	0.009-0.490	2400/F(kHz)	300	
	0.490-1.705	24000/F(kHz)	30	
	1.705-30.0	30	30	
	30-88	100 **	3	
	88-216	150 **	3	
	216-960	200 **	3	
	Above 960	500	3	
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>				
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02			
Procedure:	<ol style="list-style-type: none"> <li>For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>Test the EUT in the lowest channel, the middle channel, the Highest channel.</li> <li>The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>Repeat above procedures until all frequencies measured was complete.</li> </ol> <p>Remark:</p> <p>1) For emission below 1GHz, through pre-scan found the worst case is the lowest</p>			

channel. Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor °C

Preamplifier Factor

3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.


#### 4.10.1 E.U.T. Operation:

Operating Environment:

Temperature:	22.3 °C	Humidity:	49 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1, TM2				
Final test mode:	TM1				

#### 4.10.2 Test Data:


TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L



#### Suspected Data List


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4804.53	43.31	-6.94	74.00	30.69	150	333	Horizontal
2	7782.06	36.91	-0.69	74.00	37.09	150	72	Horizontal
3	10493.7	38.92	2.88	74.00	35.08	150	355	Horizontal
4	4806.00	35.40	-6.94	54.00	18.60	150	338	Horizontal
5	7770.31	26.37	-0.74	54.00	27.63	150	180	Horizontal
6	10528.9	29.01	2.92	54.00	24.99	150	162	Horizontal

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L

**Suspected Data List**


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4804.53	41.01	-6.94	74.00	32.99	150	120	Vertical
2	7993.59	37.07	0.04	74.00	36.93	150	360	Vertical
3	11442.6	40.02	3.55	74.00	33.98	150	193	Vertical
4	4806.00	32.21	-6.94	54.00	21.79	150	120	Vertical
5	8043.53	27.13	-0.01	54.00	26.87	150	80	Vertical
6	11517.5	29.38	3.54	54.00	24.62	150	182	Vertical

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: M

**Suspected Data List**


NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4885.32	46.48	-6.64	74.00	27.52	150	316	Horizontal
2	7923.08	37.45	-0.20	74.00	36.55	150	33	Horizontal
3	11179.7	38.80	3.51	74.00	35.20	150	208	Horizontal
4	4886.79	38.16	-6.63	54.00	15.84	150	316	Horizontal
5	7937.77	26.73	-0.15	54.00	27.27	150	208	Horizontal
6	11115.0	28.58	3.50	54.00	25.42	150	152	Horizontal

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: M

**Suspected Data List**


NO.	Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4885.32	41.35	-6.64	74.00	32.65	150	123	Vertical
2	8049.41	37.11	-0.03	74.00	36.89	150	134	Vertical
3	11178.2	40.08	3.51	74.00	33.92	150	259	Vertical
4	4888.26	30.96	-6.63	54.00	23.04	150	112	Vertical
5	7967.15	27.13	-0.05	54.00	26.87	150	202	Vertical
6	11159.1	28.87	3.50	54.00	25.13	150	72	Vertical

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: H

**Suspected Data List**

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4960.24	48.87	-6.36	74.00	25.13	150	315	Horizontal
2	7441.27	36.61	-1.85	74.00	37.39	150	327	Horizontal
3	11496.9	39.32	3.56	74.00	34.68	150	299	Horizontal
4	4961.71	43.74	-6.35	54.00	10.26	150	310	Horizontal
5	7441.27	30.58	-1.85	54.00	23.42	150	315	Horizontal
6	11466.1	28.85	3.55	54.00	25.15	150	99	Horizontal

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: H

**Suspected Data List**


NO.	Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4960.24	43.13	-6.36	74.00	30.87	150	115	Vertical
2	7992.12	37.50	0.04	74.00	36.50	150	359	Vertical
3	11452.9	39.27	3.55	74.00	34.73	150	335	Vertical
4	4961.71	35.51	-6.35	54.00	18.49	150	110	Vertical
5	8005.34	26.77	0.06	54.00	27.23	150	224	Vertical
6	11449.9	29.12	3.55	54.00	24.88	150	21	Vertical

## 5 TEST SETUP PHOTOS


Conducted Emission at AC power line



Emissions in frequency bands (below 1GHz)



Emissions in frequency bands (above 1GHz)



## 6 PHOTOS OF THE EUT

External

















**Internal**








# Appendix



# HT240822007--CDB233BT--EDR--FCC



## FCC\_BT (Part15.247) Test Data


### 1. -20dB Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	if larger than CFS
NVNT	ANT1	1-DH5	2402.00	0.916	No
NVNT	ANT1	1-DH5	2441.00	0.919	No
NVNT	ANT1	1-DH5	2480.00	0.918	No
NVNT	ANT1	2-DH5	2402.00	1.225	Yes
NVNT	ANT1	2-DH5	2441.00	1.227	Yes
NVNT	ANT1	2-DH5	2480.00	1.227	Yes















## 2. 99% Occupied Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	99%BW(MHz)
NVNT	ANT1	1-DH5	2402.00	0.847
NVNT	ANT1	1-DH5	2441.00	0.839
NVNT	ANT1	1-DH5	2480.00	0.842
NVNT	ANT1	2-DH5	2402.00	1.163
NVNT	ANT1	2-DH5	2441.00	1.164
NVNT	ANT1	2-DH5	2480.00	1.164















### 3. Peak Output Power

Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1-DH5	2402.00	-3.33	0.47	1000	Pass
NVNT	ANT1	1-DH5	2441.00	-3.34	0.46	1000	Pass
NVNT	ANT1	1-DH5	2480.00	-3.98	0.40	1000	Pass
NVNT	ANT1	2-DH5	2402.00	-1.83	0.66	125	Pass
NVNT	ANT1	2-DH5	2441.00	-1.89	0.65	125	Pass
NVNT	ANT1	2-DH5	2480.00	-2.58	0.55	125	Pass











#### 4. Spurious Emissions


Condition	Antenna	Modulation	TX Mode	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1-DH5	2402.00	-49.875	-23.404	Pass
NVNT	ANT1	1-DH5	2441.00	-47.018	-23.410	Pass
NVNT	ANT1	1-DH5	2480.00	-46.493	-24.041	Pass
NVNT	ANT1	2-DH5	2402.00	-54.165	-23.301	Pass
NVNT	ANT1	2-DH5	2441.00	-50.862	-23.337	Pass
NVNT	ANT1	2-DH5	2480.00	-45.130	-23.982	Pass


















## 5. Bandedge


Condition	Antenna	Modulation	TX Mode	Bandedge MAX.Value	Limit	Result
NVNT	ANT1	1-DH5	2402.00	-31.912	-23.404	Pass
NVNT	ANT1	1-DH5	Hopping_LCH	-33.279	-23.283	Pass
NVNT	ANT1	1-DH5	2480.00	-53.599	-24.041	Pass
NVNT	ANT1	1-DH5	Hopping_HCH	-52.720	-23.173	Pass
NVNT	ANT1	2-DH5	2402.00	-31.867	-23.301	Pass
NVNT	ANT1	2-DH5	Hopping_LCH	-33.073	-23.144	Pass
NVNT	ANT1	2-DH5	2480.00	-54.006	-23.982	Pass
NVNT	ANT1	2-DH5	Hopping_HCH	-51.996	-23.135	Pass





























## 6. Carrier Frequencies Separation (Hopping)

Condition	Antenna	Modulation	Frequency(MHz)	Hopping NO.0 (MHz)	Hopping NO.1 (MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	1-DH5	2402.00	2401.975	2402.977	1.00	0.916	Pass
NVNT	ANT1	1-DH5	2441.00	2440.975	2441.974	1.00	0.919	Pass
NVNT	ANT1	1-DH5	2480.00	2478.813	2479.974	1.16	0.918	Pass
NVNT	ANT1	2-DH5	2402.00	2402.134	2402.971	0.84	0.817	Pass
NVNT	ANT1	2-DH5	2441.00	2440.822	2441.953	1.13	0.818	Pass
NVNT	ANT1	2-DH5	2480.00	2479.116	2480.112	1.00	0.818	Pass














## 7. Number of Hopping Channel (Hopping)

Condition	Antenna	Modulation	Hopping Num	Limit	Result
NVNT	ANT1	1-DH5	79	15	Pass
NVNT	ANT1	1-DH5	79	15	Pass
NVNT	ANT1	1-DH5	79	15	Pass
NVNT	ANT1	2-DH5	79	15	Pass
NVNT	ANT1	2-DH5	79	15	Pass
NVNT	ANT1	2-DH5	79	15	Pass













## 8. Dwell Time (Hopping)


Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	1-DH5	2.914	103.00	300.142	0.40	Pass
NVNT	ANT1	2-DH5	2.920	107.00	312.440	0.40	Pass
NVNT	ANT1	1-DH1	0.410	320.00	131.200	0.40	Pass
NVNT	ANT1	1-DH3	1.666	164.00	273.224	0.40	Pass
NVNT	ANT1	2-DH1	0.420	319.00	134.086	0.40	Pass
NVNT	ANT1	2-DH3	1.672	159.00	265.848	0.40	Pass














\*\*\*\*\* End of Report \*\*\*\*\*