

## FCC ID: 2AY49-KRC-T401RC

According to KDB 447498 D01 General RF Exposure Guidance.

At 100 MHz to 6 GHz and for test separation distances  $\leq$  50 mm, the SAR test exclusion threshold is determined according to the following

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0$$

### 1. SAR test exclusion threshold

**Frequency: 2 480 MHz (min. separation distances = 0 mm)**

SAR test exclusion thresholds(5 mm) =  $3 \times 5 / (\sqrt{2.480}) = 9.525 \text{ mW}$

Max. tune-up tolerance (mW)	SAR Test Exclusion Thresholds (5 mm) (mW)
8.91	9.525

Calculation value:  $8.91 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 2.806$

So, Calculation value  $\leq$  3.0

#### Remark;

- Max. conducted power (mW): maximum tolerance power of EUT (9.5 dBm)
- Max. conducted power 8.91 (mW) was calculated.
- When the minimum test separation distance is  $< 5 \text{ mm}$ , a distance of 5 mm is applied to determine SAR test exclusion.

### 2. Conclusion: No SAR is required.