

Intertek  
731 Enterprise Drive  
Lexington, KY 40510

Tel 859 226 1000  
Fax 859 226 1040

[www.intertek.com](http://www.intertek.com)

# Zurn Water, LLC

# RF EXPOSURE

# REPORT

**SCOPE OF WORK**

RF EXPOSURE CALCULATION  
ON THE EZ GEAR FAUCET MODEL ZG6913

**REPORT NUMBER**

105704106LEX-003

**ISSUE DATE**

4/12/2024

**PAGES**

11

**DOCUMENT CONTROL NUMBER**

Non-Specific EMC Report Shell Rev. December 2017  
© 2017 INTERTEK



## RF EXPOSURE TEST REPORT

**Report Number:** 105704106LEX-003

**Project Number:** G105704106

**Report Issue Date:** 4/12/2024

**Product Name:** EZ Gear Faucet

**Product Model:** ZG6913

**Variant Model(s) not Tested but Declared** ZG6915, ZG6920, ZG6922, ZG6950,

**By Manufacturer to be Electrically Identical:** ZG6951, ZG6953, ZG6955, ZG6956

**Standards:** FCC Title 47 CFR Part 1.1310(e)(1) Limits for  
Maximum Permissible Exposure (MPE)

RSS-102 Issue 6 RF Field Strength Limits for  
Devices Used by the General Public

Tested by:

Intertek Testing Services NA, Inc.  
731 Enterprise Drive  
Lexington, KY 40510  
USA

Client:

Zurn Water, LLC  
3700 Regency Parkway  
Suite 100  
Cary, NC 27518  
USA

Report prepared by



Brian Lackey, EMC Staff Engineer

Report reviewed by



Michael Carlson, Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.





## Table of Contents

<b>1</b>	<b><i>Introduction and Conclusion</i></b> .....	<b>4</b>
<b>2</b>	<b><i>Test Summary</i></b> .....	<b>4</b>
<b>3</b>	<b><i>Client Information</i></b> .....	<b>Error! Bookmark not defined.</b>
<b>4</b>	<b><i>Description of Equipment under Test and Variant Models</i></b> .....	<b>5</b>
<b>5</b>	<b><i>Output Power</i></b> .....	<b>6</b>
<b>6</b>	<b><i>Antenna Gain</i></b> .....	<b>7</b>
<b>7</b>	<b><i>FCC RF Exposure Limits</i></b> .....	<b>8</b>
<b>8</b>	<b><i>RSS-102 Issue 6 RF Exposure Limits</i></b> .....	<b>9</b>
<b>9</b>	<b><i>Test Procedure</i></b> .....	<b>10</b>
<b>10</b>	<b><i>Results:</i></b> .....	<b>10</b>
<b>11</b>	<b><i>Revision History</i></b> .....	<b>11</b>



## 1 Introduction and Conclusion

The tests indicated in section 2 were performed on the product constructed as described in section 4. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

## 2 Test Summary

Section	Test full name	Result
10	FCC Title 47 CFR Part 1.1310(e)(1) Limits for Maximum Permissible Exposure (MPE) (Limits for General Population / Uncontrolled Exposure)	Pass
	RSS-102 Issue 6 RF Field Strength Limits (For Devices Used by the General Public)	Pass



### 3 Client Information

This product was tested at the request of the following:

Client Information	
<b>Client Name:</b>	Zurn Water, LLC
<b>Address:</b>	3700 Regency Parkway Suite 100 Cary, NC 27518 USA
<b>Contact:</b>	Malcolm James
<b>Telephone:</b>	+1 (919) 777-6413
<b>Email:</b>	malcolm.james@zurn.com
Manufacturer Information	
<b>Manufacturer Name:</b>	Zurn Water, LLC
<b>Manufacturer Address:</b>	5900 Elwin Buckanan Dr. Sanford, NC 27330 USA



#### 4 Description of Equipment under Test and Variant Models

Equipment Under Test	
Product Name	EZ Gear Faucet
Model Number	ZG6913
Hardware Version	Rev B
Software Version	Valve – 79 Nordic Radio Test 1.17.1
Embedded Module(s)	Nordic nRF52810
Wireless Technology	Bluetooth Low Energy (BLE)
Supported Transmit Bands	2402 – 2480MHz
Supported Transmit Modes	1Mbit/s, 2Mbit/s
Antenna Gain	1Mbit/s Data Rate: 1.52dBi (2402MHz), 0.27dBi (2440MHz), -0.70dBi (2480MHz) 2Mbit/s Data Rate: 0.97dBi (2402MHz), 0.27dBi (2440MHz), -0.79dBi (2480MHz)
Maximum Output Power	1Mbit/s Data Rate: 4.15dBm (2402MHz), 3.93dBm (2440MHz), 3.79dBm (2480MHz) 2Mbit/s Data Rate: 4.17dBm (2402MHz), 3.95dBm (2440MHz), 3.81dBm (2480MHz)
Ratings	3.0v AA 6 Cell Battery or 100-240Vac 32A LIFEPO
Description of Equipment Under Test (provided by client)	
Electronic Sensor Faucet	

##### 4.1 Variant Models:

The following variant models were not tested as part of this evaluation, but have been identified by the manufacturer as being electrically identical models, depopulated models, or with reasonable similarity to the model(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

- ZG6915, ZG6920, ZG6922, ZG6950, ZG6951, ZG6953, ZG6955, and ZG6956 – alternate faucet style with identical electronics



## 5 Output Power

The output power was taken from Intertek report 105704106LEX-001.

Data Rate	Frequency (MHz)	Peak Output Power (dBm)
1Mbit/s	2402	4.15
	2440	3.93
	2480	3.79
2Mbit/s	2402	4.17
	2440	3.95
	2480	3.81

## 6 Antenna Gain

The antenna gain was taken from Intertek report 105704106LEX-012.

Data Rate	Frequency (MHz)	Maximum Realized Gain (dBi)
1Mbit/s	2402	1.51
	2440	0.27
	2480	-0.70
2Mbit/s	2402	0.97
	2440	0.27
	2480	-0.79



## 7 FCC RF Exposure Limits

### Title 47 CFR Part 1.1310(d)(2):

For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in § 1.1307(b) of this part, except for portable devices as defined in § 2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in § 2.1093.

Table 1 to § 1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30–300	61.4	0.163	1.0	<6
300–1,500			f/300	<6
1,500–100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30–300	27.5	0.073	0.2	<30
300–1,500			f/1500	<30
1,500–100,000			1.0	<30

f = frequency in MHz. \* = Plane-wave equivalent power density.



## 8 RSS-102 Issue 6 RF Exposure Limits

### RSS-102 Issue 6 § 6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where f is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where f is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance)

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

### RSS-102 Issue 6 § 5.3.2:

The electric and magnetic field strength reference levels, power density reference levels, and associated reference period for devices employed by the general public (uncontrolled environment) and controlled-use devices (controlled environment) are specified in table 7 and table 8. Note that the power density limits specified in these tables apply to whole body exposure conditions.

Table 7: RF field strength and power density limits for devices used by the general public (uncontrolled environment)

Frequency range (MHz)	Electric field (V <sub>RMS</sub> /m)	Magnetic field (A <sub>RMS</sub> /m)	Power density (W/m <sup>2</sup> )	Reference period (minutes)
10-20	27.46	0.0728	2	6
20-48	$58.07 / f^{0.25}$	$0.1540 / f^{0.25}$	$8.944 / f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000 / f^{1.2}$
150000-300000	$0.158 f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	$616000 / f^{1.2}$

**Note:** f is frequency in MHz.



## 9 Test Procedure

An RF exposure calculation was performed to show that the device was compliant with the general population exposure limits from FCC Title 47 CFR Part 1.1310(e)(1), RSS-102 Issue 6, and ICNIRP Guidelines (2020). The maximum power density was calculated for each transmitter at a separation distance of 20cm using the maximum conducted output power (including tune up tolerance) plus antenna gain, or measured EIRP.

For each transmitter the maximum power density at a 20cm distance using the formula:

$$EIRP(dBm) = Conducted\ Power(dBm) + Antenna\ Gain(dBi)$$

$$EIRP(mW) = 10^{EIRP(dBm)/10}$$

$$Power\ Density\left(mW/cm^2\right) = \frac{EIRP(mW)}{4\pi \cdot (20cm)^2}$$

$$Power\ Density\left(W/m^2\right) = \left(\frac{100cm}{1m}\right)^2 \left(\frac{1W}{1000mW}\right) Power\ Density\left(mW/cm^2\right)$$

## 10 Results:

The calculated maximum power density at 20cm was less than or equal to the limits for general population exposure in FCC Title 47 CFR Part 1.1310(e)(1) and RSS-102 Issue 6.

### 10.1 FCC RF Exposure Data

Data Rate	Frequency (MHz)	Conducted Output Power <sup>(1)</sup> (dBm)	Antenna Gain (dBi)	EIRP <sup>(1)</sup> (dBm)	EIRP <sup>(1)</sup> (mW)	Power Density <sup>(1)</sup> (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
1Mbit/s	2402	4.15	1.51	5.66	3.68	0.000732	1.0
	2440	3.93	0.27	4.20	2.63	0.000523	1.0
	2480	3.79	-0.70	3.09	2.04	0.000405	1.0
2Mbit/s	2402	4.17	0.97	5.14	3.27	0.000650	1.0
	2440	3.95	0.27	4.22	2.64	0.000526	1.0
	2480	3.81	-0.79	3.02	2.00	0.000399	1.0

### 10.2 RSS-102 Issue 6 RF Exposure Data

Data Rate	Frequency (MHz)	Conducted Output Power <sup>(1)</sup> (dBm)	Antenna Gain (dBi)	EIRP <sup>(1)</sup> (dBm)	EIRP <sup>(1)</sup> (mW)	Power Density <sup>(1)</sup> (W/m <sup>2</sup> )	Limit (W/m <sup>2</sup> )
1Mbit/s	2402	4.15	1.51	5.66	3.68	0.00732	5.35
	2440	3.93	0.27	4.20	2.63	0.00523	5.41
	2480	3.79	-0.70	3.09	2.04	0.00405	5.47
2Mbit/s	2402	4.17	0.97	5.14	3.27	0.00650	5.35
	2440	3.95	0.27	4.22	2.64	0.00526	5.41
	2480	3.81	-0.79	3.02	2.00	0.00399	5.47

<sup>1</sup> Values reported are for source-based, time-averaged output as described in section 4.1 of this report.



## 11 Revision History

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	4/12/2024	105704106LEX-003	BL	MC	Original Issue