



TEST REPORT

Test Report No.: UL-RPT-EMC-13729908-116-FCC

Applicant : EHEIM GmbH & Co. KG
Model Number : 3669090 (5310052)
FCC ID : 2AY5F-7376960
Technology : WLAN 2.4 GHz (802.11 b, g, n)
Test Standard(s) : FCC Part 15.107 & 15.109

1. This test report shall not be reproduced in full or partial, without the written approval of UL International Germany GmbH.
2. The results in this report apply only to the sample tested.
3. The test results in this report are traceable to the national or international standards.
4. Test Report Version 1.1; supersedes Test Report Version 1.0
5. Result of the tested sample: **PASS**
6. For details of applied tests and test results refer to test results summary

Prepared by: M. Asim Shahzad
Title: Engineer
Date: 07.06.2021

Approved by: Bernd Woerl
Title: Operations leader
Date: 16.06.2021



Deutsche
Akkreditierungsstelle
D-PL-19381-02-00

This laboratory is accredited by DAkkS.
The tests reported herein have been performed in
accordance with its' terms of accreditation.

UL INTERNATIONAL GERMANY GMBH

Hedelfinger Str. 61
70327 Stuttgart, Germany
STU.CTECHLab@ul.com

This page has been left intentionally blank.

Table of Contents

1. Customer Information	4
1.1. Applicant information	4
1.2. Manufacturer Information	4
2. Summary of Testing	5
2.1. General Information	5
2.2. Summary of Test Results	6
2.3. Method and procedure	6
2.4. Deviations from the Test Specification	6
3 Equipment Under Test (EUT)	7
3.1 Identification of Equipment under Test (EUT)	7
3.2 Description of Equipment Under Test (EUT)	7
3.3 Modifications Incorporated in the EUT	7
3.4 Operating Modes	7
3.5 Additional Information Related to Testing	7
3.6 Support Equipment	8
A. Support Equipment (In-house)	8
B. Support Equipment (Manufacturer supplied)	8
C. Interconnecting cables and Ports (Manufacturer/Applicant supplied)	8
4 Operation and Monitoring of the EUT during Testing	9
4.1 Operating Modes	9
4.2 Configuration and Peripherals	9
5 Measurement Uncertainty	10
5.1 Overview	10
6 Test Results	11
6.1 AC Conducted Emission	11
6.1.1 Test Summary:	11
6.1.2 Test Setup:	11
6.1.3 Numerical Results:	12
6.1.4 Graphical Plots:	13
6.2 Radiated Emissions below 1GHz	14
6.2.1 Test Summary:	14
6.2.2 Test Setup:	14
6.2.3 Numerical Results:	15
6.2.4 Graphical Plots:	16
6.3 Radiated Emissions above 1GHz/ Radiated Emissions from 1GHz to 18GHz	17
6.3.1 Test Summary:	17
6.3.2 Test Setup:	17
6.3.3 Numerical Results:	18
6.3.4 Graphical Plots:	19
7 Used equipment	20
8 Report Revision History	21

1. Customer Information

1.1. Applicant information

Company Name:	EHEIM GmbH & Co. KG
Company Address:	Plochinger Strasse 54; 73779 Deizisau; Germany
Contact Person:	Mr. Jan Winnacker
Contact E-Mail Address:	Jan.winnacker@eheim.com
Contact Phone No.:	+49 7153 7002 240

1.2. Manufacturer Information

Company Name:	EHEIM GmbH & Co. KG
Company Address:	Plochinger Strasse 54; 73779 Deizisau; Germany
Contact Person:	Mr. Jan Winnacker
Contact E-Mail Address:	Jan.winnacker@eheim.com
Contact Phone No.:	+49 7153 7002 240

2. Summary of Testing

2.1. General Information

Applied Standards

Specification Reference:	47CFR15.107 and 47CFR15.109
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart B (Unintentional Radiators) – Sections 15.107 and 15.109
Test Firm Registration:	399704

Location

Location of Testing:	UL International Germany GmbH Hedelfinger Str. 61 70327 Stuttgart Germany
-----------------------------	--

Date information

Order Date:	08.03.2021
EUT arrived:	11.05.2021
Test Dates:	20.05.2021 & 22.05.2021
EUT returned:	-/-

2.2. Summary of Test Results

Clause	Measurement	Complied	Did not comply	Not performed	Not applicable
Part 15.107 (a)	AC Conducted Emissions	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Part 15.109 (a)	Radiated Emissions	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Decision rule:
Where not otherwise specified or communicated in writing, statements of conformity (e.g. Pass/Fail) are established according to the following decision rule: considering that the applied test standards take measurement uncertainty into account, acceptance limit equals the tolerance limit (Accuracy Method). This leads to a maximum 50% of false accept or false reject when the measured value equals the tolerance limit. See ILAC-G8:09/2019 for further details.

Note: Complies with class B limits.

Information regarding class A and class B devices

Excerpt of Title 47 chapter I Part 15 subchapter A § 15.3 Definitions

(h) *Class A digital device*. A digital device that is marketed for use in a commercial, industrial or business environment, exclusive of a device which is marketed for use by the general public or is intended to be used in the home.

(i) *Class B digital device*. A digital device that is marketed for use in a residential environment notwithstanding use in commercial, business and industrial environments. Examples of such devices include, but are not limited to, personal computers, calculators, and similar electronic devices that are marketed for use by the general public.

2.3. Method and procedure

Reference:	ANSI C63.4-2014; ANSI C63.4a-2017
Title:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
Reference:	KDB 174176 D01 Line Conducted FAQ v01r01 June 3, 2015
Title:	AC Power-Line Conducted Emissions Frequently Asked Questions

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3 Equipment Under Test (EUT)

3.1 Identification of Equipment under Test (EUT)

EUT Description:	WiFi automatic aquarium heater
Brand Name:	EHEIM
Model Name or Number:	3669090 (5310052)
Test Sample Serial Number:	210401-003
Hardware Version Number:	7376960
Firmware Version Number:	website 05.0, server 06.2
FCC ID	2AY5F-7376960

3.2 Description of Equipment Under Test (EUT)

The EUT was an aquarium heater with WiFi functionality supplied by a FCC certified module (FCC ID: 2AHMR-EPS12F). This device was able to adjust the water temperature by a heating element. The user can set up a WiFi connection, configure and monitor the aquarium bar heater via an app (e.g. website, ...).

3.3 Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.4 Operating Modes

Mode Reference	Definition
Mode 1	Idle - The WLAN (Idle) not connected; rest of the EUT functions continuously operational: set by the customer.

3.5 Additional Information Related to Testing

Type of Device:	Intentional Radiator	
Power Supply Requirement(s):	Nominal	120V/ 60Hz AC
Highest Internal frequency generated/ used	CPU: 160MHz, Flash Frequency: 80MHz, Crystal Frequency: 60MHz	

3.6 Support Equipment

The following support equipment was used to exercise the EUT during testing:

A. Support Equipment (In-house)

Item	Description	Brand Name	Model Name or Number	Serial Number
1	Plug Adaptor	SKROSS	IP20	BS8546:2016

B. Support Equipment (Manufacturer supplied)

Item	Description	Brand Name	Model Name or Number	Serial Number
1	-/-	-/-	-/-	-/-

C. Interconnecting cables and Ports (Manufacturer/Applicant supplied)

Item	Description	Port type	Quantity	Length of attached cable(s)
1	US cable – AC AWM Style 2129 / 2x 18AWG	TP-01 (10A 125V) E157860	1	2150 mm

4 Operation and Monitoring of the EUT during Testing

4.1 Operating Modes

The EUT was tested in the following operating mode(s):

Transmitting Mode

Idle Mode


Receiving Mode

Unintentional Radiator

4.2 Configuration and Peripherals

EUT has been tested in following configuration:

- The EUT was preconfigured by the customer into WLAN (Idle) Mode and all other functions (e.g. heating coil) were continuously operational.
- The EUT was powered from 120V/ 60Hz for AC Conducted and Radiated Emissions.



5 Measurement Uncertainty

5.1 Overview

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%.

In accordance with DAkkS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Emissions	0.15 MHz to 30 MHz	95%	±2.49 dB
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±4.40 dB
Radiated Spurious Emissions	1 GHz to 18 GHz	95%	±4.76 dB
Radiated Spurious Emissions	18 GHz to 25 GHz	95%	±4.20 dB
Radiated Spurious Emissions	25 GHz to 40 GHz	95%	±4.76 dB

6 Test Results

6.1 AC Conducted Emission

6.1.1 Test Summary:

Test Engineer:	A. Shahzad	Test Date:	20.05.2021
Test Sample S/N:	210401-003		
Test Site Identification:	SR 7/8		

Clause:	Part 15.107
Test Method:	ANSI C63.4 Section 7
Title:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz AC power-line conducted emission measurements
Reference:	KDB 174176 D01 Line Conducted FAQ v01r01 June 3, 2015
Title:	AC Power-Line Conducted Emissions Frequently Asked Questions
Class:	Class B Limit


Environmental Conditions:

Temperature (°C):	20
Relative Humidity (%):	41

Note(s)

1. Measurement software used: Toyo EMI Software; CE measurement software EP5/CE Ver 4.0.1.
2. The final measured value, for the given emission, in the table below incorporates the cable loss. Calculation: Level = test receiver reading + path loss (cable attenuation + correction LISN).
3. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
4. Measurements were performed in a shielded room (SR7/ 8 Asset Number 1603671). The EUT was placed at a height of 80 cm above the reference ground plane and in a distance of 40 cm from the vertical ground plane at the edge of the table.
5. Supporting equipment necessary to feed/ drive the Eut in the specified operation mode were connected to a separate LISN during testing.

6.1.2 Test Setup:



6.1.3 Numerical Results:**Quasi Peak (Operating Mode1_120v/60Hz)**

Frequency [MHz]	Line Phase	Reading QP [dB(µV)]	Factor [dB]	Level QP [dB(µV)]	Limit QP [dB(µV)]	Margin QP [dB]	Result
0.1901	N	46.5	9.9	56.4	64.0	7.6	complied
0.2091	N	45.7	9.9	55.6	63.2	7.6	complied
0.2933	N	44.5	9.8	54.3	60.4	6.1	complied
1.0323	N	31.4	10.0	41.4	56.0	14.6	complied
1.7840	N	23.9	9.9	33.8	56.0	22.2	complied
19.5852	N	22.1	10.2	32.3	60.0	27.7	complied
0.1545	L1	47.4	9.9	57.3	65.8	8.5	complied
0.1926	L1	46.5	9.9	56.4	63.9	7.5	complied
0.2151	L1	45.9	9.9	55.8	63.0	7.2	complied
0.2833	L1	44.6	9.8	54.4	60.7	6.3	complied
1.4776	L1	22.6	9.9	32.5	56.0	23.5	complied
1.2836	L1	29.7	9.9	39.6	56.0	16.4	complied


Average (Operating Mode1_120v/60Hz)

Frequency [MHz]	Line Phase	Reading AV [dB(µV)]	Factor [dB]	Level AV [dB(µV)]	Limit AV [dB(µV)]	Margin AV [dB]	Result
0.1901	N	39.5	9.9	49.4	54.0	4.6	complied
0.2091	N	37.5	9.9	47.4	53.2	5.8	complied
0.2933	N	36.7	9.8	46.5	50.4	3.9	complied
1.0323	N	24.2	10.0	34.2	46.0	11.8	complied
1.7840	N	18.9	9.9	28.8	46.0	17.2	complied
19.5852	N	16.0	10.2	26.2	50.0	23.8	complied
0.1545	L1	42.0	9.9	51.9	55.8	3.9	complied
0.1926	L1	39.3	9.9	49.2	53.9	4.7	complied
0.2151	L1	38.1	9.9	48.0	53.0	5.0	complied
0.2833	L1	35.1	9.8	44.9	50.7	5.8	complied
1.4776	L1	12.9	9.9	22.8	46.0	23.2	complied
1.2836	L1	21.4	9.9	31.3	46.0	14.7	complied

Result: Pass

6.1.4 Graphical Plots:

Conducted Emissions for Line L & N (120V/60Hz)



Note: The plots show the max hold (peak detector) pre-scan results measured. Blue graph represents the result of the N-Line; green graph - the results for L1-Line. The bar graphs indicate the final measurement result applying the dedicated detector at selected frequencies for each limit line (red cycle for quasi peak limit; violet cycle for average limit).

Legend (Conducted Emissions)	
Items	Description
Blue line	Blue graph is the result of peak measurement phase L
Green line	Green graph is the result of peak measurement phase N
Red line	Limit line Quasi-Peak
Pink line	Limit line Average
Blue circle	Suspected item
Green circle	Suspected item
Red circle	Final item Quasi-Peak
Pink circle	Final item Average

6.2 Radiated Emissions below 1GHz

6.2.1 Test Summary:

Test Engineer:	A. Shahzad	Test Date:	22.05.2021
Test Sample S/N:	210401-003		
Test Site Identification:	SR 1/2		

FCC Reference:	Part 15.109
Test Method Used:	ANSI C63.4 Section 8
Title:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz Radiated emission measurements
Frequency Range:	30 MHz to 1000 MHz
Class:	Class B Limit


Environmental Conditions:

Temperature (°C):	22
Relative Humidity (%):	44

Note(s):

6. Measurement SW used: Toyo EMI Software; RE measurement software EP5/RE Ver 4.0.1
7. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
Calculation: Level = test receiver reading + path loss (cable attenuation + antenna factor).
8. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
9. Measurements below 1 GHz were performed in a semi-anechoic chamber (SR1/2 Asset Number 1603665) at a distance of 3 m. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 to 4 m.

6.2.2 Test Setup:




6.2.3 Numerical Results:**Operating Mode 1**

Frequency [MHz]	(P)	Reading QP dB(µV)	Factor dB(1/m)	Level QP dB(µV/m)	Limit QP dB(µV/m)	Margin QP dB	Height [cm]	Angle [°]
49.7519	H	5.0	20.9	25.9	40.0	14.1	142.0	317.0
57.9289	V	7.8	20.5	28.3	40.0	11.7	142.0	137.0
75.3846	V	20.1	17.9	38.0	40.0	2.0	101.0	271.0
150.1467	H	5.3	21.2	26.5	43.5	17.0	142.0	137.0
319.9648	V	15.0	23.2	38.2	46.0	7.8	141.0	138.0
319.9808	H	15.7	23.2	38.9	46.0	7.1	145.0	135.0
939.0986	V	6.4	35.4	41.8	46.0	4.2	142.0	137.0

Result: Pass

6.2.4 Graphical Plots:

Radiated Emissions for Vertical & Horizontal Polarization



Note: The plots show the max hold (peak detector) pre-scan results measured while rotating the TT continuously and an antenna movement between 1 – 4m height. Blue graph represents the result of the horizontal antenna polarization; green graph the results measured with vertical antenna polarization. The bar graphs indicate the final measurement result applying the detector at selected frequencies (red cycle for quasi peak limit).

Legend (Radiated Emissions below 1 GHz)	
Items	Description
—	Blue graph is the result of peak measurement for horizontal antenna polarization
—	Green graph is the result of peak measurement for vertical antenna polarization
—	Limit line Quasi-Peak
—○—	Suspected item for horizontal antenna polarization – not shown on actual graphs
—○—	Suspected item for vertical antenna polarization – not shown on actual graphs
—○—	Final item Quasi-Peak for horizontal and vertical antenna polarization

6.3 Radiated Emissions above 1GHz/ Radiated Emissions from 1GHz to 18GHz

6.3.1 Test Summary:

Test Engineer:	A. Shahzad	Test Date:	22.05.2021
Test Sample S/N:	210401-003		
Test Site Identification:	SR 1/2		

FCC Reference:	Part 15.109
Test Method Used:	ANSI C63.4 Section 8
Title:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz Radiated emission measurements
Frequency Range:	1000 MHz to 18000 MHz
Class:	Class B Limit


Environmental Conditions:

Temperature (°C):	22
Relative Humidity (%):	44

Note(s):

10. Measurement SW used: Toyo EMI Software; RE measurement software EP5/RE Ver 4.0.1.
11. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
Calculation: Level = test receiver reading + path loss (cable attenuation + antenna factor).
12. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
13. Measurements Above 1 GHz were performed in a semi-anechoic chamber (SR1/ 2 Asset Number 1603665) with absorbers on the ground floor at a distance of 3 m. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 to 4 m.

6.3.2 Test Setup:




6.3.3 Numerical Results:**Operating Mode 1**

Frequency [MHz]	(P)	Level AV [dB(µV/m)]	Level PK [dB(µV/m)]	Limit AV [dB(µV/m)]	Limit PK [dB(µV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [°]
4570.3450	V	36.3	48.5	54.0	74.0	17.7	25.5	100.0	53.0
4714.7290	H	37.5	50.6	54.0	74.0	16.5	23.4	100.0	53.0
6555.4970	H	42.1	54.5	54.0	74.0	11.9	19.5	100.0	194.0
7384.4640	V	43.8	56.0	54.0	74.0	10.2	18.0	100.0	194.0
9020.3610	H	48.7	61.0	54.0	74.0	5.3	13.0	100.0	53.0
9583.9500	V	47.7	60.2	54.0	74.0	6.3	13.8	100.0	53.0

Result: Pass

6.3.4 Graphical Plots:

Radiated Emissions for Vertical & Horizontal Polarization



Note: The plots show the max hold (peak detector) pre-scan results measured while rotating the TT continuously and an antenna movement between 1 – 4m height. Blue graph represents the result of the horizontal antenna polarization; green graph the results measured with vertical antenna polarization. The bar graphs indicate the final measurement result applying the dedicated detector at selected frequencies for each limit line (red cycle for peak limit; violet cycle for average limit).

Legend (Radiated Emissions above 1 GHz)	
Items	Description
Blue line	Blue graph is the result of peak measurement for horizontal antenna polarization
Green line	Green graph is the result of peak measurement for vertical antenna polarization
Blue line	Limit line Average
Red line	Limit line Peak
Blue circle	Suspected item for horizontal antenna polarization – not shown on actual graphs
Green circle	Suspected item for vertical antenna polarization – not shown on actual graphs
Blue circle	Final item Average for horizontal and vertical antenna polarization
Red circle	Final item Peak for horizontal antenna polarization
Pink circle	Final item Peak for vertical antenna polarization

7 Used equipment

SR 1/ 2

ID	used	Manufacturer	Type	Model	Serial	Cal Date	Cal. Cycle
1	<input type="checkbox"/>	Rohde & Schwarz	Antenna, Loop	HFH2-Z2	831247/012	2020-07-10	36
363	<input type="checkbox"/>	Wainwright	Notch Filter GSM900	WW-NF9	100002	lab verification	n/a
377	<input type="checkbox"/>	BONN Elektronik	Amplifier, Low Noise Pre	BLMA 0118-1A	025294B	2020-07-08	12
460	<input checked="" type="checkbox"/>	Deisl	Turntable	DT 4250 S		n/a	n/a
465	<input checked="" type="checkbox"/>	Schwarzbeck	Antenna, Trilog Broadband	VULB 9168	9168-240	2020-09-02	24
-/-	<input type="checkbox"/>	Schwarzbeck	Antenna, Trilog Broadband	VULB 9163	9163-966	2019-12-14	24
495	<input type="checkbox"/>	Rohde & Schwarz	Antenna, Log.- Periodical	HL050	100296	2019-10-20	24
496	<input checked="" type="checkbox"/>	Rohde & Schwarz	Antenna, log. - periodical	HL050	100297	2020-08-05	24
587	<input checked="" type="checkbox"/>	Maturo	antenna mast, tilting	TAM 4.0-E	011/7180311	n/a	n/a
588	<input checked="" type="checkbox"/>	Maturo	Controller	NCD	029/7180311	n/a	n/a
591	<input type="checkbox"/>	Rohde & Schwarz	Receiver	ESU 40	100244/040	2020-07-07	12
608	<input checked="" type="checkbox"/>	Rohde & Schwarz	Switch Matrix	OSP 120	101227	lab verification	n/a
611	<input type="checkbox"/>	Wainwright Instruments	Band Reject Filter DL LTE	WRCGV8-	1	lab verification	n/a
612	<input type="checkbox"/>	Wainwright Instruments	Band Reject Filter UL LTE	WRCGV8-	1	lab verification	n/a
613	<input checked="" type="checkbox"/>	Wainwright Instruments	Band Reject Filter WLAN/ BT	WRCTF12-	1	lab verification	n/a
614	<input type="checkbox"/>	Wainwright Instruments	Highpass Filter 3GHz	WHKX10-	1	lab verification	n/a
615	<input checked="" type="checkbox"/>	Wainwright Instruments	Highpass Filter 1GHz	WHKX12-	3	lab verification	n/a
620	<input type="checkbox"/>	Bonn Elektronik	pre-amplifier	BLNA 0110-01N	1510111	2020-07-09	24
624	<input type="checkbox"/>	Wainwright	6 GHz high-pass filter	WHKX10-5850-6500-18000-40SS	5	lab verification	n/a
628	<input checked="" type="checkbox"/>	Maturo	Antenna mast	CAM 4.0-P	224/19590716	n/a	n/a
-/-	<input checked="" type="checkbox"/>	TFA Dostmann	Digital Thermo-Hygrometer	No. 30.5002	06	lab verification	n/a

SR 7/8

ID	used	Manufacturer	Type	Model	Serial	Cal Date	Cal. Cycle
22	<input type="checkbox"/>	Rohde & Schwarz	Artificial Mains	ESH3-Z5	831767/014	2020-07-07	12
23	<input checked="" type="checkbox"/>	Rohde & Schwarz	Artificial Mains	ESH3-Z5	831767/013	2020-07-07	12
215	<input type="checkbox"/>	Rohde & Schwarz	Artificial Mains Network	ESH2-Z5	879675/002	2019-07-05	24
349	<input checked="" type="checkbox"/>	Rohde & Schwarz	Receiver, EMI Test	ESIB7	836697/009	2020-07-09	12
351	<input type="checkbox"/>	Rohde & Schwarz	network, Artificial Mains	ESH3-Z5	862770/018	2020-07-07	12
564	<input type="checkbox"/>	Teseq	Impedance stabilisation network (ISN)	ISN T800	26076	2020-07-07	24
565	<input type="checkbox"/>	Teseq	Impedance stabilisation network (ISN)	ISN ST08	26575	2020-07-07	12
616	<input type="checkbox"/>	Rohde & Schwarz	ISN	ENY81-CA6	101656	2020-07-07	12
-/-	<input checked="" type="checkbox"/>	TFA Dostmann	Digital Thermo-Hygrometer	No. 30.5002	05	lab verification	n/a

8 Report Revision History

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	24	-	AS: Initial Version
1.1	21	2.1 3.2 6.1.5, 6.2.5,6.3.5	AS: corrected information regarding Test Dates corrected information regarding EUT Info removed pictures and added separately into Setup photo's report.

--End of Report--