

**47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091
Maximum Permissible Exposure Calculations**

For FCC ID: 2AY6O-SHN01

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one ISM band radio operating over a range of: **2402 MHz to 2480 MHz**

MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure						
Frequency (MHz)	Range	Electric Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)	Time
0.3-1.34	614	1.63	*(100)	30		
1.34-30		824/f	2.19/f	*(180/f ²)	30	
30-300		27.5	0.073	0.2	30	
300-1500	/	/	/	f/1500	30	
1500-100,000	/	/	/	1.0	30	

f = frequency in MHz;

* = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated for this device as follows:

2.402 GHz to 2.48 GHz Frequency Band								
Freq	Output Power (dBm)	Tune Up Tolerance (dB)	Max Antenna Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density at 20 cm (mW/cm ²)	Limit (mW)	Margin (mW)
2402	4.950	0.5	0.5	5.950	3.936	0.001	1.000	0.999
2440	4.950	0.5	0.5	5.950	3.936	0.001	1.000	0.999
2480	4.860	0.5	0.5	5.860	3.855	0.001	1.000	0.999

Result: The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CRF §1.1310 and §2.1091.