



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

FCC PART 15 SUBPART C 15.247

Report Reference No.: **CTL2103097042-WF**

Compiled by: (position+printed name+signature)	Happy Guo (File administrators)	<u>Happy Guo</u>
Tested by: (position+printed name+signature)	Cary Gao (Test Engineer)	<u>Gary Gao</u>
Approved by: (position+printed name+signature)	Ivan Xie (Manager)	<u>Ivan Xie</u>

Product Name	: 3D Scanner
Model/Type reference	: POP
List Model(s)	: POP2, POP3, POP Blue, POP Blue2, POP Blue3, Master, Master 2, Master 3, Geek, Geek2, Geek3
Trade Mark	: Revopoint
FCC ID	: 2AY7J-POP
Applicant's name	: Revopoint 3D Technologies Inc. Room 706B, Block A, TCL Building, No. 006, Gaoxin South, Gaoxin Community, Yuehai Street, Nanshan District, Shenzhen, China
Test Firm	: Shenzhen CTL Testing Technology Co., Ltd.
Address of Test Firm	: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055
Test specification	: 47 CFR FCC Part 15 Subpart C 15.247
Standard	: 47 CFR FCC Part 15 Subpart C 15.247
TRF Originator	: Shenzhen CTL Testing Technology Co., Ltd.
Master TRF	: Dated 2011-01
Date of receipt of test item	: Mar. 09, 2021
Date of sampling	: Mar. 09, 2021
Date of Test Date	: Mar. 09, 2021–Mar. 29, 2021
Date of Issue	: Mar. 29, 2021
Result	: Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2103097042-WF	Mar. 29, 2021
Date of issue		

Equipment under Test : 3D Scanner

Sample No : CTL210309704-1-S002

Model /Type : POP

Listed Models : POP2, POP3, POP Blue, POP Blue2, POP Blue3, Master, Master 2, Master 3, Geek, Geek2, Geek3

Applicant : Revopoint 3D Technologies Inc.

Address : Room 706B, Block A, TCL Building, No. 006, Gaoxin South, Gaoxin Community, Yuehai Street, Nanshan District, Shenzhen, China

Manufacturer : Suzhou Decca Inspection Technology Co.,Ltd

Address : No. 2, Jianye Road, Changshu City Jiangsu Province, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

** Modified History **

	Table of Contents	Page
1. SUMMARY.....		5
1.1. TEST STANDARDS.....		5
1.2. TEST DESCRIPTION.....		5
1.3. TEST FACILITY.....		6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....		6
2. GENERAL INFORMATION.....		8
2.1. ENVIRONMENTAL CONDITIONS.....		8
2.2. GENERAL DESCRIPTION OF EUT.....		8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....		8
2.4. EQUIPMENTS USED DURING THE TEST.....		10
2.5. RELATED SUBMITTAL(S) / GRANT (S).....		10
2.6. MODIFICATIONS.....		10
3. TEST CONDITIONS AND RESULTS.....		11
3.1. CONDUCTED EMISSIONS TEST.....		11
3.2. RADIATED EMISSIONS AND BAND EDGE.....		14
3.3. MAXIMUM CONDUCTED OUTPUT POWER.....		22
3.4. POWER SPECTRAL DENSITY.....		23
3.5. 6dB BANDWIDTH.....		24
3.6. OUT-OF-BAND EMISSIONS.....		25
3.7. ANTENNA REQUIREMENT.....		26
4. TEST SETUP PHOTOS OF THE EUT.....		27
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....		28

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10: 2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05r02](#) : Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

1.2. Test Description

FCC PART 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Conducted Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)

Conducted Disturbance0.15~30MHz	±3.20dB	(1)
---------------------------------	---------	-----

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	3D Scanner
Model/Type reference:	POP
Power supply:	DC 5.0V
WIFI	
Supported type:	802.11b/802.11g/802.11n(H20)/802.11n(H40)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20)/802.11n(H40): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz 802.11n(H40): 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11 802.11n(H40): 7
Channel separation:	5MHz
Antenna type:	FPC Antenna
Antenna gain:	3.01dBi

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.

All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency WIFI :

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

Note: The line display in grey were the channel selected for testing

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
	11n(40MHz)/OFDM	13.5 Mbps	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11
	11n(40MHz)/OFDM	13.5 Mbps	3//9

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ESH2-Z5	860014/010	2020/05/15	2021/05/14
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2020/04/08	2021/04/07
EMI Test Receiver	R&S	ESCI	1166.5950.03	2020/05/18	2021/05/17
Spectrum Analyzer	Agilent	E4407B	MY41440676	2020/05/14	2021/05/13
Spectrum Analyzer	Agilent	N9020A	US46220290	2020/05/14	2021/05/13
Spectrum Analyzer	Keysight	N9020A	MY53420874	2020/05/14	2021/05/13
Controller	EM Electronics	EM 1000	060859	2020/05/20	2021/05/19
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2020/05/20	2021/05/19
Active Loop Antenna	Da Ze	ZN30900A	/	2020/05/20	2021/05/19
Amplifier	Agilent	8449B	3008A02306	2020/05/15	2021/05/14
Amplifier	Agilent	8447D	2944A10176	2020/05/15	2021/05/14
Temperature/Humidity Meter	Gangxing	CTH-608	02	2020/05/16	2021/05/15
Power Sensor	Agilent	U2021XA	MY55130004	2020/05/14	2021/05/13
Power Sensor	Agilent	U2021XA	MY55130006	2020/05/14	2021/05/13
Spectrum Analyzer	RS	FSP	1164.4391.38	2020/05/15	2021/05/14
Test Software					
Name of Software		Version			
TST-PASS		1.1.0			
ES-K1(Below 1GHz)		V1.71			
e3(Above 1GHz)		6.111221a			

The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15 Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION




TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Remark: 802.11b/802.11g/802.11n(H20) mode all have been tested, only worse case of 802.11b High Channel was reported.



MEASUREMENT RESULT: "CTL210318290_fin"


3/18/2021 3:16PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.163500	52.80	10.0	65	12.5	QP	L1	GND
2.598000	33.00	10.3	56	23.0	QP	L1	GND
2.755500	33.20	10.3	56	22.8	QP	L1	GND
2.949000	34.20	10.3	56	21.8	QP	L1	GND
3.102000	34.40	10.3	56	21.6	QP	L1	GND
4.524000	27.30	10.3	56	18.7	QP	L1	GND

MEASUREMENT RESULT: "CTL210318290_fin2"

3/18/2021 3:16PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.159000	39.40	10.0	56	16.1	AV	L1	GND
0.235500	25.10	10.0	52	27.2	AV	L1	GND
1.896000	19.70	10.2	46	26.3	AV	L1	GND
4.659000	31.00	10.3	46	16.0	AV	L1	GND
5.122500	31.30	10.4	50	18.7	AV	L1	GND
7.998000	25.80	10.6	50	24.2	AV	L1	GND



MEASUREMENT RESULT: "CTL210318291_fin"

3/18/2021 3:20PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.159000	52.30	10.0	66	13.2	QP	N	GND
2.526000	33.30	10.3	56	22.7	QP	N	GND
2.638500	33.80	10.3	56	22.2	QP	N	GND
2.674500	33.70	10.3	56	22.3	QP	N	GND
3.142500	35.50	10.3	56	20.5	QP	N	GND
4.632000	38.60	10.3	56	17.4	QP	N	GND

MEASUREMENT RESULT: "CTL210318291_fin2"

3/18/2021 3:20PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.168000	37.50	10.0	55	17.6	AV	N	GND
0.244500	28.40	10.0	52	26.5	AV	N	GND
2.103000	20.60	10.3	46	26.4	AV	N	GND
4.731000	31.10	10.3	46	14.9	AV	N	GND
5.131500	31.00	10.4	50	19.0	AV	N	GND
7.971000	28.80	10.6	50	24.2	AV	N	GND

3.2. Radiated Emissions and Band Edge

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission


Unwanted emissions that fall into restricted bands shall comply with the limits specified in RSS-Gen; and Unwanted emissions that do not fall within the restricted frequency bands shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**


1. The EUT was placed on turn table which is 0.8m above ground plane for below 1GHz test, and on a low permittivity and low loss tangent turn table which is 1.5m above ground plane for above 1GHz test.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.


TEST RESULTS

Remark:

1. We tested three channels (lowest/middle/highest) of each mode and recorded worst case for below 1GHz measurement.
2. For WIFI test we tested three channels (lowest/middle/highest) of each mode and recorded worst case at 802.11b mode above 1GHz.
3. Radiated emission test from 9KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz

Test mode:	WIFI	Polarization:	Horizontal					
SWEET TABLE: "test (30M-1G)"								
Short Description: Field Strength								
Start Stop Detector Meas. IF Transducer								
Frequency Frequency Time Bandw. VULB9168 20200407								
30.0 MHz 1.0 GHz MaxPeak 300.0 ms 120 kHz								
								
X X X MES CTL210324424_red								
MEASUREMENT RESULT: "CTL210324424_red"								
2021-3-24 20:37								
Frequency MHz	Level dB _{microm} /m	Transd dB	Limit dB _{microm} /m	Margin dB	Det. ---	Height cm	Azimuth deg	Polarization
239.520000	41.50	13.7	46.0	4.5	---	0.0	0.00	HORIZONTAL
268.620000	30.70	13.8	46.0	15.3	---	0.0	0.00	HORIZONTAL
299.660000	31.90	14.9	46.0	14.1	---	0.0	0.00	HORIZONTAL
480.080000	37.70	19.1	46.0	8.3	---	0.0	0.00	HORIZONTAL
565.440000	31.50	20.9	46.0	14.5	---	0.0	0.00	HORIZONTAL
901.060000	35.70	26.4	46.0	10.3	---	0.0	0.00	HORIZONTAL


MEASUREMENT RESULT: "CTL210324425_red"

2021-3-24 20:39

Frequency MHz	Level dB _{microm} /m	Transd dB	Limit dB _{microm} /m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
43.580000	18.40	14.8	40.0	21.6	---	0.0	0.00	VERTICAL
62.980000	17.70	14.0	40.0	22.3	---	0.0	0.00	VERTICAL
239.520000	34.40	13.7	46.0	11.6	---	0.0	0.00	VERTICAL
350.100000	27.80	16.1	46.0	18.2	---	0.0	0.00	VERTICAL
551.860000	35.40	20.4	46.0	10.6	---	0.0	0.00	VERTICAL
901.060000	32.60	26.4	46.0	13.4	---	0.0	0.00	VERTICAL

For 1GHz to 25GHz**802.11b Mode (above 1GHz)**

Note: 802.11b/802.11g/802.11n (H20) all have been tested, only worse case 802.11b is reported

Frequency(MHz):		2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	45.32	PK	74	28.68	40.77	33.52	6.92	35.89
4824.00	--	AV	54	--	--	--	--	--
5436.00	46.58	PK	74	27.42	39.38	34.38	7.10	34.28
5436.00	--	AV	54	--	--	--	--	--
7236.00	47.34	PK	74	26.66	36.07	37.1	9.19	35.02
7236.00	--	AV	54	--	--	--	--	--

Frequency(MHz):		2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	44.96	PK	74	29.04	40.41	33.52	6.92	35.89
4824.00	--	AV	54	--	--	--	--	--
5626.00	45.36	PK	74	28.64	38.16	34.38	7.10	34.28
5626.00	--	AV	54	--	--	--	--	--
7236.00	47.21	PK	74	26.79	35.94	37.1	9.19	35.02
7236.00	--	AV	54	--	--	--	--	--

Frequency(MHz):		2437		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	44.75	PK	74	29.25	38.51	33.59	6.95	34.3
4874.00	--	AV	54	--	--	--	--	--
5738.00	45.82	PK	74	28.18	38.22	34.56	7.15	34.11
5738.00	--	AV	54	--	--	--	--	--
7311.00	47.86	PK	74	26.14	36.20	37.44	9.22	35
7311.00	--	AV	54	--	--	--	--	--

Frequency(MHz):		2437		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	44.32	PK	74	29.68	37.98	33.59	6.95	34.2
4874.00	--	AV	54	--	--	--	--	--
5730.00	45.61	PK	74	28.39	38.71	34.07	7.05	34.22
5730.00	--	AV	54	--	--	--	--	--
7311.00	46.85	PK	74	27.15	35.19	37.44	9.22	35
7311.00	--	AV	54	--	--	--	--	--

Frequency(MHz):		2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	44.23	PK	74	29.77	53.55	33.71	6.98	35.91
4924.00	--	AV	54	--	--	--	--	--
5854.00	45.84	PK	74	28.16	41.24	34.34	7.09	34.27
5854.00	--	AV	54	--	--	--	--	--
7386.00	46.95	PK	74	27.05	37.4	37.61	9.25	34.98
7386.00	--	AV	54	--	--	--	--	--

Frequency(MHz):		2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	44.34	PK	74	29.66	39.56	33.71	6.98	35.91
4924.00	--	AV	54	--	--	--	--	--
5530.00	45.89	PK	74	28.11	38.72	34.34	7.09	34.27
5530.00	--	AV	54	--	--	--	--	--
7386.00	47.01	PK	74	26.99	35.13	37.61	9.25	34.98
7386.00	--	AV	54	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Results of Band Edges Test (Radiated)

Note: 802.11b/802.11g/802.11n (H20) all have been tested, only worse case 802.11b is reported

Frequency(MHz):			2412		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2412.00	104.24	PK	--	--	70.85	28.78	4.61	0	33.39
2412.00	101.17	AV	--	--	67.78	28.78	4.61	0	33.39
2372.00	44.66	PK	74	29.34	11.58	28.52	4.56	0	33.08
2372.00	--	AV	54	--	--	--	--	--	--
2390.00	46.3	PK	74	27.7	12.98	28.72	4.6	0	33.32
2390.00	--	AV	54	--	--	--	--	--	--
2400.00	48.91	PK	74	25.09	15.52	28.78	4.61	0	33.39
2400.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2412		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2412.00	104.95	PK	--	--	71.56	28.78	4.61	0	33.39
2412.00	100.32	AV	--	--	66.93	28.78	4.61	0	33.39
2366.00	43.95	PK	74	30.05	10.87	28.52	4.56	0	33.08
2366.00	--	AV	54	--	--	--	--	--	--
2390.00	46.53	PK	74	27.47	13.21	28.72	4.60	0	33.32
2390.00	--	AV	54	--	--	--	--	--	--
2400.00	48.28	PK	74	25.72	14.89	28.78	4.61	0	33.39
2400.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2462		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2462.00	104.14	PK	--	--	70.52	28.92	4.7	0	33.62
2462.00	99.28	AV	--	--	65.66	28.92	4.7	0	33.62
2483.50	49.29	PK	74	24.71	15.66	28.93	4.7	0	33.63
2483.50	--	AV	--	--	--	--	--	--	--
2491.00	45.63	PK	74	28.37	11.99	28.94	4.71	0	33.64
2491.00	--	AV	54	--	--	--	--	--	--
2500.00	43.98	PK	74	30.02	10.3	28.96	4.72	0	33.68
2500.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2462		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2462.00	103.91	PK	--	--	70.29	28.92	4.7	0	33.62
2462.00	98.67	AV	--	--	65.05	28.92	4.7	0	33.62
2483.50	48.13	PK	74	25.87	14.5	28.93	4.7	0	33.63
2483.50	--	AV	54	--	--	--	--	--	--
2487.00	45.68	PK	74	28.32	12.04	28.94	4.71	0	33.64
2487.00	--	AV	54	--	--	--	--	--	--
2500.00	43.58	PK	74	30.42	9.9	28.96	4.72	0	33.68
2500.00	--	AV	54	--	--	--	--	--	--

REMARKS:

1. Emission level (dB_{uV}/m) = Raw Value (dB_{uV}) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
7. For fundamental frequency, RBW 3MHz VBW 3MHz Peak detector is for PK Value; RMS detector is for AV value.

3.3. Maximum Conducted Output Power


Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

Raw data reference to Section 2 from Appendix.

3.4. Power Spectral Density

Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW \geq 3 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

Test Configuration



Test Results

Raw data reference to Section 3 from Appendix.

3.5. 6dB Bandwidth


Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

Test Configuration



Test Results

Raw data reference to Section 1 from Appendix.

3.6. Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration



Test Results

Raw data reference to Section 4 from Appendix.

3.7. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.


Test Result:

The maximum gain of antenna was 3.01dBi.



4. Test Setup Photos of the EUT


Note: AE device (Dell laptop) model Inspiron 3180, provided by the lab



5. External and Internal Photos of the EUT




External Photos of EUT








Internal Photos of EUT







***** End of Report *****