

Shenzhen ICHECKKEY Technology Co., Ltd
*B302, Building 4, TianYanXuan, No.1 Lane14, Bantian East Village, Bantian Street,
LongGang District, Shenzhen, China*

Date: October 28, 2024

FCC ID: 2AYA5-T12

Model Number: T12

To: Federal Communication Commission
Authorization and Evaluation Division 7435 Oakland Mills Road
Columbia, MD 21048

To Whom It May Concern,

We, **Shenzhen ICHECKKEY Technology Co., Ltd** hereby declare that our product (**T12 5 in 1 Desktop Wireless Charger**) Model Number: **T12** meet item 5.2 of KDB 680106v03r01 as follow;

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device works in the frequency range 115.0 KHz -205 KHz, 300.0 KHz -350 KHz
Output power from each primary coil is less than or equal to 15 watts.	Yes	The device support 3 primary coils and the maximum output power of primary coil is 15W.
The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes	The transfer system includes three primary coils and clients that can detect and allow coupling three of coils.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Shenzhen ICHECKKEY Technology Co., Ltd

*B302, Building 4, TianYanXuan, No.1 Lane14, Bantian East Village, Bantian Street,
LongGang District, Shenzhen, China*

For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested	Yes	Only one radiating structure and tested at maximum Output Power
--	-----	---

Please contact me if you have any question.

Sincerely,

Huolin Xie

(Signed)

Name / Title: Huolin. Xie / manager

Company: Shenzhen ICHECKKEY Technology Co., Ltd

Address: B302, Building 4, TianYanXuan, No.1 Lane14, Bantian East Village, Bantian Street, LongGang District, Shenzhen, China

Phone: +86-755-28227437

Fax: +86-755-28227437

E-Mail: 112383182@qq.com