



RF exposure Estimation

1. Introduction

Product: Intelligent voice mouse

Model no.: TG-SD, TG-CN, TG-EN, TG-OP, TG-CU

FCC ID: 2AYAETG01

The EUT is Intelligent voice mouse, which contain 2.4GHz wireless function inside.

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r01, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

3. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Conducted Power + tune up tolerance = $7.13 \text{ dBm} = 5.164 \text{ mW}$

Distance = 5 mm

$f = 2.435 \text{ GHz}$

$[5.164/5] \cdot \text{SQRT}(2.435) = 1.612$

$1.162 \leq 3.0$

Therefore, excluded from SAR testing.

- TÜV SÜD Shenzhen LTD.

Reviewed by:

Prepared By:

John Zhi/Project Manager
Date: 2021-06-29

Mark Chen/EMC Project Engineer
Date: 2021-06-29