

TEST REPORT

Product : Wireless 3D wheel Aligner
Trade mark : SmartSafe
Model/Type reference : WA613
Serial Number : N/A
Report Number : EED32Q81688504
FCC ID : 2AYANWA613
Date of Issue : Nov. 22, 2024
Test Standards : 47 CFR Part 15 Subpart E
Test result : PASS

Prepared for:

SHENZHEN SMARTSAFE TECH CO., LTD
3F, Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua
New District, Shenzhen, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Keven Tan.

Keven Tan

Reviewed by:

Frazer Li

Frazer Li

Approved by:

Aaron Ma

Aaron Ma

Date:

Nov. 22, 2024



Check No.: 7125221024

1 Content

1 CONTENT	2
2 VERSION	3
3 TEST SUMMARY	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 TEST CONFIGURATION	7
4.4 TEST ENVIRONMENT	7
4.5 DESCRIPTION OF SUPPORT UNITS	8
4.6 TEST LOCATION	8
4.7 DEVIATION FROM STANDARDS	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
4.10 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	8
5 EQUIPMENT LIST	9
6 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	12
6.1 ANTENNA REQUIREMENT	12
6.2 AC POWER LINE CONDUCTED EMISSIONS	13
6.3 MAXIMUM CONDUCTED OUTPUT POWER	17
6.4 6dB EMISSION BANDWIDTH	18
6.5 26dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	19
6.6 MAXIMUM POWER SPECTRAL DENSITY	20
6.7 FREQUENCY STABILITY	21
6.8 RADIATED EMISSION	22
RADIATED SPURIOUS EMISSIONS TEST DATA:	25
6.9 RADIATED EMISSION WHICH FALL IN THE RESTRICTED BANDS	162
7 APPENDIX 5G WI-FI	199
PHOTOGRAPHS OF TEST SETUP	200
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	202

2 Version

Version No.	Date	Description
00	Nov. 22, 2024	Original

3 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(6)	PASS
Duty Cycle	47 CFR Part 15 Subpart E Section 15.407	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
26dB emission bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
99% Occupied bandwidth	\	PASS
6dB emission bandwidth	47 CFR Part 15 Subpart E Section 15.407 (e)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	PASS
Radiated Emissions	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS
Radiated Emissions which fall in the restricted bands	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS
Remark: Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. Note: The product consists of two identical modules working together. All modules have been tested, and the report only records the worst one (left module).		

4 General Information

4.1 Client Information

Applicant:	SHENZHEN SMARTSAFE TECH CO., LTD
Address of Applicant:	3F, Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua New District, Shenzhen, China
Manufacturer:	SHENZHEN SMARTSAFE TECH CO., LTD
Address of Manufacturer:	3F, Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua New District, Shenzhen, China
Factory :	SHENZHEN SMARTSAFE TECH CO., LTD
Address of Factory :	3F, Building B, Qiao'an Technology Industrial Park, Guanlan, Longhua New District, Shenzhen, China

4.2 General Description of EUT

Product Name:	Wireless 3D wheel Aligner	
Model No.:	WA613	
Trade mark:	SmartSafe	
Product Type:	☐ Mobile ☐ Portable ☒ Fixed Location	
Type of Modulation:	IEEE 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11n(HT20/HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11ac(VHT20/VHT40/VHT80): OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)	
Operating Frequency	U-NII-1: 5150-5250MHz U-NII-3:5745-5825MHz	
Antenna Type:	FPC antenna	
Antenna Gain:	U-NII-1: 2.47 dBi U-NII-3: 2.32 dBi	
Power Supply:	Battery:	DC 7.4V
Test voltage:	DC 7.4V	
Sample Received Date:	Oct. 31, 2024	
Sample tested Date:	Oct. 31, 2024 to Nov. 19, 2024	

Operation Frequency each of channel

802.11a/802.11n/802.11ac (20MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	149	5745
40	5200	153	5765
44	5220	157	5785
48	5240	161	5805
-	-	165	5825

802.11n/802.11ac (40MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
38	5190	151	5755
46	5230	159	5795

802.11ac (80MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
42	5210	155	5775

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

4.3 Test Configuration

EUT Test Software Settings:	
Software:	Adb.exe
EUT Power Grade:	Default
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Test Mode:	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
802.11ac(VHT20)	MCS0
802.11ac(VHT40)	MCS0
802.11ac(VHT80)	MCS0

4.4 Test Environment

Operating Environment:		
Radiated Spurious Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Conducted Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
RF Conducted:		
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Temperature:	NT (Normal Temperature)	22~25.0 °C
	LT (Low Temperature)	0 °C
	HT (High Temperature)	55.0 °C
Working Voltage of the EUT:	NV (Normal Voltage)	7.4 V
	LV (Low Voltage)	6.66 V
	HV (High Voltage)	8.14 V

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

4.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

5 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Communication test set	R&S	CMW500	107929	06-26-2024	06-25-2025
Signal Generator	R&S	SMBV100A	1407.6004K02- 262149-CV	09-02-2024	09-01-2025
Spectrum Analyzer	R&S	FSV40	101200	07-18-2024	07-17-2025
RF control unit(power unit)	MWRF-test	MW100-RFCB	MW220620CTI-42	06-25-2024	06-24-2025
High-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-12-2023	12-10-2024
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	05-29-2024	05-28-2025
BT&WI-FI Automatic test software	MWRF-test	MTS 8310	V2.0.0.0	---	---
Spectrum Analyzer	R&S	FSV3044	101509	01-17-2024	01-16-2025

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-18-2024	04-17-2025
Temperature/ Humidity Indicator	Defu	TH128	/	04-25-2024	04-24-2025
LISN	R&S	ENV216	100098	09-19-2024	09-18-2025
Barometer	changchun	DYM3	1188	---	---
Test software	Fara	EZ-EMC	EMC-CON 3A1.1	---	---
Capacitive voltage probe	Schwarzbeck	CVP 9222C	00124	06-18-2024	06-17-2025

ISN	TESEQ	ISN T800	30297	12-14-2023	12-13-2024
3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05/22/2022	05/21/2025
Receiver	R&S	ESCI7	100938-003	09/07/2024	09/06/2025
Spectrum Analyzer	R&S	FSV40	101200	07/18/2024	07/17/2025
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/22/2022	05/21/2025
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04/16/2024	04/15/2025
Microwave Preamplifier	Tonscend	EMC051845SE	980380	12/14/2023	12/13/2024
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07/02/2023	07/01/2026
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	04/16/2024	04/15/2025
Preamplifier	Agilent	11909A	12-1	03/22/2024	03/21/2025
Preamplifier	CD	PAP-1840-60	6041.6042	06/19/2024	06/18/2025
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---


3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2024	01-08-2027
Receiver	Keysight	N9038A	MY57290136	01-09-2024	01-08-2025
Spectrum Analyzer	Keysight	N9020B	MY57111112	01-29-2024	01-28-2025
Spectrum Analyzer	Keysight	N9030B	MY57140871	01-23-2024	01-22-2025
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-28-2024	04-27-2025
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-16-2024	04-15-2025
Horn Antenna	ETS-LINDGREN	3117	57407	07-03-2024	07-02-2025
Preamplifier	EMCI	EMC001330	980563	03-08-2024	03-07-2025
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-18-2024	07-17-2025
Preamplifier	Tonscend	EMC051845SE	980380	12-14-2023	12-13-2024
Communication test set	R&S	CMW500	102898	12-14-2023	12-13-2024
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	04-07-2024	04-06-2025
RSE Automatic test software	JS Tonscend	JS36-RSE	V4.0.0.0	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

6 Radio Technical Requirements Specification

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	Please see Internal photos
The antenna is FPC antenna. The best case gain of the antenna for U-NII-1 is 2.47dBi, for U-NII-3 is 2.32 dBi.	


6.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Setup:			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		

Test Mode:	All modes were tested, only the worst case of 5G Wi-Fi Band 1 was recorded in the report.
Test Results:	Pass

Measurement Data

Live line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	41.95	9.84	51.79	66.00	-14.21	QP	
2		0.2175	44.95	9.81	54.76	62.91	-8.15	QP	
3	*	0.2175	37.41	9.81	47.22	52.91	-5.69	AVG	
4		0.2670	35.15	9.65	44.80	51.21	-6.41	AVG	
5		0.3660	37.26	9.70	46.96	58.59	-11.63	QP	
6		0.3660	28.27	9.70	37.97	48.59	-10.62	AVG	
7		0.5190	35.53	9.74	45.27	56.00	-10.73	QP	
8		0.5235	26.36	9.74	36.10	46.00	-9.90	AVG	
9		0.6315	36.75	9.72	46.47	56.00	-9.53	QP	
10		0.6315	25.65	9.72	35.37	46.00	-10.63	AVG	
11		2.2650	30.75	9.76	40.51	56.00	-15.49	QP	
12		2.3100	22.38	9.76	32.14	46.00	-13.86	AVG	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	48.03	9.84	57.87	66.00	-8.13	QP	
2		0.2490	44.03	9.71	53.74	61.79	-8.05	QP	
3	*	0.2714	39.48	9.63	49.11	51.07	-1.96	AVG	
4		0.3930	28.79	9.77	38.56	48.00	-9.44	AVG	
5		0.4740	34.72	9.78	44.50	56.44	-11.94	QP	
6		0.4740	25.60	9.78	35.38	46.44	-11.06	AVG	
7		0.6360	26.54	9.74	36.28	46.00	-9.72	AVG	
8		0.6630	33.76	9.85	43.61	56.00	-12.39	QP	
9		2.2830	30.72	9.76	40.48	56.00	-15.52	QP	
10		2.2920	22.37	9.76	32.13	46.00	-13.87	AVG	
11		4.2270	21.78	9.82	31.60	46.00	-14.40	AVG	
12		4.2900	31.25	9.82	41.07	56.00	-14.93	QP	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.407 (a)												
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E												
Test Setup:													
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power and record the results in the test report.												
Limit:	<table border="1"> <thead> <tr> <th>Frequency band (MHz)</th><th>Limit</th></tr> </thead> <tbody> <tr> <td>5150-5250</td><td> $\leq 1W(30dBm)$ for master device $\leq 250mW(24dBm)$ for client device </td></tr> <tr> <td>5250-5350</td><td>$\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$</td></tr> <tr> <td>5470-5725</td><td>$\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$</td></tr> <tr> <td>5725-5850</td><td>$\leq 1W(30dBm)$</td></tr> <tr> <td>Remark:</td><td> * Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. </td></tr> </tbody> </table>	Frequency band (MHz)	Limit	5150-5250	$\leq 1W(30dBm)$ for master device $\leq 250mW(24dBm)$ for client device	5250-5350	$\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$	5470-5725	$\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$	5725-5850	$\leq 1W(30dBm)$	Remark:	* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.
Frequency band (MHz)	Limit												
5150-5250	$\leq 1W(30dBm)$ for master device $\leq 250mW(24dBm)$ for client device												
5250-5350	$\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$												
5470-5725	$\leq 250mW(24dBm)$ for client device or $11dBm+10\log B^*$												
5725-5850	$\leq 1W(30dBm)$												
Remark:	* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.												
Test Mode:	Transmitting mode with modulation												
Test Results:	Refer to Appendix 5G Wi-Fi												


6.4 6dB Emission Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (e)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Limit:	≥ 500 kHz
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi


6.5 26dB Emission Bandwidth and 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Test Setup:	 Diagram illustrating the test setup for 26dB Emission Bandwidth and 99% Occupied Bandwidth measurement. The setup includes an EUT (Equipment Under Test) placed on a Table inside a TEMPERATURE CABINET. The EUT is connected to a Control Computer and a Power Supply. The EUT's Antenna port(s) is connected to an Attenuator, which is then connected to the RF test System Instrument. Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Limit:	No restriction limits
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi

6.6 Maximum Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.407 (a)												
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F												
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.												
Test Procedure:	- Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. - Allow the sweeps to continue until the trace stabilizes. - Use the peak marker function to determine the maximum amplitude level.												
Limit:	<table border="1"> <thead> <tr> <th>Frequency band (MHz)</th><th>Limit</th></tr> </thead> <tbody> <tr> <td>5150-5250</td><td>≤17dBm in 1MHz for master device ≤11dBm in 1MHz for client device</td></tr> <tr> <td>5250-5350</td><td>≤11dBm in 1MHz for client device</td></tr> <tr> <td>5470-5725</td><td>≤11dBm in 1MHz for client device</td></tr> <tr> <td>5725-5850</td><td>≤30dBm in 500kHz</td></tr> <tr> <td>Remark:</td><td>The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.</td></tr> </tbody> </table>	Frequency band (MHz)	Limit	5150-5250	≤17dBm in 1MHz for master device ≤11dBm in 1MHz for client device	5250-5350	≤11dBm in 1MHz for client device	5470-5725	≤11dBm in 1MHz for client device	5725-5850	≤30dBm in 500kHz	Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.
Frequency band (MHz)	Limit												
5150-5250	≤17dBm in 1MHz for master device ≤11dBm in 1MHz for client device												
5250-5350	≤11dBm in 1MHz for client device												
5470-5725	≤11dBm in 1MHz for client device												
5725-5850	≤30dBm in 500kHz												
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.												
Test Mode:	Transmitting mode with modulation												
Test Results:	Refer to Appendix 5G Wi-Fi												

6.7 Frequency Stability

Test Requirement:	47 CFR Part 15C Section 15.407 (g)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1.The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. 2. Turn the EUT on and couple its output to a spectrum analyzer. 3. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. 4. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. 5. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi

6.8 Radiated Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.407 (b)				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed				

	the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. Note: (i) $EIRP = ((E*d)^2) / 30$ where: • E is the field strength in V/m; • d is the measurement distance in meters; • EIRP is the equivalent isotropically radiated power in watts. (ii) Working in dB units, the above equation is equivalent to: $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$ (iii) Or, if d is 3 meters: $EIRP[dBm] = E[dB\mu V/m] - 95.2$
Test Setup:	




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

Figure 3. Above 1 GHz


Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz:
-----------------	--

	Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel and the highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Transmitting mode with modulation
Test Results:	Pass

Radiated Spurious Emissions test Data:
Radiated Emission below 1GHz


Only the worst case data of 5G Wi-Fi Band 1 was recorded in the report.

Horizontal:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		213.8008	23.34	12.90	36.24	43.50	-7.26	QP	199	191
2	*	242.6103	29.81	13.99	43.80	46.00	-2.20	QP	100	186
3		477.5041	19.52	19.43	38.95	46.00	-7.05	QP	199	309
4		721.3463	14.48	23.32	37.80	46.00	-8.20	QP	100	38
5	!	827.3483	16.03	24.89	40.92	46.00	-5.08	QP	199	169
6		960.1400	17.03	26.27	43.30	54.00	-10.70	QP	100	101

Vertical:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	55.5801	18.69	13.21	31.90	40.00	-8.10	200	103	
2		146.8619	24.03	9.17	33.20	43.50	-10.30	100	234	
3		241.9731	23.56	13.96	37.52	46.00	-8.48	100	63	
4		479.4336	16.52	19.47	35.99	46.00	-10.01	200	306	
5		797.8598	10.66	24.47	35.13	46.00	-10.87	200	231	
6		960.1401	16.77	26.27	43.04	54.00	-10.96	100	9	

Transmitter Emission above 1GHz
5G Wi-Fi Band 1:

Test_Mode	802.11 a Transmitting	Test_Frequency	5180
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1302.5303	8.04	37.56	45.60	68.20	22.60	PASS	Horizontal	PK
2	2063.8064	9.83	36.41	46.24	68.20	21.96	PASS	Horizontal	PK
3	3053.3553	12.39	36.54	48.93	68.20	19.27	PASS	Horizontal	PK
4	8365.9683	-4.47	48.44	43.97	68.20	24.23	PASS	Horizontal	PK
5	11660.308	0.42	45.35	45.77	68.20	22.43	PASS	Horizontal	PK
6	14914.3957	5.34	43.09	48.43	68.20	19.77	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5180
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1249.725	7.72	38.01	45.73	68.20	22.47	PASS	Vertical	PK
2	1920.242	8.89	37.06	45.95	68.20	22.25	PASS	Vertical	PK
3	2537.9538	11.68	37.08	48.76	68.20	19.44	PASS	Vertical	PK
4	3877.8878	14.46	35.88	50.34	68.20	17.86	PASS	Vertical	PK
5	8157.2329	-3.58	47.57	43.99	68.20	24.21	PASS	Vertical	PK
6	14213.4357	6.89	41.67	48.56	68.20	19.64	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1221.1221	7.54	37.95	45.49	68.20	22.71	PASS	Horizontal	PK
2	1636.9637	8.29	36.85	45.14	68.20	23.06	PASS	Horizontal	PK
3	2558.3058	11.63	36.98	48.61	68.20	19.59	PASS	Horizontal	PK
4	3535.7536	13.62	35.61	49.23	68.20	18.97	PASS	Horizontal	PK
5	7499.975	-6.04	50.20	44.16	68.20	24.04	PASS	Horizontal	PK
6	9999.625	-0.55	48.34	47.79	68.20	20.41	PASS	Horizontal	PK
7	14183.5342	7.07	41.94	49.01	68.20	19.19	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1400.9901	8.35	37.44	45.79	68.20	22.41	PASS	Vertical	PK
2	2153.4653	10.00	36.65	46.65	68.20	21.55	PASS	Vertical	PK
3	3531.9032	13.63	35.84	49.47	68.20	18.73	PASS	Vertical	PK
4	7724.2362	-4.85	48.48	43.63	68.20	24.57	PASS	Vertical	PK
5	10802.3651	-0.48	46.15	45.67	68.20	22.53	PASS	Vertical	PK
6	13673.4837	5.37	43.73	49.10	68.20	19.10	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1138.0638	7.22	38.43	45.65	68.20	22.55	PASS	Horizontal	PK
2	1850.385	8.79	36.53	45.32	68.20	22.88	PASS	Horizontal	PK
3	2704.6205	11.74	37.25	48.99	68.20	19.21	PASS	Horizontal	PK
4	8045.1023	-3.71	47.98	44.27	68.20	23.93	PASS	Horizontal	PK
5	11034.1017	0.37	45.49	45.86	68.20	22.34	PASS	Horizontal	PK
6	14107.6304	7.43	40.71	48.14	68.20	20.06	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1316.2816	8.09	37.82	45.91	68.20	22.29	PASS	Vertical	PK
2	1955.9956	9.02	37.70	46.72	68.20	21.48	PASS	Vertical	PK
3	3201.3201	13.01	37.51	50.52	68.20	17.68	PASS	Vertical	PK
4	8211.2856	-3.90	47.53	43.63	68.20	24.57	PASS	Vertical	PK
5	10967.3984	0.47	46.05	46.52	68.20	21.68	PASS	Vertical	PK
6	13500.4	5.83	41.73	47.56	68.20	20.64	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1252.4752	7.74	38.46	46.20	68.20	22.00	PASS	Horizontal	PK
2	1578.1078	8.14	37.64	45.78	68.20	22.42	PASS	Horizontal	PK
3	2580.8581	11.58	37.27	48.85	68.20	19.35	PASS	Horizontal	PK
4	7499.975	-6.04	50.95	44.91	68.20	23.29	PASS	Horizontal	PK
5	10000.2	-0.55	48.49	47.94	68.20	20.26	PASS	Horizontal	PK
6	14184.1092	7.07	41.67	48.74	68.20	19.46	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1418.5919	8.29	37.67	45.96	68.20	22.24	PASS	Vertical	PK
2	2300.8801	10.40	37.18	47.58	68.20	20.62	PASS	Vertical	PK
3	3282.1782	13.46	36.49	49.95	68.20	18.25	PASS	Vertical	PK
4	8140.557	-3.49	46.85	43.36	68.20	24.84	PASS	Vertical	PK
5	10061.1531	-0.58	45.10	44.52	68.20	23.68	PASS	Vertical	PK
6	13467.6234	5.43	41.83	47.26	68.20	20.94	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5230
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1278.8779	7.91	38.05	45.96	68.20	22.24	PASS	Horizontal	PK
2	1662.2662	8.37	37.62	45.99	68.20	22.21	PASS	Horizontal	PK
3	3259.0759	13.34	36.32	49.66	68.20	18.54	PASS	Horizontal	PK
4	7499.975	-6.04	50.61	44.57	68.20	23.63	PASS	Horizontal	PK
5	9999.625	-0.55	47.20	46.65	68.20	21.55	PASS	Horizontal	PK
6	14129.4815	7.33	40.90	48.23	68.20	19.97	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5230
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1254.1254	7.75	37.31	45.06	68.20	23.14	PASS	Vertical	PK
2	1778.8779	8.70	37.00	45.70	68.20	22.50	PASS	Vertical	PK
3	2678.2178	11.68	36.75	48.43	68.20	19.77	PASS	Vertical	PK
4	7499.975	-6.04	49.93	43.89	68.20	24.31	PASS	Vertical	PK
5	10792.0146	-0.48	46.11	45.63	68.20	22.57	PASS	Vertical	PK
6	13655.0828	5.59	42.69	48.28	68.20	19.92	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1623.2123	8.25	38.71	46.96	68.20	21.24	PASS	Horizontal	PK
2	2212.3212	9.91	36.77	46.68	68.20	21.52	PASS	Horizontal	PK
3	3197.4697	12.99	36.52	49.51	68.20	18.69	PASS	Horizontal	PK
4	7500.55	-6.04	50.44	44.40	68.20	23.80	PASS	Horizontal	PK
5	9999.625	-0.55	48.97	48.42	68.20	19.78	PASS	Horizontal	PK
6	13666.0083	5.46	42.83	48.29	68.20	19.91	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1250.275	7.73	39.01	46.74	68.20	21.46	PASS	Vertical	PK
2	2184.2684	9.90	36.52	46.42	68.20	21.78	PASS	Vertical	PK
3	3195.2695	12.98	37.24	50.22	68.20	17.98	PASS	Vertical	PK
4	7354.4927	-6.47	49.75	43.28	68.20	24.92	PASS	Vertical	PK
5	10950.1475	0.45	45.39	45.84	68.20	22.36	PASS	Vertical	PK
6	14316.3658	6.15	41.87	48.02	68.20	20.18	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1398.7899	8.35	37.98	46.33	68.20	21.87	PASS	Horizontal	PK
2	1924.6425	8.90	38.03	46.93	68.20	21.27	PASS	Horizontal	PK
3	2533.0033	11.68	38.71	50.39	68.20	17.81	PASS	Horizontal	PK
4	7499.975	-6.04	50.49	44.45	68.20	23.75	PASS	Horizontal	PK
5	9999.625	-0.55	49.40	48.85	68.20	19.35	PASS	Horizontal	PK
6	14169.1585	7.14	41.70	48.84	68.20	19.36	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1428.49 28	8.25	38.41	46.66	68.20	21.54	PASS	Vertical	PK
2	2399.89	10.71	37.78	48.49	68.20	19.71	PASS	Vertical	PK
3	3031.35 31	12.39	36.80	49.19	68.20	19.01	PASS	Vertical	PK
4	7499.97 5	-6.04	50.06	44.02	68.20	24.18	PASS	Vertical	PK
5	10000.2	-0.55	46.57	46.02	68.20	22.18	PASS	Vertical	PK
6	13665.4 333	5.46	43.15	48.61	68.20	19.59	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1277.7778	7.89	37.77	45.66	68.20	22.54	PASS	Horizontal	PK
2	2187.5688	9.89	37.49	47.38	68.20	20.82	PASS	Horizontal	PK
3	3315.1815	13.49	36.82	50.31	68.20	17.89	PASS	Horizontal	PK
4	7499.975	-6.04	53.11	47.07	68.20	21.13	PASS	Horizontal	PK
5	10000.2	-0.55	47.89	47.34	68.20	20.86	PASS	Horizontal	PK
6	13642.4321	5.74	42.90	48.64	68.20	19.56	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1285.4785	7.94	37.99	45.93	68.20	22.27	PASS	Vertical	PK
2	1573.1573	8.14	37.34	45.48	68.20	22.72	PASS	Vertical	PK
3	3085.2585	12.41	36.59	49.00	68.20	19.20	PASS	Vertical	PK
4	7499.975	-6.04	49.85	43.81	68.20	24.39	PASS	Vertical	PK
5	10000.2	-0.55	45.74	45.19	68.20	23.01	PASS	Vertical	PK
6	14140.407	7.28	41.97	49.25	68.20	18.95	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1396.03 96	8.34	37.14	45.48	68.20	22.72	PASS	Horizontal	PK
2	2713.42 13	11.75	37.59	49.34	68.20	18.86	PASS	Horizontal	PK
3	4107.26 07	15.73	34.16	49.89	68.20	18.31	PASS	Horizontal	PK
4	7499.97 5	-6.04	50.45	44.41	68.20	23.79	PASS	Horizontal	PK
5	10000.2	-0.55	46.69	46.14	68.20	22.06	PASS	Horizontal	PK
6	14115.6 808	7.40	41.38	48.78	68.20	19.42	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1167.76 68	7.31	38.41	45.72	68.20	22.48	PASS	Vertical	PK
2	1721.12 21	8.54	37.64	46.18	68.20	22.02	PASS	Vertical	PK
3	3196.36 96	12.98	36.55	49.53	68.20	18.67	PASS	Vertical	PK
4	7434.99 68	-6.41	49.20	42.79	68.20	25.41	PASS	Vertical	PK
5	10150.8 575	-0.96	46.30	45.34	68.20	22.86	PASS	Vertical	PK
6	14142.1 321	7.27	41.91	49.18	68.20	19.02	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5200
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1223.87 24	7.56	37.79	45.35	68.20	22.85	PASS	Horizontal	PK
2	2336.08 36	10.51	38.16	48.67	68.20	19.53	PASS	Horizontal	PK
3	3200.22	13.00	36.54	49.54	68.20	18.66	PASS	Horizontal	PK
4	7499.97 5	-6.04	50.86	44.82	68.20	23.38	PASS	Horizontal	PK
5	9999.62 5	-0.55	48.73	48.18	68.20	20.02	PASS	Horizontal	PK
6	14201.9 351	6.98	41.21	48.19	68.20	20.01	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5200
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1414.19 14	8.31	37.16	45.47	68.20	22.73	PASS	Vertical	PK
2	2416.39 16	10.89	36.66	47.55	68.20	20.65	PASS	Vertical	PK
3	3441.14 41	13.35	36.38	49.73	68.20	18.47	PASS	Vertical	PK
4	7499.97 5	-6.04	49.81	43.77	68.20	24.43	PASS	Vertical	PK
5	11146.8 073	-0.39	46.66	46.27	68.20	21.93	PASS	Vertical	PK
6	13649.9 075	5.65	42.49	48.14	68.20	20.06	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5240
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1400.44	8.35	38.75	47.10	68.20	21.10	PASS	Horizontal	PK
2	1955.99 56	9.02	36.91	45.93	68.20	22.27	PASS	Horizontal	PK
3	2530.25 3	11.69	36.63	48.32	68.20	19.88	PASS	Horizontal	PK
4	7499.97 5	-6.04	50.71	44.67	68.20	23.53	PASS	Horizontal	PK
5	9999.62 5	-0.55	46.81	46.26	68.20	21.94	PASS	Horizontal	PK
6	13691.8 846	5.15	43.50	48.65	68.20	19.55	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5240
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1267.32 67	7.84	38.19	46.03	68.20	22.17	PASS	Vertical	PK
2	1754.67 55	8.64	37.09	45.73	68.20	22.47	PASS	Vertical	PK
3	2394.93 95	10.69	37.27	47.96	68.20	20.24	PASS	Vertical	PK
4	7761.03 81	-4.36	47.81	43.45	68.20	24.75	PASS	Vertical	PK
5	10127.2 814	-0.79	45.99	45.20	68.20	23.00	PASS	Vertical	PK
6	13660.2 58	5.53	43.64	49.17	68.20	19.03	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1158.41 58	7.29	37.18	44.47	68.20	23.73	PASS	Horizontal	PK
2	1513.20 13	8.04	36.50	44.54	68.20	23.66	PASS	Horizontal	PK
3	2443.89 44	11.17	36.93	48.10	68.20	20.10	PASS	Horizontal	PK
4	3650.71 51	13.80	33.53	47.33	68.20	20.87	PASS	Horizontal	PK
5	7500.55	-6.04	50.38	44.34	68.20	23.86	PASS	Horizontal	PK
6	10000.2	-0.55	47.63	47.08	68.20	21.12	PASS	Horizontal	PK
7	13671.7 586	5.39	42.75	48.14	68.20	20.06	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1605.61 06	8.19	36.53	44.72	68.20	23.48	PASS	Vertical	PK
2	2165.56 66	9.96	37.45	47.41	68.20	20.79	PASS	Vertical	PK
3	3051.70 52	12.39	37.35	49.74	68.20	18.46	PASS	Vertical	PK
4	7866.84 33	-4.02	47.48	43.46	68.20	24.74	PASS	Vertical	PK
5	9999.62 5	-0.55	45.74	45.19	68.20	23.01	PASS	Vertical	PK
6	13625.1 813	5.95	41.51	47.46	68.20	20.74	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1406.49 06	8.32	37.21	45.53	68.20	22.67	PASS	Horizontal	PK
2	1957.09 57	9.03	36.71	45.74	68.20	22.46	PASS	Horizontal	PK
3	3047.30 47	12.40	37.41	49.81	68.20	18.39	PASS	Horizontal	PK
4	7499.4	-6.04	50.44	44.40	68.20	23.80	PASS	Horizontal	PK
5	10000.2	-0.55	47.55	47.00	68.20	21.20	PASS	Horizontal	PK
6	14301.4 151	6.23	42.18	48.41	68.20	19.79	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1432.34 32	8.24	37.99	46.23	68.20	21.97	PASS	Vertical	PK
2	2559.95 6	11.62	36.99	48.61	68.20	19.59	PASS	Vertical	PK
3	3512.65 13	13.66	36.34	50.00	68.20	18.20	PASS	Vertical	PK
4	8046.25 23	-3.70	49.12	45.42	68.20	22.78	PASS	Vertical	PK
5	10607.4 304	-0.48	47.33	46.85	68.20	21.35	PASS	Vertical	PK
6	13667.7 334	5.44	43.48	48.92	68.20	19.28	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1399.89	8.35	37.40	45.75	68.20	22.45	PASS	Horizontal	PK
2	2042.90 43	9.62	36.00	45.62	68.20	22.58	PASS	Horizontal	PK
3	3180.96 81	12.89	36.85	49.74	68.20	18.46	PASS	Horizontal	PK
4	7499.4	-6.04	51.33	45.29	68.20	22.91	PASS	Horizontal	PK
5	10000.2	-0.55	48.93	48.38	68.20	19.82	PASS	Horizontal	PK
6	14208.8 354	6.93	41.97	48.90	68.20	19.30	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210
Tset_Engineer	chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1249.725	7.72	38.97	46.69	68.20	21.51	PASS	Vertical	PK
2	2154.0154	10.00	37.15	47.15	68.20	21.05	PASS	Vertical	PK
3	3169.967	12.82	37.34	50.16	68.20	18.04	PASS	Vertical	PK
4	8081.9041	-3.44	46.68	43.24	68.20	24.96	PASS	Vertical	PK
5	10295.1898	-1.38	47.20	45.82	68.20	22.38	PASS	Vertical	PK
6	14303.7152	6.22	42.00	48.22	68.20	19.98	PASS	Vertical	PK

5G Wi-Fi Band 4:

Test_Mode	802.11 a Transmitting	Test_Frequency	5745
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1268.42 68	7.96	38.21	46.17	68.20	22.03	PASS	Horizontal	PK
2	1606.71 07	8.72	37.91	46.63	68.20	21.57	PASS	Horizontal	PK
3	2286.57 87	10.61	38.02	48.63	68.20	19.57	PASS	Horizontal	PK
4	3200.22	12.81	38.35	51.16	68.20	17.04	PASS	Horizontal	PK
5	7499.8	-6.04	50.24	44.20	68.20	24.00	PASS	Horizontal	PK
6	10000.0 667	-0.55	47.67	47.12	68.20	21.08	PASS	Horizontal	PK
7	14266.8 511	6.49	43.05	49.54	68.20	18.66	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5745
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1203.5204	7.82	38.60	46.42	68.20	21.78	PASS	Vertical	PK
2	1567.6568	8.45	37.71	46.16	68.20	22.04	PASS	Vertical	PK
3	2290.9791	10.67	37.15	47.82	68.20	20.38	PASS	Vertical	PK
4	3310.231	13.27	37.63	50.90	68.20	17.30	PASS	Vertical	PK
5	8315.5877	-4.69	48.47	43.78	68.20	24.42	PASS	Vertical	PK
6	11622.4415	0.63	46.55	47.18	68.20	21.02	PASS	Vertical	PK
7	14232.3488	6.75	42.49	49.24	68.20	18.96	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5785
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1209.57 1	7.83	37.81	45.64	68.20	22.56	PASS	Horizontal	PK
2	1670.51 71	8.41	36.91	45.32	68.20	22.88	PASS	Horizontal	PK
3	2712.87 13	11.86	38.49	50.35	68.20	17.85	PASS	Horizontal	PK
4	3834.43 34	14.50	36.74	51.24	68.20	16.96	PASS	Horizontal	PK
5	8113.94 09	-3.36	47.65	44.29	68.20	23.91	PASS	Horizontal	PK
6	11644.6 763	0.51	46.05	46.56	68.20	21.64	PASS	Horizontal	PK
7	14687.7	7.67	42.38	50.05	68.20	18.15	PASS	Horizontal	PK

	792								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 a Transmitting	Test_Frequency	5785
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1324.53 25	8.05	38.71	46.76	68.20	21.44	PASS	Vertical	PK
2	1838.83 39	8.43	37.41	45.84	68.20	22.36	PASS	Vertical	PK
3	3191.96 92	12.80	38.74	51.54	68.20	16.66	PASS	Vertical	PK
4	4342.68 43	16.31	35.97	52.28	68.20	15.92	PASS	Vertical	PK
5	8994.89 97	-2.77	46.85	44.08	68.20	24.12	PASS	Vertical	PK
6	13168.9 113	2.35	44.20	46.55	68.20	21.65	PASS	Vertical	PK

7	15261.2 841	6.70	42.94	49.64	68.20	18.56	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 a Transmitting	Test_Frequency	5825
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1393.28 93	8.08	38.20	46.28	68.20	21.92	PASS	Horizontal	PK
2	1976.34 76	9.21	37.76	46.97	68.20	21.23	PASS	Horizontal	PK
3	3049.50 5	12.65	37.04	49.69	68.20	18.51	PASS	Horizontal	PK
4	3947.19 47	14.96	36.37	51.33	68.20	16.87	PASS	Horizontal	PK
5	7790.38 6	-3.96	48.33	44.37	68.20	23.83	PASS	Horizontal	PK
6	10000.0 667	-0.55	47.76	47.21	68.20	20.99	PASS	Horizontal	PK

7	14180.9 787	7.08	42.58	49.66	68.20	18.54	PASS	Horizontal	PK
---	----------------	------	-------	-------	-------	-------	------	------------	----

Test_Mode	802.11 a Transmitting	Test_Frequency	5825
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1280.52 81	7.99	40.11	48.10	68.20	20.10	PASS	Vertical	PK
2	2028.05 28	9.42	38.38	47.80	68.20	20.40	PASS	Vertical	PK
3	3095.15 95	12.59	38.99	51.58	68.20	16.62	PASS	Vertical	PK
4	4544.00 44	17.39	35.40	52.79	68.20	15.41	PASS	Vertical	PK
5	8051.83 68	-3.66	46.92	43.26	68.20	24.94	PASS	Vertical	PK
6	10943.1 295	0.43	45.77	46.20	68.20	22.00	PASS	Vertical	PK

7	14112.7 408	7.41	41.74	49.15	68.20	19.05	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1290.78 61	8.84	38.67	47.51	68.20	20.69	PASS	Horizontal	PK
2	2028.20 19	9.93	38.15	48.08	68.20	20.12	PASS	Horizontal	PK
3	2820.25 47	12.51	37.62	50.13	68.20	18.07	PASS	Horizontal	PK
4	4333.95 56	17.50	35.58	53.08	68.20	15.12	PASS	Horizontal	PK
5	7715.24 77	-4.98	48.74	43.76	68.20	24.44	PASS	Horizontal	PK
6	9546.93 65	-0.96	44.99	44.03	68.20	24.17	PASS	Horizontal	PK

7	13638.9 093	5.78	42.87	48.65	68.20	19.55	PASS	Horizontal	PK
---	----------------	------	-------	-------	-------	-------	------	------------	----

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1278.31 86	8.70	37.76	46.46	68.20	21.74	PASS	Vertical	PK
2	1675.44 5	8.69	37.03	45.72	68.20	22.48	PASS	Vertical	PK
3	2297.35 32	11.49	38.00	49.49	68.20	18.71	PASS	Vertical	PK
4	3516.23 44	14.14	37.13	51.27	68.20	16.93	PASS	Vertical	PK
5	8074.83 83	-3.49	47.21	43.72	68.20	24.48	PASS	Vertical	PK
6	10917.0 611	0.38	45.65	46.03	68.20	22.17	PASS	Vertical	PK

7	14184.8 123	7.06	42.35	49.41	68.20	18.79	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5785
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1224.42 24	7.87	38.45	46.32	68.20	21.88	PASS	Horizontal	PK
2	1618.26 18	8.67	37.47	46.14	68.20	22.06	PASS	Horizontal	PK
3	2110.01 1	9.65	37.56	47.21	68.20	20.99	PASS	Horizontal	PK
4	2811.88 12	12.04	38.96	51.00	68.20	17.20	PASS	Horizontal	PK
5	4199.11 99	16.34	34.56	50.90	68.20	17.30	PASS	Horizontal	PK
6	7500.56 67	-6.04	49.90	43.86	68.20	24.34	PASS	Horizontal	PK

7	8966.53 11	-2.85	47.23	44.38	68.20	23.82	PASS	Horizontal	PK
8	11635.4 757	0.56	46.01	46.57	68.20	21.63	PASS	Horizontal	PK
9	14143.4 096	7.26	42.11	49.37	68.20	18.83	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5785
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1255.22 55	7.93	37.98	45.91	68.20	22.29	PASS	Vertical	PK
2	1733.22 33	8.22	37.21	45.43	68.20	22.77	PASS	Vertical	PK
3	2328.93 29	10.76	37.27	48.03	68.20	20.17	PASS	Vertical	PK
4	3040.15 4	12.65	37.67	50.32	68.20	17.88	PASS	Vertical	PK
5	4038.50 38	15.43	35.99	51.42	68.20	16.78	PASS	Vertical	PK
6	8902.89 35	-3.03	47.01	43.98	68.20	24.22	PASS	Vertical	PK

7	13569.9 047	6.12	42.51	48.63	68.20	19.57	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1141.91 42	7.20	38.72	45.92	68.20	22.28	PASS	Horizontal	PK
2	1474.69 75	7.88	38.34	46.22	68.20	21.98	PASS	Horizontal	PK
3	1981.29 81	9.24	37.49	46.73	68.20	21.47	PASS	Horizontal	PK
4	3185.91 86	12.78	38.04	50.82	68.20	17.38	PASS	Horizontal	PK
5	7499.8	-6.04	49.86	43.82	68.20	24.38	PASS	Horizontal	PK
6	10959.2 306	0.46	46.14	46.60	68.20	21.60	PASS	Horizontal	PK
7	14999.8	4.02	45.08	49.10	68.20	19.10	PASS	Horizontal	PK

	333								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1311.33 11	8.04	38.65	46.69	68.20	21.51	PASS	Vertical	PK
2	1944.44 44	9.08	37.26	46.34	68.20	21.86	PASS	Vertical	PK
3	2438.94 39	10.91	38.99	49.90	68.20	18.30	PASS	Vertical	PK
4	4061.05 61	15.45	36.76	52.21	68.20	15.99	PASS	Vertical	PK
5	7747.44 98	-4.55	47.81	43.26	68.20	24.94	PASS	Vertical	PK
6	10564.3 71	-0.46	45.58	45.12	68.20	23.08	PASS	Vertical	PK

7	14361.1 574	5.90	43.79	49.69	68.20	18.51	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5755
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1273.55 16	8.65	38.33	46.98	68.20	21.22	PASS	Vertical	PK
2	1531.33 54	8.91	37.53	46.44	68.20	21.76	PASS	Vertical	PK
3	1925.52 84	9.22	37.39	46.61	68.20	21.59	PASS	Vertical	PK
4	3609.37 4	14.33	37.43	51.76	68.20	16.44	PASS	Vertical	PK
5	7499.8	-6.04	49.59	43.55	68.20	24.65	PASS	Vertical	PK
6	10429.4 286	-1.24	46.40	45.16	68.20	23.04	PASS	Vertical	PK
7	13475.5 984	5.53	43.43	48.96	68.20	19.24	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5795
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1305.45 37	8.91	38.29	47.20	68.20	21.00	PASS	Horizontal	PK
2	2103.74 02	10.87	38.05	48.92	68.20	19.28	PASS	Horizontal	PK
3	2825.75 51	12.56	38.34	50.90	68.20	17.30	PASS	Horizontal	PK
4	3983.03 22	16.45	35.28	51.73	68.20	16.47	PASS	Horizontal	PK
5	7499.8	-6.04	49.36	43.32	68.20	24.88	PASS	Horizontal	PK
6	9999.3	-0.56	46.51	45.95	68.20	22.25	PASS	Horizontal	PK
7	14134.2 089	7.31	42.38	49.69	68.20	18.51	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5795
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1385.02 57	8.42	39.06	47.48	68.20	20.72	PASS	Vertical	PK
2	2083.57 22	10.67	37.99	48.66	68.20	19.54	PASS	Vertical	PK
3	3054.93 7	13.33	38.56	51.89	68.20	16.31	PASS	Vertical	PK
4	7882.39 22	-4.07	47.58	43.51	68.20	24.69	PASS	Vertical	PK
5	10000.0 667	-0.55	46.22	45.67	68.20	22.53	PASS	Vertical	PK
6	11618.6 079	0.65	46.80	47.45	68.20	20.75	PASS	Vertical	PK
7	13655.0	5.59	43.69	49.28	68.20	18.92	PASS	Vertical	PK

	103								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1440.76 27	8.67	37.94	46.61	68.20	21.59	PASS	Horizontal	PK
2	2036.63 58	10.04	38.01	48.05	68.20	20.15	PASS	Horizontal	PK
3	3095.27 3	13.66	37.69	51.35	68.20	16.85	PASS	Horizontal	PK
4	4365.85 77	17.82	35.95	53.77	68.20	14.43	PASS	Horizontal	PK
5	7767.38 45	-4.28	48.01	43.73	68.20	24.47	PASS	Horizontal	PK
6	10943.1 295	0.43	45.92	46.35	68.20	21.85	PASS	Horizontal	PK

7	13654.2 436	5.60	43.34	48.94	68.20	19.26	PASS	Horizontal	PK
---	----------------	------	-------	-------	-------	-------	------	------------	----

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1321.58 81	8.81	38.25	47.06	68.20	21.14	PASS	Vertical	PK
2	2131.97 55	10.75	37.91	48.66	68.20	19.54	PASS	Vertical	PK
3	3123.50 82	13.76	37.91	51.67	68.20	16.53	PASS	Vertical	PK
4	4397.75 99	18.15	35.04	53.19	68.20	15.01	PASS	Vertical	PK
5	7441.52 94	-6.37	49.33	42.96	68.20	25.24	PASS	Vertical	PK
6	10434.0 289	-1.18	47.49	46.31	68.20	21.89	PASS	Vertical	PK

7	14102.0 068	7.46	42.31	49.77	68.20	18.43	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5785
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1314.98 77	8.84	37.94	46.78	68.20	21.42	PASS	Horizontal	PK
2	1843.38 96	8.90	37.20	46.10	68.20	22.10	PASS	Horizontal	PK
3	2943.82 96	13.04	38.46	51.50	68.20	16.70	PASS	Horizontal	PK
4	4141.80 95	16.81	35.57	52.38	68.20	15.82	PASS	Horizontal	PK
5	7499.8	-6.04	50.42	44.38	68.20	23.82	PASS	Horizontal	PK
6	10000.0 667	-0.55	46.18	45.63	68.20	22.57	PASS	Horizontal	PK
7	13726.3	4.67	43.83	48.50	68.20	19.70	PASS	Horizontal	PK

	151								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5785
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1291.51 94	8.85	37.55	46.40	68.20	21.80	PASS	Vertical	PK
2	1982.73 22	9.47	38.02	47.49	68.20	20.71	PASS	Vertical	PK
3	3168.24 46	13.89	38.88	52.77	68.20	15.43	PASS	Vertical	PK
4	4424.89 5	18.09	35.04	53.13	68.20	15.07	PASS	Vertical	PK
5	7710.64 74	-5.03	47.93	42.90	68.20	25.30	PASS	Vertical	PK
6	10185.6 124	-1.19	45.82	44.63	68.20	23.57	PASS	Vertical	PK

7	13710.9 807	4.89	43.71	48.60	68.20	19.60	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5825
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1303.62 02	8.91	37.96	46.87	68.20	21.33	PASS	Horizontal	PK
2	2036.63 58	10.04	37.36	47.40	68.20	20.80	PASS	Horizontal	PK
3	3080.23 87	13.54	38.46	52.00	68.20	16.20	PASS	Horizontal	PK
4	7499.8	-6.04	49.66	43.62	68.20	24.58	PASS	Horizontal	PK
5	9999.3	-0.56	47.18	46.62	68.20	21.58	PASS	Horizontal	PK
6	14277.5 852	6.41	43.60	50.01	68.20	18.19	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5825
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1312.78 75	8.86	37.11	45.97	68.20	22.23	PASS	Vertical	PK
2	2037.00 25	10.05	37.38	47.43	68.20	20.77	PASS	Vertical	PK
3	3187.31 25	13.95	39.80	53.75	68.20	14.45	PASS	Vertical	PK
4	4091.57 28	16.61	36.72	53.33	68.20	14.87	PASS	Vertical	PK
5	7762.78 42	-4.34	47.62	43.28	68.20	24.92	PASS	Vertical	PK
6	10860.3 24	0.01	45.96	45.97	68.20	22.23	PASS	Vertical	PK

7	14163.3 442	7.17	42.38	49.55	68.20	18.65	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5755
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1280.52 81	7.99	39.24	47.23	68.20	20.97	PASS	Horizontal	PK
2	1718.37 18	8.24	37.42	45.66	68.20	22.54	PASS	Horizontal	PK
3	2550.05 5	11.48	38.82	50.30	68.20	17.90	PASS	Horizontal	PK
4	4196.36 96	16.32	35.58	51.90	68.20	16.30	PASS	Horizontal	PK
5	7499.8	-6.04	49.83	43.79	68.20	24.41	PASS	Horizontal	PK
6	10539.8 36	-0.42	46.53	46.11	68.20	22.09	PASS	Horizontal	PK
7	13679.5	5.30	43.67	48.97	68.20	19.23	PASS	Horizontal	PK

	453								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5755
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1242.57 43	7.90	38.30	46.20	68.20	22.00	PASS	Vertical	PK
2	2103.41 03	9.66	37.78	47.44	68.20	20.76	PASS	Vertical	PK
3	2943.89 44	12.26	38.71	50.97	68.20	17.23	PASS	Vertical	PK
4	4210.12 1	16.32	35.04	51.36	68.20	16.84	PASS	Vertical	PK
5	7499.8	-6.04	48.61	42.57	68.20	25.63	PASS	Vertical	PK
6	11492.8 662	0.68	45.98	46.66	68.20	21.54	PASS	Vertical	PK
7	14681.6	7.52	41.12	48.64	68.20	19.56	PASS	Vertical	PK

	454								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5795
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1226.62 27	7.87	37.79	45.66	68.20	22.54	PASS	Horizontal	PK
2	2075.35 75	9.59	38.13	47.72	68.20	20.48	PASS	Horizontal	PK
3	3304.73 05	13.28	37.68	50.96	68.20	17.24	PASS	Horizontal	PK
4	4652.36 52	17.68	35.35	53.03	68.20	15.17	PASS	Horizontal	PK
5	7499.8	-6.04	50.33	44.29	68.20	23.91	PASS	Horizontal	PK
6	11669.9 78	0.36	46.93	47.29	68.20	20.91	PASS	Horizontal	PK
7	14125.0	7.35	41.17	48.52	68.20	19.68	PASS	Horizontal	PK

	083								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5795
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1242.57 43	7.90	38.34	46.24	68.20	21.96	PASS	Vertical	PK
2	1943.89 44	9.08	37.94	47.02	68.20	21.18	PASS	Vertical	PK
3	3300.88 01	13.29	38.74	52.03	68.20	16.17	PASS	Vertical	PK
4	7817.22 11	-3.88	47.15	43.27	68.20	24.93	PASS	Vertical	PK
5	11508.9 673	0.79	44.82	45.61	68.20	22.59	PASS	Vertical	PK
6	13665.7 444	5.46	44.62	50.08	68.20	18.12	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5775
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1239.82 4	7.90	37.77	45.67	68.20	22.53	PASS	Horizontal	PK
2	1632.01 32	8.60	38.39	46.99	68.20	21.21	PASS	Horizontal	PK
3	2330.03 3	10.76	37.62	48.38	68.20	19.82	PASS	Horizontal	PK
4	3541.80 42	13.68	36.59	50.27	68.20	17.93	PASS	Horizontal	PK
5	7499.8	-6.04	51.12	45.08	68.20	23.12	PASS	Horizontal	PK
6	10000.0 667	-0.55	47.29	46.74	68.20	21.46	PASS	Horizontal	PK
7	14772.1	7.52	40.98	48.50	68.20	19.70	PASS	Horizontal	PK

	181								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5775
Tset_Engineer	Chenjun	Test_Date	2024/11/12
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1229.37 29	7.87	38.66	46.53	68.20	21.67	PASS	Vertical	PK
2	1810.23 1	8.22	37.55	45.77	68.20	22.43	PASS	Vertical	PK
3	2531.35 31	11.38	37.37	48.75	68.20	19.45	PASS	Vertical	PK
4	4143.56 44	15.87	36.19	52.06	68.20	16.14	PASS	Vertical	PK
5	7739.78 27	-4.65	47.73	43.08	68.20	25.12	PASS	Vertical	PK
6	10971.4 981	0.49	45.96	46.45	68.20	21.75	PASS	Vertical	PK

7	14213.1 809	6.89	42.05	48.94	68.20	19.26	PASS	Vertical	PK
---	----------------	------	-------	-------	-------	-------	------	----------	----

Transmitter Emission above 18GHz
5G Wi-Fi Band 1:

Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Chenjun	Test_Date	2024\11\13
Remark	\		

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19311.0 524	-24.12	62.76	38.64	68.2	29.56	PASS	Horizontal	PK
2	22176.9 671	-24.75	61.28	36.53	68.2	31.67	PASS	Horizontal	PK
3	24630.7 052	-19.85	57.90	38.05	68.2	30.15	PASS	Horizontal	PK
4	28265.7 706	-20.54	58.54	38.00	68.2	30.2	PASS	Horizontal	PK
5	32355.3 342	-15.71	55.03	39.32	68.2	28.88	PASS	Horizontal	PK
6	36485.3	-14.63	51.88	37.25	68.2	30.95	PASS	Horizontal	PK

	794								
--	-----	--	--	--	--	--	--	--	--

Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Chenjun	Test_Date	2024\11\13
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19411.3 365	-23.94	63.58	39.64	68.2	28.56	PASS	Vertical	PK
2	22105.2 042	-24.89	61.76	36.87	68.2	31.33	PASS	Vertical	PK
3	25947.2 779	-19.05	58.39	39.34	68.2	28.86	PASS	Vertical	PK
4	30409.4 564	-18.67	56.88	38.21	68.2	29.99	PASS	Vertical	PK
5	35880.9 152	-15.14	52.07	36.93	68.2	31.27	PASS	Vertical	PK
6	39721.1 488	-11.12	46.37	35.25	68.2	32.95	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Chenjun	Test_Date	2024\11\13
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19222.7 289	-24.29	62.42	38.13	68.2	30.07	PASS	Horizontal	PK
2	20869.5 948	-24.50	62.10	37.60	68.2	30.6	PASS	Horizontal	PK
3	24808.2 723	-19.80	58.07	38.27	68.2	29.93	PASS	Horizontal	PK
4	29203.2 881	-20.27	59.31	39.04	68.2	29.16	PASS	Horizontal	PK
5	32704.0 282	-16.42	54.13	37.71	68.2	30.49	PASS	Horizontal	PK
6	37146.8 859	-15.19	50.96	35.77	68.2	32.43	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Chenjun	Test_Date	2024\11\13
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19117.8 447	-24.41	63.70	39.29	68.2	28.91	PASS	Vertical	PK
2	21055.4 422	-24.74	61.62	36.88	68.2	31.32	PASS	Vertical	PK
3	23733.6 693	-21.25	58.79	37.54	68.2	30.66	PASS	Vertical	PK
4	27206.8 083	-20.46	58.70	38.24	68.2	29.96	PASS	Vertical	PK
5	31323.0 529	-17.59	55.96	38.37	68.2	29.83	PASS	Vertical	PK
6	36271.0 108	-14.93	51.53	36.60	68.2	31.6	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Chenjun	Test_Date	2024\11\13
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19256.7 703	-24.23	62.45	38.22	68.2	29.98	PASS	Horizontal	PK
2	21188.8 476	-24.64	63.04	38.40	68.2	29.8	PASS	Horizontal	PK
3	24431.9 773	-19.82	58.32	38.50	68.2	29.7	PASS	Horizontal	PK
4	26901.3 561	-20.05	59.14	39.09	68.2	29.11	PASS	Horizontal	PK
5	29962.3 185	-19.61	57.98	38.37	68.2	29.83	PASS	Horizontal	PK
6	33538.5 015	-15.61	53.78	38.17	68.2	30.03	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Chenjun	Test_Date	2024\11\13
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19427.8 971	-23.94	62.26	38.32	68.2	29.88	PASS	Vertical	PK
2	23121.8 449	-24.07	60.27	36.20	68.2	32	PASS	Vertical	PK
3	27070.6 428	-20.29	58.34	38.05	68.2	30.15	PASS	Vertical	PK
4	29674.3 47	-19.39	57.64	38.25	68.2	29.95	PASS	Vertical	PK
5	34034.4 014	-16.12	52.97	36.85	68.2	31.35	PASS	Vertical	PK
6	38634.5 854	-12.14	49.80	37.66	68.2	30.54	PASS	Vertical	PK