EMTEK
Access to the World

TEST REPORT

Product Name	:	RF Wireless remote controller
Model Number	:	KCA-RC10MR
FCC ID	:	2AYBO-KCARC10MR

Prepared for	:	JVCKENWOOD USA Corporation
Address	:	4001 Worsham Avenue, Long Beach, CA 90808, U.S.A.
Prepared by	:	EMTEK (NINGBO) CO., LTD.
Address	:	No. 8, Building 8, Lane 216, Qingyi Road, Ningbo Hi-Tech Zone, Ningbo, Zhejiang, China Tel: +86-574-27907998 Fax: +86-574-27721538

Report Number	:	ENB2401110055W00402R
Date(s) of Tests	:	January 11, 2024 to March 28, 2024
Date of Issue	:	March 14, 2025

TABLE OF CONTENT

Test Report Description

Applicant	:	JVCKENWOOD USA Corporation
Address	:	4001 Worsham Avenue, Long Beach, CA 90808, U.S.A.
Manufacturer	:	Ningbo Ultimate Acoustics Co.,Ltd
Address	:	126# Huiyuan Road Fenghua Ningbo China
EUT	:	RF Wireless remote controller
Model Name	:	KCA-RC10MR
Trademark	:	N/A

The device described above is tested by EMTEK (NINGBO) CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report shows the EUT to be technically compliant with the FCC 1.1310 and KDB 447498 D01 General RF Exposure Guidance v07 requirements. The test results are contained in this report and EMTEK (NINGBO) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests.

This report applies to above tested sample only and shall not be reproduced in part without written approval of EMTEK (NINGBO) CO., LTD.

Date of Test : January 11, 2024 to March 28, 2024

Prepared by : June Gao/Engineer

Reviewer : Vinay/Supervisor

Approved & Authorized Signer : Tony Wei/Manager

EMTEK(NINGBO) CO., LTD. TESTING

Modified Information

Version	Report No.	Revision Date	Summary
/	ENB2401110055W00402R	/	Original Report

1. Facilities And Accreditations

1.1. Test Facility

All measurement facilities used to collect the measurement data are located at

No. 8, Building 8, Lane 216, Qingyi Road, Ningbo Hi-Tech Zone, Ningbo, Zhejiang, China
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 32.

1.2. LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : **Accredited by CNAS**
The Certificate Registration Number is L6666.
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)

Designation by FCC
Designation Number: CN1354
Test Firm Registration Number: 427606

Accredited by A2LA
The Certificate Number is 4321.03.
The certificate is valid until May 31, 2025

Designation by Industry Canada
The Conformity Assessment Body Identifier is CN0114

Name of Firm : EMTEK (NINGBO) CO., LTD.

Site Location : No. 8, Building 8, Lane 216, Qingyi Road, Hi-Tech Zone, Ningbo, Zhejiang, China

2. General Product Information

Characteristics	Description
Product:	RF Wireless remote controller
Model Number:	KCA-RC10MR
Sample Number:	ENB2401110055W004-1-1
Modulation:	FSK modulation
Operating Frequency:	433.92MHz
Number of Channels:	1 channel
Max Transmit Power:	81.07 dBuV/m
Antenna Type :	PCB Antenna
Antenna Gain:	0.0 dBi
Power supply:	DC 3V
Temperature Range:	-20°C ~ +60°C
Date of Received:	January 11, 2024

Note: for more details, please refer to the User's manual of the EUT.

3. Limit

According to §15.249(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.
According to KDB447498 D01 General RF Exposure Guidance V07
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
f(GHz) is the RF channel transmit frequency in GHz;
Power and distance are rounded to the nearest mW and mm before calculation;
The result is rounded to one decimal place for comparison;
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
We use 5mm as separation distance to calculate.

4. Test Results

Maximum measured transmitter power:
EIRP=E+20log(d)-104.7=81.07+9.54-104.7=-14.09 dBm

Transmit Frequency (MHz)	Mode	EIRP Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
433.92	FSK	-14.09 dBm	-14.0	0.01	3

Conclusion:
For the max result : 0.01≤ 3.0 for 1-g SAR extremity SAR.

*** End of Report ***

声 明
Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效；
   This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制；
   This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；
   The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；
   The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；
   The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；
   Objections shall be raised within 20 days from the date receiving the report.