

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC TEST REPORT**FCC Part 22/Part 24/Part 27****Report Reference No.....: GTS20201211011-1-4****FCC ID.....: 2AYCA-LQM78N**

Compiled by

(position+printed name+signature)..: File administrators Peter Xiao

Supervised by

(position+printed name+signature)..: Test Engineer Moon Tan

Approved by

(position+printed name+signature)..: Manager Simon Hu

Date of issue.....: Dec.24, 2020

Representative Laboratory Name ..: Shenzhen Global Test Service Co.,Ltd.

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name: Caxon Technology

Address: Pedro Ruiz 1058 int. 06 cercado Chiclayo Lambayeque Peru

Test specification

Standard: **FCC CFR Title 47 Part 2, Part 22H, Part 24E, Part 27**
TIA-603-E March 2016
FCC KDB971168 D01 Power Meas License Digital Systems v03r01

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd..

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Tablet PC

Trade Mark: Caxon Technology

Manufacturer: Shenzhen Longqi Technology Co., Ltd

Model/Type reference.....: LQ-M7863

Listed Models: LQ-M1063,LQ-M8863,LQ-M1062,LQ-M7765,LQ-M7832

Modulation Type: QPSK, 16QAM

Hardware Version: V1.1

Software Version: V1.0.10

Rating: DC 3.7V by battery
Recharged by DC 5.0V/2.0A

Result.....: **PASS**

TEST REPORT

Test Report No. :	GTS20201211011-1-4	Dec.24, 2020
		Date of issue

Equipment under Test : Tablet PC

Model /Type : LQ-M7863

Listed model : LQ-M1063,LQ-M8863,LQ-M1062,LQ-M7765,LQ-M7832

Applicant : **Caxon Technology**

Address : Pedro Ruiz 1058 int. 06 cercado Chiclayo Lambayeque Peru

Manufacturer : **Shenzhen Longqi Technology Co., Ltd**

Address : 16-701, Yayuan Road, Bantian, Longgang Dist. Shenzhen, Guangdong, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 4.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 SUMMARY	4
1.1 TEST STANDARDS	4
2 GENERAL INFORMATION.....	5
2.1 General Remarks	5
2.2 Product Description	5
2.3 Equipment Under Test	7
2.4 Short description of the Equipment under Test (EUT).....	7
2.5 Environmental conditions	7
2.6 Description of Test Modes	7
2.7 Block Diagram of Test Setup	7
2.8 Special Accessories	7
2.9 Related Submittal(s) / Grant (s)	7
2.10 Modifications	7
3 TEST ENVIRONMENT.....	8
3.1 Address of the test laboratory	8
3.2 Test Facility	8
3.3 Environmental conditions	8
3.4 Statement of the measurement uncertainty	8
3.5 Test Description	9
3.6 Equipments Used during the Test.....	10
4 TEST CONDITIONS AND RESULTS	11
4.1 Output Power	11
4.2 Peak-to-Average Ratio (PAR)	26
4.3 Occupied Bandwidth and Emission Bandwidth.....	31
4.4 Band Edge compliance	36
4.5 Spurious Emission.....	40
4.6 Frequency Stability under Temperature & Voltage Variations	66
5 TEST SETUP PHOTOS OF THE EUT.....	71
6 EXTERNAL AND INTERNAL PHOTOS OF THE EUT	71

1 SUMMARY

1.1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22](#) : PUBLIC MOBILE SERVICES

[FCC Part 24](#) : PERSONAL COMMUNICATIONS SERVICES

[FCC Part 27](#) : MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

[TIA-603-E March 2016](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): - Unintentional Radiators

[FCC Part 2](#): FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[FCC KDB971168 D01](#) Power Meas License Digital Systems v03r01

[ANSI C63.4:2014](#): Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2 GENERAL INFORMATION

2.1 General Remarks

Date of receipt of test sample	:	Dec.04, 2020
Testing commenced on	:	Dec.04, 2020
Testing concluded on	:	Dec.24, 2020

2.2 Product Description

Product Name	Tablet PC
Trade Mark	Caxon Technology
Model/Type reference	LQ-M7863
List Models	LQ-M1063,LQ-M8863,LQ-M1062,LQ-M7765,LQ-M7832
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name is different , So no additional models were tested.
Power supply:	DC 3.7V by battery Recharged by DC 5.0V/2.0A
Sample ID	GTS20201211011-1 -1#
2G	
Support Band	GSM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900
Release Version	R99
GPRS Class	Class 12
EGPRS Class	Class 12
GSM/EDGE/GPRS Power Class	GSM850:Power Class 4/ PCS1900:Power Class 1
GPRS/EDGE Multislot Class	GPRS/EDGE: Multi-slot Class 12
Type Of Modulation	GMSK for GSM/GPRS; GMSK/8PSK for EGPRS
Antenna Description	FPC Antenna; -2.50dBi (max.) For GSM 850; -2.40dBi (max.) For DCS 1900;
3G	
UMTS Operation Frequency Band	UMTS FDD Band 2(1850 MHz -1910MHz) UMTS FDD Band 5(824 MHz -849MHz)
WCDMA Release Version	R6
HSDPA Release Version	Release 6
Modulation Type	QPSK for UMTS
Antenna Description	FPC Antenna; -2.20dBi (max.) For WCDMA Band 2; -2.50dBi (max.) For WCDMA Band 5;
LTE	
LTE Operation Frequency Band	E-UTRA Band 2(1850 MHz -1910MHz) E-UTRA Band 5(824 MHz -849MHz) E-UTRA Band 7(2500 MHz -2570MHz)
LTE Release Version	R9
Type Of Modulation	QPSK/16QAM
Antenna Description	FPC Antenna; -2.20dBi (max.) For LTE Band 2;

	-2.50dBi (max.) For LTE Band 5; -2.70dBi (max.) For LTE Band 7;
Bluetooth	
Operation frequency	2402-2480MHz
Channel Number	79 channels for Bluetooth (DSS) 40 channels for Bluetooth (DTS)
Channel Spacing	1MHz for Bluetooth (DSS) 2MHz for Bluetooth (DTS)
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK for Bluetooth (DSS) GFSK for Bluetooth (DTS)
WIFI(2.4G Band)	
Frequency Range	2412MHz ~ 2462MHz
Channel Spacing	5MHz
Channel Number	11 Channel for 20MHz bandwidth(2412~2462MHz)
Modulation Type	802.11b: DSSS; 802.11g/n: OFDM
Antenna Description	FPC Antenna,1.50dBi(Max.) for 2.4G Band

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐	230V / 50 Hz	☐	120V / 60Hz
		☐	12 V DC	☐	24 V DC
		☒	Other (specified in blank below)		

2.4 Short description of the Equipment under Test (EUT)

This is a GSM&WCDMA+LTE Control and Navigation System. For more details, refer to the user's manual of the EUT.

2.5 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25℃
Relative Humidity:	55 %
Air Pressure:	101 kPa


2.6 Description of Test Modes

The EUT has been tested under typical operating condition. The CMW500 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

Note:

1. For the ERP/EIRP and radiated emission test, every axis (X, Y, Z) was verified, and show the worst result on this report.
2. Test method and refer to 3GPP TS136521.

2.7 Block Diagram of Test Setup



2.8 Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN JC-HICI TECHNOLOGY CO LTD	Adapter	JC-0060	--	SDOC

2.9 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with of the FCC Part 22, Part 24, Part 27, Part 90 Rules.

2.10 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong,China.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is165725.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.5 Test Description

Test Item	Section in CFR 47	Test Sample	Result
RF Output Power	Part 2.1046 Part 22.913(a) Part 24.232(c) Part 27.50	GTS20201211011-1 -1#	Pass
Peak-to-Average Ratio	Part 2.1046 Part 24.232 Part 27.50(d)	GTS20201211011-1 -1#	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049	GTS20201211011-1 -1#	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 Part 24.238 Part 27.53	GTS20201211011-1 -1#	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917(b) Part 24.238 Part 27.53	GTS20201211011-1 -1#	Pass
Out of band emission, Band Edge	Part 2.1051 Part 22.917(b) Part 24.238 Part 27.53	GTS20201211011-1 -1#	Pass
Frequency stability	Part 2.1055 Part 22.355 Part 24.235 Part 27.54	GTS20201211011-1 -1#	Pass

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Note 1 – Test results inside test report;
4. Note 2 – Test results in other test report (SAR Report).
5. We tested all test mode and recorded worst case in report

3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2020/09/19	2021/09/18
LISN	R&S	ESH2-Z5	893606/008	2020/09/19	2021/09/18
EMI Test Receiver	R&S	ESPI3	101841-cd	2020/09/19	2021/09/18
EMI Test Receiver	R&S	ESCI7	101102	2020/09/19	2021/09/18
Spectrum Analyzer	Agilent	N9020A	MY48010425	2020/09/19	2021/09/18
Radio Communication Tester	Rohde&Schwarz	CMW500	107519	2020/09/19	2021/09/18
Spectrum Analyzer	R&S	FSV40	100019	2020/09/19	2021/09/18
Vector Signal generator	Agilent	N5181A	MY49060502	2020/09/19	2021/09/18
Signal generator	Agilent	E4421B	3610AO1069	2020/09/19	2021/09/18
Climate Chamber	ESPEC	EL-10KA	A20120523	2020/09/19	2021/09/18
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2020/09/19	2021/09/18
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	15006	2020/10/11	2021/10/10
Bilog Antenna	Schwarzbeck	VULB9163	000976	2020/05/26	2021/05/25
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2020/09/19	2021/09/18
Amplifier	Schwarzbeck	BBV 9743	#202	2020/09/19	2021/09/18
Amplifier	Schwarzbeck	BBV9179	9719-025	2020/09/19	2021/09/18
Amplifier	EMCI	EMC051845B	980355	2020/09/19	2021/09/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2020/09/19	2021/09/18
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	KL142031	2020/09/19	2021/09/18
High-Pass Filter	K&L	41H10-1375/U12750-O/O	KL142032	2020/09/19	2021/09/18
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2020/09/19	2021/09/18
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2020/09/19	2021/09/18
Data acquisition card	Agilent	U2531A	TW53323507	2020/09/19	2021/09/18
Power Sensor	Agilent	U2021XA	MY5365004	2020/09/19	2021/09/18
Test Control Unit	Tonscend	JS0806-1	178060067	2020/06/20	2021/06/19
Automated filter bank	Tonscend	JS0806-F	19F8060177	2020/06/20	2021/06/19
EMI Test Software	Tonscend	JS1120-1	Ver 2.6.8.0518	/	/
EMI Test Software	Tonscend	JS1120-3	Ver 2.5.77.0418	/	/
EMI Test Software	Tonscend	JS32-CE	Ver 2.5	/	/
EMI Test Software	Tonscend	JS32-RE	Ver 2.5.1.8	/	/

Note: The Cal.Interval was one year.

4 TEST CONDITIONS AND RESULTS

4.1 Output Power


LIMIT

The ERP of mobile transmitters must not exceed 7 Watts for GSM&WCDMA/LTE Band 5.


The EIRP of mobile transmitters must not exceed 2 Watts for GSM&WCDMA/LTE Band 2, LTE Band 7

TEST CONFIGURATION

Conducted Power Measurement



Radiated Power Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- EUT Communicate with CMW500, then select a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

Radiated Power Measurement:

- The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- The output of the test antenna shall be connected to the measuring receiver.
- The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.

- g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. Test site anechoic chamber refer to ANSI C63.26.

TEST RESULTS

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

Conducted Measurement:

GSM 850		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8
GSM		32.63	32.42	32.62
GPRS (GMSK)	1TX slot	32.61	32.58	32.60
	2TX slot	31.51	31.49	31.48
	3TX slot	30.01	29.98	29.99
	4TX slot	29.02	29.02	28.99
EDGE (8PSK)	1TX slot	28.02	28.00	28.01
	2TX slot	26.97	26.98	27.00
	3TX slot	24.51	24.52	24.52
	4TX slot	22.99	23.02	22.99

GSM 1900		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8
GSM		30.15	29.75	29.81
GPRS (GMSK)	1TX slot	29.61	29.58	29.60
	2TX slot	28.03	27.98	27.98
	3TX slot	27.00	27.01	27.01
	4TX slot	26.00	26.03	26.02
EDGE (8PSK)	1TX slot	25.01	25.02	25.03
	2TX slot	24.01	23.99	24.02
	3TX slot	23.01	22.97	23.02
	4TX slot	21.99	21.98	22.00

WCDMA Band II

Mode	3GPP Sub Test	Low Channel	Middle Channel	High Channel
		Ave.Power (dBm)	Ave.Power (dBm)	Ave. Power (dBm)
Rel 99	1	23.62	23.59	23.50
HSDPA	1	23.43	23.49	23.49
	2	22.60	22.51	22.56
	3	21.36	21.42	21.43
	4	20.57	20.53	20.59
HSUPA	1	21.63	21.68	21.53
	2	21.01	21.16	21.18
	3	20.28	20.22	20.16
	4	19.61	19.63	19.69
	5	19.18	19.04	19.13
HSPA+	1	18.62	18.51	18.66

WCDMA Band V

Mode	3GPP Sub Test	Low Channel	Middle Channel	High Channel
		Ave.Power (dBm)	Ave.Power (dBm)	Ave. Power (dBm)
Rel 99	1	23.54	23.51	23.49
HSDPA	1	23.56	23.47	23.42
	2	22.59	22.66	22.58
	3	21.40	21.34	21.42
	4	20.66	20.62	20.54
HSUPA	1	21.69	21.68	21.65
	2	21.07	21.13	21.10
	3	20.10	20.11	20.12
	4	19.67	19.68	19.70
	5	19.00	19.02	19.04
HSPA+	1	18.58	18.53	18.60

LTE FDD Band 2				
TX Channel Bandwidth	RB Size/Offset	Frequency (MHz)	Average Power [dBm]	
			QPSK	16QAM
1.4 MHz	1 RB low	1850.70	23.26	22.03
		1880.00	23.44	21.57
		1909.30	22.88	21.46
	1 RB high	1850.70	23.44	21.66
		1880.00	23.44	22.26
		1909.30	23.45	22.26
	50% RB mid	1850.70	23.49	22.10
		1880.00	23.34	21.64
		1909.30	22.83	21.48
	100% RB	1850.70	23.48	21.75
		1880.00	23.25	21.45
		1909.30	23.15	21.55
3 MHz	1 RB low	1851.50	23.27	21.65
		1880.00	23.36	21.34
		1908.50	22.76	21.76
	1 RB high	1851.50	23.47	21.86
		1880.00	23.04	21.31
		1908.50	23.40	21.69
	50% RB mid	1851.50	22.58	22.19
		1880.00	23.50	22.23
		1908.50	23.28	21.46
	100% RB	1851.50	21.55	20.69
		1880.00	21.60	20.97
		1908.50	22.45	21.14
5 MHz	1 RB low	1852.50	21.60	20.98
		1880.00	22.50	20.75
		1907.50	21.68	20.33
	1 RB high	1852.50	22.17	20.65
		1880.00	22.36	20.43
		1907.50	22.00	20.74
	50% RB mid	1852.50	22.20	20.88
		1880.00	22.29	20.50
		1907.50	22.49	20.32
	100% RB	1852.50	22.42	21.04
		1880.00	22.17	20.80
		1907.50	22.20	21.14
10 MHz	1 RB low	1855.00	21.57	20.35
		1880.00	22.29	20.66
		1905.00	21.77	20.35
	1 RB high	1855.00	21.68	21.06
		1880.00	22.35	21.22
		1905.00	22.29	20.44
	50% RB mid	1855.00	22.36	20.67
		1880.00	22.27	20.69
		1905.00	22.09	20.79
	100% RB	1855.00	21.51	20.88
		1880.00	22.28	20.62
		1905.00	22.14	21.27
15 MHz	1 RB low	1857.50	22.44	20.30
		1880.00	22.25	21.16
		1902.50	22.21	21.07
	1 RB high	1857.50	22.48	20.68
		1880.00	22.30	21.07
		1902.50	22.07	21.28
	50% RB mid	1857.50	22.40	21.30
		1880.00	22.30	20.32
		1902.50	21.69	20.88

20 MHz	100% RB	1857.50	22.38	20.81
		1880.00	22.33	20.59
		1902.50	22.37	20.60
	1 RB low	1860.00	22.05	20.39
		1880.00	22.40	20.78
		1900.00	21.76	20.95
	1 RB high	1860.00	21.68	20.88
		1880.00	21.73	21.17
		1900.00	22.38	20.86
	50% RB mid	1860.00	21.55	21.03
		1880.00	22.30	20.42
		1900.00	21.88	20.65
	100% RB	1860.00	21.75	20.51
		1880.00	22.24	20.39
		1900.00	21.75	21.08

LTE FDD Band 5				
TX Channel Bandwidth	RB Size/Offset	Frequency (MHz)	Average Power [dBm]	
			QPSK	16QAM
1.4 MHz	1 RB low	824.70	22.51	21.40
		836.50	22.64	21.78
		848.30	22.68	21.54
	1 RB high	824.70	23.27	21.29
		836.50	22.89	21.18
		848.30	22.48	21.98
	50% RB mid	824.70	22.51	21.15
		836.50	22.86	21.19
		848.30	22.96	21.11
	100% RB	824.70	23.08	21.26
		836.50	22.32	21.48
		848.30	23.14	21.12
3 MHz	1 RB low	825.50	23.01	21.87
		836.50	22.68	21.41
		847.50	22.99	21.75
	1 RB high	825.50	22.45	21.23
		836.50	22.36	21.65
		847.50	22.65	21.57
	50% RB mid	825.50	22.65	21.65
		836.50	23.16	21.34
		847.50	22.32	21.48
	100% RB	825.50	21.87	20.46
		836.50	21.52	20.11
		847.50	21.70	20.01
5 MHz	1 RB low	826.50	21.25	20.67
		836.50	21.67	20.78
		846.50	21.58	20.49
	1 RB high	826.50	21.46	20.80
		836.50	21.26	20.61
		846.50	21.28	20.25
	50% RB mid	826.50	21.55	20.13
		836.50	22.14	20.19
		846.50	21.56	20.36
	100% RB	826.50	22.08	20.76
		836.50	21.32	20.46
		846.50	21.72	20.61
10 MHz	1 RB low	829.00	21.61	20.33
		836.50	21.21	20.32
		844.00	21.79	20.75
	1 RB high	829.00	21.72	20.14
		836.50	22.08	20.33
		844.00	22.19	20.70

	50% RB mid	829.00	21.27	20.38
		836.50	21.29	20.26
		844.00	21.75	20.66
	100% RB	829.00	21.70	20.63
		836.50	21.78	20.88
		844.00	22.33	20.10

LTE FDD Band 7				
TX Channel Bandwidth	RB Size/Offset	Frequency (MHz)	Average Power [dBm]	
			QPSK	16QAM
5 MHz	1 RB low	2502.5	23.29	21.59
		2535	22.93	21.81
		2567.5	23.29	21.93
	1 RB high	2502.5	22.78	21.32
		2535	22.97	21.84
		2567.5	22.46	21.52
	50% RB mid	2502.5	22.55	22.00
		2535	22.97	21.53
		2567.5	23.05	21.71
	100% RB	2502.5	22.82	21.70
		2535	22.94	21.72
		2567.5	22.44	21.75
10 MHz	1 RB low	2505	22.70	22.05
		2535	23.23	21.83
		2565	23.22	21.29
	1 RB high	2505	22.75	22.09
		2535	22.89	21.72
		2565	22.56	21.50
	50% RB mid	2505	22.88	21.76
		2535	22.78	21.71
		2565	22.88	21.12
	100% RB	2505	22.14	20.84
		2535	21.57	20.40
		2565	21.75	20.49
15 MHz	1 RB low	2507.5	22.07	20.98
		2535	21.42	20.28
		2562.5	21.42	20.96
	1 RB high	2507.5	21.65	20.04
		2535	22.11	20.20
		2562.5	21.36	20.92
	50% RB mid	2507.5	21.27	20.20
		2535	21.89	20.76
		2562.5	21.80	20.84
	100% RB	2507.5	21.50	20.74
		2535	21.99	20.49
		2562.5	21.85	20.76
20 MHz	1 RB low	2510	21.60	20.21
		2532.5	21.44	20.22
		2560	22.02	20.10
	1 RB high	2510	21.80	20.61
		2532.5	21.88	20.79
		2560	21.27	20.46
	50% RB mid	2510	21.49	20.84
		2532.5	21.32	20.23
		2560	21.57	20.59
	100% RB	2510	22.04	20.66
		2532.5	21.95	20.47
		2560	22.72	20.97

Radiated Measurement:

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7; recorded worst case for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7.
2. $ERP = EIRP - 2.15\text{dBi}$ as EIRP by subtracting the gain of the dipole.
3. The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
4. Absolute Level = Substituted Level - Cable loss + Antenna Gain
5. Margin = Limit-Absolute Level

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substitute d Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Low Channel								
824.20	H	86.44	20.45	1.65	0.58	21.52	38.45	16.93
824.20	V	84.90	20.07	1.65	0.58	21.14	38.45	17.31
GSM 850 Middle Channel								
836.60	H	86.88	19.67	1.59	0.65	20.61	38.45	17.84
836.60	V	84.96	20.87	1.59	0.65	21.81	38.45	16.64
GSM 850 High Channel								
848.80	H	87.13	19.39	1.53	0.71	20.21	38.45	18.24
848.80	V	85.78	19.38	1.53	0.71	20.20	38.45	18.25
EDGE 850 Low Channel								
824.20	H	85.79	21.31	1.65	0.58	22.38	38.45	16.07
824.20	V	84.65	21.16	1.65	0.58	22.23	38.45	16.22
EDGE 850 Middle Channel								
836.60	H	85.52	20.23	1.59	0.65	21.17	38.45	17.28
836.60	V	84.90	21.04	1.59	0.65	21.98	38.45	16.47
EDGE 850 High Channel								
848.80	H	85.83	19.77	1.53	0.71	20.59	38.45	17.86
848.80	V	84.26	20.69	1.53	0.71	21.51	38.45	16.94
GSM 1900 Low Channel								
1850.20	H	85.32	13.35	11.59	2.11	22.83	33.00	10.17
1850.20	V	85.35	11.89	11.59	2.11	21.37	33.00	11.63
GSM 1900 Middle Channel								
1880.00	H	86.25	13.24	11.56	2.14	22.66	33.00	10.34
1880.00	V	85.63	12.09	11.56	2.14	21.51	33.00	11.49
GSM 1900 High Channel								
1909.80	H	85.58	13.43	11.52	2.18	22.77	33.00	10.23
1909.80	V	85.62	11.40	11.52	2.18	20.74	33.00	12.26
EDGE 1900 Low Channel								
1850.20	H	85.41	13.63	11.59	2.11	23.11	33.00	9.89
1850.20	V	84.84	11.87	11.59	2.11	21.35	33.00	11.65
EDGE 1900 Middle Channel								
1880.00	H	85.97	13.26	11.56	2.14	22.68	33.00	10.32
1880.00	V	84.32	11.83	11.56	2.14	21.25	33.00	11.75
EDGE 1900 High Channel								
1909.80	H	85.97	13.91	11.52	2.18	23.25	33.00	9.75
1909.80	V	85.90	11.30	11.52	2.18	20.64	33.00	12.36

nnelFrequ ency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level EIRP/ERP (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss(dB)			
WCDMA Band II Low Channel								
1852.4	H	85.66	12.30	11.59	2.11	21.78	33.00	11.22
1852.4	V	84.37	12.07	11.59	2.11	21.55	33.00	11.45
WCDMA Band II Middle Channel								
1880.00	H	85.95	14.22	11.56	2.14	23.64	33.00	9.36
1880.00	V	84.58	12.36	11.56	2.14	21.78	33.00	11.22
WCDMA Band II High Channel								
1907.6	H	85.92	13.58	11.52	2.18	22.92	33.00	10.08
1907.6	V	85.58	12.40	11.52	2.18	21.74	33.00	11.26
WCDMA Band V Low Channel								
826.4	H	86.02	20.16	1.65	0.58	21.23	38.45	17.22
826.4	V	85.34	19.79	1.65	0.58	20.86	38.45	17.59
WCDMA Band V Middle Channel								
836.60	H	86.10	21.12	1.59	0.65	22.06	38.45	16.39
836.60	V	85.26	21.26	1.59	0.65	22.20	38.45	16.25
WCDMA Band V High Channel								
846.6	H	86.70	19.83	1.53	0.71	20.65	38.45	17.80
846.6	V	85.48	20.89	1.53	0.71	21.71	38.45	16.74

LTE Band 2

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level EIRP (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1850.70	1.4	QPSK	H	86.38	14.07	11.64	2.55	23.16	33.00	9.84
1850.70			V	84.32	13.21	11.64	2.55	22.29	33.00	10.71
1851.50	3		H	85.35	14.02	11.64	2.55	23.11	33.00	9.89
1851.50			V	85.31	11.63	11.64	2.55	20.72	33.00	12.28
1852.50	5		H	87.46	14.67	11.64	2.55	23.75	33.00	9.25
1852.50			V	86.38	12.25	11.64	2.55	21.34	33.00	11.66
1855.00	10		H	86.90	12.92	11.64	2.55	22.00	33.00	11.00
1855.00			V	84.31	12.18	11.64	2.55	21.26	33.00	11.74
1857.50	15		H	85.39	12.67	11.64	2.55	21.75	33.00	11.25
1857.50			V	86.36	13.15	11.64	2.55	22.24	33.00	10.76
1860.00	20		H	85.99	12.78	11.64	2.55	21.87	33.00	11.13
1860.00			V	87.16	14.07	11.64	2.55	23.16	33.00	9.84
1850.70	1.4	16QAM	H	85.41	13.33	11.64	2.55	22.42	33.00	10.58
1850.70			V	86.50	14.67	11.64	2.55	23.75	33.00	9.25
1851.50	3		H	87.14	12.49	11.64	2.55	21.57	33.00	11.43
1851.50			V	87.06	13.31	11.64	2.55	22.40	33.00	10.60
1852.50	5		H	86.10	11.47	11.64	2.55	20.55	33.00	12.45
1852.50			V	87.29	13.36	11.64	2.55	22.44	33.00	10.56
1855.00	10		H	87.53	11.51	11.64	2.55	20.60	33.00	12.40
1855.00			V	87.21	13.52	11.64	2.55	22.61	33.00	10.39
1857.50	15		H	86.51	12.58	11.64	2.55	21.67	33.00	11.33
1857.50			V	86.34	13.35	11.64	2.55	22.44	33.00	10.56
1860.00	20		H	86.58	13.62	11.64	2.55	22.71	33.00	10.29
1860.00			V	86.10	12.03	11.64	2.55	21.11	33.00	11.89

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level EIRP (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1880.000	1.4	QPSK	H	86.05	12.67	11.45	1.73	22.38	33.00	10.62
1880.000			V	84.63	11.85	11.45	1.73	21.56	33.00	11.44
1880.000	3		H	85.51	12.93	11.45	1.73	22.64	33.00	10.36
1880.000			V	84.28	12.97	11.45	1.73	22.68	33.00	10.32
1880.000	5		H	87.00	13.77	11.45	1.73	23.48	33.00	9.52
1880.000			V	85.79	12.10	11.45	1.73	21.81	33.00	11.19
1880.000	10		H	86.09	13.40	11.45	1.73	23.11	33.00	9.89
1880.000			V	84.42	13.43	11.45	1.73	23.14	33.00	9.86
1880.000	15		H	85.70	12.22	11.45	1.73	21.94	33.00	11.06
1880.000			V	87.10	13.73	11.45	1.73	23.44	33.00	9.56
1880.000	20		H	86.38	12.17	11.45	1.73	21.88	33.00	11.12
1880.000			V	86.87	13.93	11.45	1.73	23.64	33.00	9.36
1880.000	1.4	16QAM	H	87.03	11.42	11.45	1.73	21.13	33.00	11.87
1880.000			V	85.50	13.10	11.45	1.73	22.81	33.00	10.19
1880.000	3		H	86.41	13.57	11.45	1.73	23.28	33.00	9.72
1880.000			V	85.87	13.73	11.45	1.73	23.45	33.00	9.55
1880.000	5		H	87.40	13.06	11.45	1.73	22.78	33.00	10.22
1880.000			V	85.82	13.58	11.45	1.73	23.29	33.00	9.71
1880.000	10		H	87.31	13.14	11.45	1.73	22.85	33.00	10.15
1880.000			V	85.72	13.53	11.45	1.73	23.24	33.00	9.76
1880.000	15		H	86.43	12.87	11.45	1.73	22.59	33.00	10.41
1880.000			V	86.98	12.99	11.45	1.73	22.70	33.00	10.30
1880.000	20		H	87.50	13.23	11.45	1.73	22.94	33.00	10.06
1880.000			V	87.33	12.93	11.45	1.73	22.64	33.00	10.36

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level EIRP (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1909.30	1.4	QPSK	H	86.41	13.42	11.68	1.95	23.15	33.00	9.85
1909.30			V	84.46	11.78	11.68	1.95	21.51	33.00	11.49
1908.50	3		H	85.22	14.18	11.68	1.95	23.91	33.00	9.09
1908.50			V	86.01	13.35	11.68	1.95	23.08	33.00	9.92
1907.50	5		H	85.77	13.71	11.68	1.95	23.44	33.00	9.56
1907.50			V	87.33	11.71	11.68	1.95	21.44	33.00	11.56
1905.00	10		H	86.65	12.84	11.68	1.95	22.57	33.00	10.43
1905.00			V	86.05	12.60	11.68	1.95	22.33	33.00	10.67
1902.50	15		H	86.98	11.99	11.68	1.95	21.71	33.00	11.29
1902.50			V	85.68	13.86	11.68	1.95	23.59	33.00	9.41
1900.00	20		H	85.49	12.83	11.68	1.95	22.56	33.00	10.44
1900.00			V	86.77	13.24	11.68	1.95	22.97	33.00	10.03
1909.30	1.4	16QAM	H	85.44	11.59	11.68	1.95	21.31	33.00	11.69
1909.30			V	87.15	13.04	11.68	1.95	22.77	33.00	10.23
1908.50	3		H	86.10	11.88	11.68	1.95	21.61	33.00	11.39
1908.50			V	86.74	13.45	11.68	1.95	23.18	33.00	9.82
1907.50	5		H	85.92	13.04	11.68	1.95	22.77	33.00	10.23
1907.50			V	87.06	12.37	11.68	1.95	22.10	33.00	10.90
1905.00	10		H	87.27	11.84	11.68	1.95	21.57	33.00	11.43
1905.00			V	87.17	13.19	11.68	1.95	22.92	33.00	10.08
1902.50	15		H	86.38	12.55	11.68	1.95	22.28	33.00	10.72
1902.50			V	87.34	12.64	11.68	1.95	22.37	33.00	10.63
1900.00	20		H	86.38	12.97	11.68	1.95	22.70	33.00	10.30
1900.00			V	86.42	11.45	11.68	1.95	21.18	33.00	11.82

LTE Band 5

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level ERP (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
824.70	1.4	QPSK	H	86.53	20.98	1.70	0.55	22.12	38.45	16.33
824.70			V	85.23	20.36	1.70	0.55	21.51	38.45	16.94
825.50	3		H	85.70	20.17	1.70	0.55	21.32	38.45	17.13
825.50			V	85.79	19.56	1.70	0.55	20.71	38.45	17.74
826.50	5		H	86.21	19.04	1.70	0.55	20.19	38.45	18.26
826.50			V	86.96	20.31	1.70	0.55	21.46	38.45	16.99
829.00	10		H	86.24	19.20	1.70	0.55	20.35	38.45	18.10
829.00			V	85.85	20.47	1.70	0.55	21.61	38.45	16.84
824.70	1.4	16QAM	H	86.56	20.38	1.70	0.55	21.53	38.45	16.92
824.70			V	86.43	20.23	1.70	0.55	21.38	38.45	17.07
825.50	3		H	85.86	19.49	1.70	0.55	20.64	38.45	17.81
825.50			V	86.84	19.05	1.70	0.55	20.19	38.45	18.26
826.50	5		H	85.50	20.78	1.70	0.55	21.93	38.45	16.52
826.50			V	86.41	19.30	1.70	0.55	20.44	38.45	18.01
829.00	10		H	85.69	19.88	1.70	0.55	21.02	38.45	17.43
829.00			V	86.65	19.68	1.70	0.55	20.83	38.45	17.62

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level ERP (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
836.50	1.4	QPSK	H	85.58	20.69	1.89	0.60	21.98	38.45	16.47
836.50			V	86.00	19.82	1.89	0.60	21.11	38.45	17.34
836.50	3		H	85.70	19.98	1.89	0.60	21.27	38.45	17.18
836.50			V	84.13	19.18	1.89	0.60	20.47	38.45	17.98
836.50	5		H	87.26	20.54	1.89	0.60	21.83	38.45	16.62
836.50			V	87.09	19.83	1.89	0.60	21.12	38.45	17.33
836.50	10		H	86.84	19.03	1.89	0.60	20.33	38.45	18.12
836.50			V	84.74	19.69	1.89	0.60	20.98	38.45	17.47
836.50	1.4	16QAM	H	85.98	19.93	1.89	0.60	21.22	38.45	17.23
836.50			V	85.85	19.21	1.89	0.60	20.50	38.45	17.95
836.50	3		H	85.85	20.87	1.89	0.60	22.16	38.45	16.29
836.50			V	86.16	20.08	1.89	0.60	21.37	38.45	17.08
836.50	5		H	85.70	19.00	1.89	0.60	20.29	38.45	18.16
836.50			V	85.45	20.93	1.89	0.60	22.22	38.45	16.23
836.50	10		H	86.54	19.51	1.89	0.60	20.80	38.45	17.65
836.50			V	87.26	20.93	1.89	0.60	22.23	38.45	16.22

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level ERP (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
848.30	1.4	QPSK	H	85.47	20.94	1.93	0.38	22.49	38.45	15.96
848.30			V	84.21	19.56	1.93	0.38	21.10	38.45	17.35
847.50	3		H	85.56	19.12	1.93	0.38	20.66	38.45	17.79
847.50			V	85.52	19.72	1.93	0.38	21.27	38.45	17.18
846.50	5		H	87.66	20.97	1.93	0.38	22.52	38.45	15.93
846.50			V	85.99	19.52	1.93	0.38	21.07	38.45	17.38
844.00	10		H	87.05	20.67	1.93	0.38	22.21	38.45	16.24
844.00			V	85.13	19.18	1.93	0.38	20.73	38.45	17.72
848.30	1.4	16QAM	H	86.52	19.47	1.93	0.38	21.02	38.45	17.43
848.30			V	85.61	19.21	1.93	0.38	20.76	38.45	17.69
847.50	3		H	86.24	19.14	1.93	0.38	20.69	38.45	17.76
847.50			V	86.28	20.39	1.93	0.38	21.93	38.45	16.52
846.50	5		H	86.20	19.23	1.93	0.38	20.77	38.45	17.68
846.50			V	87.28	19.49	1.93	0.38	21.04	38.45	17.41
844.00	10		H	86.22	19.71	1.93	0.38	21.26	38.45	17.19
844.00			V	86.52	20.84	1.93	0.38	22.39	38.45	16.06

LTE Band 7

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substitut ed Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
2502.50	5	QPSK	H	85.96	12.86	11.59	1.77	22.68	30.00	7.32
2502.50			V	84.28	12.02	11.59	1.77	21.84	30.00	8.16
2505.00	10		H	85.94	13.00	11.59	1.77	22.81	30.00	7.19
2505.00			V	85.63	13.01	11.59	1.77	22.83	30.00	7.17
2507.50	15		H	86.90	14.43	11.59	1.77	24.25	30.00	5.75
2507.50			V	87.05	12.32	11.59	1.77	22.14	30.00	7.86
2510.00	20		H	85.61	12.37	11.59	1.77	22.19	30.00	7.81
2510.00			V	84.89	13.67	11.59	1.77	23.48	30.00	6.52
2502.50	5	16QAM	H	86.83	12.29	11.59	1.77	22.11	30.00	7.89
2502.50			V	87.09	14.19	11.59	1.77	24.01	30.00	5.99
2505.00	10		H	86.09	13.21	11.59	1.77	23.03	30.00	6.97
2505.00			V	86.67	12.61	11.59	1.77	22.43	30.00	7.57
2507.50	15		H	87.13	12.18	11.59	1.77	21.99	30.00	8.01
2507.50			V	85.62	13.35	11.59	1.77	23.16	30.00	6.84
2510.00	20		H	85.45	12.81	11.59	1.77	22.63	30.00	7.37
2510.00			V	86.88	12.98	11.59	1.77	22.80	30.00	7.20

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substitut ed Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
2535.00	5	QPSK	H	86.40	13.57	11.06	2.52	22.11	30.00	7.89
2535.00			V	84.61	12.57	11.06	2.52	21.11	30.00	8.89
2535.00	10		H	86.90	13.60	11.06	2.52	22.14	30.00	7.86
2535.00			V	85.01	11.54	11.06	2.52	20.08	30.00	9.92
2535.00	15		H	86.86	14.42	11.06	2.52	22.96	30.00	7.04
2535.00			V	85.38	11.94	11.06	2.52	20.48	30.00	9.52
2535.00	20		H	86.25	13.05	11.06	2.52	21.59	30.00	8.41
2535.00			V	84.84	13.19	11.06	2.52	21.72	30.00	8.28
2535.00	5	16QAM	H	86.89	12.04	11.06	2.52	20.58	30.00	9.42
2535.00			V	85.87	13.19	11.06	2.52	21.73	30.00	8.27
2535.00	10		H	86.43	12.77	11.06	2.52	21.31	30.00	8.69
2535.00			V	87.17	13.85	11.06	2.52	22.39	30.00	7.61
2535.00	15		H	87.00	11.60	11.06	2.52	20.14	30.00	9.86
2535.00			V	86.78	12.88	11.06	2.52	21.42	30.00	8.58
2535.00	20		H	87.36	13.14	11.06	2.52	21.68	30.00	8.32
2535.00			V	85.63	12.56	11.06	2.52	21.10	30.00	8.90


Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substitut ed Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
2567.50	5	QPSK	H	86.21	13.21	11.26	2.64	21.83	30.00	8.17
2567.50			V	84.63	13.11	11.26	2.64	21.73	30.00	8.27
2565.00	10		H	86.79	12.93	11.26	2.64	21.56	30.00	8.44
2565.00			V	84.53	12.33	11.26	2.64	20.95	30.00	9.05
2562.50	15		H	86.90	14.29	11.26	2.64	22.91	30.00	7.09
2562.50			V	85.82	12.54	11.26	2.64	21.16	30.00	8.84
2560.00	20		H	85.27	12.90	11.26	2.64	21.52	30.00	8.48
2560.00			V	84.56	13.89	11.26	2.64	22.51	30.00	7.49
2567.50	5	16QAM	H	86.22	11.82	11.26	2.64	20.44	30.00	9.56
2567.50			V	85.64	12.72	11.26	2.64	21.35	30.00	8.65
2565.00	10		H	86.87	11.52	11.26	2.64	20.14	30.00	9.86
2565.00			V	86.73	13.60	11.26	2.64	22.23	30.00	7.77
2562.50	15		H	86.56	12.73	11.26	2.64	21.35	30.00	8.65
2562.50			V	85.64	13.89	11.26	2.64	22.52	30.00	7.48
2560.00	20		H	86.58	13.44	11.26	2.64	22.07	30.00	7.93
2560.00			V	86.12	12.74	11.26	2.64	21.37	30.00	8.63

4.2 Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
 - 1). for continuous transmissions, set to 1 ms,
 - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

Remark:

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7; recorded worst case for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II , WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7.

1. For E-UTRA Band 2, please refer to Appendix Band 2: Section A;
2. For E-UTRA Band 5, please refer to Appendix Band 5: Section A;
3. For E-UTRA Band 7, please refer to Appendix Band 7: Section A;

GSM:


Test Mode	Channel	Frequency (MHz)	PAPR Value (dB)	Limits (dB)	Verdict
GSM/TM1/GSM850	128	824.2	8.67	13.0	PASS
	190	836.6	9.91	13.0	
	251	848.8	8.64	13.0	
GSM/TM3/EDGE850	128	824.2	7.80	13.0	PASS
	190	836.6	8.09	13.0	
	251	848.8	4.64	13.0	
GSM/TM1/GSM1900	512	1850.2	9.97	13.0	PASS
	661	1880.0	8.75	13.0	
	810	1909.8	8.96	13.0	
GSM/TM3/EDGE1900	512	1850.2	8.75	13.0	PASS
	661	1880.0	8.75	13.0	
	810	1909.8	8.75	13.0	

WCDMA :


Test Mode	Channel	Frequency (MHz)	PAPR Value (dB)	Limits (dB)	Verdict
UMTS/TM1/ WCDMA Band II	9262	1852.4	2.99	13.0	PASS
	9400	1880.0	2.09	13.0	PASS
	9538	1907.6	2.14	13.0	PASS
UMTS/TM1/ WCDMA Band V	4132	826.4	2.96	13.0	PASS
	4182	836.4	3.10	13.0	PASS
	4233	846.6	3.07	13.0	PASS

Peak-to-Average Ratio (PAR)


GSM/TM1/GSM850




GSM/TM3/EDGE850




Channel 128/ 824.2 MHz




Channel 128/ 824.2 MHz



Channel 190/ 836.6 MHz



Channel 190/ 836.6 MHz




Channel 251/ 848.8 MHz


Channel 251/ 848.8 MHz

Peak-to-Average Ratio (PAR)


GSM/TM1/GSM1900




GSM/TM3/EDGE1900




Channel 512/ 1850.2 MHz




Channel 512/ 1850.2 MHz



Channel 661/ 1880 MHz









Channel 661/ 1880 MHz



Channel 810/ 1909.8 MHz

Channel 810/ 1909.8 MHz

Peak-to-Average Ratio (PAR)**UMTS/TM1/ WCDMA Band II****UMTS/TM1/ WCDMA Band V****Channel 9262 / 1852.4 MHz****Channel 4132/ 826.4 MHz****Channel 9400 / 1880.0 MHz****Channel 4182/ 836.4 MHz****Channel 9538 / 1907.6 MHz****Channel 4233/ 846.6 MHz**


NOTE: We measured all modes and only recorded the worst case.

4.3 Occupied Bandwidth and Emission Bandwidth

LIMIT

FCC §2.1049, §22.917, §22.905, §24.238, §27.53 .

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded.

Set RBW was set to about 1% of emission BW, VBW $\geq$ 3 times RBW.

-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

Remark:

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7; recorded worst case for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II , WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7.

1. For E-UTRA Band 2, please refer to Appendix Band 2: Section B;
2. For E-UTRA Band 5, please refer to Appendix Band 5: Section B;
3. For E-UTRA Band 7, please refer to Appendix Band 7: Section B;

Test Mode	Channel	Frequency (MHz)	Occupied Bandwidth (99% BW) (KHz)	Emission Bandwidth (-26 dBc BW) (KHz)	Verdict
GSM/TM1 /GSM850	128	824.2	240.32	303.1	PASS
	190	836.6	240.07	298.8	PASS
	251	848.8	241.61	305.5	PASS
GSM/TM3 /EDGE850	128	824.2	239.96	300.2	PASS
	190	836.6	240.39	300.9	PASS
	251	848.8	240.69	305.6	PASS
GSM/TM1 /GSM1900	512	1850.2	240.95	302.9	PASS
	661	1880.0	241.72	303.3	PASS
	810	1909.8	241.44	305.5	PASS
GSM/TM3 /EDGE1900	512	1850.2	245.16	308.4	PASS
	661	1880.0	240.96	302.8	PASS
	810	1909.8	237.77	297.5	PASS


Test Mode	Channel	Frequency (MHz)	Occupied Bandwidth (99% BW) (MHz)	Emission Bandwidth (-26 dBc BW) (MHz)	Verdict
UMTS/TM1/ WCDMA Band II	9262	1852.4	4.1558	4.678	PASS
	9400	1880.0	4.1539	4.695	PASS
	9538	1907.6	4.1500	4.710	PASS
UMTS/TM1/ WCDMA Band V	4132	826.4	4.1292	4.680	PASS
	4182	836.4	4.1709	4.695	PASS
	4233	846.6	4.1435	4.674	PASS

Remark:

1. Test results including cable loss;
2. Please refer to following plots;

Occupied Bandwidth and Emission Bandwidth


GSM/TM1/GSM850



GSM/TM3/EDGE850



Channel 128 / 824.2 MHz



Channel 128 / 824.2 MHz




Channel 190 / 836.6 MHz




Channel 190 / 836.6 MHz



Channel 251 / 848.8 MHz



Channel 251 / 848.8 MHz




Occupied Bandwidth and Emission Bandwidth


GSM/TM1/GSM1900




GSM/TM3/ EDGE1900




Channel 512 / 1850.2 MHz




Channel 512 / 1850.2 MHz



Channel 661 / 1880.0MHz



Channel 661 / 1880.0MHz




Channel 810 / 1909.8 MHz



Channel 810 / 1909.8 MHz






NOTE: We measured all modes and only recorded the worst case.

4.4 Band Edge compliance

LIMIT

FCC § 2.1053, §22.917, § 24.238 and § 27.53.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest and highest channels for each band and different modulation.
5. Measure Band edge using RMS (Average) detector by spectrum

TEST RESULTS

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

Remark:

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7; recorded worst case for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II , WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7.


1. For E-UTRA Band 2, please refer to Appendix Band 2: Section C;
2. For E-UTRA Band 5, please refer to Appendix Band 5: Section C;
3. For E-UTRA Band 7, please refer to Appendix Band 7: Section C;





Test Mode	Channel	Frequency (MHz)	Band Edge Compliance (dBm)	Limits (dBm)	Verdict
GSM/TM1/GSM850	128	824.2	<-13dBm	-13dBm	PASS
	251	848.8	<-13dBm	-13dBm	
GSM/TM3/EDGE850	128	824.2	<-13dBm	-13dBm	PASS
	251	848.8	<-13dBm	-13dBm	
GSM/TM1/GSM1900	512	1850.2	<-13dBm	-13dBm	PASS
	810	1909.8	<-13dBm	-13dBm	
GSM/TM3/EDGE1900	512	1850.2	<-13dBm	-13dBm	PASS
	810	1909.8	<-13dBm	-13dBm	


Test Mode	Channel	Frequency (MHz)	Band Edge Compliance (dBm)	Limits (dBm)	Verdict
UMTS/TM1/WCDMA Band II	9262	1852.40	<-13dBm	-13dBm	PASS
	9538	1907.60	<-13dBm	-13dBm	
UMTS/TM1/WCDMA Band V	4132	826.40	<-13dBm	-13dBm	PASS
	4233	846.60	<-13dBm	-13dBm	

Remark:

1. Test results including cable loss;
2. Please refer to following plots;



Band-edge Compliance**GSM/TM1/GSM1900****GSM/TM3/EDGE1900****Channel 512 / 1850.2 MHz****Channel 512 / 1850.2 MHz****Channel 810 / 1909.8 MHz****Channel 810 / 1909.8 MHz**



NOTE: We measured all modes and only recorded the worst case.


4.5 Spurious Emission

LIMIT


FCC § 2.1053, §22.917, § 24.238 and § 27.53.

TEST CONFIGURATION

Conducted Spurious Measurement:



Radiated Spurious Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603-E

Conducted Spurious Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- EUT Communicate with CMW500, then select a channel for testing.
- Add a correction factor to the display of spectrum, and then test.
- The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.
- Please refer to following tables for test antenna conducted emissions.

Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBm)	Limits (dBm)	Verdict
GSM/TM1/GSM850	128	824.2	<-13dBm	-13dBm	PASS
	190	836.6	<-13dBm	-13dBm	
	251	848.8	<-13dBm	-13dBm	
GSM/TM3/EDGE850	128	824.2	<-13dBm	-13dBm	PASS
	190	836.6	<-13dBm	-13dBm	
	251	848.8	<-13dBm	-13dBm	
GSM/TM1/GSM1900	512	1850.2	<-13dBm	-13dBm	PASS
	661	1880.0	<-13dBm	-13dBm	
	810	1909.8	<-13dBm	-13dBm	
GSM/TM3/EDGE1900	512	1850.2	<-13dBm	-13dBm	PASS
	661	1880.0	<-13dBm	-13dBm	
	810	1909.8	<-13dBm	-13dBm	

Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBm)	Limits (dBm)	Verdict
UMTS/TM1/WCDMA Band II	9262	1852.4	<-13dBm	-13dBm	PASS
	9400	1880.0	<-13dBm	-13dBm	
	9538	1907.6	<-13dBm	-13dBm	
UMTS/TM1/WCDMA Band V	4132	826.4	<-13dBm	-13dBm	PASS
	4182	836.4	<-13dBm	-13dBm	
	4233	846.6	<-13dBm	-13dBm	

Working Frequency	Sub range (GHz)	RBW	VBW	Sweep time (s)
LTE FDD Band 2	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 5	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 7	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto

Remark:

1. Test results including cable loss;
2. Please refer to following plots;
3. Not reorded test plots from 9 KHz to 30 MHz as emission levels 20dB lower than emission limit;

Radiated Spurious Measurement:

- a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c. The output of the test antenna shall be connected to the measuring receiver.
- d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.
- r. Test site anechoic chamber refer to ANSI C63.4:2014.

TEST RESULTS

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

Conducted Measurement:

Remark:

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7; recorded worst case for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II , WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7.

1. For E-UTRA Band 2, please refer to Appendix Band 2: Section D;
2. For E-UTRA Band 5, please refer to Appendix Band 5: Section D;
3. For E-UTRA Band 7, please refer to Appendix Band 7: Section D;


Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBm)	Limits (dBm)	Verdict
GSM/TM1/GSM850	128	824.2	<-13dBm	-13dBm	PASS
	190	836.6	<-13dBm	-13dBm	
	251	848.8	<-13dBm	-13dBm	
GSM/TM3/EDGE850	128	824.2	<-13dBm	-13dBm	PASS
	190	836.6	<-13dBm	-13dBm	
	251	848.8	<-13dBm	-13dBm	
GSM/TM1/GSM1900	512	1850.2	<-13dBm	-13dBm	PASS
	661	1880.0	<-13dBm	-13dBm	
	810	1909.8	<-13dBm	-13dBm	
GSM/TM3/EDGE1900	512	1850.2	<-13dBm	-13dBm	PASS
	661	1880.0	<-13dBm	-13dBm	
	810	1909.8	<-13dBm	-13dBm	

Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBm)	Limits (dBm)	Verdict
UMTS/TM1/WCDMA Band II	9262	1852.4	<-13dBm	-13dBm	PASS
	9400	1880.0	<-13dBm	-13dBm	
	9538	1907.6	<-13dBm	-13dBm	
UMTS/TM1/WCDMA Band V	4132	826.4	<-13dBm	-13dBm	PASS
	4182	836.4	<-13dBm	-13dBm	
	4233	846.6	<-13dBm	-13dBm	


Working Frequency	Sub range (GHz)	RBW	VBW	Sweep time (s)
LTE FDD Band 2	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 5	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 7	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto

Remark:


1. Test results including cable loss;
2. Please refer to following plots;
3. We measured all modes and only recorded the worst case.

Spurious Emission on Antenna Port**GSM/TM1/GSM850****Channel 128 / 824.2 MHz**


Date: 18.DEC.2020 09:43:23

GSM/TM1/GSM850**Channel 190 / 836.6 MHz**

Date: 18.DEC.2020 09:44:58


30 MHz – 1000 MHz

Date: 18.DEC.2020 09:51:36


30 MHz – 1000 MHz

Date: 18.DEC.2020 09:51:51


1 GHz – 10 GHz**1 GHz – 10 GHz**

Spurious Emission on Antenna Port**GSM/TM1/GSM850****Channel 251 / 848.8 MHz**


Date: 18.DEC.2020 09:46:53

GSM/TM3/EDGE850**Channel 128 / 824.2 MHz**

Date: 18.DEC.2020 09:55:46





30 MHz – 1000 MHz







Date: 18.DEC.2020 09:51:06


30 MHz – 1000 MHz

Date: 18.DEC.2020 09:52:08


1 GHz – 10 GHz**1 GHz – 10 GHz**

Spurious Emission on Antenna Port**GSM/TM3/EDGE850****Channel 190 / 836.6 MHz****GSM/TM3/EDGE850****Channel 251 / 848.8 MHz****30 MHz – 1000 MHz****30 MHz – 1000 MHz****1 GHz – 10 GHz****1 GHz – 10 GHz**


Spurious Emission on Antenna Port**GSM/TM1/GSM1900****Channel 512/ 1850.2 MHz****GSM/TM1/GSM1900****Channel 661 / 1880.0 MHz****30 MHz – 1000 MHz****30 MHz – 1000 MHz****1 GHz – 2 GHz****1 GHz – 2 GHz****2 GHz – 20 GHz****2 GHz – 20 GHz**

Spurious Emission on Antenna Port**GSM/TM1/GSM1900****Channel 810/ 1909.8 MHz**


Date: 17.DEC.2020 19:49:09

GSM/TM3/EDGE1900**Channel 512/ 1850.2 MHz**


Date: 18.DEC.2020 10:05:30

30 MHz – 1000 MHz


Date: 17.DEC.2020 19:52:29

30 MHz – 1000 MHz

Date: 18.DEC.2020 10:12:40


1 GHz – 2 GHz

Date: 17.DEC.2020 19:53:08


1 GHz – 2 GHz

Date: 18.DEC.2020 10:16:06


2 GHz – 20 GHz**2 GHz – 20 GHz**

Spurious Emission on Antenna Port**GSM/TM1/GSM1900****Channel 661 / 1880.0 MHz**


Date: 18.DEC.2020 10:10:22

GSM/TM3/EDGE1900**Channel 810/ 1909.8 MHz**


Date: 18.DEC.2020 10:10:40

30 MHz – 1000 MHz


Date: 18.DEC.2020 10:13:47

30 MHz – 1000 MHz

Date: 18.DEC.2020 10:14:24

1 GHz – 2 GHz

Date: 18.DEC.2020 10:15:37


1 GHz – 2 GHz

Date: 18.DEC.2020 10:15:15

2 GHz – 20 GHz**2 GHz – 20 GHz**


Spurious Emission on Antenna Port UMTS/TM1/WCDMA Band II

Channel 9262 / 1852.4 MHz




Date: 17.DEC.2020 19:17:35

Channel 9400 / 1880 MHz




Date: 17.DEC.2020 19:18:42

30 MHz – 1000 MHz




Date: 17.DEC.2020 19:22:52

30 MHz – 1000 MHz




Date: 17.DEC.2020 19:21:53

1 GHz – 2 GHz



Date: 17.DEC.2020 19:23:16

1 GHz – 2 GHz




Date: 17.DEC.2020 19:24:14

2 GHz – 20 GHz


2 GHz – 20 GHz

Spurious Emission on Antenna Port UMTS/TM1/WCDMA Band II


Channel 9538 / 1907.6 MHz



30 MHz – 1000 MHz




1 GHz – 2 GHz



2 GHz – 20 GHz


Spurious Emission on Antenna Port UMTS/TM1/WCDMA Band V

Channel 4132 / 826.4 MHz




Date: 17,DEC,2020 19:37:12

Channel 4182 / 836.4 MHz




Date: 17,DEC,2020 19:38:06

30 MHz – 1000 MHz



Date: 17,DEC,2020 19:40:49

30 MHz – 1000 MHz




Date: 17,DEC,2020 19:40:28

1 GHz – 10 GHz


1 GHz – 10 GHz

Spurious Emssion on Antenna Port
UMTS/TM1/WCDMA Band V

Channel 4233 / 846.6 MHz



30 MHz – 1000 MHz



1 GHz – 10 GHz

Radiated Measurement:

Remark:

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7; recorded worst case for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II , WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7.

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

For Less than 1 GHz:*GSM/TM1/GSM850_ Low Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
150.42	-45.98	3.97	3.00	8.39	-41.56	-13.00	-28.56	H
236.55	-46.10	4.30	3.00	7.08	-43.32	-13.00	-30.32	H
555.85	-41.68	3.92	3.00	8.51	-37.09	-13.00	-24.09	V
903.57	-43.73	4.46	3.00	7.07	-41.12	-13.00	-28.12	V

GSM/TM1/GSM850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
155.21	-45.96	3.88	3.00	8.56	-41.28	-13.00	-28.28	H
235.95	-46.55	4.40	3.00	7.08	-43.86	-13.00	-30.86	H
552.36	-42.91	3.73	3.00	8.49	-38.14	-13.00	-25.14	V
907.09	-44.67	4.16	3.00	7.03	-41.80	-13.00	-28.80	V

GSM/TM1/GSM850_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
150.21	-47.66	4.04	3.00	8.66	-43.04	-13.00	-30.04	H
239.31	-45.71	4.31	3.00	7.15	-42.88	-13.00	-29.88	H
558.87	-44.38	4.03	3.00	8.68	-39.74	-13.00	-26.74	V
903.65	-45.07	4.21	3.00	6.81	-42.47	-13.00	-29.47	V

GSM/TM3/ EDGE850_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.29	-45.65	3.83	3.00	8.76	-40.71	-13.00	-27.71	H
240.27	-45.82	4.23	3.00	6.92	-43.13	-13.00	-30.13	H
553.27	-42.00	4.04	3.00	8.57	-37.47	-13.00	-24.47	V
899.32	-43.59	4.20	3.00	6.86	-40.92	-13.00	-27.92	V

GSM/TM3/ EDGE850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
154.19	-47.46	3.67	3.00	8.46	-42.67	-13.00	-29.67	H
238.31	-45.77	4.25	3.00	6.94	-43.09	-13.00	-30.09	H
556.90	-44.27	3.69	3.00	8.58	-39.38	-13.00	-26.38	V
899.51	-45.14	4.37	3.00	6.78	-42.72	-13.00	-29.72	V

GSM/TM3/ EDGE850_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
158.00	-47.57	3.93	3.00	8.69	-42.81	-13.00	-29.81	H
237.52	-45.64	4.28	3.00	6.99	-42.93	-13.00	-29.93	H
556.62	-44.55	3.73	3.00	8.49	-39.80	-13.00	-26.80	V
900.81	-45.26	4.34	3.00	6.88	-42.71	-13.00	-29.71	V

GSM/TM1/GSM1900_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.04	-46.00	3.95	3.00	8.72	-41.23	-13.00	-28.23	H
233.92	-45.97	4.23	3.00	6.87	-43.33	-13.00	-30.33	H
556.08	-41.78	3.94	3.00	8.47	-37.25	-13.00	-24.25	V
901.00	-43.62	4.33	3.00	6.80	-41.14	-13.00	-28.14	V

GSM/TM1/GSM1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
155.22	-46.13	3.97	3.00	8.46	-41.65	-13.00	-28.65	H
242.02	-46.45	4.31	3.00	6.92	-43.83	-13.00	-30.83	H
558.83	-42.67	3.84	3.00	8.44	-38.07	-13.00	-25.07	V
901.31	-44.68	4.45	3.00	7.17	-41.96	-13.00	-28.96	V

GSM/TM1/GSM1900_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.93	-47.70	3.99	3.00	8.64	-43.05	-13.00	-30.05	H
234.67	-45.92	4.46	3.00	7.14	-43.24	-13.00	-30.24	H
561.04	-44.47	3.90	3.00	8.47	-39.90	-13.00	-26.90	V
897.58	-45.09	4.10	3.00	7.09	-42.10	-13.00	-29.10	V

GSM/TM3/ EDGE1900_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
150.88	-45.80	3.79	3.00	8.66	-40.93	-13.00	-27.93	H
234.02	-46.07	4.33	3.00	6.81	-43.59	-13.00	-30.59	H
559.56	-41.81	3.87	3.00	8.46	-37.22	-13.00	-24.22	V
899.77	-43.45	4.28	3.00	7.02	-40.71	-13.00	-27.71	V

GSM/TM3/ EDGE1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.17	-45.91	3.69	3.00	8.58	-41.02	-13.00	-28.02	H
238.16	-46.48	4.37	3.00	7.09	-43.75	-13.00	-30.75	H
560.32	-42.59	4.05	3.00	8.66	-37.98	-13.00	-24.98	V
902.43	-44.56	4.23	3.00	7.03	-41.76	-13.00	-28.76	V

GSM/TM3/ EDGE1900_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.14	-47.72	3.98	3.00	8.41	-43.28	-13.00	-30.28	H
237.49	-45.85	4.13	3.00	7.01	-42.98	-13.00	-29.98	H
557.68	-44.52	3.88	3.00	8.65	-39.75	-13.00	-26.75	V
899.93	-45.14	4.18	3.00	6.88	-42.43	-13.00	-29.43	V

UMTS/TM1/ WCDMA Band II _ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
154.87	-46.04	3.70	3.00	8.64	-41.09	-13.00	-28.09	H
235.07	-46.06	4.21	3.00	7.00	-43.27	-13.00	-30.27	H
559.15	-41.86	4.00	3.00	8.67	-37.18	-13.00	-24.18	V
903.97	-43.60	4.31	3.00	7.14	-40.76	-13.00	-27.76	V

UMTS/TM1/ WCDMA Band II _ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
155.38	-46.04	3.93	3.00	8.39	-41.58	-13.00	-28.58	H
238.41	-46.48	4.26	3.00	6.80	-43.94	-13.00	-30.94	H
561.29	-42.77	4.05	3.00	8.42	-38.41	-13.00	-25.41	V
900.24	-44.45	4.17	3.00	6.92	-41.71	-13.00	-28.71	V

UMTS/TM1/ WCDMA Band II _ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
151.54	-47.59	3.79	3.00	8.43	-42.94	-13.00	-29.94	H
236.69	-45.89	4.29	3.00	6.79	-43.39	-13.00	-30.39	H
553.83	-44.27	3.66	3.00	8.41	-39.53	-13.00	-26.53	V
901.93	-45.23	4.20	3.00	6.86	-42.57	-13.00	-29.57	V

UMTS/TM1/ WCDMA Band V _ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
153.61	-45.88	3.76	3.00	8.72	-40.92	-13.00	-27.92	H
240.73	-45.77	4.43	3.00	6.94	-43.27	-13.00	-30.27	H
555.08	-41.67	3.97	3.00	8.44	-37.19	-13.00	-24.19	V
900.83	-43.66	4.36	3.00	7.03	-40.99	-13.00	-27.99	V

UMTS/TM1/ WCDMA Band V _ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
149.44	-46.13	4.05	3.00	8.57	-41.61	-13.00	-28.61	H
242.76	-46.60	4.15	3.00	6.88	-43.87	-13.00	-30.87	H
557.40	-42.88	4.01	3.00	8.43	-38.46	-13.00	-25.46	V
901.42	-44.42	4.40	3.00	6.94	-41.88	-13.00	-28.88	V

UMTS/TM1/ WCDMA Band V _ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
155.50	-47.55	3.93	3.00	8.37	-43.11	-13.00	-30.11	H
241.88	-45.80	4.21	3.00	7.01	-43.00	-13.00	-30.00	H
559.03	-44.58	3.85	3.00	8.50	-39.92	-13.00	-26.92	V
906.74	-45.33	4.40	3.00	6.80	-42.93	-13.00	-29.93	V

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.84	-45.76	3.76	3.00	8.60	-40.93	-13.00	-27.93	H
234.93	-46.01	4.48	3.00	7.16	-43.32	-13.00	-30.32	H
553.18	-41.74	3.72	3.00	8.58	-36.87	-13.00	-23.87	V
901.28	-43.35	4.24	3.00	6.90	-40.68	-13.00	-27.68	V

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
149.09	-45.83	3.94	3.00	8.47	-41.30	-13.00	-28.30	H
233.64	-46.43	4.32	3.00	7.11	-43.64	-13.00	-30.64	H
558.80	-42.63	3.72	3.00	8.64	-37.72	-13.00	-24.72	V
903.12	-44.60	4.28	3.00	6.80	-42.09	-13.00	-29.09	V

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
153.74	-47.44	3.93	3.00	8.40	-42.98	-13.00	-29.98	H
240.23	-45.93	4.45	3.00	7.01	-43.37	-13.00	-30.37	H
555.64	-44.28	3.97	3.00	8.37	-39.87	-13.00	-26.87	V
904.86	-45.01	4.28	3.00	7.13	-42.15	-13.00	-29.15	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
150.79	-45.85	4.04	3.00	8.59	-41.29	-13.00	-28.29	H
240.39	-45.93	4.39	3.00	7.11	-43.20	-13.00	-30.20	H
559.11	-41.93	3.79	3.00	8.40	-37.32	-13.00	-24.32	V
904.84	-43.48	4.40	3.00	6.89	-40.99	-13.00	-27.99	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
155.64	-46.02	3.77	3.00	8.70	-41.10	-13.00	-28.10	H
235.09	-46.78	4.14	3.00	7.03	-43.89	-13.00	-30.89	H
553.88	-42.57	3.82	3.00	8.63	-37.75	-13.00	-24.75	V
903.11	-44.45	4.10	3.00	6.94	-41.61	-13.00	-28.61	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
149.41	-47.63	3.76	3.00	8.42	-42.97	-13.00	-29.97	H
241.70	-45.75	4.36	3.00	6.99	-43.12	-13.00	-30.12	H
557.63	-44.38	3.76	3.00	8.43	-39.72	-13.00	-26.72	V
904.23	-45.33	4.46	3.00	6.95	-42.85	-13.00	-29.85	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
153.21	-46.02	3.71	3.00	8.58	-41.15	-13.00	-28.15	H
237.30	-46.07	4.13	3.00	6.94	-43.27	-13.00	-30.27	H
560.63	-41.66	3.87	3.00	8.57	-36.97	-13.00	-23.97	V
899.00	-43.66	4.34	3.00	6.90	-41.09	-13.00	-28.09	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
155.56	-45.80	3.78	3.00	8.70	-40.89	-13.00	-27.89	H
238.06	-46.78	4.42	3.00	6.86	-44.35	-13.00	-31.35	H
553.76	-42.90	3.80	3.00	8.57	-38.13	-13.00	-25.13	V
900.81	-44.48	4.37	3.00	6.79	-42.06	-13.00	-29.06	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
150.98	-47.46	3.91	3.00	8.76	-42.61	-13.00	-29.61	H
237.56	-45.63	4.18	3.00	6.90	-42.90	-13.00	-29.90	H
554.60	-44.62	3.95	3.00	8.64	-39.94	-13.00	-26.94	V
903.24	-45.29	4.14	3.00	6.88	-42.55	-13.00	-29.55	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
153.26	-45.85	3.66	3.00	8.52	-40.99	-13.00	-27.99	H
236.70	-46.04	4.10	3.00	6.98	-43.16	-13.00	-30.16	H
552.75	-41.81	3.82	3.00	8.41	-37.22	-13.00	-24.22	V
899.38	-43.69	4.35	3.00	6.92	-41.12	-13.00	-28.12	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
150.55	-46.03	3.74	3.00	8.55	-41.22	-13.00	-28.22	H
239.10	-46.69	4.33	3.00	7.09	-43.94	-13.00	-30.94	H
554.01	-42.61	3.70	3.00	8.46	-37.85	-13.00	-24.85	V
903.88	-44.62	4.15	3.00	7.01	-41.76	-13.00	-28.76	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.94	-47.70	4.00	3.00	8.72	-42.98	-13.00	-29.98	H
242.52	-45.72	4.33	3.00	7.16	-42.89	-13.00	-29.89	H
554.18	-44.48	3.73	3.00	8.54	-39.67	-13.00	-26.67	V
901.16	-45.12	4.24	3.00	6.89	-42.48	-13.00	-29.48	V

LTE FDD Band 7_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
150.54	-42.64	3.86	3.00	8.46	-38.05	-25.00	-13.05	H
242.97	-48.19	4.13	3.00	6.99	-45.33	-25.00	-20.33	H
552.39	-44.65	3.88	3.00	8.36	-40.17	-25.00	-15.17	V
903.58	-49.94	4.41	3.00	6.95	-47.40	-25.00	-22.40	V

LTE FDD Band 7_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
153.83	-44.58	4.03	3.00	8.47	-40.14	-25.00	-15.14	H
233.62	-49.72	4.26	3.00	7.01	-46.97	-25.00	-21.97	H
556.76	-45.01	3.81	3.00	8.56	-40.26	-25.00	-15.26	V
899.63	-50.86	4.33	3.00	6.96	-48.23	-25.00	-23.23	V

LTE FDD 7_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
156.28	-45.60	4.05	3.00	8.56	-41.09	-25.00	-16.09	H
242.57	-50.88	4.34	3.00	7.04	-48.18	-25.00	-23.18	H
557.72	-46.29	3.89	3.00	8.54	-41.63	-25.00	-16.63	V
902.26	-51.44	4.48	3.00	7.08	-48.84	-25.00	-23.84	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
156.80	-42.83	3.73	3.00	8.73	-37.83	-25.00	-12.83	H
236.05	-48.37	4.43	3.00	6.96	-45.85	-25.00	-20.85	H
555.51	-44.96	3.71	3.00	8.47	-40.20	-25.00	-15.20	V
900.31	-50.11	4.42	3.00	6.90	-47.63	-25.00	-22.63	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.58	-44.57	3.81	3.00	8.54	-39.84	-25.00	-14.84	H
240.79	-49.69	4.19	3.00	6.89	-46.99	-25.00	-21.99	H
560.20	-45.24	3.88	3.00	8.55	-40.57	-25.00	-15.57	V
899.30	-50.94	4.34	3.00	6.95	-48.34	-25.00	-23.34	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
152.01	-45.44	3.72	3.00	8.53	-40.63	-25.00	-15.63	H
234.38	-50.91	4.13	3.00	7.18	-47.86	-25.00	-22.86	H
557.68	-46.51	3.94	3.00	8.62	-41.82	-25.00	-16.82	V
906.19	-51.58	4.43	3.00	7.14	-48.87	-25.00	-23.87	V

For More than 1 GHz:*GSM/TM1/GSM850_ Low Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.40	-45.76	3.86	3.00	8.56	-41.06	-14.00	-27.06	H
2472.60	-46.09	4.29	3.00	6.98	-43.40	-13.00	-30.40	H
1648.40	-41.73	3.86	3.00	8.56	-37.03	-13.00	-24.03	V
2472.60	-43.69	4.29	3.00	6.98	-41.00	-13.00	-28.00	V

GSM/TM1/GSM850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.20	-45.78	3.90	3.00	8.58	-41.10	-13.00	-28.10	H
2509.80	-46.67	4.32	3.00	6.80	-44.19	-13.00	-31.19	H
1673.20	-42.55	3.90	3.00	8.58	-37.87	-13.00	-24.87	V
2509.80	-44.56	4.32	3.00	6.80	-42.08	-13.00	-29.08	V

GSM/TM1/GSM850_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.60	-47.39	3.91	3.00	9.06	-42.24	-13.00	-29.24	H
2546.40	-45.74	4.32	3.00	6.65	-43.41	-13.00	-30.41	H
1697.60	-44.62	3.91	3.00	9.06	-39.47	-13.00	-26.47	V
2546.40	-45.06	4.32	3.00	6.65	-42.73	-13.00	-29.73	V

GSM/TM3/ EDGE850_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.40	-45.81	3.86	3.00	8.56	-41.11	-14.00	-27.11	H
2472.60	-45.72	4.29	3.00	6.98	-43.03	-13.00	-30.03	H
1648.40	-41.76	3.86	3.00	8.56	-37.06	-13.00	-24.06	V
2472.60	-43.71	4.29	3.00	6.98	-41.02	-13.00	-28.02	V

GSM/TM3/ EDGE850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.20	-45.75	3.90	3.00	8.58	-41.07	-13.00	-28.07	H
2509.80	-46.47	4.32	3.00	6.80	-43.99	-13.00	-30.99	H
1673.20	-42.88	3.90	3.00	8.58	-38.20	-13.00	-25.20	V
2509.80	-44.62	4.32	3.00	6.80	-42.14	-13.00	-29.14	V

GSM/TM3/ EDGE850_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.60	-47.50	3.91	3.00	9.06	-42.35	-13.00	-29.35	H
2546.40	-45.81	4.32	3.00	6.65	-43.48	-13.00	-30.48	H
1697.60	-44.63	3.91	3.00	9.06	-39.48	-13.00	-26.48	V
2546.40	-45.18	4.32	3.00	6.65	-42.85	-13.00	-29.85	V

GSM/TM1/GSM1900_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.40	-42.63	5.26	3.00	9.88	-38.01	-13.00	-25.01	H
5550.60	-48.20	6.11	3.00	11.36	-42.95	-13.00	-29.95	H
3700.40	-44.72	5.26	3.00	9.88	-40.10	-13.00	-27.10	V
5550.60	-50.02	6.11	3.00	11.36	-44.77	-13.00	-31.77	V

GSM/TM1/GSM1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-44.53	5.32	3.00	10.03	-39.82	-13.00	-26.82	H
5640.00	-49.94	6.19	3.00	11.41	-44.72	-13.00	-31.72	H
3760.00	-45.26	5.32	3.00	10.03	-40.55	-13.00	-27.55	V
5640.00	-50.91	6.19	3.00	11.41	-45.69	-13.00	-32.69	V

GSM/TM1/GSM1900_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.60	-45.41	5.36	3.00	9.62	-41.15	-13.00	-28.15	H
5729.40	-50.98	6.24	3.00	11.46	-45.76	-13.00	-32.76	H
3819.60	-46.52	5.36	3.00	9.62	-42.26	-13.00	-29.26	V
5729.40	-51.47	6.24	3.00	11.46	-46.25	-13.00	-33.25	V

GSM/TM3/ EDGE1900_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.40	-42.75	5.26	3.00	9.88	-38.13	-13.00	-25.13	H
5550.60	-48.39	6.11	3.00	11.36	-43.14	-13.00	-30.14	H
3700.40	-44.94	5.26	3.00	9.88	-40.32	-13.00	-27.32	V
5550.60	-50.01	6.11	3.00	11.36	-44.76	-13.00	-31.76	V

GSM/TM3/ EDGE1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-44.35	5.32	3.00	10.03	-39.64	-13.00	-26.64	H
5640.00	-49.86	6.19	3.00	11.41	-44.64	-13.00	-31.64	H
3760.00	-45.26	5.32	3.00	10.03	-40.55	-13.00	-27.55	V
5640.00	-50.88	6.19	3.00	11.41	-45.66	-13.00	-32.66	V

GSM/TM3/ EDGE1900_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.60	-45.39	5.36	3.00	9.62	-41.13	-13.00	-28.13	H
5729.40	-50.70	6.24	3.00	11.46	-45.48	-13.00	-32.48	H
3819.60	-46.24	5.36	3.00	9.62	-41.98	-13.00	-28.98	V
5729.40	-51.57	6.24	3.00	11.46	-46.35	-13.00	-33.35	V

UMTS/TM1/ WCDMA Band II_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3704.8	-43.60	5.26	3.00	9.88	-38.98	-13.00	-25.98	H
5557.2	-47.79	6.11	3.00	11.36	-42.54	-13.00	-29.54	H
3704.8	-47.18	5.26	3.00	9.88	-42.56	-13.00	-29.56	V
5557.2	-50.99	6.11	3.00	11.36	-45.74	-13.00	-32.74	V

UMTS/TM1/ WCDMA Band II_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-42.73	5.32	3.00	10.03	-38.02	-13.00	-25.02	H
5640.0	-45.94	6.19	3.00	11.41	-40.72	-13.00	-27.72	H
3760.0	-46.85	5.32	3.00	10.03	-42.14	-13.00	-29.14	V
5640.0	-51.39	6.19	3.00	11.41	-46.17	-13.00	-33.17	V

UMTS/TM1/ WCDMA Band II _ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3815.2	-41.40	5.36	3.00	9.62	-37.14	-13.00	-24.14	H
5722.8	-44.35	6.24	3.00	11.46	-39.13	-13.00	-26.13	H
3815.2	-45.77	5.36	3.00	9.62	-41.51	-13.00	-28.51	V
5722.8	-47.06	6.24	3.00	11.46	-41.84	-13.00	-28.84	V

UMTS/TM1/ WCDMA Band V _ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1652.8	-46.32	3.86	3.00	8.56	-41.62	-13.00	-28.62	H
2479.2	-47.04	4.29	3.00	6.98	-44.35	-13.00	-31.35	H
1652.8	-45.39	3.86	3.00	8.56	-40.69	-13.00	-27.69	V
2479.2	-48.70	4.29	3.00	6.98	-46.01	-13.00	-33.01	V

UMTS/TM1/ WCDMA Band V _ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1672.8	-46.05	3.90	3.00	8.58	-41.37	-13.00	-28.37	H
2509.2	-46.50	4.32	3.00	6.80	-44.02	-13.00	-31.02	H
1672.8	-46.25	3.90	3.00	8.58	-41.57	-13.00	-28.57	V
2509.2	-49.76	4.32	3.00	6.80	-47.28	-13.00	-34.28	V

UMTS/TM1/ WCDMA Band V _ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1693.2	-44.09	3.91	3.00	9.06	-38.94	-13.00	-25.94	H
2539.8	-45.41	4.32	3.00	6.65	-43.08	-13.00	-30.08	H
1693.2	-46.16	3.91	3.00	9.06	-41.01	-13.00	-28.01	V
2539.8	-47.69	4.32	3.00	6.65	-45.36	-13.00	-32.36	V

LTE FDD Band 2 _Channel Bandwidth 20MHz_ QPSK_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3715.0	-42.83	5.26	3.00	9.88	-38.21	-13.00	-25.21	H
5572.5	-49.07	6.11	3.00	11.36	-43.82	-13.00	-30.82	H
3715.0	-46.57	5.26	3.00	9.88	-41.95	-13.00	-28.95	V
5572.5	-51.87	6.11	3.00	11.36	-46.62	-13.00	-33.62	V

LTE FDD Band 2 _Channel Bandwidth 20MHz_ QPSK_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3720.0	-43.77	5.32	3.00	10.03	-39.06	-13.00	-26.06	H
5580.0	-47.81	6.19	3.00	11.41	-42.59	-13.00	-29.59	H
3720.0	-47.28	5.32	3.00	10.03	-42.57	-13.00	-29.57	V
5580.0	-50.94	6.19	3.00	11.41	-45.72	-13.00	-32.72	V

LTE FDD Band 2 _Channel Bandwidth 20MHz_ QPSK_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3800.0	-42.76	5.36	3.00	9.62	-38.50	-13.00	-25.50	H
5700.0	-46.15	6.24	3.00	11.46	-40.93	-13.00	-27.93	H
3800.0	-46.77	5.36	3.00	9.62	-42.51	-13.00	-29.51	V
5700.0	-51.21	6.24	3.00	11.46	-45.99	-13.00	-32.99	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3715.0	-42.71	5.26	3.00	9.88	-38.09	-13.00	-25.09	H
5572.5	-49.08	6.11	3.00	11.36	-43.83	-13.00	-30.83	H
3715.0	-46.53	5.26	3.00	9.88	-41.91	-13.00	-28.91	V
5572.5	-51.54	6.11	3.00	11.36	-46.29	-13.00	-33.29	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3720.0	-43.67	5.32	3.00	10.03	-38.96	-13.00	-25.96	H
5580.0	-47.75	6.19	3.00	11.41	-42.53	-13.00	-29.53	H
3720.0	-47.15	5.32	3.00	10.03	-42.44	-13.00	-29.44	V
5580.0	-51.04	6.19	3.00	11.41	-45.82	-13.00	-32.82	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3800.0	-42.68	5.36	3.00	9.62	-38.42	-13.00	-25.42	H
5700.0	-46.05	6.24	3.00	11.46	-40.83	-13.00	-27.83	H
3800.0	-46.74	5.36	3.00	9.62	-42.48	-13.00	-29.48	V
5700.0	-51.38	6.24	3.00	11.46	-46.16	-13.00	-33.16	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1658.00	-40.81	4.74	3.00	10.45	-35.10	-13.00	-22.10	H
2487.00	-46.56	5.65	3.00	12.32	-39.89	-13.00	-26.89	H
1658.00	-44.45	4.74	3.00	10.45	-38.74	-13.00	-25.74	V
2487.00	-49.96	5.65	3.00	12.32	-43.29	-13.00	-30.29	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.00	-39.84	5.98	3.00	11.12	-34.70	-13.00	-21.70	H
2509.50	-47.00	6.45	3.00	12.02	-41.43	-13.00	-28.43	H
1673.00	-43.15	5.98	3.00	11.12	-38.01	-13.00	-25.01	V
2509.50	-47.65	6.45	3.00	12.02	-42.08	-13.00	-29.08	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1688.00	-41.18	5.95	3.00	9.98	-37.15	-13.00	-24.15	H
2532.00	-46.80	6.63	3.00	11.66	-41.77	-13.00	-28.77	H
1688.00	-43.81	5.95	3.00	9.98	-39.78	-13.00	-26.78	V
2532.00	-49.31	6.63	3.00	11.66	-44.28	-13.00	-31.28	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1658.00	-40.72	4.74	3.00	10.45	-35.01	-13.00	-22.01	H
2487.00	-46.68	5.65	3.00	12.32	-40.01	-13.00	-27.01	H
1658.00	-44.29	4.74	3.00	10.45	-38.58	-13.00	-25.58	V
2487.00	-49.74	5.65	3.00	12.32	-43.07	-13.00	-30.07	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.00	-39.75	5.98	3.00	11.12	-34.61	-13.00	-21.61	H
2509.50	-46.78	6.45	3.00	12.02	-41.21	-13.00	-28.21	H
1673.00	-43.12	5.98	3.00	11.12	-37.98	-13.00	-24.98	V
2509.50	-47.76	6.45	3.00	12.02	-42.19	-13.00	-29.19	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1688.00	-40.94	5.95	3.00	9.98	-36.91	-13.00	-23.91	H
2532.00	-46.69	6.63	3.00	11.66	-41.66	-13.00	-28.66	H
1688.00	-43.85	5.95	3.00	9.98	-39.82	-13.00	-26.82	V
2532.00	-49.49	6.63	3.00	11.66	-44.46	-13.00	-31.46	V

LTE FDD Band 7_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5020.0	-45.55	5.88	3.00	10.77	-40.66	-25.00	-15.66	H
7530.0	-48.07	7.12	3.00	12.26	-42.93	-25.00	-17.93	H
5020.0	-49.56	5.88	3.00	10.77	-44.67	-25.00	-19.67	V
7530.0	-53.70	7.12	3.00	12.26	-48.56	-25.00	-23.56	V

LTE FDD Band 7_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070.0	-42.90	5.9	3.00	10.81	-37.99	-25.00	-12.99	H
7605.0	-45.94	7.19	3.00	12.32	-40.81	-25.00	-15.81	H
5070.0	-46.95	5.9	3.00	10.81	-42.04	-25.00	-17.04	V
7605.0	-49.28	7.19	3.00	12.32	-44.15	-25.00	-19.15	V

LTE FDD 7_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5120.0	-48.96	5.94	3.00	10.86	-44.04	-25.00	-19.04	H
7680.0	-54.49	7.25	3.00	12.98	-48.76	-25.00	-23.76	H
5120.0	-52.73	5.94	3.00	10.86	-47.81	-25.00	-22.81	V
7680.0	-57.01	7.25	3.00	12.98	-51.28	-25.00	-26.28	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5020.0	-45.53	5.88	3.00	10.77	-40.64	-25.00	-15.64	H
7530.0	-48.00	7.12	3.00	12.26	-42.86	-25.00	-17.86	H
5020.0	-49.34	5.88	3.00	10.77	-44.45	-25.00	-19.45	V
7530.0	-53.50	7.12	3.00	12.26	-48.36	-25.00	-23.36	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070.0	-43.06	5.9	3.00	10.81	-38.15	-25.00	-13.15	H
7605.0	-45.84	7.19	3.00	12.32	-40.71	-25.00	-15.71	H
5070.0	-46.79	5.9	3.00	10.81	-41.88	-25.00	-16.88	V
7605.0	-49.19	7.19	3.00	12.32	-44.06	-25.00	-19.06	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5120.0	-49.06	5.94	3.00	10.86	-44.14	-25.00	-19.14	H
7680.0	-54.52	7.25	3.00	12.98	-48.79	-25.00	-23.79	H
5120.0	-52.61	5.94	3.00	10.86	-47.69	-25.00	-22.69	V
7680.0	-56.82	7.25	3.00	12.98	-51.09	-25.00	-26.09	V

Notes:


1. All channel bandwidth were tested, the report recorded the worst data.
2. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + P_{Ag}(dB) + G_a(dBi)$
3. $ERP = EIRP - 2.15dBi$ as EIRP by subtracting the gain of the dipole.
4. $Margin = EIRP - Limit$
5. We measured all modes and only recorded the worst case.

4.6 Frequency Stability under Temperature & Voltage Variations

LIMIT

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235,§27.54 .

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Frequency Stability Under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 5, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Remark:

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II ,WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7; recorded worst case for each Channel Bandwidth of GSM900M,GSM1800M, WCDMA Band II , WCDMA Band V , LTE FDD Band 2, LTE FDD Band 5, LTE FDD Band 7.

Temperature	24.5°C	Humidity	53.7%
Test Engineer	Moon Tan	Configurations	WCDMA/LTE

GSM/TM1/GSM850					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	25	-39	-0.047	±2.50	PASS
3.7	25	-37	-0.045	±2.50	PASS
4.2	25	5	0.006	±2.50	PASS
3.7	-30	2	0.002	±2.50	PASS
3.7	-20	-42	-0.051	±2.50	PASS
3.7	-10	41	0.050	±2.50	PASS
3.7	0	-24	-0.029	±2.50	PASS
3.7	10	16	0.019	±2.50	PASS
3.7	20	-18	-0.022	±2.50	PASS
3.7	30	-48	-0.058	±2.50	PASS
3.7	40	40	0.049	±2.50	PASS
3.7	50	13	0.016	±2.50	PASS

GSM/TM1/GSM1900					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	25	17	0.009	±2.50	PASS
3.7	25	36	0.019	±2.50	PASS
4.2	25	42	0.022	±2.50	PASS
3.7	-30	21	0.011	±2.50	PASS
3.7	-20	-40	-0.021	±2.50	PASS
3.7	-10	-16	-0.009	±2.50	PASS
3.7	0	5	0.003	±2.50	PASS
3.7	10	41	0.022	±2.50	PASS
3.7	20	31	0.016	±2.50	PASS
3.7	30	-1	-0.001	±2.50	PASS
3.7	40	15	0.008	±2.50	PASS
3.7	50	-8	-0.004	±2.50	PASS

UMTS/TM1/WCDMA Band II					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	25	3	0.002	±2.50	PASS
3.7	25	-2	-0.001	±2.50	PASS
4.2	25	-9	-0.005	±2.50	PASS
3.7	-30	17	0.009	±2.50	PASS
3.7	-20	-15	-0.008	±2.50	PASS
3.7	-10	13	0.007	±2.50	PASS
3.7	0	-16	-0.009	±2.50	PASS
3.7	10	5	0.003	±2.50	PASS
3.7	20	18	0.010	±2.50	PASS
3.7	30	11	0.006	±2.50	PASS
3.7	40	-19	-0.010	±2.50	PASS
3.7	50	-8	-0.004	±2.50	PASS

UMTS/TM1/WCDMA Band V					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	25	-20	-0.024	±2.50	PASS
3.7	25	-6	-0.007	±2.50	PASS
4.2	25	-16	-0.019	±2.50	PASS
3.7	-30	8	0.010	±2.50	PASS
3.7	-20	-2	-0.002	±2.50	PASS
3.7	-10	9	0.011	±2.50	PASS
3.7	0	-12	-0.015	±2.50	PASS
3.7	10	0	0.000	±2.50	PASS
3.7	20	-10	-0.012	±2.50	PASS
3.7	30	-11	-0.013	±2.50	PASS
3.7	40	4	0.005	±2.50	PASS
3.7	50	14	0.017	±2.50	PASS

LTE Band 2, QPSK, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	20	79	0.042	±2.50	PASS
3.7	20	44	0.023	±2.50	PASS
4.2	20	24	0.013	±2.50	PASS
3.7	-30	51	0.027	±2.50	PASS
3.7	-20	41	0.022	±2.50	PASS
3.7	-10	67	0.036	±2.50	PASS
3.7	0	82	0.044	±2.50	PASS
3.7	10	33	0.018	±2.50	PASS
3.7	20	0	0.000	±2.50	PASS
3.7	30	35	0.019	±2.50	PASS
3.7	40	83	0.044	±2.50	PASS
3.7	50	9	0.005	±2.50	PASS

LTE Band 2, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	20	30	0.016	±2.50	PASS
3.7	20	82	0.044	±2.50	PASS
4.2	20	46	0.024	±2.50	PASS
3.7	-30	71	0.038	±2.50	PASS
3.7	-20	62	0.033	±2.50	PASS
3.7	-10	95	0.051	±2.50	PASS
3.7	0	63	0.034	±2.50	PASS
3.7	10	56	0.030	±2.50	PASS
3.7	20	27	0.014	±2.50	PASS
3.7	30	44	0.023	±2.50	PASS
3.7	40	74	0.039	±2.50	PASS
3.7	50	19	0.010	±2.50	PASS

LTE Band 5, QPSK, 1.4MHz bandwidth(worst case of all bandwidths)

LTE FDD Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	20	15	0.018	±2.50	PASS
3.7	20	25	0.030	±2.50	PASS
4.2	20	69	0.084	±2.50	PASS
3.7	-30	40	0.049	±2.50	PASS
3.7	-20	72	0.087	±2.50	PASS
3.7	-10	11	0.013	±2.50	PASS
3.7	0	64	0.078	±2.50	PASS
3.7	10	27	0.033	±2.50	PASS
3.7	20	72	0.087	±2.50	PASS
3.7	30	20	0.024	±2.50	PASS
3.7	40	41	0.050	±2.50	PASS
3.7	50	38	0.046	±2.50	PASS

LTE Band 5, 16QAM, 1.4MHz bandwidth(worst case of all bandwidths)

LTE FDD Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	20	20	0.024	±2.50	PASS
3.7	20	79	0.096	±2.50	PASS
4.2	20	6	0.007	±2.50	PASS
3.7	-30	90	0.109	±2.50	PASS
3.7	-20	65	0.079	±2.50	PASS
3.7	-10	39	0.047	±2.50	PASS
3.7	0	52	0.063	±2.50	PASS
3.7	10	26	0.032	±2.50	PASS
3.7	20	36	0.044	±2.50	PASS
3.7	30	67	0.081	±2.50	PASS
3.7	40	95	0.115	±2.50	PASS
3.7	50	95	0.115	±2.50	PASS

LTE Band 7, QPSK, 5MHz bandwidth (worst case of all bandwidths and modulation type)

<i>LTE FDD Band 7</i>					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	20	20	0.008	±2.50	PASS
3.7	20	-13	-0.005	±2.50	PASS
4.2	20	8	0.003	±2.50	PASS
3.7	-30	10	0.004	±2.50	PASS
3.7	-20	8	0.003	±2.50	PASS
3.7	-10	-4	-0.002	±2.50	PASS
3.7	0	-12	-0.005	±2.50	PASS
3.7	10	16	0.006	±2.50	PASS
3.7	20	-4	-0.002	±2.50	PASS
3.7	30	-12	-0.005	±2.50	PASS
3.7	40	-8	-0.003	±2.50	PASS
3.7	50	-11	-0.004	±2.50	PASS

LTE Band 7, 16QAM, 5MHz bandwidth (worst case of all bandwidths and modulation type)

<i>LTE FDD Band 7</i>					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.3	20	-5	-0.002	±2.50	PASS
3.7	20	16	0.006	±2.50	PASS
4.2	20	-11	-0.004	±2.50	PASS
3.7	-30	10	0.004	±2.50	PASS
3.7	-20	-13	-0.005	±2.50	PASS
3.7	-10	-1	0.000	±2.50	PASS
3.7	0	-5	-0.002	±2.50	PASS
3.7	10	-5	-0.002	±2.50	PASS
3.7	20	16	0.006	±2.50	PASS
3.7	30	-3	-0.001	±2.50	PASS
3.7	40	1	0.000	±2.50	PASS
3.7	50	10	0.004	±2.50	PASS

NOTE:We measured all modes and only recorded the worst case.

5 TEST SETUP PHOTOS OF THE EUT



6 EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the Test Report: GTS20201211011-1-1.

.....End of Report.....