

Appendix A

RF Test Data for BT(BLE) (Conducted Measurement)


Product Name: Tablet PC
Trade Mark: KEYTHA
Test Model: JK0001
FCC ID: 2AYCLJK0001

Environmental Conditions

Temperature:	22.8° C
Relative Humidity:	50%
ATM Pressure:	100.0 kPa
Test Engineer:	Anna Hu
Supervised by:	Hugo Chen
NOTE	N/A

A.1. 6dB Bandwidth

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.712	2401.636	2402.348	0.5	PASS
		2440	0.704	2439.644	2440.348	0.5	PASS
		2480	0.700	2479.632	2480.332	0.5	PASS




A.2. Occupied Bandwidth

Test Mode	Test Channel	Ant	OBW[MHz]	Limit[MHz]	Verdict
-----------	--------------	-----	----------	------------	---------

A.3. Maximum peak conducted output power

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-1.42	<=30	PASS
		2440	-1.07	<=30	PASS
		2480	-1.26	<=30	PASS




A.4. Maximum Peak power spectral density

Test Mode	Ant	Test	PSD[dBm/10KHz]	Converter Factor [dB]	PSD[dBm/3KHz]	Limit[dBm/3KHz]	Verdict
BLE(1Mbps)	Ant1	2402	-11.89	5.23	-17.12	8.00	PASS
		2440	-11.53	5.23	-16.76	8.00	PASS
		2480	-11.8	5.23	-17.03	8.00	PASS

Note:


- 1, Converter factor = $10 * \lg(\text{RBW}/3 \text{ kHz}) = 5.23 \text{ (dB)}$
- 2, $\text{PSD[dBm/3KHz]} = \text{PSD[dBm/10KHz]} - \text{Converter Factor}$




A.5. Band-edge for RF Conducted Emissions

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-2.81	-49.98	<=-22.81	PASS
		High	2480	-2.45	-49.17	<=-22.45	PASS

BLE_1M_Ant1_Low_2402




BLE_1M_Ant1_High_2480




A.6. RF Conducted Spurious Emissions


BLE_1M_Ant1_2402_0~Reference




BLE_1M_Ant1_2402_30~1000




BLE_1M_Ant1_2402_1000~26500




BLE_1M_Ant1_2440_0~Reference




BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_0~Reference



BLE_1M_Ant1_2480_30~1000



BLE_1M_Ant1_2480_1000~26500




A.7. Restrict-band band-edge measurements


TestMode	Antenna	ChName	Channel	Detector	Freq. [MHz]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	Low	2402	AV	2310.000	-49.36	<=-41.20	PASS
				AV	2390.000	-49.04	<=-41.20	PASS
				Peak	2310.000	-44.88	<=-21.20	PASS
				Peak	2390.000	-45.22	<=-21.20	PASS
		High	2480	AV	2483.500	-48.39	<=-41.20	PASS
				AV	2500.000	-48.34	<=-41.20	PASS
				Peak	2483.500	-45.14	<=-21.20	PASS
				Peak	2500.000	-43.69	<=-21.20	PASS

1. The Antenna Gain is compensated in the graph with 2dBi and Antenna Gain which is Higher.
2. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.


BLE_1M_Ant1_Low_2402_AV




BLE_1M_Ant1_Low_2402_Peak



BLE_1M_Ant1_High_2480_AV



BLE_1M_Ant1_High_2480_Peak



A.8. Duty Cycle

Test Mode	Test	Ant	1/B[KHz]	Duty Cycle[%]	Verdict
BLE_1M	2480	Ant1	2.96	60.93	PASS

