

FCC REPORT

Applicant: OLIMPIA IT S.A.S

Address of Applicant: CALLE 24 NO. 7- 43 PISO 16 EDIFICIO SIETE24 BOGOTA DC
Colombia

Equipment Under Test (EUT)

Product Name: Fingerprint Smart Terminal

Model No.: R1000, OT-100

Trade mark: 

FCC ID: 2AYCPR1000

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 27 Nov., 2020

Date of Test: 28 Nov., to 10 Dec., 2020

Date of report issued: 11 Dec., 2020

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the JYT product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	11 Dec., 2020	Original

Tested by:

Mike.ou
Test Engineer

Date:

11 Dec., 2020

Reviewed by:

Winner Zhang
Project Engineer

Date:

11 Dec., 2020

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY	6
5.5 DESCRIPTION OF SUPPORT UNITS	6
5.6 RELATED SUBMITTAL(S) / GRANT (S).....	6
5.7 DESCRIPTION OF CABLE USED	6
5.8 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD	6
5.9 LABORATORY FACILITY	6
5.10 LABORATORY LOCATION.....	6
5.11 TEST INSTRUMENTS LIST	7
6 TEST RESULTS AND MEASUREMENT DATA	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION	13
7 TEST SETUP PHOTO	19
8 EUT CONSTRUCTIONAL DETAILS	21

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: The EUT not applicable of the test item.		
Test Method:	ANSI C63.4:2014	

5 General Information

5.1 Client Information

Applicant:	OLIMPIA IT S.A.S
Address:	CALLE 24 NO. 7- 43 PISO 16 EDIFICIO SIETE24 BOGOTA DC Colombia
Manufacturer:	Aratek Biometrics Technology CO., LTD.
Address:	2F, T2-A Building, Shenzhen Software Park, South Area, Hi-Tech Park, Shenzhen, Guangdong, China
Factory:	Aratek Biometrics Technology CO., LTD.
Address:	4F, 2th building, Nangang first industrial park, Baimang Songbai Road #1029, Nanshan district, Shenzhen, Guangdong, China.

5.2 General Description of E.U.T.

Product Name:	Fingerprint Smart Terminal
Model No.:	R1000, OT-100
Power supply:	Rechargeable Li-polymer Battery DC3.7V, 3000mAh
AC adapter:	Model: K-T10052000U Input: AC100-240V, 50/60Hz, 0.35A Output: DC 5.0V, 2000mA
Remark:	Model No.: R1000, OT-100 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Playing mode	Keep the EUT in Charging+Playing mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX7070	2J8XSZ2	DoC
DELL	MONITOR	SE2018HR	3M7QPY2	DoC
DELL	KEYBOARD	KB216d	N/A	DoC
DELL	MOUSE	MS116t1	N/A	DoC
HP	Printer	HP LaserJet P1007	VNFP409729	DoC

5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

5.7 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Shielding	1.0m	EUT	PC/Adapter

5.8 Additions to, deviations, or exclusions from the method

No

5.9 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.10 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>


5.11 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2020	07-21-2021
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-07-2020	03-06-2021
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
				11-18-2020	11-17-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
				11-18-2020	11-17-2021
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2020	07-20-2021
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dBμV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4(latest version) on conducted measurement.		
Test Instruments:	Refer to section 5.11 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement data:

Product name:	Fingerprint Smart Terminal	Product model:	R1000
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%




Trace: 17

	Freq	Read	LISN	Aux	Cable	Level	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	40.69	-0.57	-0.05	10.78	50.85	66.00	-15.15	QP
2	0.174	38.49	-0.58	-0.11	10.77	48.57	64.77	-16.20	QP
3	0.202	36.84	-0.59	-0.16	10.76	46.85	63.54	-16.69	QP
4	0.246	23.19	-0.57	-0.21	10.75	33.16	51.91	-18.75	Average
5	0.377	34.68	-0.50	0.27	10.72	45.17	58.34	-13.17	QP
6	0.377	22.64	-0.50	0.27	10.72	33.13	48.34	-15.21	Average
7	0.402	32.81	-0.48	0.42	10.72	43.47	57.81	-14.34	QP
8	0.402	23.69	-0.48	0.42	10.72	34.35	47.81	-13.46	Average
9	0.527	30.67	-0.45	-0.36	10.76	40.62	56.00	-15.38	QP
10	0.665	22.47	-0.51	-0.39	10.77	32.34	46.00	-13.66	Average
11	1.511	20.04	-0.55	-0.01	10.92	30.40	46.00	-15.60	Average
12	1.585	22.09	-0.55	-0.05	10.93	32.42	46.00	-13.58	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss + Aux Factor.

Product name:	Fingerprint Smart Terminal	Product model:	R1000
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




Trace: 19

	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.166	40.98	-0.68	0.01	10.77	51.08	65.16	-14.08	QP
2	0.377	35.76	-0.64	-0.04	10.72	45.80	58.34	-12.54	QP
3	0.377	24.46	-0.64	-0.04	10.72	34.50	48.34	-13.84	Average
4	0.402	32.43	-0.63	-0.06	10.72	42.46	57.81	-15.35	QP
5	0.402	22.31	-0.63	-0.06	10.72	32.34	47.81	-15.47	Average
6	0.454	30.33	-0.64	-0.01	10.74	40.42	56.80	-16.38	QP
7	0.489	19.78	-0.65	0.02	10.76	29.91	46.19	-16.28	Average
8	0.527	27.86	-0.65	0.03	10.76	38.00	56.00	-18.00	QP
9	0.665	18.59	-0.64	0.04	10.77	28.76	46.00	-17.24	Average
10	1.511	19.90	-0.70	0.13	10.92	30.25	46.00	-15.75	Average
11	1.577	25.82	-0.70	0.14	10.93	36.19	56.00	-19.81	QP
12	1.585	19.36	-0.70	0.14	10.93	29.73	46.00	-16.27	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss + Aux Factor.

Product name:	Fingerprint Smart Terminal	Product model:	R1000
Test by:	Mike	Test mode:	Charging & Playing mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%




	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	31.37	-0.57	-0.05	10.78	41.53	56.00	-14.47	Average
2	0.152	45.79	-0.57	-0.06	10.78	55.94	65.87	-9.93	QP
3	0.174	43.61	-0.58	-0.11	10.77	53.69	64.77	-11.08	QP
4	0.174	29.69	-0.58	-0.11	10.77	39.77	54.77	-15.00	Average
5	0.202	43.05	-0.59	-0.16	10.76	53.06	63.54	-10.48	QP
6	0.202	28.33	-0.59	-0.16	10.76	38.34	53.54	-15.20	Average
7	0.377	26.36	-0.50	0.27	10.72	36.85	48.34	-11.49	Average
8	0.381	37.57	-0.49	0.31	10.72	48.11	58.25	-10.14	QP
9	0.406	36.25	-0.48	0.36	10.72	46.85	57.73	-10.88	QP
10	0.406	26.02	-0.48	0.36	10.72	36.62	47.73	-11.11	Average
11	0.481	32.67	-0.44	-0.24	10.75	42.74	56.32	-13.58	QP
12	1.511	23.73	-0.55	-0.01	10.92	34.09	46.00	-11.91	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss + Aux Factor.

Product name:	Fingerprint Smart Terminal	Product model:	R1000
Test by:	Mike	Test mode:	Charging & Playing mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%





	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	43.05	-0.69	0.01	10.78	53.15	56.00	-2.85	Average
2	0.170	42.57	-0.68	0.01	10.77	52.67	54.94	-2.27	Average
3	0.174	22.20	-0.68	0.00	10.77	32.29	54.77	-22.48	Average
4	0.373	35.21	-0.64	-0.04	10.73	45.26	48.43	-3.17	Average
5	0.373	24.53	-0.64	-0.04	10.73	34.58	48.43	-13.85	Average
6	0.402	22.65	-0.63	-0.06	10.72	32.68	47.81	-15.13	Average
7	0.402	32.31	-0.63	-0.06	10.72	42.34	47.81	-5.47	Average
8	0.426	20.62	-0.64	-0.03	10.73	30.68	47.33	-16.65	Average
9	0.481	31.66	-0.65	0.02	10.75	41.78	46.32	-4.54	Average
10	0.665	17.78	-0.64	0.04	10.77	27.95	46.00	-18.05	Average
11	1.511	28.72	-0.70	0.13	10.92	39.07	46.00	-6.93	Average
12	1.585	18.85	-0.70	0.14	10.93	29.22	46.00	-16.78	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss + Aux Factor

6.2 Radiated Emission


Test Requirement:	FCC Part 15 B Section 15.109				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
RMS		1MHz	3MHz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
74.0			Peak Value		
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.				

	4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.11 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	All of the observed value above 6GHz were the noise floor , which were no recorded

Measurement Data:

Below 1GHz:

Product Name:	Fingerprint Smart Terminal	Product Model:	R1000
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB		dB	dBuV/m	dBuV/m	dB	
1	78.689	49.12	12.46	0.47	0.00	29.65	32.40	40.00	-7.60	QP
2	151.597	47.66	14.33	0.62	0.00	29.21	33.40	43.50	-10.10	QP
3	174.424	49.01	16.76	0.67	0.00	29.02	37.42	43.50	-6.08	QP
4	199.986	40.80	18.30	0.72	0.00	28.83	30.99	43.50	-12.51	QP
5	216.024	40.21	18.37	0.74	0.00	28.73	30.59	46.00	-15.41	QP
6	289.002	49.89	18.66	0.85	0.00	28.47	40.93	46.00	-5.07	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The Aux Factor is a notch filter switch box loss, this item is not used.

Product Name:	Fingerprint Smart Terminal	Product Model:	R1000
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	151.067	46.34	14.32	0.62	0.00	29.21	32.07	43.50	-11.43 QP
2	178.758	51.12	16.88	0.68	0.00	28.98	39.70	43.50	-3.80 QP
3	183.201	50.88	17.09	0.69	0.00	28.95	39.71	43.50	-3.79 QP
4	199.286	47.34	18.23	0.72	0.00	28.83	37.46	43.50	-6.04 QP
5	286.982	51.70	18.65	0.85	0.00	28.47	42.73	46.00	-3.27 QP
6	307.831	50.67	18.72	0.87	0.00	28.47	41.79	46.00	-4.21 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The Aux Factor is a notch filter switch box loss, this item is not used.

Above 1GHz:

Product Name:	Fingerprint Smart Terminal	Product Model:	R1000
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	4808.328	50.02	30.78	6.40	2.44	41.81	47.83	74.00	-26.17	Peak
2	4808.328	41.35	30.78	6.40	2.44	41.81	39.16	54.00	-14.84	Average
3	5279.087	50.04	31.83	6.81	2.58	41.91	49.35	74.00	-24.65	Peak
4	5279.087	41.23	31.83	6.81	2.58	41.91	40.54	54.00	-13.46	Average
5	5762.199	49.33	32.41	7.12	2.73	41.98	49.61	74.00	-24.39	Peak
6	5762.199	40.28	32.41	7.12	2.73	41.98	40.56	54.00	-13.44	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss + Aux Factor – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Fingerprint Smart Terminal	Product Model:	R1000
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



	Freq	Read	Antenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	dBuV/m	dBuV/m	dB	
		dBuV	dB/m	dB	dB	dB				
1	4864.797	49.25	30.90	6.44	2.47	41.83	47.23	74.00	-26.77	Peak
2	4864.797	41.41	30.90	6.44	2.47	41.83	39.39	54.00	-14.61	Average
3	5477.920	48.79	32.23	6.97	2.65	41.84	48.80	74.00	-25.20	Peak
4	5477.920	40.29	32.23	6.97	2.65	41.84	40.30	54.00	-13.70	Average
5	5967.604	49.64	32.49	7.21	2.79	42.04	50.09	74.00	-23.91	Peak
6	5967.604	41.53	32.49	7.21	2.79	42.04	41.98	54.00	-12.02	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss + Aux Factor – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.