

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093) and
IEEE Std 1528-2013**

Product Name: POS Device

Model No.: I24M01

Serial Model: N/A

Brand Name: N/A

Report No.: AiTSZ-250402032FW1

FCC ID: 2AYD5-I24M01

Prepared for

IMIN TECHNOLOGY PTE LTD

11 Bishan Street 21 #03-05 Singapore 573943

Prepared by

Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai
Street, Bao'an District, Shenzhen, Guangdong, China

Tel.: +86 0755-230967639

Fax.: +86 0755-230967639

TEST RESULT CERTIFICATION

Applicant's name : IMIN TECHNOLOGY PTE LTD
Address : 11 Bishan Street 21 #03-05 Singapore 573943
Manufacturer's Name : IMIN TECHNOLOGY PTE LTD
Address : 11 Bishan Street 21 #03-05 Singapore 573943

Product description

Product name : POS Device
Trademark : N/A
Model and/or type reference : I24M01
Serial Model..... : N/A
FCC 47 CFR Part 2(2.1093)

Standards : IEEE Std 1528-2013

Published RF exposure KDB procedures

This device described above has been tested by Guangdong Asia Hongke Test Technology Limited. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited, this document may be altered or revised by Guangdong Asia Hongke Test Technology Limited, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... : Apr. 03, 2025 ~ Apr. 16, 2025
Date of Issue..... : Apr. 19, 2025
Test Result..... : **Pass**

Reviewed by: 
Simba Huang

Approved by: 
Seal.chen

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Apr. 19, 2025	Seal.chen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits	6
1.2. Statement of Compliance	7
1.3. EUT Description	8
1.4. Test specification(s)	10
1.5. Ambient Condition	10
1.6. Test Facility	10
2. SAR Measurement System	11
2.1. SATIMO SAR Measurement Set-up Diagram	11
2.2. Robot	12
2.3. Probe	13
2.3.1. E-Field Probe Calibration	13
2.4. Phantoms	14
2.5. Technical Data	15
2.6. Device Holder	16
2.7. Test Equipment List	17
3. SAR Measurement Procedures	19
3.1. Power Reference	19
3.2. Area scan & Zoom scan	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure	22
4.1. Tissue Verification	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	25
5. SAR measurement variabilit.....	26
6. SAR Measurement Uncertainty.....	27
7. RF Exposure Positions	28
7.1. Devices used next to or against the body without an accessory.....	28
7.2. Extremity exposure considerations	29
8. RF Output Power	30
8.1. GSM Conducted Power	30
8.2. WCDMA Conducted Power.....	31
8.3. LTE Conducted Power.....	33
8.4. Wi-Fi & BT Output Power	53
8.5. NFC	55
9. Antenna Location.....	56
10. Stand-alone SAR test exclusion	57

11. SAR Measurement Results	58
12. Simultaneous Transmission Analysis	72
Appendix A. Photo documentation	73
Appendix B. System Check Plots	74
Appendix C. SAR Test Plots.....	95
Appendix D. Calibration Certificate	140
Appendix E. Justification of the extended calibration	209

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
TRUNK EXTREMITY LIMIT
4.0 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing as follows.

Band	Max SAR Value Reported(W/kg)	
	10-g Body (Separation distance of 0mm)	Max SAR Summation
GSM850	0.739	Body : 1.263
GSM1900	0.459	
WCDMA Band II	0.689	
WCDMA Band V	0.380	
LTE band 2	0.879	
LTE band 4	0.865	
LTE band 5	0.417	
LTE band 7	0.566	
LTE band 12	0.474	
LTE band 13	0.807	
LTE band 14	0.443	
LTE band 17	0.448	
LTE band 25	0.769	
LTE band 26a	0.427	
LTE band 26b	0.435	
LTE band 41	0.621	
LTE band 66	0.850	
2.4GHz WLAN	0.122	
5.2GHz WLAN	0.321	
5.3GHz WLAN	0.284	
5.6GHz WLAN	0.336	
5.8GHz WLAN	0.384	

NOTE: The Max SAR Summation is calculated based on the same configuration and test position.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (extremity limit for 4.0 W/kg) specified in FCC 47 CFR Part 2(2.1093), and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name	POS Device		
Model Name	I24M01		
Family Model	N/A		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna Type	Internal Antenna		
Power rating:	DC 7.7V 3350mAh 25.795Wh Rechargeable Li-ion battery		
Hardware version	N/A		
Software version	N/A		
Device Operating Configurations			
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/5, LTE Band 2/4/5/7/12/13/14/17/25/26a/26b/41/66, WLAN 2.4G/5G, Bluetooth, NFC		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16-QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, π /4DQPSK, 8DPSK), NFC(ASK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 13	777-787	746-756
	LTE Band 14	788-798	758-768
	LTE Band 17	704-716	734-746
	LTE Band 25	1850-1915	1930-1995
	LTE Band 26a	814-824	859-869
	LTE Band 26b	824-849	869-894
	LTE Band 41	2496-2690	
	LTE Band 66	1710-1780	2110-2200
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	

	WLAN 5.3G	5260-5320
	WLAN 5.6G	5500-5700
	WLAN 5.8G	5745-5825
	NFC	13.56
	Bluetooth	2402-2480
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
EGPRS Multislot Class(12)	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
Power Class	4, tested with power level 5(GSM 850)	
	1, tested with power level 0(GSM 1900)	
	3, tested with power control "all 1"(WCDMA Band 2)	
	3, tested with power control "all 1"(WCDMA Band 5)	
	3, tested with power control all Max.(LTE Band 2)	
	3, tested with power control all Max.(LTE Band 4)	
	3, tested with power control all Max.(LTE Band 5)	
	3, tested with power control all Max.(LTE Band 7)	
	3, tested with power control all Max.(LTE Band 12)	
	3, tested with power control all Max.(LTE Band 13)	
	3, tested with power control all Max.(LTE Band 14)	
	3, tested with power control all Max.(LTE Band 17)	
	3, tested with power control all Max.(LTE Band 25)	
	3, tested with power control all Max.(LTE Band 26a)	
	3, tested with power control all Max.(LTE Band 26b)	
	3, tested with power control all Max.(LTE Band 41)	
	3, tested with power control all Max.(LTE Band 66)	

1.4. Test specification(s)

FCC 47 CFR Part 2(2.1093)
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

1.6. Test Facility

Test Laboratory:

Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

FCC-Registration No.: 251906 Designation Number: CN1376

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 31737 CAB identifier: CN0165


The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

A2LA-Lab Cert. No.: 7133.01

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe EPGO 0523-403 with following specifications is used.



- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 150 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within $\pm 0.25\text{dB}$. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. Phantoms


For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



SAM

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.6. Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

2.7. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	EPGO 0523-403	Sep. 11, 2024	Sep. 10, 2025
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DI P 0G900-348	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	2300 MHz Dipole	SID2300	SN 03/16 DIP 2G300-358	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	Jul. 01, 2024	Jun. 30, 2025
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	Jul. 01, 2024	Jun. 30, 2025
☒	R&S	Universal radio communication tester	CMU200	117858	Jul. 01, 2024	Jun. 30, 2025
☒	R&S	Wideband radio communication tester	CMW500	116581	Jul. 01, 2024	Jun. 30, 2025
☒	HP	Network Analyzer	8753D	3410J01136	Jul. 01,	Jun. 30,

					2024	2025
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power meter	E4419B	MY45102538	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power meter	E4419B	MY45102140	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power meter	E4419B	MY45102215	Jul. 01, 2024	Jun. 30, 2025
☒	JFW	attenuator	50FPE-006	4360846-494-4	Jul. 01, 2024	Jun. 30, 2025
☒	JFW	attenuator	50FPE-006	4360846-492-1	Jul. 01, 2024	Jun. 30, 2025
☒	JFW	attenuator	50FPE-006	4360846-490-6	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power sensor	E9301A	MY41495644	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power sensor	E9301A	US39212148	Jul. 01, 2024	Jun. 30, 2025
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2024	Jul. 16, 2027
☒	MVG	SAR Phantom	SSM2	SN 24/11 SAM87	NCR	NCR
☒	MVG	Device Holder	SMPPD	SN 24/11 MSH73	NCR	NCR

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For Wi-Fi/BT power measurement, use engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure Wi-Fi/BT output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan

above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^{\circ} \pm 1^{\circ}$	$20^{\circ} \pm 1^{\circ}$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine these highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists of a full 3D scan over a specific area. This 3D scan is useful for multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scans to calculate the SAR value of the combined measurement as it is defined in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT installed full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
	750	835	900	1800	1900	2000	2450	2600	5200	5800
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.



4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	$\sigma \text{ (S/m)} (\pm 5\%)$	ϵ_r	$\sigma \text{ (S/m)}$		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	42.56	0.91	21.4 °C	Apr. 03, 2025
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	42.01	0.94	21.0 °C	Apr. 04, 2025
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.61	1.41	21.3 °C	Apr. 07, 2025
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	41.42	1.39	21.7 °C	Apr. 08, 2025
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	40.41	1.82	21.6 °C	Apr. 09, 2025
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	39.43	1.99	21.2 °C	Apr. 10, 2025
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	37.40	4.51	21.1 °C	Apr. 11, 2025
Head 5400	5400	35.80 (34.01~37.59)	4.86 (4.62~5.10)	35.10	4.70	21.0 °C	Apr. 14, 2025
Head 5600	5600	35.50 (33.73~37.28)	5.07 (4.82~5.32)	34.20	4.90	21.3 °C	Apr. 15, 2025
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	35.30	5.27	21.2 °C	Apr. 16, 2025

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Power fed to reference dipole (mW)	Measured SAR Value		Measured SAR (Normalized to 1W)		Target SAR Value (1W)		Deviation (%)		Test Date
		1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)	
750MHz	100	0.930	0.621	9.30	6.21	8.60	5.78	8.14%	7.44%	Apr. 03, 2025
835MHz	100	1.011	0.612	10.11	6.12	9.40	6.28	7.55%	-2.55%	Apr. 04, 2025
1800MHz	100	3.832	2.025	38.32	20.25	37.06	20.01	3.40%	1.20%	Apr. 07, 2025
1900MHz	100	4.154	2.153	41.54	21.53	39.69	20.92	4.66%	2.92%	Apr. 08, 2025
2450MHz	100	5.184	2.359	51.84	23.59	50.05	23.80	3.58%	-0.88%	Apr. 09, 2025
2600MHz	100	5.433	2.523	54.33	25.23	54.16	24.85	0.31%	1.53%	Apr. 10, 2025
5200MHz	100	14.712	5.212	147.12	52.12	162.59	56.21	-9.51%	-7.28%	Apr. 11, 2025
5400MHz	100	14.820	5.532	148.20	55.32	159.81	55.00	-7.26%	0.58%	Apr. 14, 2025
5600MHz	100	16.421	5.602	164.21	56.02	179.15	61.01	-8.34%	-8.18%	Apr. 15, 2025
5800MHz	100	16.421	5.623	164.21	56.23	182.20	61.32	-9.87%	-8.30%	Apr. 16, 2025

5. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.

2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.

3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

6. SAR Measurement Uncertainty


Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

7. RF Exposure Positions

7.1. Devices used next to or against the body without an accessory

A typical example of a device used next to the body is a wireless enabled laptop or a tablet device containing a peripheral plug-in radio transmitter that can be supported on the user's body. Other devices that fall into this category include tablets of equivalent sizes or larger than a netbook computer (> 20 cm diagonal display), credit card transaction authorization terminals, and point-of-sale and/or inventory terminals.

The DUT shall be positioned with its base (bottom surface) and applicable edges against the flat phantom. The orientations and other use positions can be host device specific. Therefore, these should be determined according to the transmitter and antenna locations on the host device.



Test positions for body supported devices (Wireless credit card transaction authorization terminal)

7.2. Extremity exposure considerations

1. Based on the actual use, we always hold it by our left hand, so we only take the Extremity SAR of left side, front side and back side at device into consideration. We will test the front side, left side and right side of this device. (We test the right side aiming to stimulate left hand for finger exposes to LTE, WCDMA, GSM when using.)
2. WIFI antenna is the nearest away from left side at the device. LTE, WCDMA, GSM antenna are far away from left side at the device.
3. The nearest distance between the left hand's fingers and the LTE, WCDMA, GSM antenna is 6cm, when we always hold it by our left hand. And we use 0cm from the phantom to the right side at the device to test SAR, which is substitution method we mentioned, to evaluate the SAR of the left hand's fingers.
4. The Extremity SAR of the backside of this device for WIFI antenna, we will calculate it by following SAR exemption.

8. RF Output Power

8.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Factor	Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	128	189	251		Tune-up	128	189	251
Frequency (MHz)		824.2	836.4	848.8			824.2	836.4	848.8
GSM (GMSK)	/	/	/	/	/	/	/	/	/
GPRS(GMSK,1 Tx slot)	33.00	32.62	32.62	32.60	-9.03	23.97	23.59	23.59	23.57
GPRS(GMSK,2 Tx slot)	32.50	32.02	31.99	32.02	-6.02	26.48	26.00	25.97	26.00
GPRS(GMSK,3 Tx slot)	30.50	29.98	29.99	30.02	-4.26	26.24	25.72	25.73	25.76
GPRS(GMSK,4 Tx slot)	30.50	30.01	29.99	29.97	-3.01	27.49	27.00	26.98	26.96
EGPRS(8PSK,1 Tx slot)	30.50	29.98	29.98	30.01	-9.03	21.47	20.95	20.95	20.98
EGPRS(8PSK,2 Tx slot)	30.50	30.02	30.00	29.99	-6.02	24.48	24.00	23.98	23.97
EGPRS(8PSK,3 Tx slot)	30.50	29.99	30.01	29.99	-4.26	26.24	25.73	25.75	25.73
EGPRS(8PSK,4 Tx slot)	30.50	30.01	30.01	30.03	-3.01	27.49	27.00	27.00	27.02

Band GSM1900	Burst-Averaged output Power (dBm)				Factor	Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	512	661	810		Tune-up	512	661	810
Frequency (MHz)		1850.2	1880	1909.8			1850.2	1880	1909.8
GSM (GMSK)	/	/	/	/	/	/	/	/	/
GPRS(GMSK,1 Tx slot)	30.00	29.61	29.62	29.59	-9.03	20.97	20.58	20.59	20.56
GPRS(GMSK,2 Tx slot)	30.00	29.53	29.50	29.50	-6.02	23.98	23.51	23.48	23.48
GPRS(GMSK,3 Tx slot)	29.50	28.99	29.02	28.99	-4.26	25.24	24.73	24.76	24.73
GPRS(GMSK,4 Tx slot)	29.50	28.99	29.01	29.02	-3.01	26.49	25.98	26.00	26.01
EGPRS(8PSK,1 Tx slot)	29.50	29.03	29.03	29.03	-9.03	20.47	20.00	20.00	20.00
EGPRS(8PSK,2 Tx slot)	29.50	28.98	29.01	29.01	-6.02	23.48	22.96	22.99	22.99
EGPRS(8PSK,3 Tx slot)	29.50	29.02	28.99	29.02	-4.26	25.24	24.76	24.73	24.76
EGPRS(8PSK,4 Tx slot)	29.50	29.02	29.01	28.98	-3.01	26.49	26.01	26.00	25.97

Note:

Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme.

Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link

Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link

Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link

SAR testing was performed on the maximum frame-averaged power mode.

The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum

Burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB

Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB

Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB

Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB

8.2. WCDMA Conducted Power

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

1. Release99 Setup Configuration

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm1
	β_c/β_d	8/15

2. HSDPA Setup Configuration

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 1			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

3. HSUPA Setup Configuration

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm1				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	15/15
	β_{ec}	209/225	12/15	30/15	2/15	24/15
	β_c/β_d	11/15	6/15	15/9	2/15	15/15
	β_{hs}	22/15	12/15	30/15	4/15	30/15
	β_{ed}	1309/225	94/75	47/15 47/15	56/75	134/15
	CM (dB)	1.0	3.0	2.0	3.0	1.0
HSDPA Specific Settings	D_{ACK}	8				
	D_{NAK}	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				

HSUPA Specific Settings	CQI Repetition Factor (Table 5.2B.4)	2				
	Ahs = β_{hs}/β_c	30/15				
	D E-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9

4. WCDMA Conducted Power Results

Choose the highest output power mode RMC 12.2Kbps for Band V/II at middle channel to test SAR and determine the worst configuration for further high/low channel test.

WCDMA Band II	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC12.2K	24.00	23.51	23.57	23.51
HSDPA Sub 1	24.00	23.54	23.56	23.59
HSDPA Sub 2	23.00	22.57	22.61	22.60
HSDPA Sub 3	23.00	22.53	22.61	22.62
HSDPA Sub 4	23.00	22.53	22.57	22.54
HSUPA Sub 1	23.00	22.50	22.53	22.58
HSUPA Sub 2	23.00	22.63	22.57	22.62
HSUPA Sub 3	23.00	22.58	22.66	22.63
HSUPA Sub 4	23.00	22.59	22.63	22.65
HSUPA Sub 5	23.00	22.67	22.67	22.51

WCDMA Band V	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC12.2K	24.00	23.54	23.46	23.61
HSDPA Sub 1	24.00	23.48	23.57	23.53
HSDPA Sub 2	23.00	22.68	22.55	22.62
HSDPA Sub 3	23.00	22.56	22.66	22.53
HSDPA Sub 4	23.00	22.63	22.56	22.53
HSUPA Sub 1	23.00	22.51	22.55	22.57
HSUPA Sub 2	23.00	22.64	22.60	22.66
HSUPA Sub 3	23.00	22.57	22.52	22.66
HSUPA Sub 4	23.00	22.64	22.59	22.53
HSUPA Sub 5	23.00	22.64	22.54	22.64

8.3. LTE Conducted Power

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 36.521-1 specification. A summary of these configurations are illustrated below:

Test Parameters for Channel Bandwidths				
Ch BW	Downlink Configuration	Mod'n	Uplink Configuration	
	N/A for Max UE output power testing		RB allocation	
			FDD	TDD
1.4MHz		QPSK	1	1
1.4MHz		QPSK	5	5
3MHz		QPSK	1	1
3MHz		QPSK	4	4
5MHz		QPSK	1	1
5MHz		QPSK	8	8
10MHz		QPSK	1	1
10MHz		QPSK	12	12
15MHz		QPSK	1	1
15MHz		QPSK	16	16
20MHz		QPSK	1	1
20MHz		QPSK	18	18

Note 1: Test Channel Bandwidths are checked separately for each E-UTRA band, the applicable channel bandwidths are specified in Table 5.4.2.1-1.

Note 2: For E-UTRA bands not applied with Note 2 in Table 6.2.2.3-1:

- The 1 RB allocation shall be tested at RB#0 for low and mid range, RB #max for high range test frequency.
- The RBstart of non-1RB allocation shall be RB #0 for low and mid range, RB# (max +1 - RB allocation) for high range test frequency.

Note 3: For E-UTRA bands applied with Note 2 in Table 6.2.2.3-1:

- If the test channel bandwidth is larger than 4MHz, then the 1 RB allocation shall be tested at both RB #0 and RB #max.
- If the test channel bandwidth is smaller or equal to 4MHz, then the 1 RB allocation shall be tested at RB #0.
- If the test channel bandwidth = (FUL_high - FUL_low) specified by the operating band, then only one frequency range shall be tested and the 1 RB allocation shall be tested at RB #0, RB # $\left\lceil N_{RB}^{UL} / 2 \right\rceil$ and RB #max.
- For non-1RB allocation, test frequency is middle range, and the RBstart shall be RB #0.

2. LTE Conducted Power Results

LTE output list

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	22.50	22.33	22.38	22.43
			1	2	22.50	22.37	22.33	22.42
			1	5	22.50	22.28	22.38	22.47
			3	0	23.00	22.40	22.41	22.52
			3	1	23.00	22.40	22.42	22.52
			3	2	23.00	22.36	22.42	22.51
			6	0	22.00	21.49	21.52	21.61
		16QAM	1	0	21.50	21.11	21.24	21.16
			1	2	21.50	21.12	21.24	21.31
			1	5	21.50	21.15	21.04	21.35
			3	0	21.50	21.20	21.31	21.30
			3	1	21.50	21.20	21.24	21.38
			3	2	21.50	21.28	21.18	21.27
			6	0	21.00	20.46	20.35	20.58
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	22.50	22.25	22.26	22.26
			1	7	22.50	22.32	22.33	22.42
			1	14	22.50	22.24	22.25	22.28
			8	0	22.00	21.39	21.44	21.48
			8	4	22.00	21.39	21.42	21.47
			8	7	22.00	21.46	21.45	21.52
			15	0	21.50	21.46	21.47	21.49
		16QAM	1	0	21.50	20.94	21.00	21.03
			1	7	21.50	21.19	21.18	21.30
			1	14	21.50	21.19	21.25	21.31
			8	0	21.00	20.35	20.38	20.51
			8	4	21.00	20.39	20.40	20.47
			8	7	21.00	20.44	20.42	20.57
			15	0	20.50	20.33	20.34	20.46
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	23.00	22.51	22.59	22.53
			1	12	23.00	22.61	22.61	22.66
			1	24	23.00	22.40	22.47	22.54
			12	0	22.00	21.49	21.49	21.59
			12	6	22.00	21.44	21.50	21.61
			12	11	22.00	21.43	21.53	21.53
			25	0	22.00	21.46	21.53	21.59
		16QAM	1	0	22.00	21.53	21.56	21.54
			1	12	22.00	21.50	21.56	21.65
			1	24	22.00	21.36	21.41	21.53
			12	0	21.00	20.45	20.51	20.66

			12	6	21.00	20.38	20.46	20.53
			12	11	21.00	20.47	20.50	20.56
			25	0	21.00	20.46	20.52	20.54
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.00	22.52	22.56	22.50
			1	24	23.00	22.59	22.57	22.60
			1	49	23.00	22.51	22.55	22.72
			25	0	22.00	21.45	21.51	21.51
			25	12	22.00	21.43	21.50	21.51
			25	24	22.00	21.48	21.57	21.51
			50	0	22.00	21.50	21.53	21.47
		16QAM	1	0	22.00	21.40	21.47	21.34
			1	24	22.00	21.54	21.57	21.61
			1	49	22.00	21.29	21.31	21.41
			25	0	21.00	20.42	20.51	20.52
			25	12	21.00	20.43	20.44	20.49
			25	24	21.00	20.53	20.57	20.52
			50	0	21.00	20.52	20.57	20.54
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band 2	15MHz	QPSK	1	0	23.00	22.43	22.51	22.37
			1	37	23.00	22.64	22.65	22.63
			1	74	23.00	22.43	22.33	22.51
			36	0	22.00	21.47	21.55	21.39
			36	18	22.00	21.31	21.39	21.38
			36	37	22.00	21.63	21.52	21.70
			75	0	22.00	21.53	21.52	21.48
		16QAM	1	0	22.00	21.51	21.63	21.49
			1	37	22.00	21.59	21.66	21.64
			1	74	22.00	21.31	21.28	21.35
			36	0	22.00	21.54	21.62	21.48
			36	18	22.00	21.60	21.61	21.68
			36	37	22.00	21.30	21.25	21.35
			75	0	21.00	20.48	20.50	20.46
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.00	22.35	22.45	22.27
			1	49	23.00	22.55	22.56	22.62
			1	99	23.00	22.53	22.35	22.54
			50	0	22.00	21.54	21.38	21.39
			50	24	22.00	21.54	21.41	21.41
			50	49	22.00	21.66	21.50	21.47
			100	0	22.00	21.58	21.49	21.48
		16QAM	1	0	22.00	21.55	21.59	21.38
			1	49	22.00	21.48	21.57	21.56
			1	99	22.00	21.36	21.17	21.36
			50	0	21.00	20.56	20.45	20.35

			50	24	21.00	20.55	20.41	20.35
			50	49	21.00	20.66	20.51	20.55
			100	0	21.00	20.58	20.44	20.45

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	22.50	21.40	22.22	22.25
			1	2	22.50	22.25	22.30	22.17
			1	5	22.50	22.16	22.16	22.25
			3	0	22.50	22.32	22.30	22.33
			3	1	22.50	22.31	22.31	22.31
			3	2	22.50	22.33	22.27	22.28
			6	0	21.50	21.40	21.40	21.41
		16QAM	1	0	21.50	21.06	21.13	21.03
			1	2	21.50	21.02	21.05	21.07
			1	5	21.50	21.11	21.10	21.11
			3	0	21.50	21.06	21.12	21.15
			3	1	21.50	21.13	21.13	21.10
			3	2	21.50	21.07	21.15	21.15
			6	0	20.50	20.21	20.34	20.39
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	22.50	22.10	21.98	22.07
			1	7	22.50	22.16	22.22	22.23
			1	14	22.50	22.09	22.11	22.07
			8	0	21.50	21.25	21.27	21.28
			8	4	21.50	21.27	21.31	21.28
			8	7	21.50	21.30	21.33	21.39
			15	0	21.50	21.31	21.29	21.33
		16QAM	1	0	21.50	20.80	20.95	21.01
			1	7	21.50	21.00	21.23	21.01
			1	14	21.50	21.10	20.91	20.93
			8	0	20.50	20.24	20.24	20.25
			8	4	20.50	20.26	20.29	20.26
			8	7	20.50	20.28	20.32	20.27
			15	0	20.50	20.23	20.22	20.28
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.00	22.20	22.31	22.31
			1	12	23.00	22.51	22.49	22.43
			1	24	23.00	22.35	22.31	22.41
			12	0	21.50	21.32	21.32	21.32
			12	6	21.50	21.33	21.30	21.33
			12	11	21.50	21.42	21.39	21.39
			25	0	21.50	21.35	21.33	21.35
		16QAM	1	0	22.00	21.16	21.32	21.22
			1	12	22.00	21.52	21.44	21.44
			1	24	22.00	21.33	21.32	21.44

			12	0	20.50	20.25	20.30	20.26
			12	6	20.50	20.31	20.23	20.31
			12	11	20.50	20.33	20.34	20.37
			25	0	20.50	20.41	20.34	20.40
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.00	22.30	22.26	22.31
			1	24	23.00	22.41	22.51	22.47
			1	49	23.00	22.45	22.44	22.44
			25	0	21.50	21.24	21.30	21.26
			25	12	21.50	21.25	21.27	21.32
			25	24	21.50	21.40	21.41	21.37
			50	0	21.50	21.33	21.37	21.39
		16QAM	1	0	21.50	21.12	21.13	21.33
			1	24	21.50	21.29	21.48	21.21
			1	49	21.50	21.45	21.26	21.29
			25	0	20.50	20.30	20.26	20.25
			25	12	20.50	20.27	20.29	20.26
			25	24	20.50	20.42	20.39	20.45
			50	0	20.50	20.36	20.39	20.39
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.00	22.11	22.20	22.22
			1	37	23.00	22.48	22.52	22.36
			1	74	23.00	22.44	22.32	22.40
			36	0	22.00	21.28	21.22	20.99
			36	18	22.00	21.48	21.27	21.59
			36	37	22.00	21.21	21.57	21.54
			75	0	21.50	21.40	21.39	21.42
		16QAM	1	0	22.00	20.96	21.25	21.19
			1	37	22.00	21.54	21.51	21.28
			1	74	22.00	21.50	21.22	21.55
			36	0	22.00	20.98	21.25	21.22
			36	18	22.00	21.56	21.52	21.24
			36	37	22.00	21.49	21.26	21.51
			75	0	20.50	20.38	20.35	20.34
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.00	22.14	22.12	22.09
			1	49	23.00	22.53	22.45	22.52
			1	99	23.00	22.36	22.39	22.49
			50	0	21.50	21.27	21.24	21.21
			50	24	21.50	21.26	21.26	21.22
			50	49	21.50	21.41	21.38	21.39
			100	0	21.50	21.33	21.32	21.32
		16QAM	1	0	22.00	20.91	21.25	21.08
			1	49	22.00	21.66	21.42	21.28
			1	99	22.00	21.35	21.21	21.60

			50	0	20.50	20.27	20.24	20.25
			50	24	20.50	20.25	20.20	20.30
			50	49	20.50	20.39	20.43	20.41
			100	0	20.50	20.31	20.31	20.31

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	25.00	24.66	24.80	24.71
			1	2	25.00	24.70	24.76	24.75
			1	5	25.00	24.76	24.75	24.71
			3	0	25.00	24.67	24.83	24.72
			3	1	25.00	24.67	24.84	24.66
			3	2	25.00	24.74	24.78	24.66
			6	0	24.00	23.87	23.92	23.82
		16QAM	1	0	24.00	23.37	23.52	23.37
			1	2	24.00	23.56	23.60	23.43
			1	5	24.00	23.37	23.55	23.42
			3	0	24.00	23.46	23.61	23.42
			3	1	24.00	23.42	23.59	23.47
			3	2	24.00	23.41	23.54	23.37
			6	0	23.00	22.66	22.80	22.80
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	25.00	24.50	24.61	24.59
			1	7	25.00	24.71	24.76	24.65
			1	14	25.00	24.70	24.70	24.57
			8	0	24.00	23.73	23.80	23.66
			8	4	24.00	23.77	23.82	23.64
			8	7	24.00	23.75	23.81	23.72
			15	0	24.00	23.68	23.79	23.67
		16QAM	1	0	24.00	23.36	23.49	23.23
			1	7	24.00	23.58	23.66	23.43
			1	14	24.00	23.33	23.36	23.46
			8	0	23.00	22.70	22.80	22.71
			8	4	23.00	22.72	22.82	22.66
			8	7	23.00	22.70	22.87	22.70
			15	0	23.00	22.63	22.77	22.61
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	25.50	24.79	24.93	24.89
			1	12	25.50	25.13	25.06	24.96
			1	24	25.50	24.90	24.86	24.82
			12	0	24.00	23.81	23.80	23.75
			12	6	24.00	23.81	23.80	23.75
			12	11	24.00	23.78	23.89	23.79
			25	0	24.00	23.80	23.85	23.78
		16QAM	1	0	24.00	23.74	23.93	23.67
			1	12	24.00	23.85	23.90	23.90
			1	24	24.00	23.72	23.70	23.68

			12	0	23.00	22.78	22.87	22.71
			12	6	23.00	22.73	22.83	22.77
			12	11	23.00	22.76	22.90	22.83
			25	0	23.00	22.78	22.88	22.87
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band 5	10MHz	QPSK	1	0	25.00	24.87	24.96	24.98
			1	24	25.00	25.00	24.95	24.92
			1	49	25.00	24.97	24.95	24.85
			25	0	24.00	23.91	23.77	23.95
			25	12	24.00	23.88	23.75	23.90
			25	24	24.00	23.92	23.85	23.95
			50	0	24.00	23.92	23.79	23.97
		16QAM	1	0	24.00	23.47	23.66	23.61
			1	24	24.00	23.72	23.77	23.65
			1	49	24.00	23.90	23.83	23.76
			25	0	23.00	22.86	22.81	22.91
			25	12	23.00	22.85	22.74	22.95
			25	24	23.00	22.88	22.89	22.91
			50	0	23.00	22.86	22.81	22.93

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	23.00	22.15	22.55	22.78
			1	12	23.00	22.26	22.64	22.84
			1	24	23.00	22.13	22.45	22.77
			12	0	22.00	21.07	21.53	21.81
			12	6	22.00	21.10	21.56	21.81
			12	11	22.00	21.10	21.47	21.69
			25	0	22.00	21.14	21.52	21.77
		16QAM	1	0	22.00	21.17	21.55	21.74
			1	12	22.00	21.18	21.56	21.81
			1	24	22.00	21.01	21.40	21.67
			12	0	21.00	20.15	20.58	20.86
			12	6	21.00	20.10	20.53	20.78
			12	11	21.00	20.13	20.47	20.70
			25	0	21.00	20.14	20.55	20.78
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	23.00	22.14	22.52	22.67
			1	24	23.00	22.22	22.62	22.77
			1	49	23.00	22.21	22.60	22.91
			25	0	22.00	21.08	21.56	21.66
			25	12	22.00	21.08	21.54	21.69
			25	24	22.00	21.17	21.52	21.64
			50	0	22.00	21.15	21.57	21.70
		16QAM	1	0	22.00	20.97	21.41	21.51
			1	24	22.00	21.17	21.65	21.77
			1	49	22.00	20.96	21.34	21.64

			25	0	21.00	20.16	20.58	20.75
			25	12	21.00	20.10	20.58	20.65
			25	24	21.00	20.26	20.58	20.77
			50	0	21.00	20.23	20.62	20.79
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	15.50	14.57	15.03	15.19
			1	37	15.50	14.89	15.29	15.48
			1	74	15.50	14.90	15.10	15.37
			36	0	15.00	13.58	14.04	14.16
			36	18	15.00	13.65	13.98	14.18
			36	37	15.00	14.04	14.19	14.52
			75	0	14.50	13.79	14.14	14.26
		16QAM	1	0	14.50	13.64	13.64	14.27
			1	37	14.50	13.87	13.87	14.44
			1	74	14.50	13.69	13.69	14.19
			36	0	14.50	13.67	13.67	14.22
			36	18	14.50	13.84	13.84	14.44
			36	37	14.50	13.69	13.69	14.26
			75	0	13.50	12.86	12.86	13.33
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.00	22.03	22.32	22.41
			1	49	23.00	22.21	22.63	22.72
			1	99	23.00	22.24	22.49	22.83
			50	0	22.00	20.92	21.60	21.44
			50	24	22.00	20.92	21.57	21.45
			50	49	22.00	21.28	21.44	21.58
			100	0	22.00	21.14	21.51	21.55
		16QAM	1	0	22.00	21.11	21.44	21.46
			1	49	22.00	21.16	21.58	21.71
			1	99	22.00	21.01	21.28	21.59
			50	0	21.00	19.94	20.60	20.44
			50	24	21.00	19.94	20.55	20.47
			50	49	21.00	20.37	20.50	20.73
			100	0	21.00	20.17	20.53	20.59

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	24.50	24.44	24.33	24.45
			1	2	24.50	24.46	24.44	24.42
			1	5	24.50	24.46	24.39	24.49
			3	0	25.00	24.47	24.45	24.55
			3	1	25.00	24.49	24.43	24.50
			3	2	25.00	24.47	24.44	24.51
			6	0	24.00	23.56	23.54	23.61
		16QAM	1	0	23.50	23.33	23.27	23.29
			1	2	23.50	23.38	23.33	23.38
			1	5	23.50	23.18	23.17	23.22
			3	0	23.50	23.31	23.22	23.34

			3	1	23.50	23.22	23.27	23.27
			3	2	23.50	23.19	23.23	23.23
			6	0	23.00	22.40	22.55	22.42
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	25.00	24.27	24.27	24.25
			1	7	25.00	24.50	24.39	24.39
			1	14	25.00	24.35	24.35	24.37
			8	0	24.00	23.41	23.40	23.58
			8	4	24.00	23.44	23.46	23.55
			8	7	24.00	23.49	23.50	23.48
			15	0	24.00	23.50	23.49	23.50
		16QAM	1	0	23.50	23.26	23.19	23.10
			1	7	23.50	23.38	23.34	23.36
			1	14	23.50	23.05	23.08	23.17
			8	0	23.00	22.37	22.39	22.42
			8	4	23.00	22.45	22.50	22.54
			8	7	23.00	22.45	22.47	22.54
			15	0	22.50	22.37	22.44	22.40
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	25.00	24.64	24.61	24.57
			1	12	25.00	24.72	24.67	24.73
			1	24	25.00	24.57	24.57	24.55
			12	0	24.00	23.56	23.51	23.58
			12	6	24.00	23.51	23.52	23.57
			12	11	24.00	23.49	23.68	23.39
			25	0	24.00	23.51	23.63	23.53
		16QAM	1	0	24.00	23.67	23.54	23.53
			1	12	24.00	23.60	23.68	23.57
			1	24	24.00	23.49	23.46	23.55
			12	0	23.00	22.57	22.61	22.53
			12	6	23.00	22.48	22.50	22.51
			12	11	23.00	22.47	22.72	22.40
			25	0	23.00	22.44	22.59	22.46
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	25.00	24.64	24.54	24.63
			1	24	25.00	24.63	24.69	24.66
			1	49	25.00	24.70	24.66	24.71
			25	0	24.00	23.58	23.52	23.36
			25	12	24.00	23.54	23.52	23.37
			25	24	24.00	23.55	23.74	23.33
			50	0	24.00	23.59	23.62	23.40
		16QAM	1	0	24.00	23.49	23.42	23.51
			1	24	24.00	23.58	23.64	23.58
			1	49	24.00	23.47	23.37	23.50
			25	0	23.00	22.55	22.58	22.38
			25	12	23.00	22.45	22.53	22.34
			25	24	23.00	22.57	22.72	22.34

			50	0	23.00	22.61	22.64	22.37
--	--	--	----	---	-------	-------	-------	-------

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23205/779.5	23230/782	23255/784.5
LTE Band 13	5MHz	QPSK	1	0	25.00	24.56	24.52	24.49
			1	12	25.00	24.67	24.65	24.63
			1	24	25.00	24.50	24.49	24.52
			12	0	24.00	23.12	23.50	23.35
			12	6	24.00	23.13	23.49	23.35
			12	11	24.00	23.42	23.52	23.55
			25	0	24.00	23.28	23.52	23.51
		16QAM	1	0	24.00	23.54	23.47	23.41
			1	12	24.00	23.53	23.55	23.54
			1	24	24.00	23.36	23.41	23.40
			12	0	23.00	22.21	22.53	22.47
			12	6	23.00	22.23	22.44	22.41
			12	11	23.00	22.43	22.49	22.54
			25	0	23.00	22.35	22.56	22.52
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		/	23230/782	/
LTE Band 13	10MHz	QPSK	1	0	25.00	/	24.60	/
			1	24	25.00	/	24.62	/
			1	49	25.00	/	24.61	/
			25	0	24.00	/	23.26	/
			25	12	24.00	/	23.24	/
			25	24	24.00	/	23.61	/
			50	0	23.50	/	23.46	/
		16QAM	1	0	23.50	/	23.44	/
			1	24	23.50	/	23.31	/
			1	49	23.50	/	23.43	/
			25	0	23.00	/	22.26	/
			25	12	23.00	/	22.25	/
			25	24	23.00	/	22.65	/
			50	0	22.50	/	22.49	/

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23305/790.5	23330/793	23355/795.5
LTE Band 14	5MHz	QPSK	1	0	25.00	24.55	24.60	24.62
			1	12	25.00	24.74	24.76	24.82
			1	24	25.00	24.64	24.65	24.66
			12	0	24.00	23.55	23.53	23.57
			12	6	24.00	23.54	23.57	23.55
			12	11	24.00	23.55	23.61	23.49
			25	0	24.00	23.62	23.66	23.54
		16QAM	1	0	24.00	23.52	23.53	23.61
			1	12	24.00	23.62	23.69	23.64
			1	24	24.00	23.47	23.50	23.56
			12	0	23.00	22.63	22.60	22.58
			12	6	23.00	22.57	22.56	22.56

			12	11	23.00	22.62	22.67	22.51
			25	0	23.00	22.60	22.67	22.54
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		/	23330/793	/
LTE Band 14	10MHz	QPSK	1	0	25.00	/	24.54	/
			1	24	25.00	/	24.72	/
			1	49	25.00	/	24.75	/
			25	0	24.00	/	23.51	/
			25	12	24.00	/	23.58	/
			25	24	24.00	/	23.57	/
			50	0	24.00	/	23.56	/
		16QAM	1	0	24.00	/	23.48	/
			1	24	24.00	/	23.45	/
			1	49	24.00	/	23.53	/
			25	0	23.00	/	22.51	/
			25	12	23.00	/	22.61	/
			25	24	23.00	/	22.62	/
			50	0	23.00	/	22.63	/

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	25.00	24.59	24.68	24.64
			1	12	25.00	24.72	24.71	24.81
			1	24	25.00	24.59	24.61	24.62
			12	0	24.00	23.60	23.47	23.63
			12	6	24.00	23.59	23.46	23.58
			12	11	24.00	23.66	23.55	23.55
			25	0	24.00	23.63	23.56	23.60
		16QAM	1	0	24.00	23.55	23.64	23.54
			1	12	24.00	23.68	23.66	23.67
			1	24	24.00	23.55	23.43	23.57
			12	0	23.00	22.62	22.50	22.59
			12	6	23.00	22.49	22.45	22.55
			12	11	23.00	22.60	22.57	22.49
			25	0	23.00	22.62	22.54	22.55
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	25.00	24.59	24.66	24.65
			1	24	25.00	24.76	24.76	24.73
			1	49	25.00	24.73	24.76	24.75
			25	0	24.00	23.53	23.45	23.42
			25	12	24.00	23.52	23.42	23.36
			25	24	24.00	23.60	23.49	23.45
			50	0	24.00	23.57	23.49	23.39
		16QAM	1	0	24.00	23.45	23.56	23.47
			1	24	24.00	23.67	23.64	23.65
			1	49	24.00	23.40	23.43	23.51
			25	0	23.00	22.52	22.47	22.40
			25	12	23.00	22.54	22.43	22.37

			25	24	23.00	22.59	22.51	22.42
			50	0	23.00	22.56	22.47	22.41

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26047/1850.7	26365/1882.5	26683/1914.3
LTE Band 25	1.4MHz	QPSK	1	0	22.50	22.19	22.25	22.29
			1	2	22.50	22.25	22.24	22.32
			1	5	22.50	22.27	22.13	22.35
			3	0	22.50	22.28	22.38	22.42
			3	1	22.50	22.37	22.34	22.45
			3	2	22.50	22.31	22.30	22.45
		16QAM	6	0	22.00	21.45	21.39	21.52
			1	0	21.50	21.09	21.14	21.12
			1	2	21.50	21.15	21.03	21.25
			1	5	21.50	21.00	21.06	21.08
			3	0	21.50	21.25	21.17	21.28
			3	1	21.50	21.19	21.16	21.28
			3	2	21.50	21.10	21.19	21.22
			6	0	20.50	20.41	20.39	20.36
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26055/1851.5	26365/1882.5	26675/1913.5
LTE Band 25	3MHz	QPSK	1	0	22.50	22.12	22.15	22.25
			1	7	22.50	22.19	22.26	22.25
			1	14	22.50	22.16	22.10	22.18
			8	0	21.50	21.28	21.31	21.37
			8	4	21.50	21.24	21.27	21.41
			8	7	21.50	21.35	21.36	21.46
			15	0	21.50	21.30	21.34	21.46
		16QAM	1	0	21.50	20.83	20.92	20.97
			1	7	21.50	21.03	21.05	21.15
			1	14	21.50	21.07	21.13	21.22
			8	0	20.50	20.30	20.33	20.36
			8	4	20.50	20.26	20.28	20.35
			8	7	20.50	20.29	20.31	20.40
			15	0	20.50	20.19	20.23	20.37
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26065/1852.5	26365/1882.5	26665/1912.5
LTE Band 25	5MHz	QPSK	1	0	23.00	22.38	22.40	22.52
			1	12	23.00	22.56	22.60	22.65
			1	24	23.00	22.39	22.39	22.45
			12	0	22.00	21.42	21.39	21.59
			12	6	22.00	21.35	21.35	21.57
			12	11	22.00	21.36	21.37	21.48
			25	0	22.00	21.39	21.42	21.54
		16QAM	1	0	22.00	21.28	21.36	21.43
			1	12	22.00	21.58	21.60	21.75
			1	24	22.00	21.35	21.35	21.43
			12	0	21.00	20.33	20.44	20.54

			12	6	21.00	20.37	20.43	20.59
			12	11	21.00	20.34	20.34	20.49
			25	0	21.00	20.45	20.49	20.63
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26090/1855	26365/1882.5	26640/1910
LTE Band 25	10MHz	QPSK	1	0	23.00	21.37	22.49	22.49
			1	24	23.00	22.43	22.46	22.54
			1	49	23.00	22.48	22.37	22.52
			25	0	22.00	21.34	21.32	21.55
			25	12	22.00	21.38	21.41	21.54
			25	24	22.00	21.40	21.37	21.51
			50	0	22.00	21.42	21.42	21.55
		16QAM	1	0	22.00	21.22	21.24	21.30
			1	24	22.00	21.30	21.31	21.48
			1	49	22.00	21.51	21.43	21.51
			25	0	21.00	20.39	20.41	20.58
			25	12	21.00	20.39	20.43	20.62
			25	24	21.00	20.39	20.39	20.49
			50	0	21.00	20.40	20.41	20.59
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26115/1857.5	26365/1882.5	26615/1907.5
LTE Band 25	15MHz	QPSK	1	0	23.00	22.30	22.39	22.27
			1	37	23.00	22.54	22.49	22.62
			1	74	23.00	22.44	22.38	22.47
			36	0	22.00	21.42	21.58	21.42
			36	18	22.00	21.55	21.56	21.66
			36	37	22.00	21.20	21.12	21.29
			75	0	22.00	21.41	21.37	21.50
		16QAM	1	0	22.00	21.18	21.25	21.17
			1	37	22.00	21.57	21.61	21.75
			1	74	22.00	21.47	21.37	21.54
			36	0	22.00	21.16	21.25	21.18
			36	18	22.00	21.59	21.58	21.69
			36	37	22.00	21.46	21.39	21.51
			75	0	21.00	20.41	20.40	20.52
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26140/1860	26365/1882.5	26590/1905
LTE Band 25	20MHz	QPSK	1	0	23.00	22.27	22.41	22.21
			1	49	23.00	22.52	22.51	22.60
			1	99	23.00	22.35	22.21	22.37
			50	0	22.00	21.45	21.40	21.33
			50	24	22.00	21.46	21.33	21.32
			50	49	22.00	21.52	21.32	21.42
			100	0	21.50	21.47	21.39	21.36
		16QAM	1	0	22.00	21.08	21.23	21.01
			1	49	22.00	21.68	21.64	21.76
			1	99	22.00	21.32	21.21	21.41
			50	0	21.00	20.50	20.37	20.37

			50	24	21.00	20.46	20.38	20.30
			50	49	21.00	20.50	20.34	20.42
			100	0	20.50	20.46	20.34	20.38

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26697/814.7	26740/819	26783/823.3
LTE Band 26a	1.4MHz	QPSK	1	0	25.00	24.65	24.63	24.75
			1	2	25.00	24.69	24.63	24.77
			1	5	25.00	24.70	24.65	24.71
			3	0	25.00	24.62	24.63	24.72
			3	1	25.00	24.64	24.66	24.74
			3	2	25.00	24.69	24.63	24.67
			6	0	24.00	23.85	23.80	23.84
		16QAM	1	0	24.00	23.43	23.39	23.53
			1	2	24.00	23.50	23.50	23.43
			1	5	24.00	23.32	23.31	23.45
			3	0	23.50	23.44	23.45	23.48
			3	1	23.50	23.41	23.39	23.47
			3	2	23.50	23.33	23.36	23.49
			6	0	23.00	22.66	22.59	22.84
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26705/818.5	26740/819	26775/822.5
LTE Band 26a	3MHz	QPSK	1	0	25.00	24.47	24.47	24.58
			1	7	25.00	24.66	24.60	24.73
			1	14	25.00	24.43	24.50	24.56
			8	0	24.00	23.67	23.68	23.68
			8	4	24.00	23.63	23.57	23.69
			8	7	24.00	23.67	23.68	23.77
			15	0	24.00	23.62	23.65	23.70
		16QAM	1	0	23.50	23.41	23.31	23.46
			1	7	23.50	23.26	23.23	23.40
			1	14	23.50	23.22	23.29	23.28
			8	0	23.00	22.64	22.64	22.72
			8	4	23.00	22.63	22.60	22.73
			8	7	23.00	22.59	22.69	22.71
			15	0	23.00	22.57	22.63	22.67
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26715/816.5	26740/819	26765/821.5
LTE Band 26a	5MHz	QPSK	1	0	25.00	24.77	24.69	24.75
			1	12	25.00	24.84	24.85	24.91
			1	24	25.00	24.77	24.84	24.81
			12	0	24.00	23.70	23.60	23.60
			12	6	24.00	23.68	23.58	23.60
			12	11	24.00	23.70	23.77	23.75
			25	0	24.00	23.65	23.72	23.71
		16QAM	1	0	24.00	23.62	23.60	23.62
			1	12	24.00	23.67	23.70	23.80
			1	24	24.00	23.71	23.80	23.77
			12	0	23.00	22.63	22.59	22.59
			12	6	23.00	22.70	22.61	22.63

			12	11	23.00	22.70	22.81	22.80
			25	0	23.00	22.69	22.72	22.70
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		/	26740/819	/
LTE Band 26a	10MHz	QPSK	1	0	25.00	/	24.71	/
			1	24	25.00	/	24.85	/
			1	49	25.00	/	24.89	/
			25	0	24.00	/	23.62	/
			25	12	24.00	/	23.65	/
			25	24	24.00	/	23.84	/
			50	0	24.00	/	23.73	/
		16QAM	1	0	24.00	/	23.64	/
			1	24	24.00	/	23.51	/
			1	49	24.00	/	23.66	/
			25	0	23.00	/	22.58	/
			25	12	23.00	/	22.68	/
			25	24	23.00	/	22.85	/
			50	0	23.00	/	22.72	/

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26797/824.7	26915/836.5	27033/848.3
LTE Band 26b	1.4MHz	QPSK	1	0	25.00	24.60	24.60	24.54
			1	2	25.00	24.55	24.65	24.55
			1	5	25.00	24.67	24.62	24.53
			3	0	25.00	24.57	24.66	24.53
			3	1	25.00	24.61	24.69	24.48
			3	2	25.00	24.57	24.65	24.48
			6	0	24.00	23.74	23.78	23.67
		16QAM	1	0	24.00	23.31	23.40	23.18
			1	2	24.00	23.43	23.52	23.28
			1	5	24.00	23.25	23.29	23.31
			3	0	23.50	23.35	23.44	23.26
			3	1	23.50	23.32	23.44	23.32
			3	2	23.50	23.26	23.39	23.20
			6	0	23.00	22.54	22.74	22.62
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26805/825.5	26915/836.5	27025/847.5
LTE Band 26b	3MHz	QPSK	1	0	25.00	24.38	24.48	24.46
			1	7	25.00	24.56	24.57	24.47
			1	14	25.00	24.60	24.54	24.39
			8	0	24.00	23.61	23.62	23.50
			8	4	24.00	23.60	23.65	23.52
			8	7	24.00	23.60	23.65	23.58
			15	0	24.00	23.59	23.68	23.51
		16QAM	1	0	24.00	23.23	23.34	23.08
			1	7	24.00	23.43	23.50	23.27
			1	14	24.00	23.12	23.27	23.29
			8	0	23.00	22.56	22.63	22.55

			8	4	23.00	22.57	22.71	22.51
			8	7	23.00	22.58	22.71	22.52
			15	0	23.00	22.45	22.64	22.40
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26815/826.5	26915/836.5	27015/846.5
LTE Band 26b	5MHz	QPSK	1	0	25.00	24.71	24.76	24.68
			1	12	25.00	24.94	24.91	24.80
			1	24	25.00	24.81	24.77	24.70
			12	0	24.00	23.68	23.65	23.59
			12	6	24.00	23.68	23.64	23.56
			12	11	24.00	23.67	23.77	23.61
			25	0	24.00	23.65	23.72	23.61
		16QAM	1	0	24.00	23.61	23.72	23.45
			1	12	24.00	23.71	23.80	23.76
			1	24	24.00	23.60	23.64	23.49
			12	0	23.00	22.68	22.69	22.55
			12	6	23.00	22.62	22.67	22.61
			12	11	23.00	22.59	22.72	22.62
			25	0	23.00	22.58	22.70	22.66
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26840/829	26915/836.5	26990/844
LTE Band 26b	10MHz	QPSK	1	0	25.00	24.72	24.76	24.84
			1	24	25.00	24.85	24.80	24.76
			1	49	25.00	24.88	24.83	24.67
			25	0	24.00	23.69	23.61	23.80
			25	12	24.00	23.74	23.58	23.78
			25	24	24.00	23.79	23.64	23.75
			50	0	24.00	23.74	23.69	23.83
		16QAM	1	0	24.00	23.45	23.60	23.45
			1	24	24.00	23.74	23.75	23.46
			1	49	24.00	23.61	23.46	23.59
			25	0	23.00	22.72	22.62	22.80
			25	12	23.00	22.72	22.61	22.82
			25	24	23.00	22.77	22.72	22.74
			50	0	23.00	22.75	22.69	22.79
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26865/831.5	26915/836.5	26965/841.5
LTE Band 26b	15MHz	QPSK	1	0	25.00	24.64	24.76	24.67
			1	37	25.00	24.91	24.85	24.88
			1	74	25.00	24.73	24.74	24.67
			36	0	24.00	23.57	23.68	23.75
			36	18	24.00	23.61	23.61	23.72
			36	37	24.00	23.83	23.65	23.39
			75	0	24.00	23.90	23.73	23.77
		16QAM	1	0	24.00	23.64	23.74	23.51
			1	37	24.00	23.81	23.78	23.81
			1	74	24.00	23.50	23.41	23.58
			36	0	24.00	23.68	23.74	23.50

			36	18	24.00	23.80	23.79	23.80
			36	37	24.00	23.53	23.44	23.57
			75	0	23.00	22.90	22.77	22.70

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39675/2498.5	40620/2593	41565/2687.5
LTE Band 41	5MHz	QPSK	1	0	23.50	22.35	23.22	22.94
			1	12	23.50	22.56	23.34	23.15
			1	24	23.50	22.42	23.31	23.03
			12	0	22.50	21.31	22.02	21.98
			12	6	22.50	21.26	22.03	22.00
			12	11	22.50	21.41	22.04	21.93
			25	0	22.00	21.35	21.98	21.97
		16QAM	1	0	22.50	21.23	21.83	21.83
			1	12	22.50	21.48	22.07	22.08
			1	24	22.50	21.23	21.93	21.90
			12	0	21.00	20.17	20.84	20.97
			12	6	21.00	20.25	20.87	21.00
			12	11	21.00	20.30	20.90	20.89
			25	0	21.00	20.30	20.91	20.98
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39700/2501	40620/2593	41540/2685
LTE Band 41	10MHz	QPSK	1	0	23.50	22.38	23.12	23.07
			1	24	23.50	22.45	23.23	23.08
			1	49	23.50	22.46	23.44	23.05
			25	0	22.50	21.18	21.97	21.96
			25	12	22.50	21.21	21.97	21.98
			25	24	22.50	21.38	22.05	21.99
			50	0	22.50	21.27	22.01	21.99
		16QAM	1	0	22.50	21.17	21.73	21.76
			1	24	22.50	21.34	22.05	21.88
			1	49	22.50	21.07	21.87	22.00
			25	0	21.00	20.14	20.87	21.00
			25	12	21.00	20.10	20.82	20.97
			25	24	21.00	20.33	20.98	20.95
			50	0	21.00	20.25	20.89	20.96
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39725/2503.5	40620/2593	41515/2682.5
LTE Band 41	15MHz	QPSK	1	0	23.50	22.34	23.02	22.95
			1	37	23.50	22.44	23.28	23.11
			1	74	23.50	22.43	23.38	22.99
			36	0	22.50	21.27	21.85	22.06
			36	18	22.50	21.11	21.90	22.10
			36	37	22.50	21.29	22.13	21.69
			75	0	22.50	21.38	22.29	22.04
		16QAM	1	0	22.50	21.35	21.92	21.73
			1	37	22.50	21.34	22.07	22.13
			1	74	22.50	21.03	21.85	21.98

			36	0	22.50	21.34	21.91	21.73
			36	18	22.50	21.32	22.06	22.15
			36	37	22.50	21.03	21.85	21.93
			75	0	21.50	20.29	21.01	20.99
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39750/2506	40620/2593	41490/2680
LTE Band 41	20MHz	QPSK	1	0	23.50	22.28	22.97	22.98
			1	49	23.50	22.52	23.42	23.15
			1	99	23.50	22.37	23.27	22.93
			50	0	22.50	20.99	21.89	21.88
			50	24	22.50	20.97	21.86	21.91
			50	49	22.50	21.27	22.04	22.04
			100	0	22.00	21.21	21.92	21.92
		16QAM	1	0	22.50	20.95	21.58	21.69
			1	49	22.50	21.37	22.20	22.23
			1	99	22.50	21.15	21.96	21.86
			50	0	21.50	19.95	20.80	20.94
			50	24	21.50	19.93	20.79	20.87
			50	49	21.50	20.24	20.89	21.01
			100	0	21.00	20.13	20.86	20.95

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131979/1710.7	132322/1745	132665/1779.3
LTE Band 66	1.4MHz	QPSK	1	0	23.50	23.07	22.95	22.90
			1	2	23.50	23.10	22.87	22.86
			1	5	23.50	23.09	22.90	22.86
			3	0	23.50	23.13	23.00	22.97
			3	1	23.50	23.12	22.99	22.94
			3	2	23.50	23.13	22.92	22.91
			6	0	22.50	22.23	22.11	22.02
		16QAM	1	0	22.00	21.81	21.67	21.65
			1	2	22.00	21.91	21.64	21.75
			1	5	22.00	21.70	21.69	21.76
			3	0	22.00	21.92	21.80	21.81
			3	1	22.00	21.92	21.79	21.79
			3	2	22.00	21.85	21.82	21.72
			6	0	21.50	20.98	21.11	21.04
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131987/1711.5	132322/1745	132657/1778.5
LTE Band 66	3MHz	QPSK	1	0	23.50	22.97	22.84	22.75
			1	7	23.50	23.09	22.88	22.82
			1	14	23.50	23.03	22.79	22.74
			8	0	22.50	22.16	22.05	21.92
			8	4	22.50	22.23	22.05	21.92
			8	7	22.50	22.19	22.03	21.99
			15	0	22.50	22.14	22.05	21.95
			1	0	22.50	21.74	21.55	21.54
		16QAM	1	0	22.50	21.74	21.55	21.54

			1	7	22.50	22.01	21.71	21.75
			1	14	22.50	21.72	21.76	21.77
			8	0	21.50	21.13	20.97	20.93
			8	4	21.50	21.09	20.98	20.95
			8	7	21.50	21.09	21.02	20.97
			15	0	21.50	21.03	20.93	20.91
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131997/1712.5	132322/1745	132647/1777.5
LTE Band 66	5MHz	QPSK	1	0	23.50	23.32	23.10	23.04
			1	12	23.50	23.45	23.24	23.19
			1	24	23.50	23.27	23.11	23.05
			12	0	22.50	22.27	22.06	22.11
			12	6	22.50	22.19	22.16	22.04
			12	11	22.50	22.25	22.05	22.09
			25	0	22.50	22.22	22.12	22.09
		16QAM	1	0	22.50	22.24	22.06	21.99
			1	12	22.50	22.32	22.26	22.24
			1	24	22.50	22.17	22.04	22.04
			12	0	21.50	21.25	21.12	21.10
			12	6	21.50	21.20	21.14	21.09
			12	11	21.50	21.27	21.05	21.09
			25	0	21.50	21.22	21.14	21.20
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132022/1715	132322/1745	132622/1775
LTE Band 66	10MHz	QPSK	1	0	23.50	23.27	23.27	23.22
			1	24	23.50	23.32	23.16	23.17
			1	49	23.50	23.44	23.19	23.17
			25	0	22.50	22.16	22.15	22.18
			25	12	22.50	22.18	22.15	22.13
			25	24	22.50	22.30	22.10	22.21
			50	0	22.50	22.35	22.12	22.21
		16QAM	1	0	22.50	22.03	22.01	21.90
			1	24	22.50	22.31	22.00	22.03
			1	49	22.50	22.23	22.13	22.24
			25	0	21.50	21.25	21.19	21.24
			25	12	21.50	21.20	21.20	21.20
			25	24	21.50	21.41	21.05	21.20
			50	0	21.50	21.32	21.19	21.23
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132047/1717.5	132322/1745	132597/1772.5
LTE Band 66	15MHz	QPSK	1	0	23.50	23.19	23.17	23.17
			1	37	23.50	23.46	23.18	23.29
			1	74	23.50	23.28	23.14	23.10
			36	0	23.00	22.16	22.29	22.27
			36	18	23.00	22.20	22.22	22.29
			36	37	23.00	22.52	21.84	21.93
			75	0	22.50	22.42	22.23	22.33
		16QAM	1	0	22.50	22.19	21.97	21.95

			1	37	22.50	22.42	22.31	22.34
			1	74	22.50	22.19	22.11	22.17
			36	0	22.50	22.19	21.98	21.92
			36	18	22.50	22.42	22.28	22.34
			36	37	22.50	22.22	22.09	22.20
			75	0	21.50	21.45	21.12	21.27
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132072/1720	132322/1745	132572/1770
LTE Band 66	20MHz	QPSK	1	0	23.50	23.18	23.23	23.15
			1	49	23.50	23.42	23.30	23.36
			1	99	23.50	23.45	23.08	23.03
			50	0	23.00	22.34	22.12	22.30
			50	24	23.00	22.34	22.17	22.25
			50	49	23.00	22.57	22.05	22.29
			100	0	22.50	22.43	22.11	22.26
		16QAM	1	0	22.50	22.21	22.01	21.84
			1	49	22.50	22.37	22.33	22.36
			1	99	22.50	22.20	21.98	22.02
			50	0	22.00	21.43	21.13	21.31
			50	24	22.00	21.33	21.18	21.27
			50	49	22.00	21.63	21.10	21.29
			100	0	21.50	21.45	21.16	21.30

8.4. Wi-Fi & BT Output Power

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11b	1	2412	17.00	16.58
	6	2437	17.00	16.63
	11	2462	17.00	16.75
802.11g	1	2412	16.50	16.45
	6	2437	15.00	14.12
	11	2462	15.00	14.69
802.11n HT20	1	2412	12.00	11.89
	6	2437	13.00	12.32
	11	2462	14.00	13.55
802.11n HT40	3	2422	14.50	12.96
	6	2437	14.50	13.58
	9	2452	14.50	14.10

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	36	5180	11.50	10.77
	40	5200	11.50	11.41
	48	5240	11.50	10.69
802.11n HT20	36	5180	11.50	10.70
	40	5200	11.50	11.23
	48	5240	11.50	10.81
802.11n HT40	38	5190	10.50	10.37
	46	5230	10.50	9.42
802.11ac VHT20	36	5180	10.00	9.50
	40	5200	10.00	9.85
	48	5240	10.00	9.58
802.11ac VHT40	38	5190	10.00	9.82
	46	5230	10.00	9.45
802.11ac VHT80	42	5210	9.50	9.26

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	52	5260	11.00	10.53
	56	5280	11.00	10.04
	64	5320	11.00	9.18
802.11n HT20	52	5260	11.00	10.56
	56	5280	11.00	9.94
	64	5320	11.00	9.51
802.11n HT40	54	5270	10.00	9.64
	62	5310	10.00	8.88
802.11ac VHT20	52	5260	10.50	10.10

	56	5280	10.50	9.96
	64	5320	10.50	9.05
802.11ac VHT40	54	5270	10.00	9.66
	62	5310	10.00	8.90
802.11ac VHT80	58	5290	8.50	8.38

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	100	5500	13.00	12.75
	120	5600	13.00	12.86
	140	5700	11.00	10.81
802.11n	100	5500	13.00	12.70
	120	5600	13.00	12.33
	140	5700	13.00	11.11
802.11n	102	5510	12.50	12.22
	118	5590	12.50	11.84
	134	5670	12.50	11.30
802.11ac (VHT20)	100	5500	12.50	12.41
	120	5600	12.50	12.25
	140	5700	12.50	10.69
802.11ac (VHT40)	102	5510	12.50	12.36
	118	5590	12.50	11.56
	134	5670	12.50	11.49
802.11ac (VHT80)	106	5530	12.00	11.96
	122	5610	12.00	10.40

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	149	5745	10.00	8.96
	157	5785	10.00	9.81
	165	5825	10.00	9.38
802.11n HT20	149	5745	10.00	9.23
	157	5785	10.00	9.78
	165	5825	10.00	9.26
802.11n HT40	151	5755	10.00	9.13
	159	5795	10.00	9.65
802.11ac VHT20	149	5745	10.50	9.42
	157	5785	10.50	10.01
	165	5825	10.50	9.62
802.11ac VHT40	151	5755	10.00	9.30
	159	5795	10.00	9.51
802.11ac VHT80	155	5775	9.50	9.14



BR+EDR	Output Power (dBm)				
	Channel	Tune-up (dBm)	Data Rates		
			1M	2M	3M
	0CH	3.00	2.54	1.39	1.59
	39CH	4.00	3.22	3.25	3.08
	78CH	3.00	2.89	2.14	2.11

Mode	Channel	Tune-up (dBm)	Output Power (dBm)
BLE1M	CH00	1.00	0.48
	CH19	2.00	1.52
	CH39	1.00	0.57

8.5. NFC

The power is too low, so SAR testing is not necessary.

9. Antenna Location



10. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Pmax (dBm)	Pmax (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	4.00	2.51	5	2.480	0.8	7.5	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}] \leq 18.75$ W/kg for test separation distances ≤ 50 mm, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	Pmax (dBm)	Pmax (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/kg)
Bluetooth	Body	4.00	2.51	5	2.48	18.75	0.042

NOTE: Estimated SAR calculation for Bluetooth

< GSM 850 >

< GSM 1900 >

< WCDMA Band 2 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g	Date	Plot
			(W/kg)							
			1-g	10-g						

								(W/Kg)		
Front Side	9400/1880	RMC12.2K	0.384	0.254	1.29	23.57	24.00	0.280	2025/4/8	
Back Side	9400/1880	RMC12.2K	0.925	0.624	-3.78	23.57	24.00	0.689	2025/4/8	3#
Left Side	9400/1880	RMC12.2K	0.480	0.324	1.25	23.57	24.00	0.358	2025/4/8	
Right Side	9400/1880	RMC12.2K	0.534	0.360	0.16	23.57	24.00	0.397	2025/4/8	
Top Side	9400/1880	RMC12.2K	0.570	0.385	0.53	23.57	24.00	0.425	2025/4/8	
Bottom Side	9400/1880	RMC12.2K	0.194	0.126	3.03	23.57	24.00	0.139	2025/4/8	

< WCDMA Band 5 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	4182/836.4	RMC12.2K	0.208	0.139	0.30	23.46	24.00	0.157	2025/4/4	
Back Side	4182/836.4	RMC12.2K	0.497	0.336	-2.97	23.46	24.00	0.380	2025/4/4	4#
Left Side	4182/836.4	RMC12.2K	0.260	0.169	2.34	23.46	24.00	0.191	2025/4/4	
Right Side	4182/836.4	RMC12.2K	0.297	0.197	2.51	23.46	24.00	0.223	2025/4/4	
Top Side	4182/836.4	RMC12.2K	0.300	0.199	-2.19	23.46	24.00	0.225	2025/4/4	
Bottom Side	4182/836.4	RMC12.2K	0.104	0.067	0.60	23.46	24.00	0.076	2025/4/4	

< LTE Band2 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	18900/1880	20M QPSK(1,49)	0.508	0.313	-3.60	22.56	23.00	0.346	2025/4/8	
Back Side	18900/1880	20M QPSK(1,49)	1.223	0.794	-0.66	22.56	23.00	0.879	2025/4/8	10#
Left Side	18900/1880	20M QPSK(1,49)	0.630	0.409	0.92	22.56	23.00	0.453	2025/4/8	
Right Side	18900/1880	20M QPSK(1,49)	0.677	0.422	-3.16	22.56	23.00	0.467	2025/4/8	
Top Side	18900/1880	20M QPSK(1,49)	0.756	0.481	-1.29	22.56	23.00	0.532	2025/4/8	
Bottom Side	18900/1880	20M QPSK(1,49)	0.252	0.164	0.40	22.56	23.00	0.181	2025/4/8	
50%RB										
Front Side	18900/1880	20M QPSK(50,49)	0.303	0.165	-0.55	21.50	22.00	0.185	2025/4/8	
Back Side	18900/1880	20M	0.633	0.404	-0.33	21.50	22.00	0.453	2025/4/8	

		QPSK(50,49)								
Left Side	18900/1880	20M QPSK(50,49)	0.333	0.241	-3.99	21.50	22.00	0.270	2025/4/8	
Right Side	18900/1880	20M QPSK(50,49)	0.381	0.240	1.24	21.50	22.00	0.269	2025/4/8	
Top Side	18900/1880	20M QPSK(50,49)	0.435	0.269	3.85	21.50	22.00	0.302	2025/4/8	
Bottom Side	18900/1880	20M QPSK(50,49)	0.150	0.098	-0.68	21.50	22.00	0.110	2025/4/8	

< LTE Band4 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.432	0.307	2.29	22.45	23.00	0.348	2025/4/7	
Back Side	20175/1732.5	20M QPSK(1,49)	1.072	0.762	-2.77	22.45	23.00	0.865	2025/4/7	11#
Left Side	20175/1732.5	20M QPSK(1,49)	0.555	0.375	0.57	22.45	23.00	0.426	2025/4/7	
Right Side	20175/1732.5	20M QPSK(1,49)	0.611	0.434	2.26	22.45	23.00	0.493	2025/4/7	
Top Side	20175/1732.5	20M QPSK(1,49)	0.648	0.447	-0.22	22.45	23.00	0.507	2025/4/7	
Bottom Side	20175/1732.5	20M QPSK(1,49)	0.222	0.150	-0.08	22.45	23.00	0.170	2025/4/7	
50%RB										
Front Side	20175/1732.5	20M QPSK(50,49)	0.231	0.167	-0.12	21.38	21.50	0.172	2025/4/7	
Back Side	20175/1732.5	20M QPSK(50,49)	0.631	0.448	0.59	21.38	21.50	0.461	2025/4/7	
Left Side	20175/1732.5	20M QPSK(50,49)	0.312	0.212	2.24	21.38	21.50	0.218	2025/4/7	
Right Side	20175/1732.5	20M QPSK(50,49)	0.347	0.225	1.36	21.38	21.50	0.231	2025/4/7	
Top Side	20175/1732.5	20M QPSK(50,49)	0.339	0.225	-0.24	21.38	21.50	0.231	2025/4/7	
Bottom Side	20175/1732.5	20M QPSK(50,49)	0.128	0.083	4.86	21.38	21.50	0.085	2025/4/7	

< LTE Band5 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.252	0.170	-2.42	24.95	25.00	0.172	2025/4/4	
Back Side	20525/836.5	10M QPSK(1,24)	0.605	0.412	-3.29	24.95	25.00	0.417	2025/4/4	12#
Left Side	20525/836.5	10M QPSK(1,24)	0.320	0.211	-3.44	24.95	25.00	0.213	2025/4/4	
Right Side	20525/836.5	10M QPSK(1,24)	0.358	0.244	3.02	24.95	25.00	0.247	2025/4/4	
Top Side	20525/836.5	10M QPSK(1,24)	0.384	0.262	3.25	24.95	25.00	0.265	2025/4/4	
Bottom Side	20525/836.5	10M QPSK(1,24)	0.126	0.084	-1.97	24.95	25.00	0.085	2025/4/4	
50%RB										
Front Side	20525/836.5	10M QPSK(25,24)	0.134	0.087	-0.50	23.85	24.00	0.090	2025/4/4	
Back Side	20525/836.5	10M QPSK(25,24)	0.334	0.227	-1.97	23.85	24.00	0.235	2025/4/4	
Left Side	20525/836.5	10M QPSK(25,24)	0.173	0.115	2.21	23.85	24.00	0.119	2025/4/4	
Right Side	20525/836.5	10M QPSK(25,24)	0.182	0.131	-3.97	23.85	24.00	0.136	2025/4/4	
Top Side	20525/836.5	10M QPSK(25,24)	0.201	0.152	-4.10	23.85	24.00	0.157	2025/4/4	
Bottom Side	20525/836.5	10M QPSK(25,24)	0.071	0.044	0.01	23.85	24.00	0.046	2025/4/4	

< LTE Band7 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			(W/kg)							
			1-g	10-g						
1RB										
Front Side	21100/2535	20M QPSK(1,99)	0.312	0.197	-1.61	22.49	23.00	0.222	2025/4/10	
Back Side	21100/2535	20M	0.765	0.503	-3.75	22.49	23.00	0.566	2025/4/10	13#

		QPSK(1,99)								
Left Side	21100/2535	20M QPSK(1,99)	0.385	0.251	3.68	22.49	23.00	0.282	2025/4/10	
Right Side	21100/2535	20M QPSK(1,99)	0.435	0.280	-1.98	22.49	23.00	0.315	2025/4/10	
Top Side	21100/2535	20M QPSK(1,99)	0.480	0.303	1.93	22.49	23.00	0.341	2025/4/10	
Bottom Side	21100/2535	20M QPSK(1,99)	0.154	0.100	2.11	22.49	23.00	0.112	2025/4/10	
50%RB										
Front Side	21100/2535	20M QPSK(50,0)	0.170	0.106	4.35	21.60	22.00	0.116	2025/4/10	
Back Side	21100/2535	20M QPSK(50,0)	0.392	0.296	2.29	21.60	22.00	0.325	2025/4/10	
Left Side	21100/2535	20M QPSK(50,0)	0.209	0.135	-2.46	21.60	22.00	0.148	2025/4/10	
Right Side	21100/2535	20M QPSK(50,0)	0.238	0.167	-4.09	21.60	22.00	0.183	2025/4/10	
Top Side	21100/2535	20M QPSK(50,0)	0.247	0.169	-3.98	21.60	22.00	0.185	2025/4/10	
Bottom Side	21100/2535	20M QPSK(50,0)	0.081	0.056	0.36	21.60	22.00	0.061	2025/4/10	

< LTE Band12 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,49)	0.276	0.178	0.41	24.66	25.00	0.192	2025/4/3	
Back Side	23095/707.5	10M QPSK(1,49)	0.681	0.438	-0.17	24.66	25.00	0.474	2025/4/3	14#
Left Side	23095/707.5	10M QPSK(1,49)	0.365	0.230	-3.64	24.66	25.00	0.249	2025/4/3	
Right Side	23095/707.5	10M QPSK(1,49)	0.402	0.251	-1.52	24.66	25.00	0.271	2025/4/3	
Top Side	23095/707.5	10M QPSK(1,49)	0.432	0.264	-2.55	24.66	25.00	0.285	2025/4/3	
Bottom Side	23095/707.5	10M QPSK(1,49)	0.138	0.085	2.88	24.66	25.00	0.092	2025/4/3	

50%RB										
Front Side	23095/707.5	10M QPSK(25,24)	0.147	0.094	-4.76	23.74	24.00	0.100	2025/4/3	
Back Side	23095/707.5	10M QPSK(25,24)	0.357	0.254	1.06	23.74	24.00	0.270	2025/4/3	
Left Side	23095/707.5	10M QPSK(25,24)	0.216	0.117	1.60	23.74	24.00	0.124	2025/4/3	
Right Side	23095/707.5	10M QPSK(25,24)	0.215	0.140	-1.40	23.74	24.00	0.149	2025/4/3	
Top Side	23095/707.5	10M QPSK(25,24)	0.235	0.143	-3.02	23.74	24.00	0.152	2025/4/3	
Bottom Side	23095/707.5	10M QPSK(25,24)	0.082	0.043	-3.38	23.74	24.00	0.046	2025/4/3	

< LTE Band13 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23230/782	10M QPSK(1,24)	0.460	0.290	3.55	24.62	25.00	0.317	2025/4/3	
Back Side	23230/782	10M QPSK(1,24)	1.114	0.739	-1.08	24.62	25.00	0.807	2025/4/3	15#
Left Side	23230/782	10M QPSK(1,24)	0.565	0.367	3.22	24.62	25.00	0.401	2025/4/3	
Right Side	23230/782	10M QPSK(1,24)	0.638	0.419	-3.15	24.62	25.00	0.457	2025/4/3	
Top Side	23230/782	10M QPSK(1,24)	0.684	0.440	1.30	24.62	25.00	0.480	2025/4/3	
Bottom Side	23230/782	10M QPSK(1,24)	0.232	0.151	-3.82	24.62	25.00	0.165	2025/4/3	
50%RB										
Front Side	23230/782	10M QPSK(25,24)	0.231	0.172	-1.48	23.61	24.00	0.188	2025/4/3	
Back Side	23230/782	10M QPSK(25,24)	0.608	0.417	0.58	23.61	24.00	0.456	2025/4/3	
Left Side	23230/782	10M QPSK(25,24)	0.297	0.205	4.00	23.61	24.00	0.224	2025/4/3	
Right Side	23230/782	10M QPSK(25,24)	0.332	0.232	-3.81	23.61	24.00	0.254	2025/4/3	

Top Side	23230/782	10M QPSK(25,24)	0.344	0.224	3.17	23.61	24.00	0.245	2025/4/3	
Bottom Side	23230/782	10M QPSK(25,24)	0.120	0.076	-2.95	23.61	24.00	0.083	2025/4/3	

< LTE Band14 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23330/793	10M QPSK(1,49)	0.240	0.160	-3.11	24.75	25.00	0.169	2025/4/3	
Back Side	23330/793	10M QPSK(1,49)	0.596	0.418	-3.35	24.75	25.00	0.443	2025/4/3	16#
Left Side	23330/793	10M QPSK(1,49)	0.300	0.200	3.36	24.75	25.00	0.212	2025/4/3	
Right Side	23330/793	10M QPSK(1,49)	0.341	0.234	-1.75	24.75	25.00	0.248	2025/4/3	
Top Side	23330/793	10M QPSK(1,49)	0.384	0.264	-1.47	24.75	25.00	0.280	2025/4/3	
Bottom Side	23330/793	10M QPSK(1,49)	0.124	0.084	-3.04	24.75	25.00	0.089	2025/4/3	
50%RB										
Front Side	23330/793	10M QPSK(25,12)	0.133	0.082	2.92	23.58	24.00	0.090	2025/4/3	
Back Side	23330/793	10M QPSK(25,12)	0.332	0.244	-2.04	23.58	24.00	0.269	2025/4/3	
Left Side	23330/793	10M QPSK(25,12)	0.170	0.100	0.95	23.58	24.00	0.110	2025/4/3	
Right Side	23330/793	10M QPSK(25,12)	0.172	0.125	2.39	23.58	24.00	0.138	2025/4/3	
Top Side	23330/793	10M QPSK(25,12)	0.213	0.138	-3.15	23.58	24.00	0.152	2025/4/3	
Bottom Side	23330/793	10M QPSK(25,12)	0.067	0.042	-1.35	23.58	24.00	0.046	2025/4/3	

< LTE Band17 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						

1RB										
Front Side	23790/710	10M QPSK(1,49)	0.264	0.170	-3.99	24.76	25.00	0.180	2025/4/3	
Back Side	23790/710	10M QPSK(1,49)	0.659	0.424	-3.46	24.76	25.00	0.448	2025/4/3	17#
Left Side	23790/710	10M QPSK(1,49)	0.350	0.218	0.99	24.76	25.00	0.230	2025/4/3	
Right Side	23790/710	10M QPSK(1,49)	0.363	0.229	1.15	24.76	25.00	0.242	2025/4/3	
Top Side	23790/710	10M QPSK(1,49)	0.420	0.259	-2.76	24.76	25.00	0.274	2025/4/3	
Bottom Side	23790/710	10M QPSK(1,49)	0.138	0.088	3.87	24.76	25.00	0.093	2025/4/3	
50%RB										
Front Side	23790/710	10M QPSK(25,24)	0.156	0.097	-4.70	23.49	24.00	0.109	2025/4/3	
Back Side	23790/710	10M QPSK(25,24)	0.339	0.215	0.98	23.49	24.00	0.242	2025/4/3	
Left Side	23790/710	10M QPSK(25,24)	0.189	0.130	-2.83	23.49	24.00	0.146	2025/4/3	
Right Side	23790/710	10M QPSK(25,24)	0.187	0.127	-4.37	23.49	24.00	0.143	2025/4/3	
Top Side	23790/710	10M QPSK(25,24)	0.219	0.145	-1.68	23.49	24.00	0.163	2025/4/3	
Bottom Side	23790/710	10M QPSK(25,24)	0.076	0.050	1.62	23.49	24.00	0.056	2025/4/3	

< LTE Band25 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	26365/1882.5	20M QPSK(1,49)	0.416	0.266	-1.62	22.51	23.00	0.298	2025/4/8	
Back Side	26365/1882.5	20M QPSK(1,49)	1.032	0.687	-3.31	22.51	23.00	0.769	2025/4/8	18#
Left Side	26365/1882.5	20M QPSK(1,49)	0.525	0.339	-1.28	22.51	23.00	0.379	2025/4/8	
Right Side	26365/1882.5	20M QPSK(1,49)	0.572	0.366	-3.54	22.51	23.00	0.410	2025/4/8	

Top Side	26365/1882.5	20M QPSK(1,49)	0.636	0.423	-3.44	22.51	23.00	0.474	2025/4/8	
Bottom Side	26365/1882.5	20M QPSK(1,49)	0.214	0.138	3.86	22.51	23.00	0.154	2025/4/8	
50%RB										
Front Side	26365/1882.5	20M QPSK(50,49)	0.218	0.133	4.09	21.32	22.00	0.156	2025/4/8	
Back Side	26365/1882.5	20M QPSK(50,49)	0.534	0.363	1.42	21.32	22.00	0.425	2025/4/8	
Left Side	26365/1882.5	20M QPSK(50,49)	0.285	0.180	-3.99	21.32	22.00	0.211	2025/4/8	
Right Side	26365/1882.5	20M QPSK(50,49)	0.331	0.213	0.62	21.32	22.00	0.249	2025/4/8	
Top Side	26365/1882.5	20M QPSK(50,49)	0.359	0.215	-3.22	21.32	22.00	0.251	2025/4/8	
Bottom Side	26365/1882.5	20M QPSK(50,49)	0.113	0.069	-3.49	21.32	22.00	0.081	2025/4/8	

< LTE Band26a >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			(W/kg)							
			1-g	10-g						
1RB										
Front Side	26740/819	10M QPSK(1,49)	0.256	0.171	2.92	24.89	25.00	0.175	2025/4/4	
Back Side	26740/819	10M QPSK(1,49)	0.609	0.416	-2.99	24.89	25.00	0.427	2025/4/4	20#
Left Side	26740/819	10M QPSK(1,49)	0.320	0.214	3.72	24.89	25.00	0.219	2025/4/4	
Right Side	26740/819	10M QPSK(1,49)	0.352	0.233	-0.55	24.89	25.00	0.239	2025/4/4	
Top Side	26740/819	10M QPSK(1,49)	0.372	0.241	-2.93	24.89	25.00	0.247	2025/4/4	
Bottom Side	26740/819	10M QPSK(1,49)	0.128	0.083	-3.12	24.89	25.00	0.085	2025/4/4	
50%RB										
Front Side	26740/819	10M QPSK(25,24)	0.135	0.102	-1.75	23.84	24.00	0.106	2025/4/4	
Back Side	26740/819	10M QPSK(25,24)	0.310	0.210	-3.84	23.84	24.00	0.218	2025/4/4	

Left Side	26740/819	10M QPSK(25,24)	0.179	0.121	3.30	23.84	24.00	0.126	2025/4/4	
Right Side	26740/819	10M QPSK(25,24)	0.176	0.132	-4.15	23.84	24.00	0.137	2025/4/4	
Top Side	26740/819	10M QPSK(25,24)	0.195	0.142	-0.99	23.84	24.00	0.147	2025/4/4	
Bottom Side	26740/819	10M QPSK(25,24)	0.069	0.042	0.03	23.84	24.00	0.044	2025/4/4	

< LTE Band26b >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	26865/831.5	15M QPSK(1,37)	0.256	0.164	2.07	24.85	25.00	0.170	2025/4/4	
Back Side	26865/831.5	15M QPSK(1,37)	0.628	0.420	-1.08	24.85	25.00	0.435	2025/4/4	21#
Left Side	26865/831.5	15M QPSK(1,37)	0.325	0.211	3.41	24.85	25.00	0.218	2025/4/4	
Right Side	26865/831.5	15M QPSK(1,37)	0.369	0.234	3.36	24.85	25.00	0.242	2025/4/4	
Top Side	26865/831.5	15M QPSK(1,37)	0.390	0.258	0.73	24.85	25.00	0.267	2025/4/4	
Bottom Side	26865/831.5	15M QPSK(1,37)	0.130	0.087	-3.99	24.85	25.00	0.090	2025/4/4	
50%RB										
Front Side	26865/831.5	15M QPSK(36,37)	0.129	0.091	2.87	23.65	24.00	0.099	2025/4/4	
Back Side	26865/831.5	15M QPSK(36,37)	0.329	0.240	-2.19	23.65	24.00	0.260	2025/4/4	
Left Side	26865/831.5	15M QPSK(36,37)	0.182	0.125	-2.71	23.65	24.00	0.135	2025/4/4	
Right Side	26865/831.5	15M QPSK(36,37)	0.206	0.132	-0.85	23.65	24.00	0.143	2025/4/4	
Top Side	26865/831.5	15M QPSK(36,37)	0.230	0.135	3.04	23.65	24.00	0.146	2025/4/4	
Bottom Side	26865/831.5	15M QPSK(36,37)	0.076	0.051	-2.45	23.65	24.00	0.055	2025/4/4	

< LTE Band41 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			(W/kg)							
			1-g	10-g						
1RB										
Front Side	40620/2593	20M QPSK(1,49)	0.424	0.252	0.81	23.42	23.50	0.257	2025/4/10	
Back Side	40620/2593	20M QPSK(1,49)	1.025	0.610	-0.18	23.42	23.50	0.621	2025/4/10	19#
Left Side	40620/2593	20M QPSK(1,49)	0.535	0.302	3.20	23.42	23.50	0.308	2025/4/10	
Right Side	40620/2593	20M QPSK(1,49)	0.589	0.347	2.03	23.42	23.50	0.353	2025/4/10	
Top Side	40620/2593	20M QPSK(1,49)	0.624	0.353	-3.10	23.42	23.50	0.360	2025/4/10	
Bottom Side	40620/2593	20M QPSK(1,49)	0.210	0.119	-1.77	23.42	23.50	0.121	2025/4/10	
50%RB										
Front Side	40620/2593	20M QPSK(50,49)	0.221	0.142	0.71	22.04	22.50	0.158	2025/4/10	
Back Side	40620/2593	20M QPSK(50,49)	0.598	0.363	-3.19	22.04	22.50	0.404	2025/4/10	
Left Side	40620/2593	20M QPSK(50,49)	0.311	0.158	-3.47	22.04	22.50	0.176	2025/4/10	
Right Side	40620/2593	20M QPSK(50,49)	0.308	0.189	-2.81	22.04	22.50	0.210	2025/4/10	
Top Side	40620/2593	20M QPSK(50,49)	0.340	0.206	-1.64	22.04	22.50	0.229	2025/4/10	
Bottom Side	40620/2593	20M QPSK(50,49)	0.116	0.064	-3.58	22.04	22.50	0.071	2025/4/10	

< LTE Band66 >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			(W/kg)							
			1-g	10-g						
1RB										
Front Side	132322/1745	20M QPSK(1,99)	0.440	0.323	2.11	23.08	23.50	0.356	2025/4/7	
Back Side	132322/1745	20M QPSK(1,99)	1.051	0.772	-0.86	23.08	23.50	0.850	2025/4/7	22#

Left Side	132322/1745	20M QPSK(1,99)	0.550	0.384	-1.76	23.08	23.50	0.423	2025/4/7	
Right Side	132322/1745	20M QPSK(1,99)	0.594	0.428	-1.81	23.08	23.50	0.471	2025/4/7	
Top Side	132322/1745	20M QPSK(1,99)	0.636	0.458	-2.75	23.08	23.50	0.505	2025/4/7	
Bottom Side	132322/1745	20M QPSK(1,99)	0.212	0.156	1.20	23.08	23.50	0.172	2025/4/7	
50%RB										
Front Side	132322/1745	20M QPSK(50,49)	0.252	0.183	-1.36	22.05	23.00	0.228	2025/4/7	
Back Side	132322/1745	20M QPSK(50,49)	0.609	0.451	1.23	22.05	23.00	0.561	2025/4/7	
Left Side	132322/1745	20M QPSK(50,49)	0.301	0.194	-4.18	22.05	23.00	0.241	2025/4/7	
Right Side	132322/1745	20M QPSK(50,49)	0.305	0.252	-0.43	22.05	23.00	0.314	2025/4/7	
Top Side	132322/1745	20M QPSK(50,49)	0.350	0.232	1.52	22.05	23.00	0.289	2025/4/7	
Bottom Side	132322/1745	20M QPSK(50,49)	0.116	0.088	-0.35	22.05	23.00	0.110	2025/4/7	

< WLAN 2.4G >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1g	10g						
Front Side	11/2462	802.11b	0.100	0.046	-1.47	16.75	17.00	0.049	2025/4/9	
Back Side	11/2462	802.11b	0.238	0.115	-4.93	16.75	17.00	0.122	2025/4/9	9#
Left Side	11/2462	802.11b	0.104	0.050	0.12	16.75	17.00	0.053	2025/4/9	
Right Side	11/2462	802.11b	0.169	0.079	-1.65	16.75	17.00	0.084	2025/4/9	
Top Side	11/2462	802.11b	0.144	0.067	-2.58	16.75	17.00	0.071	2025/4/9	
Bottom Side	11/2462	802.11b	0.052	0.025	2.44	16.75	17.00	0.026	2025/4/9	

< WLAN 5.2G >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1g	10g						
Front Side	40/5200	802.11a	0.196	0.129	2.00	11.41	11.50	0.132	2025/4/11	
Back Side	40/5200	802.11a	0.452	0.314	-4.72	11.41	11.50	0.321	2025/4/11	5#

Left Side	40/5200	802.11a	0.196	0.129	-0.50	11.41	11.50	0.132	2025/4/11	
Right Side	40/5200	802.11a	0.325	0.224	0.01	11.41	11.50	0.229	2025/4/11	
Top Side	40/5200	802.11a	0.288	0.196	2.28	11.41	11.50	0.200	2025/4/11	
Bottom Side	40/5200	802.11a	0.094	0.065	-2.80	11.41	11.50	0.066	2025/4/11	

< WLAN 5.3G >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1g	10g						
Front Side	52/5260	802.11n HT20	0.152	0.116	1.50	10.56	11.00	0.128	2025/4/14	
Back Side	52/5260	802.11n HT20	0.331	0.257	-1.49	10.56	11.00	0.284	2025/4/14	6#
Left Side	52/5260	802.11n HT20	0.136	0.106	-3.27	10.56	11.00	0.117	2025/4/14	
Right Side	52/5260	802.11n HT20	0.241	0.178	-0.82	10.56	11.00	0.197	2025/4/14	
Top Side	52/5260	802.11n HT20	0.210	0.161	3.21	10.56	11.00	0.178	2025/4/14	
Bottom Side	52/5260	802.11n HT20	0.074	0.055	0.66	10.56	11.00	0.061	2025/4/14	

< WLAN 5.6G >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1g	10g						
Front Side	120/5600	802.11a	0.200	0.132	0.62	12.86	13.00	0.136	2025/4/15	
Back Side	120/5600	802.11a	0.473	0.325	-1.48	12.86	13.00	0.336	2025/4/15	7#
Left Side	120/5600	802.11a	0.208	0.143	-3.51	12.86	13.00	0.148	2025/4/15	
Right Side	120/5600	802.11a	0.319	0.210	-3.57	12.86	13.00	0.217	2025/4/15	
Top Side	120/5600	802.11a	0.288	0.198	2.51	12.86	13.00	0.204	2025/4/15	
Bottom Side	120/5600	802.11a	0.104	0.069	2.78	12.86	13.00	0.071	2025/4/15	

< WLAN 5.8G >

Test Position of Extremity with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 10-g (W/Kg)	Date	Plot
			1g	10g						
Front Side	157/5785	802.11ac VHT20	0.208	0.141	2.31	10.01	10.50	0.158	2025/4/16	

Back Side	157/5785	802.11ac VHT20	0.500	0.343	4.51	10.01	10.50	0.384	2025/4/16	8#
Left Side	157/5785	802.11ac VHT20	0.220	0.145	-0.50	10.01	10.50	0.162	2025/4/16	
Right Side	157/5785	802.11ac VHT20	0.338	0.227	3.12	10.01	10.50	0.254	2025/4/16	
Top Side	157/5785	802.11ac VHT20	0.312	0.210	1.59	10.01	10.50	0.235	2025/4/16	
Bottom Side	157/5785	802.11ac VHT20	0.106	0.071	2.84	10.01	10.50	0.079	2025/4/16	

12. Simultaneous Transmission Analysis

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

1) Scalar SAR summation < 1.6W/kg.

2) $SPLSR = \frac{(SAR_1 + SAR_2)^{1.5}}{r}$ / (min. separation distance, mm), and the peak separation distance is

determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where

(x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.

If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

No.	Simultaneous Tx	Body-worn
1	WWAN+WLAN	Yes
2	WWAN+Bluetooth	Yes

Note : WiFi and Bluetooth use the same antenna and cannot be transmitted at the same time.

Exposure Position		WWAN Band	DTS/DSS Band	Simultaneous Tx SAR(W/Kg)
		SAR(W/Kg)	SAR(W/Kg)	
Extremity	Front Side	0.356	0.158	0.514
	Back Side	0.879	0.384	1.263
	Left Side	0.453	0.162	0.615
	Right Side	0.493	0.254	0.747
	Top Side	0.532	0.235	0.767
	Bottom Side	0.181	0.079	0.260

Note : The Simultaneous Tx is calculated based on the same configuration and test position.

Appendix A. Photo documentation

Refer to appendix Test Setup photo-SAR

Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 1800MHz
MEASUREMENT 4 System Performance Check - 1900MHz
MEASUREMENT 5 System Performance Check - 2450MHz
MEASUREMENT 6 System Performance Check - 2600MHz
MEASUREMENT 7 System Performance Check - 5200MHz
MEASUREMENT 8 System Performance Check - 5400MHz
MEASUREMENT 9 System Performance Check - 5600MHz
MEASUREMENT 10 System Performance Check - 5800MHz

MEASUREMENT 1


Date of measurement: 3/4/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW750</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.65</u>

B. SAR Measurement Results



Frequency (MHz)	750.000000
Relative permittivity (real part)	42.562010
Relative permittivity (imaginary part)	19.132740
Conductivity (S/m)	0.912054
Variation (%)	0.210000



Maximum location: X=2.00, Y=2.00

SAR Peak: 1.87 W/kg

SAR 10g (W/Kg)	0.621031
SAR 1g (W/Kg)	0.930125



MEASUREMENT 2


Date of measurement: 4/4/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	835.000000
Relative permittivity (real part)	42.012031
Relative permittivity (imaginary part)	19.131021
Conductivity (S/m)	0.941030
Variation (%)	0.310000



Maximum location: X=2.00, Y=2.00

SAR Peak: 1.87 W/kg

SAR 10g (W/Kg)	0.612031
SAR 1g (W/Kg)	1.011231



MEASUREMENT 3


Date of measurement: 7/4/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1800</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.606403
Relative permittivity (imaginary part)	14.067180
Conductivity (S/m)	1.406718
Variation (%)	-0.140000



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.024557
SAR 1g (W/Kg)	3.832112



MEASUREMENT 4


Date of measurement: 8/4/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1900</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1900.000000
Relative permittivity (real part)	41.420140
Relative permittivity (imaginary part)	12.570123
Conductivity (S/m)	1.390503
Variation (%)	-0.440000



Maximum location: X=1.00, Y=2.00

SAR Peak: 7.65 W/kg

SAR 10g (W/Kg)	2.153165
SAR 1g (W/Kg)	4.153568



MEASUREMENT 5


Date of measurement: 9/4/2025

A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2450</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.38</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	40.408511
Relative permittivity (imaginary part)	13.399264
Conductivity (S/m)	1.823789
Variation (%)	-1.250000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.359425
SAR 1g (W/Kg)	5.183642



MEASUREMENT 6


Date of measurement: 10/4/2025

A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2600</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.35</u>

B. SAR Measurement Results



Frequency (MHz)	2600.000000
Relative permittivity (real part)	39.432362
Relative permittivity (imaginary part)	13.768602
Conductivity (S/m)	1.988798
Variation (%)	-3.980000



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.523157
SAR 1g (W/Kg)	5.432595



MEASUREMENT 7


Date of measurement: 11/4/2025

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW5200</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.30</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	37.400000
Relative permittivity (imaginary part)	16.129999
Conductivity (S/m)	4.510778
Variation (%)	-4.570000



Maximum location: X=0.00, Y=1.00

SAR Peak: 15.14 W/kg

SAR 10g (W/Kg)	5.212361
SAR 1g (W/Kg)	14.712032



MEASUREMENT 8


Date of measurement: 14/4/2025

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW5400</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.30</u>

B. SAR Measurement Results



Frequency (MHz)	5400.000000
Relative permittivity (real part)	35.102351
Relative permittivity (imaginary part)	16.341203
Conductivity (S/m)	4.701556
Variation (%)	-2.480000



Maximum location: X=-1.00, Y=2.00

SAR Peak: 17.05 W/kg

SAR 10g (W/Kg)	5.532101
SAR 1g (W/Kg)	14.820035



MEASUREMENT 9


Date of measurement: 15/4/2025

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW5600</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.29</u>

B. SAR Measurement Results



Frequency (MHz)	5600.000000
Relative permittivity (real part)	34.200000
Relative permittivity (imaginary part)	16.120115
Conductivity (S/m)	4.900712
Variation (%)	-4.570000



Maximum location: X=0.00, Y=1.00

SAR Peak: 15.13 W/kg

SAR 10g (W/Kg)	5.602361
SAR 1g (W/Kg)	16.421103



MEASUREMENT 10


Date of measurement: 16/4/2025

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW5800</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.27</u>

B. SAR Measurement Results



Frequency (MHz)	5800.000000
Relative permittivity (real part)	35.299999
Relative permittivity (imaginary part)	16.360001
Conductivity (S/m)	5.271556
Variation (%)	-2.480000



Maximum location: X=-1.00, Y=2.00

SAR Peak: 17.07 W/kg

SAR 10g (W/Kg)	5.623106
SAR 1g (W/Kg)	16.421035



Appendix C. SAR Test Plots

Table of contents
MEASUREMENT 1 GSM 850 Body
MEASUREMENT 2 GSM 1900 Body
MEASUREMENT 3 WCDMA Band 2 Body
MEASUREMENT 4 WCDMA Band 5 Body
MEASUREMENT 5 WALN 5.2G Body
MEASUREMENT 6 WALN 5.3G Body
MEASUREMENT 7 WALN 5.6G Body
MEASUREMENT 8 WALN 5.8G Body
MEASUREMENT 9 WALN 2.4G Body
MEASUREMENT 10 LTE Band 2 Body
MEASUREMENT 11 LTE Band 4 Body
MEASUREMENT 12 LTE Band 5 Body
MEASUREMENT 13 LTE Band 7 Body
MEASUREMENT 14 LTE Band 12 Body
MEASUREMENT 15 LTE Band 13 Body
MEASUREMENT 16 LTE Band 14 Body
MEASUREMENT 17 LTE Band 17 Body
MEASUREMENT 18 LTE Band 25 Body
MEASUREMENT 19 LTE Band 41 Body
MEASUREMENT 20 LTE Band 26a Body
MEASUREMENT 21 LTE Band 26b Body
MEASUREMENT 22 LTE Band 66 Body

MEASUREMENT 1


Date of measurement: 4/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.400024
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901453
Variation (%)	-3.230000



Maximum location: X=-9.00, Y=18.00

SAR Peak: 1.50 W/kg

SAR 10g (W/Kg)	0.657033
SAR 1g (W/Kg)	0.991712



MEASUREMENT 2


Date of measurement: 8/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.408000
Conductivity (S/m)	1.400391
Variation (%)	-0.280000



Maximum location: X=17.00, Y=34.00

SAR Peak: 1.09 W/kg

SAR 10g (W/Kg)	0.409535
SAR 1g (W/Kg)	0.653552



MEASUREMENT 3


Date of measurement: 8/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.408000
Conductivity (S/m)	1.400391
Variation (%)	-3.780000



Maximum location: X=-9.00, Y=33.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.624174
SAR 1g (W/Kg)	0.925166



MEASUREMENT 4


Date of measurement: 4/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.400024
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901453
Variation (%)	-2.970000



Maximum location: X=-15.00, Y=31.00

SAR Peak: 0.75 W/kg

SAR 10g (W/Kg)	0.336249
SAR 1g (W/Kg)	0.497277



MEASUREMENT 5


Date of measurement: 11/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.a (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.30</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	37.400000
Relative permittivity (imaginary part)	16.129999
Conductivity (S/m)	4.510778
Variation (%)	-4.720000



Maximum location: X=-9.00, Y=-2.00

SAR Peak: 1.14 W/kg

SAR 10g (W/Kg)	0.314435
SAR 1g (W/Kg)	0.452414



MEASUREMENT 6


Date of measurement: 14/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11n U-NII</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.n (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.30</u>

B. SAR Measurement Results



Frequency (MHz)	5260.000000
Relative permittivity (real part)	35.919998
Relative permittivity (imaginary part)	16.158001
Conductivity (S/m)	4.721723
Variation (%)	-1.490000



Maximum location: X=-20.00, Y=-12.00

SAR Peak: 1.09 W/kg

SAR 10g (W/Kg)	0.257046
SAR 1g (W/Kg)	0.331096



MEASUREMENT 7


Date of measurement: 15/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.a (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.29</u>

B. SAR Measurement Results



Frequency (MHz)	5600.000000
Relative permittivity (real part)	35.500000
Relative permittivity (imaginary part)	16.299999
Conductivity (S/m)	5.071111
Variation (%)	-1.480000



Maximum location: X=11.00, Y=7.00

SAR Peak: 1.19 W/kg

SAR 10g (W/Kg)	0.324819
SAR 1g (W/Kg)	0.473003



MEASUREMENT 8


Date of measurement: 16/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11ac U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.ac (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.27</u>

B. SAR Measurement Results



Frequency (MHz)	5785.000000
Relative permittivity (real part)	35.314999
Relative permittivity (imaginary part)	16.355499
Conductivity (S/m)	5.256476
Variation (%)	4.510000



Maximum location: X=10.00, Y=0.00

SAR Peak: 1.37 W/kg

SAR 10g (W/Kg)	0.342920
SAR 1g (W/Kg)	0.500203



MEASUREMENT 9


Date of measurement: 9/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>IEEE802.b (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.38</u>

B. SAR Measurement Results



Frequency (MHz)	2462.000000
Relative permittivity (real part)	39.228002
Relative permittivity (imaginary part)	13.205000
Conductivity (S/m)	1.806151
Variation (%)	-4.930000



Maximum location: X=-16.00, Y=11.00

SAR Peak: 0.70 W/kg

SAR 10g (W/Kg)	0.114586
SAR 1g (W/Kg)	0.237986



MEASUREMENT 10


Date of measurement: 8/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1879.500000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.411700
Conductivity (S/m)	1.400405
Variation (%)	-0.660000



Maximum location: X=-8.00, Y=32.00

SAR Peak: 1.84 W/kg

SAR 10g (W/Kg)	0.794394
SAR 1g (W/Kg)	1.222806



MEASUREMENT 11


Date of measurement: 7/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1732.500000
Relative permittivity (real part)	40.115910
Relative permittivity (imaginary part)	14.136136
Conductivity (S/m)	1.360603
Variation (%)	-2.770000



Maximum location: X=-13.00, Y=34.00

SAR Peak: 1.43 W/kg

SAR 10g (W/Kg)	0.762280
SAR 1g (W/Kg)	1.071825



MEASUREMENT 12


Date of measurement: 4/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.500000
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901561
Variation (%)	-3.290000



Maximum location: X=-15.00, Y=29.00

SAR Peak: 0.86 W/kg

SAR 10g (W/Kg)	0.412092
SAR 1g (W/Kg)	0.605319



MEASUREMENT 13


Date of measurement: 10/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.086666
Relative permittivity (imaginary part)	13.418333
Conductivity (S/m)	1.889749
Variation (%)	-3.750000



Maximum location: X=1.00, Y=32.00

SAR Peak: 1.15 W/kg

SAR 10g (W/Kg)	0.503109
SAR 1g (W/Kg)	0.764873



MEASUREMENT 14


Date of measurement: 3/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.65</u>

B. SAR Measurement Results



Frequency (MHz)	707.500000
Relative permittivity (real part)	42.126667
Relative permittivity (imaginary part)	23.264000
Conductivity (S/m)	0.914404
Variation (%)	-0.170000



Maximum location: X=-10.00, Y=30.00

SAR Peak: 1.02 W/kg

SAR 10g (W/Kg)	0.437511
SAR 1g (W/Kg)	0.681253



MEASUREMENT 15


Date of measurement: 3/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 13</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.65</u>

B. SAR Measurement Results



Frequency (MHz)	781.500000
Relative permittivity (real part)	41.751766
Relative permittivity (imaginary part)	20.633648
Conductivity (S/m)	0.895844
Variation (%)	-1.080000



Maximum location: X=-12.00, Y=29.00

SAR Peak: 1.65 W/kg

SAR 10g (W/Kg)	0.739390
SAR 1g (W/Kg)	1.113963



MEASUREMENT 16


Date of measurement: 3/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 14</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.65</u>

B. SAR Measurement Results



Frequency (MHz)	792.500000
Relative permittivity (real part)	41.700001
Relative permittivity (imaginary part)	20.379999
Conductivity (S/m)	0.897286
Variation (%)	-3.350000



Maximum location: X=-13.00, Y=27.00

SAR Peak: 0.90 W/kg

SAR 10g (W/Kg)	0.418119
SAR 1g (W/Kg)	0.596473



MEASUREMENT 17


Date of measurement: 3/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.65</u>

B. SAR Measurement Results



Frequency (MHz)	710.000000
Relative permittivity (real part)	42.113335
Relative permittivity (imaginary part)	23.152000
Conductivity (S/m)	0.913218
Variation (%)	-3.460000



Maximum location: X=-10.00, Y=30.00

SAR Peak: 1.01 W/kg

SAR 10g (W/Kg)	0.423663
SAR 1g (W/Kg)	0.658741



MEASUREMENT 18


Date of measurement: 8/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 25</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1882.500000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.393200
Conductivity (S/m)	1.400706
Variation (%)	-3.310000



Maximum location: X=-8.00, Y=34.00

SAR Peak: 1.44 W/kg

SAR 10g (W/Kg)	0.687444
SAR 1g (W/Kg)	1.031694



MEASUREMENT 19


Date of measurement: 10/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 41</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	2593.000000
Relative permittivity (real part)	39.009335
Relative permittivity (imaginary part)	13.553667
Conductivity (S/m)	1.952481
Variation (%)	-0.180000



Maximum location: X=-3.00, Y=33.00

SAR Peak: 1.67 W/kg

SAR 10g (W/Kg)	0.610264
SAR 1g (W/Kg)	1.025095



MEASUREMENT 20


Date of measurement: 4/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>CUSTOM (LTEBand26A)</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	819.000000
Relative permittivity (real part)	41.575294
Relative permittivity (imaginary part)	19.768942
Conductivity (S/m)	0.899487
Variation (%)	-2.990000



Maximum location: X=-14.00, Y=28.00

SAR Peak: 0.89 W/kg

SAR 10g (W/Kg)	0.416057
SAR 1g (W/Kg)	0.609405



MEASUREMENT 21


Date of measurement: 4/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>CUSTOM (LTEBand26B)</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	831.500000
Relative permittivity (real part)	41.516472
Relative permittivity (imaginary part)	19.480705
Conductivity (S/m)	0.899900
Variation (%)	-1.080000



Maximum location: X=-14.00, Y=28.00

SAR Peak: 0.94 W/kg

SAR 10g (W/Kg)	0.420212
SAR 1g (W/Kg)	0.628250



MEASUREMENT 22


Date of measurement: 7/4/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>CUSTOM (LTEBand66)</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.09</u>

B. SAR Measurement Results



Frequency (MHz)	1745.000000
Relative permittivity (real part)	40.104546
Relative permittivity (imaginary part)	14.103182
Conductivity (S/m)	1.367225
Variation (%)	-0.860000



Maximum location: X=-11.00, Y=34.00

SAR Peak: 1.70 W/kg

SAR 10g (W/Kg)	0.771768
SAR 1g (W/Kg)	1.050520



Appendix D. Calibration Certificate

Table of contents
E Field Probe - EPGO0523-403
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
5000-6000 MHz Dipole - SN 03/14 WGA33



COMOSAR E-Field Probe Calibration Report

Ref : ACR.307.3.24.BES.A

**GUANGDONG ASIA HONGKE TEST
TECHNOLOGY CO., LTD**
NO.1/F,BUILDING B1, JUNFENG INDUSTRIAL PARK,
CHONGQING ROAD, HEPING COMMUNITY,
FUHAIHAI STREET, BAO'AN DISTRICT,SHENZHEN,
GUANGDONG 518055, P.R.CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 39/21 EPGO0523-403

Calibrated at MVG

Z.I. de la pointe du diable

**Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE**

Calibration date: 09/11/2024



Accreditations #2-6789
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.

Summary:

This document presents the method and results from an accredited COMOSAR E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.307.3.24.BES.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme Le Gall	Measurement Responsible	09/10/2024	
<i>Checked by :</i>	Jérôme Luc	Technical Manager	09/10/2024	
<i>Approved by :</i>	Yann Toutain	Laboratory Director	09/11/2024	

	<i>Customer Name</i>
<i>Distribution :</i>	Shenzhen Asia Hongke

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Jérôme Luc	9/11/2024	Initial release



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.307.3.24.BES.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	4
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.1	Boundary Effect	5
4	Measurement Uncertainty	6
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	8
5.4	Isotropy	9
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.307.3.24.BES.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 39/21 EPG00523-403
Product Condition (new / used)	New
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.199 MΩ Dipole 2: R2=0.218 MΩ Dipole 3: R3=0.210 MΩ

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Probe

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

Page: 4/11

Template ACR.DDD.N.YY.MVGB.ISSUE COMOSAR Probe vK

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.307.3.24.BES.A

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2 (e^{-\Delta SAR_{be}(\delta/2)})}{2d_{step} \delta/2} \text{ for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.

The measured worst case boundary effect SARuncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.307.3.24.BES.A

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Expanded uncertainty 95 % confidence level k = 2					14 %

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
1.26	0.87	0.77

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
113	108	113

Calibration curves $e_i=f(V)$ (i=1,2,3) allow to obtain E-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$



COMOSAR E-FIELD PROBE CALIBRATION REPORT


Ref: ACR.307.3.24.BES.A

Calibration curves



5.2 LINEARITY

Linearity



Linearity: +/-1.42% (+/-0.06dB)



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.307.3.24.BES.A

5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz +/- 100MHz)	ConvF
HL600	600	1.62
HL750	750	1.65
HL850	835	1.66
HL900	900	1.77
HL1500	1500	2.09
HL1750	1750	2.09
HL1800	1800	2.05
HL1900	1900	2.05
HL2000	2000	2.41
HL2100	2100	2.36
HL2300	2300	2.55
HL2450	2450	2.38
HL2600	2600	2.35
HL3300	3300	2.04
HL3500	3500	1.98
HL3700	3700	2.11
HL3900	3900	2.54
HL4200	4200	2.22
HL4600	4600	2.40
HL4900	4900	2.33
HL5200	5200	2.30
HL5400	5400	2.30
HL5600	5600	2.29
HL5800	5800	2.27

LOWER DETECTION LIMIT: 8mW/kg



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.307.3.24.BES.A

5.4 ISOTROPY

HL1800 MHz

