



FCC Part 15B TEST REPORT

Report No.: STS2302331E01

Issued for

Telo Communication (Shenzhen) Co., Ltd

6/F, No. 42 Liuxian 1st Road, Bao'an District, Shenzhen,
China

Product Name:	Smart LTE Terminal
Brand:	TELOX
Model Number:	TE320
Series Model(s):	TE320L, TE320A, TE320M, TE320G, TE320P, TE320X
FCC ID:	2AYEZ-TE320
Test Standard:	FCC 47 CFR Part 15: Subpart B

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.



**TEST RESULT CERTIFICATION****Applicant's Name**: Telo Communication (Shenzhen) Co., Ltd

Address.....: 6/F, No. 42 Liuxian 1st Road, Bao'an District, Shenzhen, China

Manufacture's Name: Telo Communication (Shenzhen) Co., Ltd

Address.....: 6/F, No. 42 Liuxian 1st Road, Bao'an District, Shenzhen, China

Product Description

Product Name: Smart LTE Terminal

Brand: TELOX

Model Number.....: TE320

Series Model(s): TE320L, TE320A, TE320M, TE320G, TE320P, TE320X

Standards.....: FCC 47 CFR Part 15: Subpart B

Test Procedure.....: ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test.....:

Date of Receipt of Test Item.....: 28 Feb. 2023

Date of Performance of Tests: 28 Feb. 2023 ~ 17 Mar. 2023

Date of Issue.....: 17 Mar. 2023

Test Result: **Pass**

Testing Engineer :

Stan Deng

(Star Deng)

Technical Manager :

Bulun

(Bulun)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents

1. SUMMARY OF THE TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF THE EUT	6
2.2 DESCRIPTION OF THE TEST MODES	8
2.3 DESCRIPTION OF THE TEST SETUP	9
2.4 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3. EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.2 RADIATED EMISSION MEASUREMENT	15



**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	17 Mar. 2023	STS2302331E01	ALL	Initial Issue





1. SUMMARY OF THE TEST RESULTS

Test procedures according to the technical standards:

EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B	Conducted Emission	PASS	Meet Class B limit
	Radiated Emission	PASS	Meet Class B limit

NOTE:

(1) N/A=Not Applicable.

1.1 TEST FACTORY

Company Name:	SHENZHEN STS TEST SERVICES CO.,LTD.
Address:	A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
Telephone:	+86-755 3688 6288
Fax:	+86-755 3688 6277
Registration No.:	FCC test Firm Registration Number: 625569
	IC test Firm Registration Number: 12108A
	A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.14\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.54\text{dB}$
3	All emissions,radiated(<1G) 30MHz-1000MHz	$\pm 3.94\text{dB}$
4	All emissions,radiated(>1G) 1GHz-6GHz	$\pm 4.59\text{dB}$
5	All emissions,radiated(>1G) 6GHz-18GHz	$\pm 5.22\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart LTE Terminal	
Brand	TELOX	
Model Number	TE320	
Series Model(s)	TE320L, TE320A, TE320M, TE320G, TE320P, TE320X	
Model Difference	It's just a different model name	
Frequency Bands	GSM	850: 824~849MHz 1900: 1850~1910MHz
	WCDMA	Band II: 1850~1910MHz Band IV: 1710~1755MHz Band V: 824~849MHz
	LTE	Band 2: 1850~19010MHz Band 4: 1710~1755MHz Band 5: 824~849MHz Band 7: 2500~2570MHz Band 12: 699~716MHz Band 13: 777~787MHz Band 17: 704~716MHz Band 26: 814~849MHz Band 41: 2496~2690MHz Band 66: 1710~1780MHz
	Bluetooth	2402~2480MHz
	2.4G WLAN	802.11b/g/n 20: 2412~2462MHz
	5G WLAN	802.11a/ n(HT20): 5180MHz~5240MHz 802.11n(HT40): 5190MHz~5230MHz
		802.11a/ n(HT20): 5745MHz~5825MHz 802.11n(HT40): 5755MHz~5795MHz
	NFC	13.56MHz
Modulation Mode	GSM	GMSK for GSM/GPRS; GMSK and 8PSK for EDGE
	WCDMA	WCDMA: QPSK; HSDPA:QPSK/16QAM; HSUPA:BPSK
	LTE	QPSK/16QAM;
	Bluetooth	GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps), 8DPSK(3Mbps)
	2.4G WLAN	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM
	5G WLAN	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM
	NFC	FSK
Adapter	Input: AC100V-240V, 50.60Hz, 0.3A Output:5V, 2A	



Battery	Rated Voltage:3.8 V Capacity: 4000mAh
Hardware Version Number	PL21_V1.0
Software Version Number	TE320_INT_V1P_230214

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.





2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	PC+USB Transmitting+SD Card
Mode 2	Adapter + Rear camera+ BT Link+ GPS Rx
Mode 3	GSM850 Link + Adapter + USB cable + Earphone + BT Link + GPS Rx+NFC
Mode 4	GSM 1900 Idle + Adapter + USB cable + BT Link + GPS Rx+NFC
Mode 5	WCDMA B2 Link + Adapter + USB cable + Earphone + BT Link + WLAN Link + GPS Rx+NFC
Mode 6	WCDMA B4 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 7	WCDMA B5 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 8	LTE B2 Link + Adapter + USB cable + Earphone + BT Link + WLAN Link + GPS Rx+NFC
Mode 9	LTE B4 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 10	LTE B5 Link + Adapter + USB cable + + BT Link + WLAN Link + GPS Rx+NFC
Mode 11	LTE B7 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 12	LTE B12 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 13	LTE B13 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 14	LTE B17 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 15	LTE B26 Link + Adapter + USB cable + BT Link + WLAN Link + GPS Rx+NFC
Mode 16	LTE B41 Link + Adapter + USB cable + Earphone + BT Link + WLAN Link + GPS Rx+NFC
Mode 17	LTE B66 Link + Adapter + USB cable + Earphone + BT Link + WLAN Link + GPS Rx+NFC

For Conducted Test	
Final Test Mode	Description
Mode 1	PC+USB Transmitting+SD Card

For Radiated Test	
Final Test Mode	Description
Mode 1	PC+USB Transmitting+SD Card

**Note:**

1. For conducted emission test, test mode 1 was the worst case and only this mode was presented in this report.
2. For radiated emission test, test mode 1 was the worst case and only this mode was presented in this report.
3. We have be tested for all avaiable U.S. voltage and frequencies (For 120V, 50/60Hz) for which the device is capable of operation.

2.3 DESCRIPTION OF THE TEST SETUP

The EUT has been tested with associated equipment below and the test setup please refer to appendix 1 - test setup.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
/	Adapter	TELOX	MR-0502000US	N/A	N/A
/	Type-C Cable	N/A	N/A	100cm	NO

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
/	Personal computer	DELL	VOSTRO.3800	N/A	N/A
/	Keyboard	Acer	SK-9624	N/A	N/A
/	Mouse	HP	MODGUO	N/A	N/A
/	Printer	LENOVO	LJ2400L	N/A	N/A
/	DC Cable	N/A	N/A	120cm	NO
/	USB Cable	N/A	N/A	110cm	NO
/	USB Cable	N/A	N/A	110cm	NO
/	USB Cable	N/A	N/A	110cm	NO

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.4 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2022.09.29	2023.09.28
Bi-log Antenna	TESEQ	CBL6111D	45873	2021.10.08	2023.10.07
Horn Antenna	SCHWARZB ECK	BBHA 9120D	1343	2022.09.28	2023.09.27
Pre-amplifier(1-26.5 G)	Agilent	8449B	3008A02383	2022.07.04	2023.07.03
Pre-amplifier(0.1M-3 GHz)	EM	EM330	060665	2022.07.04	2023.07.03
Spectrum Analyzer	Agilent	N9020A	MY49100060	2022.09.28	2023.09.27
RE Cable (9K-1G)	N/A	R01	N/A	2022.09.28	2023.09.27
RE Cable (1-26G)	N/A	R02	N/A	2022.09.28	2023.09.27
Temperature & Humidity	Mieo	HH660	N/A	2022.09.28	2023.09.27
Horn Antenna(18-40G)	A-INFO	LB-180400-KF	J211020657	2022.09.30	2023.09.29
Testing Software	EZ-EMC(Ver.STSLAB-03A1 RE)				

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2022.09.28	2023.09.27
LISN	R&S	ENV216	101242	2022.09.28	2023.09.27
LISN	ETS	3810/2NM	00023625	2022.09.28	2023.09.27
Absorbing Clamp	R&S	MDS-21	100668	2023.02.28	2024.02.27
CE Cable	N/A	C01	N/A	2022.09.28	2023.09.27
Temperature & Humidity	Mieo	HH660	N/A	2022.09.30	2023.09.29
Testing Software	EZ-EMC(Ver.STSLAB-03A1 CE)				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	☐ Class A (dB μ V)		☒ Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.5 ~ 5	73.00	60.00	56.00	46.00
5 ~ 30	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



**Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS


Temperature:	25.6℃	Relative Humidity:	45%
Phase:	L	Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz	Test Date:	2023.03.01

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1620	43.71	10.33	54.04	65.36	-11.32	QP
2	0.1620	24.71	10.33	35.04	55.36	-20.32	AVG
3	0.1900	39.82	10.31	50.13	64.04	-13.91	QP
4	0.1900	18.83	10.31	29.14	54.04	-24.90	AVG
5	0.2300	35.66	10.44	46.10	62.45	-16.35	QP
6	0.2300	17.29	10.44	27.73	52.45	-24.72	AVG
7	1.6100	28.15	10.30	38.45	56.00	-17.55	QP
8	1.6100	21.29	10.30	31.59	46.00	-14.41	AVG
9	5.0260	21.62	10.46	32.08	60.00	-27.92	QP
10	5.0260	9.92	10.46	20.38	50.00	-29.62	AVG
11	21.6300	19.65	12.80	32.45	60.00	-27.55	QP
12	21.6300	6.60	12.80	19.40	50.00	-30.60	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = Insertion loss + Cable loss

100.0 dBuV






Temperature:	23.8℃	Relative Humidity:	44%
Phase:	N	Test Mode:	Mode 1
Test Voltage:	AC 120V/60Hz	Test Date:	2023.03.01

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	43.09	10.29	53.38	66.00	-12.62	QP
2	0.1500	20.67	10.29	30.96	56.00	-25.04	AVG
3	0.1980	37.62	10.40	48.02	63.69	-15.67	QP
4	0.1980	15.73	10.40	26.13	53.69	-27.56	AVG
5	0.2700	33.89	10.67	44.56	61.12	-16.56	QP
6	0.2700	13.45	10.67	24.12	51.12	-27.00	AVG
7	1.5700	27.98	10.35	38.33	56.00	-17.67	QP
8	1.5700	20.19	10.35	30.54	46.00	-15.46	AVG
9	2.0500	29.31	10.39	39.70	56.00	-16.30	QP
10	2.0500	18.66	10.39	29.05	46.00	-16.95	AVG
11	4.6940	22.96	10.52	33.48	56.00	-22.52	QP
12	4.6940	8.37	10.52	18.89	46.00	-27.11	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = Insertion loss + Cable loss

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

Below 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	☐ Class A		☒ Class B
	Field strength (dBuV/m) (at 10m)	Field strength (dBuV/m) (at 3m)	Field strength (dBuV/m) (at 3m)
30 ~ 88	39	49	40
88 ~ 216	43.5	53.5	43.5
216 ~ 960	46	56	46
Above 960	49.5	59.5	54

Above 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	☐ Class A				☒ Class B	
	(dBuV/m) (at 3m)		(dBuV/m) (at 10m)		(dBuV/m) (at 3m)	
	Peak	Average	Peak	Average	Peak	Average
Above 1000	80	60	69.5	49.5	74	54

Frequency Range of Radiated Disturbance Measurement

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 ~ 108	1000
108 ~ 500	2000
500 ~ 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Note:

- (1) The limit for radiated test was performed in the following: FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m).




3.2.2 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. EUT as the center to the edge of the auxiliary device, the distance from the maximum edge to the center of the antenna is 3 meter.
- c. The height of antenna is varied from 1 meter to 4 meter above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meter and the rotatable table was turned from 0 degrees to 360 degree to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.2.3 DEVIATION FROM TEST STANDARD

No deviation




3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 described unless otherwise a special operating condition is specified in the following during the testing.



3.2.6 TEST RESULTS

30MHz - 1000MHz

Temperature:	24.4℃	Relative Humidity:	35%
Phase:	Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 5V	Test Date:	2023.03.16

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	69.8450	59.21	-26.64	32.57	40.00	-7.43	QP
2	181.1802	59.12	-23.52	35.60	40.00	-4.40	QP
3	315.4806	56.80	-17.67	39.13	47.00	-7.87	QP
4	480.5276	44.75	-15.07	29.68	47.00	-17.32	QP
5	663.4728	40.96	-13.55	27.41	47.00	-19.59	QP
6	962.1621	38.06	-6.79	31.27	47.00	-15.73	QP

Remark:

1. All readings are Quasi-Peak
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = Cable Loss + Antenna Factor - Amplifier Gain

80.0 dBuV/m






Temperature:	24.4°C	Relative Humidity:	35%
Phase:	Vertical	Test Mode:	Mode 1
Test Voltage:	DC 5V	Test Date:	2023.03.16

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	70.0903	54.50	-26.61	27.89	40.00	-12.11	QP
2	167.8243	57.42	-21.67	35.75	40.00	-4.25	QP
3	167.8243	57.42	-21.67	35.75	40.00	-4.25	QP
4	321.0607	46.84	-17.37	29.47	47.00	-17.53	QP
5	661.1504	44.29	-13.52	30.77	47.00	-16.23	QP
6	962.1622	36.70	-6.79	29.91	47.00	-17.09	QP

Remark:

1. All readings are Quasi-Peak
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = Cable Loss + Antenna Factor - Amplifier Gain

80.0 dBuV/m





(1 GHz - 18GHz)


Temperature:	25.3℃	Relative Humidity:	53%
Phase:	Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 5V	Test Date:	2023.02.28

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4417.000	40.48	4.52	45.00	74.00	-29.00	Peak
2	4417.000	32.70	4.52	37.22	54.00	-16.78	AVG
3	6873.500	38.14	10.51	48.65	74.00	-25.35	Peak
4	6873.500	29.53	10.51	40.04	54.00	-13.96	AVG
5	9712.500	35.49	13.51	49.00	74.00	-25.00	Peak
6	9712.500	27.17	13.51	40.68	54.00	-13.32	AVG
7	12381.500	36.09	15.36	51.45	74.00	-22.55	Peak
8	12381.500	26.57	15.36	41.93	54.00	-12.07	AVG
9	14634.000	34.92	18.11	53.03	74.00	-20.97	Peak
10	14634.000	26.28	18.11	44.39	54.00	-9.61	AVG
11	17983.000	31.05	24.47	55.52	74.00	-18.48	Peak
12	17983.000	21.51	24.47	45.98	54.00	-8.02	AVG

Remark:

1. All readings are Peak and Average values
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = Cable Loss + Antenna Factor - Amplifier Gain

80.0 dBuV/m






Temperature:	25.3℃	Relative Humidity:	53%
Phase:	Vertical	Test Mode:	Mode 1
Test Voltage:	DC 5V	Test Date:	2023.02.28

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4281.000	40.38	4.57	44.95	74.00	-29.05	Peak
2	4281.000	31.73	4.57	36.30	54.00	-17.70	AVG
3	7205.000	36.09	11.27	47.36	74.00	-26.64	Peak
4	7205.000	26.62	11.27	37.89	54.00	-16.11	AVG
5	9797.500	35.39	13.57	48.96	74.00	-25.04	Peak
6	9797.500	24.94	13.57	38.51	54.00	-15.49	AVG
7	13631.000	36.44	16.04	52.48	74.00	-21.52	Peak
8	13631.000	26.62	16.04	42.66	54.00	-11.34	AVG
9	16087.500	35.62	16.49	52.11	74.00	-21.89	Peak
10	16087.500	28.07	16.49	44.56	54.00	-9.44	AVG
11	18000.000	30.24	24.57	54.81	74.00	-19.19	Peak
12	18000.000	22.66	24.57	47.23	54.00	-6.77	AVG

Remark:

1. All readings are Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = Cable Loss + Antenna Factor – Amplifier Gain

80.0 dBuV/m



Notes:

1. Measuring frequencies from 1 GHz to 18GHz.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak and average detector mode of the emission shown in Actual FS column.
3. The frequency emission of 18-25GHz is at least 20dB lower than the limit, and the frequency emission mainly comes from environmental noise.

END OF THE REPORT