

**FCC ID: 2AYGT-32-02**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Zigbee:

Antenna Type: PCB Antenna

Antenna Gain: 5 dBi

| Modulation | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | 1g SAR Exclusion threshold | SAR test exclusion |
|------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|----------------------------|--------------------|
| GFSK       | 2.405               | 4.888                  | 3.082                 | 5±1                 | 6.0                     | 3.981                  | <5            | 1.23477            | 3.00                       | YES                |
|            | 2.440               | 5.356                  | 3.432                 | 5±1                 | 6.0                     | 3.981                  | <5            | 1.24373            | 3.00                       | YES                |
|            | 2.480               | 4.786                  | 3.010                 | 5±1                 | 6.0                     | 3.981                  | <5            | 1.25388            | 3.00                       | YES                |

**Conclusion:**

For the max result :  $1.25388 \leq 3.0$  for 1-g SAR, No SAR is required.



**Signature:**

**Date:** 2023-01-17

**NAME AND TITLE** (Please print or type): Alex /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China