

Product Name: Low power video doorbell

Model No.: Bell 1, Bell 2, Bell 3, Bell 4, Bell 5, Bell J1, Bell J2, Bell J3, Bell J4, Bell J5, V10, V20, V30, V50, V55, V60, V65, V70, M1, M1 Pro, M2, M3, M3 Pro, M3s, M4, M5, M6, M6 Pro, M7, M8, M9, M9 Pro, M10, M10s, M10 Pro, M11, M12, M12 Pro, M13, M7 Plus, X1, X2, X3, X4, X5, X6, X7, X8, X9, X11, X12, X13, X14, X15

FCC ID: 2AYIT-BELL1

RF Exposure Evaluation

1.1 RF Exposure Compliance Requirement

1.1.1 Limits

According to FCC Part 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part 1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3 EUT RF Exposure Evaluation

Antenna Gain: 1.92

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.56 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

2.4G WIFI: 802.11g

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest	2462	15.292	33.82206	0.01047	1.0	PASS

Note: Refer to report No. BLA-EMC-202106-A6702 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation Requirement