

# TEST REPORT

**Product Name** : Reader Module

**Model Number** : ZX-R8204

**FCC ID** : 2AYIXZX-R8204

Prepared for : Ningbo K&D IOT Technology Co., Ltd  
Address : No.1 building, Ningchuang Sci. & Tech. Center, Panhuo  
Street, Yinzhou District, Ningbo, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.  
Address : Building 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, China

Tel: (0755) 26954280  
Fax: (0755) 26954282

Report Number : ES201123055W  
Date(s) of Tests : Nov. 24, 2020 to Dec. 23, 2020  
Date of issue : Dec. 23, 2020

## Table of Contents

<b>TEST REPORT</b> .....	1
1 TEST RESULT CERTIFICATION.....	3
2 EUT TECHNICAL DESCRIPTION.....	4
3 SUMMARY OF TEST RESULT.....	5
4 TEST METHODOLOGY .....	6
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	6
4.2 MEASUREMENT EQUIPMENT USED .....	6
4.3 DESCRIPTION OF TEST MODES .....	7
5 FACILITIES AND ACCREDITATIONS .....	8
5.1 FACILITIES .....	8
5.2 LABORATORY ACCREDITATIONS AND LISTINGS .....	8
6 TEST SYSTEM UNCERTAINTY.....	9
7 SETUP OF EQUIPMENT UNDER TEST .....	10
7.1 RADIO FREQUENCY TEST SETUP 1.....	10
7.2 RADIO FREQUENCY TEST SETUP 2.....	10
7.3 CONDUCTED EMISSION TEST SETUP .....	12
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM .....	13
7.5 SUPPORT EQUIPMENT.....	13
8 TEST REQUIREMENTS.....	14
8.1 20DB BANDWIDTH.....	14
8.2 CARRIER FREQUENCY SEPARATION .....	17
8.3 NUMBER OF HOPPING FREQUENCIES .....	20
8.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	22
8.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	24
8.6 CONDUCTED SPURIOUS EMISSION .....	27
8.7 RADIATED SPURIOUS EMISSION .....	34
8.8 CONDUCTED EMISSION TEST.....	44
8.9 ANTENNA APPLICATION .....	47

## 1 TEST RESULT CERTIFICATION

Applicant:	Ningbo K&D IOT Technology Co., Ltd
Address:	No.1 building, Ningchuang Sci. & Tech. Center, Panhuo Street, Yinzhou District, Ningbo, China
Manufacturer:	Ningbo K&D IOT Technology Co., Ltd
Address:	No.1 building, Ningchuang Sci. & Tech. Center, Panhuo Street, Yinzhou District, Ningbo, China
Product Description:	Reader Module
Model Number:	ZX-R8204
Trademark:	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J	
FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test :	Nov. 24, 2020 to Dec. 23, 2020
Prepared by :	Mill Chen
Reviewer :	Sewen Guo
Approve & Authorized Signer :	 Lisa Wang/Manager

## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
<b>Product :</b>	Reader Module
<b>Model Number :</b>	ZX-R8204
<b>Modulation:</b>	PR-ASK, DSB-ASK
<b>Operating Frequency :</b>	902.75-927.25MHz
<b>Number of Channels:</b>	50
<b>Transmit Power Max:</b>	25.30 dBm
<b>Antenna information</b>	Antenna Type: Panel Antenna Manufacturer: Laird
<b>Max support Antenna Gain:</b>	6.29dBi
<b>Power supply:</b>	DC 3.5V
<b>Test Voltage:</b>	DC 3.5V via Development Board

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d)	Radiated Spurious Emissions	PASS	
15.209			
15.207	Conducted Emission	PASS	
15.203	Antenna Application	PASS	
NOTE: N/A (Not Applicable)			

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AYIXZX-R8204 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:  
 FCC 47 CFR Part 2, Subpart J  
 FCC 47 CFR Part 15, Subpart C  
 KDB 558074: D01 15.247 Meas Guidance v05r02

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/16/2020	05/15/2021
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/16/2020	05/15/2021
50Ω Coaxial Switch	Anritsu	MP59B	M20531	05/16/2020	05/15/2021
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/16/2020	05/15/2021
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/16/2020	05/15/2021
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/16/2020	05/15/2021

#### 4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2020	05/15/2021
Pre-Amplifier	HP	8447D	2944A07999	05/16/2020	05/15/2021
Bilog Antenna	Schwarzbeck	VULB9163	142	05/16/2020	05/15/2021
Loop Antenna	ARA	PLA-1030/B	1029	05/16/2020	05/15/2021
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/16/2020	05/15/2021
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/16/2020	05/15/2021
Cable	Schwarzbeck	AK9513	ACRX1	05/16/2020	05/15/2021
Cable	Rosenberger	N/A	FP2RX2	05/16/2020	05/15/2021
Cable	Schwarzbeck	AK9513	CRPX1	05/16/2020	05/15/2021
Cable	Schwarzbeck	AK9513	CRRX2	05/16/2020	05/15/2021

#### 4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/16/2020	05/15/2021
Signal Analyzer	Agilent	N9010A	My53470879	05/16/2020	05/15/2021
Power meter	Anritsu	ML2495A	0824006	05/16/2020	05/15/2021
Power sensor	Anritsu	MA2411B	0738172	05/16/2020	05/15/2021

**Remark:** Each piece of equipment is scheduled for calibration once a year.

#### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those channels (902.75MHz, 915.25MHz and 927.25MHz) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for the EUT:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	<b>902.75</b>	24	914.25	47	925.75
2	903.25	25	914.75	48	926.25
3	903.75	<b>26</b>	<b>915.25</b>	49	926.75
...	...	...	...	<b>50</b>	<b>927.25</b>

Note:  $fc = 902.75\text{MHz} + k \cdot 0.5\text{MHz}$   $k(\text{Channel Number}) = 1 \text{ to } 50$

Test Frequency and channel for the EUT:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	902.75	26	915.25	50	927.25

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

#### Site Description

EMC Lab.

: Accredited by CNAS  
The Certificate Registration Number is L2291.  
The Laboratory has been assessed and proved to be in compliance with  
CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC  
Designation Number: CN1204  
Test Firm Registration Number: 882943

Accredited by A2LA  
The Certificate Number is 4321.01.  
Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008  
: EMTEK(SHENZHEN) CO., LTD.

Name of Firm

Site Location

: Building 69, Majialong Industry Zone,  
Nanshan District, Shenzhen, Guangdong, China

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%



## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The RFID component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


#### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Reader Module) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



#### 7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



#### 7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Remark
Development Board	Ningbo K&D IOT Technology Co., Ltd	/	Input: AC 100-240V, 50/60Hz
Note: The Development Board is provided by the manufacturer			

##### Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 8 TEST REQUIREMENTS

### 8.1 20DB BANDWIDTH

#### 8.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074: D01 15.247 Meas Guidance v05r02

#### 8.1.2 Conformance Limit

No limit requirement.

#### 8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.1.4 Test Procedure

The EUT was operating in RFID mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW  $\geq$  1% of the 20 dB bandwidth(3KHz)

Set the video bandwidth (VBW)  $\geq$  RBW(10KHz).

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.


Measure and record the results in the test report.

#### Test Results


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
ASK	01	902.75	65.99	$\leq 250$	PASS
	26	915.25	65.99	$\leq 250$	PASS
	50	927.25	65.99	$\leq 250$	PASS

Note: N/A (Not Applicable).

**Test Model**
**20dB Bandwidth**
**RFID**
**Channel 1: 902.75MHz**


Date: 1.DEC.2020 23:31:34

**Test Model**
**20dB Bandwidth**
**RFID**
**Channel 26: 915.25MHz**



Date: 1.DEC.2020 23:33:03

## Test Model

20dB Bandwidth

RFID

Channel 50: 927.25MHz



Date: 1.DEC.2020 23:36:09

## 8.2 CARRIER FREQUENCY SEPARATION

### 8.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074: D01 15.247 Meas Guidance v05r02

### 8.2.2 Conformance Limit

Frequency hopping systems operating in the 902-928MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### 8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.2.4 Test Procedure

- According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Set the RBW  $\geq$  1% of the span(100KHz).

Set the VBW  $\geq$  RBW(300KHz).

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.


Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

### Test Results


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
ASK	01	902.75	512.3	>65.99	PASS
	26	915.25	509.4	>65.99	PASS
	50	927.25	449.3	>65.99	PASS


Note: Limit = 20dB bandwidth.

**Test Model**
**Carrier Frequency Separation**  
**RFID**  
**Channel 1: 902.75MHz**


Date: 1.DEC.2020 23:38:53

**Test Model**
**Carrier Frequency Separation**  
**RFID**  
**Channel 26: 915.25MHz**


Date: 1.DEC.2020 23:39:50

**Test Model**
**Carrier Frequency Separation  
RFID  
Channel 50: 927.25MHz**


Date: 1.DEC.2020 23:40:19

### 8.3 NUMBER OF HOPPING FREQUENCIES

#### 8.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (i)and KDB 558074: D01 15.247 Meas Guidance v05r02

#### 8.3.2 Conformance Limit

Frequency hopping systems operating in the 902-928MHz band shall use at least 50 channels.

#### 8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.3.4 Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW  $\geq$  1% of the span(100KHz).

VBW  $\geq$  RBW(300KHz).

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.


#### Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
902-928	50	$\geq 50$

Test Model

Number Of Hopping Frequencies  
RFID



Date: 1.DEC.2020 22:28:17

## 8.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

### 8.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(i) and KDB 558074: D01 15.247 Meas Guidance v05r02

### 8.4.2 Conformance Limit

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz..

### 8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.4.4 Test Procedure

■ According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 100 KHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

### 8.4.5 Test Results

#### PASS.

All modes (low, mid, high channels) were tested, the data of the worst mode are described in the following pages.

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Modulation Mode	Frequency (MHz)	occupied time for each channel	dwell time (ms)	Limit(ms)	Verdict
PR-ASK, DSB-ASK	902.75	7.71ms	331.53ms	$\leq 400$	PASS


Note:

occupied time for each channel


7.71ms

Dwell time per 20 seconds

$7.71 \times 43 = 331.53$ ms

**Test Model**
**Average Time Of Occupancy (Dwell Time)**
**RFID**
**CH 01: 902.75MHz**
**The number of occupied channels per 20s**


Date: 1.DEC.2020 22:37:45

**Test Model**
**Average Time Of Occupancy (Dwell Time)**
**RFID**
**CH 01: 902.75MHz**
**occupied time for each channel**


Date: 1.DEC.2020 22:35:57

## 8.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 8.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and KDB 558074: D01 15.247 Meas Guidance v05r02

### 8.5.2 Conformance Limit

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

### 8.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.5.4 Test Procedure

- According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel (about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured (about 1MHz)

Set VBW  $\geq$  RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold


Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.

## Test Results


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
ASK	01	902.75	23.54	29.71	PASS
	26	915.25	24.19	29.71	PASS
	50	927.25	25.30	29.71	PASS

Note: Limit=30-(6.29-6)=29.71dBm

**Test Model**
**Maximum Peak Conducted Output Power**
**RFID**
**Channel 01: 902.75MHz**


Date: 1.DEC.2020 22:12:05

**Test Model**
**Maximum Peak Conducted Output Power**
**RFID**
**Channel 26: 915.25MHz**


Date: 1.DEC.2020 22:13:14

**Test Model**
**Maximum Peak Conducted Output Power  
RFID  
Channel 50: 927.25MHz**


Date: 1.DEC.2020 22:14:41



## 8.6 CONDUCTED SUPRIOUS EMISSION

### 8.6.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074: D01 15.247 Meas Guidance v05r02

### 8.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 8.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW  $\geq$  3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Conducted level.

Note that the channel found to contain the maximum Conducted level can be used to establish the reference level.

#### ■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW  $\geq$  1% of the span=100kHz Set VBW  $\geq$  RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

#### ■ Conducted Spurious RF Conducted Emission



Use the following spectrum analyzer settings:


Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz). Set RBW = 100 kHz Set VBW  $\geq$  RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.

### 8.6.5 Test Results


**Test Model**
**Maximum Conducted Level RBW=100kHz**
**RFID**
**Channel 01: 902.75MHz**

**Test Model**
**Conducted Spurious RF Conducted Emission**
**RFID**
**Channel 01: 902.75MHz**


**Test Model**
**Band-edge Conducted Emissions**
**RFID**
**Channel 01: 902.75MHz**



Date: 1.DEC.2020 23:16:43

**Test Model**
**Maximum Conducted Level RBW=100kHz**
**RFID**
**Channel 26: 915.25MHz**


Date: 1.DEC.2020 23:20:43

**Test Model**
**Conducted Spurious RF Conducted Emission  
RFID  
Channel 26: 915.25MHz**



Date: 1.DEC.2020 23:21:45

**Test Model**
**Maximum Conducted Level RBW=100kHz  
RFID  
Channel 50: 927.25MHz**


Date: 1.DEC.2020 23:22:55

**Test Model**


Conducted Spurious RF Conducted Emission  
RFID  
Channel 50: 927.25MHz




Date: 1.DEC.2020 23:24:25

**Test Model**


Band-edge Conducted Emissions  
RFID  
Channel 50: 927.25MHz




Date: 1.DEC.2020 23:23:47

**Test Model**
**Maximum Conducted Level RBW=100kHz**
**RFID**
**Hopping**



Date: 1.DEC.2020 22:17:19

**Test Model**
**Conducted Spurious RF Conducted Emission**
**RFID**
**Hopping**


Date: 1.DEC.2020 22:21:48

**Test Model**
**Band-edge Conducted Emissions**
**RFID**
**Hopping**


Date: 1.DEC.2020 22:19:25

**Test Model**
**Band-edge Conducted Emissions**
**RFID**
**Hopping**


Date: 1.DEC.2020 22:20:05

## 8.7 RADIATED SPURIOUS EMISSION

### 8.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074: D01 15.247 Meas Guidance v05r02

### 8.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength (dB $\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ( $\mu$ V/m)	300
0.490-1.705	24000/F(KHz)	20 log ( $\mu$ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Remark :1. Emission level in dB $\mu$ V/m=20 log ( $\mu$ V/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB);

Limit line=Specific limits(dB $\mu$ V) + distance extrapolation factor.

for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10\*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

### 8.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 8.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

### 8.7.5 Test Results

#### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ ( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.



## ■ Spurious Emission Above 1GHz (1GHz to 10GHz)

Test mode: ASK Frequency: Channel 01: 902.75MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1805.50	V	52.10	46.57	74.00	54.00	-21.90	-7.43
3611.35	V	45.90	38.62	74.00	54.00	-28.10	-15.38
9602.02	V	51.01	33.25	74.00	54.00	-22.99	-20.75
1805.50	H	45.16	39.63	74.00	54.00	-28.84	-14.37
2708.20	H	46.96	40.27	74.00	54.00	-27.04	-13.73
3610.90	H	54.26	49.28	74.00	54.00	-19.74	-4.72
1805.50	V	52.10	46.57	74.00	54.00	-21.90	-7.43
3611.35	V	45.90	38.62	74.00	54.00	-28.10	-15.38

Test mode: ASK Frequency: Channel 26: 915.25MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1830.25	V	50.30	44.58	74.00	54.00	-23.70	-9.42
3661.25	V	49.34	43.26	74.00	54.00	-24.66	-10.74
6909.40	V	50.67	33.29	74.00	54.00	-23.33	-20.71
1830.25	H	46.67	41.06	74.00	54.00	-27.33	-12.94
2745.55	H	45.38	40.37	74.00	54.00	-28.62	-13.63
3660.85	H	57.11	51.00	74.00	54.00	-16.89	-3.00
1830.25	V	50.30	44.58	74.00	54.00	-23.70	-9.42
3661.25	V	49.34	43.26	74.00	54.00	-24.66	-10.74

Test mode: ASK Frequency: Channel 50: 927.25MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1854.55	V	49.62	44.17	74.00	54.00	-24.38	-9.83
2781.55	V	42.27	37.35	74.00	54.00	-31.73	-16.65
3709.00	V	46.88	40.19	74.00	54.00	-27.12	-13.81
1854.55	H	44.51	39.62	74.00	54.00	-29.49	-14.38
2781.55	H	44.36	39.22	74.00	54.00	-29.64	-14.78
3709.00	H	53.62	49.03	74.00	54.00	-20.38	-4.97
1854.55	V	49.62	44.17	74.00	54.00	-24.38	-9.83
2781.55	V	42.27	37.35	74.00	54.00	-31.73	-16.65


**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3)The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(4) R\* is short for Restricted band, F\* is short for Fundamental frequency.

## ■ Spurious Emission below 1GHz (30MHz to 1GHz)



Site 3m Chamber #1

 Polarization: *Vertical*

Temperature: 25.5 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 48 %


Mode: 902.75MHz

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Degree
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1	*	49.5212	41.00	-12.12	28.88	40.00	-11.12	QP		
2		60.9187	38.56	-12.00	26.56	40.00	-13.44	QP		
3		140.0950	40.76	-14.44	26.32	43.50	-17.18	QP		
4		224.2425	46.67	-12.85	33.82	46.00	-12.18	QP		
5		241.9450	45.76	-12.07	33.69	46.00	-12.31	QP		
6		871.2324	30.53	1.90	32.43	46.00	-13.57	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator:XW



Site 3m Chamber #1

 Polarization: *Horizontal*

Temperature: 25.5 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 48 %

Mode:902.75MHz

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		140.2162	37.54	-14.43	23.11	43.50	-20.39	QP			
2	*	220.7262	53.90	-13.11	40.79	46.00	-5.21	QP			
3	!	243.7637	52.49	-12.00	40.49	46.00	-5.51	QP			
4		297.7200	42.68	-9.13	33.55	46.00	-12.45	QP			
5		347.7962	38.41	-7.69	30.72	46.00	-15.28	QP			
6		846.1337	29.12	2.90	32.02	46.00	-13.98	QP			

\*:Maximum data   x:Over limit   !:over margin


Operator:XW



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	49.5212	41.48	-12.12	29.36	40.00	-10.64	QP		
2		60.7974	40.17	-11.99	28.18	40.00	-11.82	QP		
3		140.0950	39.50	-14.44	25.06	43.50	-18.44	QP		
4		223.1512	45.93	-12.92	33.01	46.00	-12.99	QP		
5		244.8550	44.49	-11.95	32.54	46.00	-13.46	QP		
6		839.5862	29.24	2.84	32.08	46.00	-13.92	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator:XW



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		140.0950	38.50	-14.44	24.06	43.50	-19.44	QP			
2	*	221.6962	53.95	-13.03	40.92	46.00	-5.08	QP			
3		241.7024	51.21	-12.08	39.13	46.00	-6.87	QP			
4		291.0512	43.39	-9.51	33.88	46.00	-12.12	QP			
5		346.9474	37.12	-7.70	29.42	46.00	-16.58	QP			
6		865.4125	30.51	2.05	32.56	46.00	-13.44	QP			

\*:Maximum data    x:Over limit    !:over margin

Operator:XW



Site 3m Chamber #1

 Polarization: *Vertical*

Temperature: 25.5 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 48 %


Mode: 927.25MHz

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Degree
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		49.4000	39.12	-12.16	26.96	40.00	-13.04	QP		
2		60.7974	38.57	-11.99	26.58	40.00	-13.42	QP		
3		139.8524	39.24	-14.43	24.81	43.50	-18.69	QP		
4	*	223.2725	46.71	-12.91	33.80	46.00	-12.20	QP		
5		245.2187	45.51	-11.91	33.60	46.00	-12.40	QP		
6		825.8850	30.88	2.25	33.13	46.00	-12.87	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator:XW



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 25.5 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 48 %

Mode: 927.25MHz

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	
1		63.5862	28.72	-12.07	16.65	40.00	-23.35	QP			
2		139.9737	37.98	-14.44	23.54	43.50	-19.96	QP			
3	*	223.1513	53.65	-12.92	40.73	46.00	-5.27	QP			
4		242.9150	51.11	-12.03	39.08	46.00	-6.92	QP			
5		297.3562	43.35	-9.15	34.20	46.00	-11.80	QP			
6		839.8288	29.30	2.85	32.15	46.00	-13.85	QP			

\*:Maximum data    x:Over limit    !:over margin

Operator:XW

## 8.8 CONDUCTED EMISSION TEST

### 8.8.1 Applicable Standard

According to FCC Part 15.207(a)

### 8.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 8.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

### 8.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.


Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

### 8.8.5 Test Results

**PASS.**

Please refer to the following pages.



Site Conduction #1

 Phase: *L1*

Temperature: 24.7

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz


Humidity: 55 %

Mode: RFID

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	37.12	9.58	46.70	66.00	-19.30	QP	
2		0.1500	10.85	9.58	20.43	56.00	-35.57	AVG	
3 *		0.4100	33.06	9.32	42.38	57.65	-15.27	QP	
4		0.4100	13.01	9.32	22.33	47.65	-25.32	AVG	
5		1.1580	16.29	9.91	26.20	56.00	-29.80	QP	
6		1.1580	1.23	9.91	11.14	46.00	-34.86	AVG	
7		2.9420	15.69	9.95	25.64	56.00	-30.36	QP	
8		2.9420	-0.32	9.95	9.63	46.00	-36.37	AVG	
9		4.6260	15.43	9.92	25.35	56.00	-30.65	QP	
10		4.6260	-0.49	9.92	9.43	46.00	-36.57	AVG	
11		19.0780	18.03	10.17	28.20	60.00	-31.80	QP	
12		19.0780	4.62	10.17	14.79	50.00	-35.21	AVG	

\*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Vern



Site Conduction #1

 Phase: *N*

Temperature: 24.7

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz

Humidity: 55 %

Mode: RFID

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	35.68	9.58	45.26	66.00	-20.74	QP	
2		0.1500	10.75	9.58	20.33	56.00	-35.67	AVG	
3 *		0.4060	33.02	9.33	42.35	57.73	-15.38	QP	
4		0.4060	13.22	9.33	22.55	47.73	-25.18	AVG	
5		0.5140	17.20	9.25	26.45	56.00	-29.55	QP	
6		0.5140	1.34	9.25	10.59	46.00	-35.41	AVG	
7		1.5740	16.14	9.92	26.06	56.00	-29.94	QP	
8		1.5740	0.24	9.92	10.16	46.00	-35.84	AVG	
9		6.3860	15.31	10.00	25.31	60.00	-34.69	QP	
10		6.3860	-0.23	10.00	9.77	50.00	-40.23	AVG	
11		19.0060	17.78	10.17	27.95	60.00	-32.05	QP	
12		19.0060	4.94	10.17	15.11	50.00	-34.89	AVG	

:Maximum data    x:Over limit    !:over margin        Comment: Factor build in receiver.        Operator: Vern

## 8.9 ANTENNA APPLICATION

### 8.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 8.9.2 Result

**PASS.**

The EUT antenna is External Antenna, the max support antenna gain is 6.29 dBi.

Note:

- Use of permanent, industrial epoxy, "Loctite" or solder to make the connection permanent prior to shipping.
- Allow use of standard connector if the transmitter has a sensing circuitry that disables the transmitter if an unauthorized antenna is used. An application should detail how this is accomplished.
- Use of a standard connect is also allowed if the connectors is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.
- BIOS lock-Radio card and host (e.g., laptop computer) exchange code to ensure only the authorized transmission system works in the host.

which in accordance to section 15.203, please refer to the EUT photos.

## Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

----- End of Report -----