



RADIO TEST REPORT

Report No.:STS2011199W02

Issued for

Network Smartware Inc

830, Hillview Court, Suite 270 Milpitas, CA 95035

Product Name:	Netsmart Router
Brand Name:	Network Smartware
Model Name:	NSAC1200RZ
Series Model:	N/A
FCC ID:	2AYKCNSAC1200RZ
Test Standard:	FCC Part 15.407

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's Name..... : Network Smartware Inc

Address : 830, Hillview Court, Suite 270 Milpitas, CA 95035

Manufacturer's Name : JLZTLink Industry (Shen Zhen) Co.,Ltd

Address : 401, Building D, SanweiHongwan Industrial Park next to Baoan Avenue, Gushu Community, Xixiang, Sanwei Community, Hangcheng Street, Baoan District, Shenzhen, Guangdong

Product Description

Product Name..... : Netsmart Router

Brand Name : Network Smartware

Model Name : NSAC1200RZ

Series Model..... : N/A

Test Standards..... : FCC Part15.407

Test Procedure..... ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date of receipt of test item : 30 Nov. 2020

Date (s) of performance of tests : 30 Nov. 2020 ~ 28 Dec. 2020

Date of Issue..... : 28 Dec. 2020

Test Result..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 TEST SOFTWARE AND POWER LEVEL	12
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	14
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	15
3 . EMC EMISSION TEST	17
3.1 CONDUCTED EMISSION MEASUREMENT	17
3.2 RADIATED EMISSION AND (BANDEGE) MEASUREMENT	21
4. POWER SPECTRAL DENSITY TEST	43
4.1 LIMIT	43
4.2 TEST PROCEDURE	43
4.3 DEVIATION FROM STANDARD	44
4.4 TEST SETUP	44
4.5 EUT OPERATION CONDITIONS	44
4.6 TEST RESULTS	44
5. BANDWIDTH MEASUREMENT	46
5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	46
5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	48
5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	50
6. MAXIMUM CONDUCTED OUTPUT POWER	52
6.1 LIMIT	52
6.2 TEST PROCEDURE	52
6.3 DEVIATION FROM STANDARD	52
6.4 TEST SETUP	52
6.5 EUT OPERATION CONDITIONS	52
6.6 TEST RESULTS	53
7. AUTOMATICALLY DISCONTINUE TRANSMISSION	59
7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	59
7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	59



Table of Contents	Page
8. ANTENNA REQUIREMENT	60
8.1 STANDARD REQUIREMENT	60
8.2 EUT ANTENNA	60
APPENDIX - PHOTOS OF TEST SETUP	61



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	28 Dec. 2020	STS2011199W02	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

§ 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
15.407 (a) /15.407 (e)	26dB/6dB &99% Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	PASS
15.407(b)/15.205/15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(a)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203/15.204	Antenna Requirement	PASS

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 30-1GHz	$\pm 4.39\text{dB}$
4	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
5	All emissions, radiated >6G	$\pm 5.48\text{dB}$
6	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
7	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Netsmart Router	
Trade Name	Network Smartware	
Model Name	NSAC1200RZ	
Series Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Netsmart Router	
	Operation Frequency:	IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz
		IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11a/ n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz
	Modulation Type:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM
	Antenna Designation:	Please refer to the Note 4.
	Max.Output Power(Conducted):	16.227 dBm
	More details of EUT technical specification, please refer to the User Manual.	
Test Channel	Please refer to the Note 3.	
Adapter	Input: AC~100-240V AC, 50/60Hz Output: DC 12V_1A	
Hardware version number	V1.2	
Software version number	OpenWrt 19.07-SNAPSHOT r11130-a7f0a72 / LuCI openwrt-19.07 branch git-20.313.59566-7460e9d	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The EUT belong to indoor access point.



Operation Frequency of channel			
5.180GHz-5.240GHz		5.745GHz-5.825GHz	
Channel	Frequency	Channel	Frequency
36	5180	149	5745
38	5190	151	5755
40	5200	153	5765
42	5210	157	5785
44	5220	159	5795
46	5230	161	5805
48	5240	165	5825

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n(HT20)/ac(VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	149	5745
40	5200	157	5785
48	5240	165	5825

For 802.11 n(HT40)/ac(VHT40)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	151	5755
46	5230	159	5795

For 802.11ac (VHT80)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	155	5775

4. KDB 662911 D01 Multiple Transmitter Output v02r01

2) Directional Gain Calculations for In-Band Measurements

a) Basic methodology with NANT transmit antennas, each with the same directional gain G_{ANT} dBi, being driven by NANT transmitter outputs of equal power. Directional gain is to be computed as follows:

(i) If any transmit signals are correlated with each other,

$$\text{Directional gain} = G_{ANT} + 10 \log(NANT) \text{ dBi}$$

(ii) If all transmit signals are completely uncorrelated with each other,

$$\text{Directional gain} = G_{ANT}$$

Antenna number: 2

ANT 3 gain : 5dBi

ANT 4 gain : 5dBi

$$G_{ANT} + 10 \log(NANT) \text{ dBi}$$

$$\text{MIMO technology Directional gain} = 5 + 10 \log 2 = 8.01 \text{ dBi}$$



Ant	Brand	Model Name	Ant Type	Connector	Gain (dBi)	NOTE
A	Network Smartware	NSAC1200RZ	PIFA Antenna	N/A	ANT 3 gain : 5dBi ANT 4 gain : 5dBi MIMO=8.01dBi	WLAN Ant

Note: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.





2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 3	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 4	TX IEEE 802.11ac HT20 CH36&CH40&CH48	NSS1 MCS0
Mode 5	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 6	TX IEEE 802.11ac HT20 CH149&CH157&CH165	NSS1 MCS0
Mode 7	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 8	TX IEEE 802.11ac HT40 CH38&CH46	NSS1 MCS0
Mode 9	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 10	TX IEEE 802.11ac HT40 CH151&CH159	NSS1 MCS0
Mode 11	TX IEEE 802.11ac HT80 CH42	NSS1 MCS0
Mode 12	TX IEEE 802.11ac HT80 CH155	NSS1 MCS0

- Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
(4) The battery is fully-charged during the radiated and RF conducted test.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 13: Keeping TX + WLAN Link




2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	ANT 3 Power Class	ANT 4 Power Class	Software For Testing
WIFI(5G)	5G WIFI Band1 (5150MHz-5250MHz)	802.11a	ANT 3: 5 ANT 4: 5 MIMO: 8.01	0	0	MT76xxE_AP
		802.11n(HT20)		0	0	
		802.11n(HT40)		0	0	
		802.11ac(VHT20)		0	0	
		802.11ac(VHT40)		0	0	
		802.11ac(VHT80)		0	0	
RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	ANT 3 Power Class	ANT 4 Power Class	Software For Testing
WIFI(5G)	5G WIFI Band4 (5725MHz-5875MHz)	802.11a	ANT 3: 5 ANT 4: 5 MIMO: 8.01	0	0	MT76xxE_AP
		802.11n(HT20)		0	0	
		802.11n(HT40)		0	0	
		802.11ac(VHT20)		0	0	
		802.11ac(VHT40)		0	0	
		802.11ac(VHT80)		0	0	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-1	Adapter	N/A	GLH1201000	N/A	N/A
C-1	LAN Cable	N/A	N/A	120cm	NO

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-2	Notebook	DELL	Inspiron 14-3467	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
Signal Analyzer	R&S	FSV 40-N	101823	2020.10.10	2021.10.09
Active loop Antenna	ZHINAN	ZN30900C	16035	2019.07.11	2021.07.10
Bilog Antenna	TESEQ	CBL6111D	34678	2020.10.12	2022.10.11
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2019.10.15	2021.10.14
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2020.10.12	2022.10.11
Pre-Amplifier (0.1M-3GHz)	EM	EM330	060665	2020.10.12	2021.10.11
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2020.10.12	2021.10.11
Pre-Amplifier (18G-40GHz)	SKET	LNPA-1840-50	SK2018101801	2020.10.10	2021.10.09
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 RE)			

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
LISN	R&S	ENV216	101242	2020.10.12	2021.10.11
LISN	EMCO	3810/2NM	23625	2020.10.12	2021.10.11
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 CE)			



RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Power Sensor	Keysight	U2021XA	MY55520005	2020.10.10	2021.10.09
			MY55520006	2020.10.10	2021.10.09
			MY56120038	2020.10.10	2021.10.09
			MY56280002	2020.10.10	2021.10.09
Signal Analyzer	Agilent	N9020A	MY51110105	2020.03.05	2021.03.04
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Test SW	FARAD	LZ-RF /LzRf-3A3			





3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.6 TEST RESULTS

Temperature:	26.2(C)	Relative Humidity:	53%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	28.82	20.19	49.01	66.00	-16.99	QP
2	0.1500	13.57	20.19	33.76	56.00	-22.24	AVG
3	0.5620	22.78	20.38	43.16	56.00	-12.84	QP
4	0.5620	14.44	20.38	34.82	46.00	-11.18	AVG
5	1.2100	13.22	20.15	33.37	56.00	-22.63	QP
6	1.2100	2.70	20.15	22.85	46.00	-23.15	AVG
7	2.2540	13.44	20.13	33.57	56.00	-22.43	QP
8	2.2540	-0.18	20.13	19.95	46.00	-26.05	AVG
9	9.6780	10.25	19.86	30.11	60.00	-29.89	QP
10	9.6780	-2.68	19.86	17.18	50.00	-32.82	AVG
11	29.3140	13.21	20.95	34.16	60.00	-25.84	QP
12	29.3140	2.80	20.95	23.75	50.00	-26.25	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result =Reading + Factor)-Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)






Temperature:	26.2(C)	Relative Humidity:	53%RH
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	29.70	20.19	49.89	66.00	-16.11	QP
2	0.1500	14.90	20.19	35.09	56.00	-20.91	AVG
3	0.6020	19.89	20.35	40.24	56.00	-15.76	QP
4	0.6020	11.02	20.35	31.37	46.00	-14.63	AVG
5	1.2460	10.34	20.16	30.50	56.00	-25.50	QP
6	1.2460	0.01	20.16	20.17	46.00	-25.83	AVG
7	2.9340	10.12	20.09	30.21	56.00	-25.79	QP
8	2.9340	-1.05	20.09	19.04	46.00	-26.96	AVG
9	9.0540	9.39	19.88	29.27	60.00	-30.73	QP
10	9.0540	-2.96	19.88	16.92	50.00	-33.08	AVG
11	19.7380	11.18	20.62	31.80	60.00	-28.20	QP
12	19.7380	-2.00	20.62	18.62	50.00	-31.38	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)





3.2 RADIATED EMISSION AND (BANDEDGE) MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7&15.205/209(a), then the limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	68.2	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Note: In case the emission radiated emission above 1000MHz fall within the restricted band the restricted frequency bands, the peak limit is 74 dBuV/m.

**LIMITS OF EMISSIONS OUTSIDE OF THE FREQUENCY BANDS**

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: dBuV/m(at 3M) = EIRP(dBm) + 95.3.

Peak Limit = -27dBm/MHz + 95.3 = 68.3 dBuV/m.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the ANT 3re set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.


3.2.2 DEVIATION FROM TEST STANDARD

No deviation




3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage:	AC 120V/60Hz	Polarization :	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuV) + distance extrapolation factor.


**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature	23.1(C)	Relative Humidity	60%RH
Test Voltage	AC 120V/60Hz	Polarization	Horizontal
Test Mode	Mode 1~12(Mode 12 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	108.5700	58.04	-19.22	38.82	43.50	-4.68	QP
2	142.5200	54.23	-18.18	36.05	43.50	-7.45	QP
3	332.6400	42.80	-13.62	29.18	46.00	-16.82	QP
4	480.0800	41.75	-8.65	33.10	46.00	-12.90	QP
5	750.7100	32.58	-2.16	30.42	46.00	-15.58	QP
6	898.1500	34.41	-0.49	33.92	46.00	-12.08	QP

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain






Temperature	23.1(C)	Relative Humidity	60%RH
Test Voltage	AC 120V/60Hz	Polarization	Vertical
Test Mode	Mode 1~12(Mode 12 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	108.5700	55.01	-19.22	35.79	43.50	-7.71	QP
2	398.6000	40.03	-11.20	28.83	46.00	-17.17	QP
3	516.9400	39.90	-7.85	32.05	46.00	-13.95	QP
4	831.2200	33.19	-0.70	32.49	46.00	-13.51	QP
5	912.7000	33.81	-0.14	33.67	46.00	-12.33	QP
6	999.0300	34.82	2.04	36.86	54.00	-17.14	QP

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain





3.2.8 TEST RESULTS (Above 1000 MHz)

Band I 5150-5250MHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
802.11ac80/ 5210 MHz										
3277.69	44.32	44.70	6.70	28.20	-9.80	34.52	68.20	-33.68	Pk	Vertical
3277.69	41.77	44.70	6.70	28.20	-9.80	31.97	54.00	-22.03	AV	Vertical
3271.61	45.25	44.70	6.70	28.20	-9.80	35.45	68.20	-32.75	Pk	Horizontal
3271.61	42.00	44.70	6.70	28.20	-9.80	32.20	54.00	-21.80	AV	Horizontal
4006.37	39.01	44.20	7.90	29.70	-6.60	32.41	68.20	-35.79	Pk	Vertical
4006.37	36.90	44.20	7.90	29.70	-6.60	30.30	54.00	-23.70	AV	Vertical
4012.84	39.83	44.20	7.90	29.70	-6.60	33.23	68.20	-34.97	Pk	Horizontal
4012.84	35.63	44.20	7.90	29.70	-6.60	29.03	54.00	-24.97	AV	Horizontal
7264.60	36.67	43.50	11.40	35.50	3.40	40.07	68.20	-28.13	Pk	Vertical
7264.60	34.69	43.50	11.40	35.50	3.40	38.09	54.00	-15.91	AV	Vertical
7262.48	37.83	43.50	11.40	35.50	3.40	41.23	68.20	-26.97	Pk	Horizontal
7262.48	33.57	43.50	11.40	35.50	3.40	36.97	54.00	-17.03	AV	Horizontal
10419.98	39.32	44.50	13.80	38.80	8.10	47.42	68.20	-20.78	Pk	Vertical
10419.98	36.22	44.50	13.80	38.80	8.10	44.32	54.00	-9.68	AV	Vertical
10420.30	38.86	44.50	13.80	38.80	8.10	46.96	68.20	-21.24	Pk	Horizontal
10420.30	35.78	44.50	13.80	38.80	8.10	43.88	54.00	-10.12	AV	Horizontal
11088.13	33.25	43.60	14.30	39.50	10.20	43.45	68.20	-24.75	Pk	Vertical
11088.13	30.63	43.60	14.30	39.50	10.20	40.83	54.00	-13.17	AV	Vertical
11085.78	33.80	43.60	14.30	39.50	10.20	44.00	68.20	-24.20	Pk	Horizontal
11085.78	30.41	43.60	14.30	39.50	10.20	40.61	54.00	-13.39	AV	Horizontal
13369.59	31.77	42.60	15.90	38.90	12.20	43.97	68.20	-24.23	Pk	Vertical
13369.59	29.17	42.60	15.90	38.90	12.20	41.37	54.00	-12.63	AV	Vertical
13361.52	32.87	42.60	15.90	38.90	12.20	45.07	68.20	-23.13	Pk	Horizontal
13361.52	28.56	42.60	15.90	38.90	12.20	40.76	54.00	-13.24	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (VHT-20), 802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11ac (VHT-80).
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.
4. Pre-scan both the SISO and MIMO mode, only the worst-case results were reported.



Band IV(5.725-5.850) GHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Corrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11ac80/ 5775 MHz)										
3266.74	44.39	44.70	6.70	28.20	-9.80	34.59	68.20	-33.61	Pk	Vertical
3266.74	41.46	44.70	6.70	28.20	-9.80	31.66	54.00	-22.34	AV	Vertical
3281.91	43.96	44.70	6.70	28.20	-9.80	34.16	68.20	-34.04	Pk	Horizontal
3281.91	41.44	44.70	6.70	28.20	-9.80	31.64	54.00	-22.36	AV	Horizontal
4009.75	38.73	44.20	7.90	29.70	-6.60	32.13	68.20	-36.07	Pk	Vertical
4009.75	36.68	44.20	7.90	29.70	-6.60	30.08	54.00	-23.92	AV	Vertical
4003.00	39.86	44.20	7.90	29.70	-6.60	33.26	68.20	-34.94	Pk	Horizontal
4003.00	35.95	44.20	7.90	29.70	-6.60	29.35	54.00	-24.65	AV	Horizontal
7268.26	37.62	43.50	11.40	35.50	3.40	41.02	68.20	-27.18	Pk	Vertical
7268.26	34.62	43.50	11.40	35.50	3.40	38.02	54.00	-15.98	AV	Vertical
7260.00	37.16	43.50	11.40	35.50	3.40	40.56	68.20	-27.64	Pk	Horizontal
7260.00	33.73	43.50	11.40	35.50	3.40	37.13	54.00	-16.87	AV	Horizontal
10414.52	38.82	44.50	13.80	38.80	8.10	46.92	68.20	-21.28	Pk	Vertical
10414.52	35.86	44.50	13.80	38.80	8.10	43.96	54.00	-10.04	AV	Vertical
10414.35	39.45	44.50	13.80	38.80	8.10	47.55	68.20	-20.65	Pk	Horizontal
10414.35	36.26	44.50	13.80	38.80	8.10	44.36	54.00	-9.64	AV	Horizontal
11083.08	33.32	43.60	14.30	39.50	10.20	43.52	68.20	-24.68	Pk	Vertical
11083.08	30.68	43.60	14.30	39.50	10.20	40.88	54.00	-13.12	AV	Vertical
11083.92	33.31	43.60	14.30	39.50	10.20	43.51	68.20	-24.69	Pk	Horizontal
11083.92	30.44	43.60	14.30	39.50	10.20	40.64	54.00	-13.36	AV	Horizontal
13353.53	32.29	42.60	15.90	38.90	12.20	44.49	68.20	-23.71	Pk	Vertical
13353.53	29.96	42.60	15.90	38.90	12.20	42.16	54.00	-11.84	AV	Vertical
13359.36	31.77	42.60	15.90	38.90	12.20	43.97	68.20	-24.23	Pk	Horizontal
13359.36	29.43	42.60	15.90	38.90	12.20	41.63	54.00	-12.37	AV	Horizontal

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (VHT-20), 802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11ac (VHT-80).
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.
4. Pre-scan both the SISO and MIMO mode, only the worst-case results were reported.



3.2.9 RESTRICTED FREQUENCY BANDS AND BAND EDGE


Band I 5150-5250MHz

802.11n20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.000	63.21	-5.73	57.48	68.20	-10.72	peak
2	5145.000	50.09	-5.73	44.36	54.00	-9.64	AVG
3	5150.000	61.43	-5.73	55.70	68.20	-12.50	peak
4	5150.000	51.01	-5.73	45.28	54.00	-8.72	AVG


802.11n20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5133.000	59.46	-5.73	53.73	68.20	-14.47	peak
2	5150.000	59.92	-5.73	54.19	68.20	-14.01	peak
3	5150.000	49.94	-5.73	44.21	54.00	-9.79	AVG




802.11n20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.04	-5.23	45.81	68.20	-22.39	peak
2	5417.720	52.32	-5.21	47.11	68.20	-21.09	peak


802.11n20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.16	-5.23	45.93	68.20	-22.27	peak
2	5436.760	51.93	-5.16	46.77	68.20	-21.43	peak




802.11n40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5137.600	58.55	-5.74	52.81	68.20	-15.39	peak
2	5150.000	57.47	-5.73	51.74	68.20	-16.46	peak


802.11n40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5140.800	57.15	-5.74	51.41	68.20	-16.79	peak
2	5150.000	56.17	-5.73	50.44	68.20	-17.76	peak




802.11n40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.82	-5.23	46.59	68.20	-21.61	peak
2	5371.340	52.24	-5.24	47.00	68.20	-21.20	peak


802.11n40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.45	-5.23	45.22	68.20	-22.98	peak
2	5446.980	52.02	-5.14	46.88	68.20	-21.32	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4986.400	53.40	-6.28	47.12	68.20	-21.08	peak
2	5150.000	52.34	-5.73	46.61	68.20	-21.59	peak


802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4981.600	54.32	-6.31	48.01	68.20	-20.19	peak
2	5150.000	52.00	-5.73	46.27	68.20	-21.93	peak




802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.46	-5.23	45.23	68.20	-22.97	peak
2	5436.130	52.14	-5.17	46.97	68.20	-21.23	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.11	-5.23	44.88	68.20	-23.32	peak
2	5414.740	52.33	-5.22	47.11	68.20	-21.09	peak

Note: All modes have been tested. Only the worst mode shown in the report.




Band IV(5.725-5.85 GHz)

802.11ac20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5624.375	52.25	-4.69	47.56	68.20	-20.64	peak
2	5685.875	51.93	-4.66	47.27	94.75	-47.48	peak
3	5725.000	51.22	-4.57	46.65	119.20	-72.55	peak


802.11ac20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5633.375	55.39	-4.69	50.70	68.20	-17.50	peak
2	5695.438	55.94	-4.66	51.28	101.82	-50.54	peak
3	5725.000	77.81	-4.57	73.24	119.20	-45.96	peak




802.11ac20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	51.79	-4.10	47.69	119.20	-71.51	peak
2	5892.150	51.55	-3.91	47.64	92.51	-44.87	peak
3	5940.087	51.02	-3.95	47.07	68.20	-21.13	peak


802.11ac20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	62.37	-4.10	58.27	119.20	-60.93	peak
2	5898.650	55.57	-3.88	51.69	87.70	-36.01	peak
3	5936.675	54.10	-3.94	50.16	68.20	-18.04	peak




802.11ac40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5632.813	52.21	-4.69	47.52	68.20	-20.68	peak
2	5677.625	52.25	-4.67	47.58	88.64	-41.06	peak
3	5725.000	51.26	-4.57	46.69	119.20	-72.51	peak


802.11ac40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5617.813	55.75	-4.69	51.06	68.20	-17.14	peak
2	5683.625	55.19	-4.67	50.52	93.08	-42.56	peak
3	5725.000	72.41	-4.57	67.84	119.20	-51.36	peak




802.11ac40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	50.10	-4.10	46.00	119.20	-73.20	peak
2	5895.280	51.37	-3.90	47.47	90.19	-42.72	peak
3	5938.980	51.18	-3.95	47.23	68.20	-20.97	peak


802.11ac40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	55.61	-4.10	51.51	119.20	-67.69	peak
2	5877.800	54.98	-3.98	51.00	103.13	-52.13	peak
3	5935.750	53.84	-3.94	49.90	68.20	-18.30	peak




802.11ac80-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5614.700	51.87	-4.70	47.17	68.20	-21.03	peak
2	5667.550	52.19	-4.67	47.52	81.19	-33.67	peak
3	5725.000	51.48	-4.57	46.91	119.20	-72.29	peak
4	5850.000	50.41	-4.10	46.31	119.20	-72.89	peak
5	5898.550	51.83	-3.88	47.95	87.77	-39.82	peak
6	5933.550	50.97	-3.94	47.03	68.20	-21.17	peak



802.11ac80-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5643.400	58.21	-4.68	53.53	68.20	-14.67	peak
2	5700.450	70.86	-4.66	66.20	105.33	-39.13	peak
3	5725.000	73.76	-4.57	69.19	119.20	-50.01	peak
4	5850.000	67.43	-4.10	63.33	119.20	-55.87	peak
5	5884.900	60.86	-3.94	56.92	97.87	-40.95	peak
6	5936.700	53.77	-3.94	49.83	68.20	-18.37	peak

Note: All modes have been tested. Only the worst mode shown in the report.



4. POWER SPECTRAL DENSITY TEST

4.1 LIMIT

1. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

1. The setting follows Method SA-1 of FCC KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

For devices operating in the band, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (*i.e.*, 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHZ}$ is available on nearly all spectrum analyzers.



4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

5150-5250MHz								
Frequency	Direct measurement ANT 3 Power Density (dBm)	Direct measurement ANT 4 Power Density (dBm)	Duty cycle factor	Final ANT 3 Power Density (dBm)	Final ANT 4 Power Density (dBm)	Power Density Total (dBm)	Limit (dBm)	Result
802.11a								
5180	-1.115	-5.359	0.378	-0.737	-4.981	--	17	PASS
5200	-1.372	-5.986	0.378	-0.994	-5.608	--	17	PASS
5240	-2.237	-6.648	0.378	-1.859	-6.270	--	17	PASS
802.11n20								
5180	-1.750	-5.812	0.237	-1.513	-5.575	-0.075	14.99	PASS
5200	-1.576	-6.468	0.237	-1.339	-6.231	-0.120	14.99	PASS
5240	-2.413	-6.862	0.237	-2.176	-6.625	-0.844	14.99	PASS
802.11n40								
5190	-4.738	-9.324	0.463	-4.275	-8.861	-2.979	14.99	PASS
5230	-5.245	-10.110	0.463	-4.782	-9.647	-3.556	14.99	PASS
802.11ac20								
5180	-1.509	-6.302	0.176	-1.333	-6.126	-0.089	14.99	PASS
5200	-1.602	-6.370	0.176	-1.426	-6.194	-0.176	14.99	PASS
5240	-2.747	-7.068	0.176	-2.571	-6.892	-1.205	14.99	PASS
802.11ac40								
5190	-4.975	-9.998	0.725	-4.250	-9.273	-3.063	14.99	PASS
5230	-5.597	-9.935	0.725	-4.872	-9.210	-3.511	14.99	PASS
802.11ac80								
5210	-7.185	-12.111	0.415	-6.770	-11.696	-5.559	14.99	PASS



5725-5850MHz										
Frequency	Use RBW 510KHz direct measurement ANT 3 Power Density (dBm)	Use RBW 510KHz direct measurement ANT 4 Power Density (dBm)	Convert to RBW 500KHz direct measurement ANT 3 Power Density (dBm)	Convert to RBW 500KHz direct measurement ANT 4 Power Density (dBm)	Duty cycle factor (dB)	Final ANT 3 Power Density (dBm)	Final ANT 4 Power Density (dBm)	Power Density Total (dBm)	Limit (dBm)	Result
802.11a										
5745	-5.288	-5.230	-5.374	-5.316	0.299	-5.075	-5.017	--	30	PASS
5785	-5.905	-5.079	-5.991	-5.165	0.299	-5.692	-4.866	--	30	PASS
5825	-6.472	-5.517	-6.558	-5.603	0.299	-6.259	-5.304	--	30	PASS
802.11n20										
5745	-6.060	-5.656	-6.146	-5.742	0.484	-5.662	-5.258	-2.445	27.99	PASS
5785	-6.763	-5.716	-6.849	-5.802	0.484	-6.365	-5.318	-2.799	27.99	PASS
5825	-6.710	-5.180	-6.796	-5.266	0.484	-6.312	-4.782	-2.469	27.99	PASS
802.11n40										
5755	-9.457	-9.185	-9.543	-9.271	0.419	-9.124	-8.852	-5.976	27.99	PASS
5795	-9.915	-8.689	-10.001	-8.775	0.419	-9.582	-8.356	-5.916	27.99	PASS
802.11ac20										
5745	-6.007	-5.530	-6.093	-5.616	0.200	-5.893	-5.416	-2.637	27.99	PASS
5785	-6.723	-5.335	-6.809	-5.421	0.200	-6.609	-5.221	-2.849	27.99	PASS
5825	-7.414	-5.590	-7.500	-5.676	0.200	-7.300	-5.476	-3.282	27.99	PASS
802.11ac40										
5755	-10.274	-8.866	-10.360	-8.952	0.465	-9.895	-8.487	-6.124	27.99	PASS
5795	-10.723	-9.182	-10.809	-9.268	0.465	-10.344	-8.803	-6.495	27.99	PASS
802.11ac80										
5775	-11.778	-10.497	-11.864	-10.583	0.309	-11.555	-10.274	-7.857	27.99	PASS

Note: 1. RB conversion formula: $10 \cdot \log(500\text{KHz}/\text{RBW})$

2. Test plots see Attachment A.

3. The MIMO antenna gain is 8.01dBi, which is greater 6dBi, and the MIMO mode limit will be reduced by 2.01dBi.

5. BANDWIDTH MEASUREMENT

5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

The following procedure shall be used for measuring 26 bandwidth.

5.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.1.5 TEST RESULTS**

Frequency (MHz)	ANT 3 26dB Bandwidth (MHz)	ANT 4 26dB Bandwidth (MHz)	Pass/Fail
802.11a			
5180	19.34	19.49	Pass
5200	19.34	19.66	Pass
5240	19.27	19.41	Pass
802.11n(HT20)			
5180	19.79	19.79	Pass
5200	19.85	19.81	Pass
5240	19.91	19.84	Pass
802.11n(HT40)			
5190	40.03	39.86	Pass
5230	39.79	39.96	Pass
802.11ac(VHT20)			
5180	19.87	19.82	Pass
5200	19.81	19.86	Pass
5240	19.82	19.80	Pass
802.11ac(VHT40)			
5190	39.85	39.84	Pass
5230	39.80	39.94	Pass
802.11ac(VHT80)			
5210	80.25	80.88	Pass

Frequency (MHz)	ANT 3 26dB Bandwidth (MHz)	ANT 4 26dB Bandwidth (MHz)	Pass/Fail
802.11a			
5745	19.44	19.43	Pass
5785	19.41	19.44	Pass
5825	19.47	19.46	Pass
802.11n(HT20)			
5745	19.91	19.80	Pass
5785	19.83	19.91	Pass
5825	19.85	19.90	Pass
802.11n(HT40)			
5755	39.87	40.00	Pass
5795	39.98	39.88	Pass
802.11ac(VHT20)			
5745	19.89	19.83	Pass
5785	19.87	19.80	Pass
5825	19.92	19.87	Pass
802.11ac(VHT40)			
5755	39.98	39.65	Pass
5795	39.80	39.91	Pass
802.11ac(VHT80)			
5775	80.07	80.01	Pass

Test plot see Attachment B

5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth.

5.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

5.2.2 DEVIATION FROM STANDARD

No deviation.

5.2.3 TEST SETUP



5.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.2.5 TEST RESULTS**

Frequency (MHz)	ANT 3 99% Bandwidth (MHz)	ANT 4 99% Bandwidth (MHz)	Pass/Fail
802.11a			
5180	16.57	16.57	Pass
5200	16.58	16.58	Pass
5240	16.54	16.58	Pass
802.11n(HT20)			
5180	17.58	17.57	Pass
5200	17.57	17.57	Pass
5240	17.57	17.56	Pass
802.11n(HT40)			
5190	36.01	36.04	Pass
5230	36.03	36.02	Pass
802.11ac(VHT20)			
5180	17.57	17.57	Pass
5200	17.58	17.57	Pass
5240	17.57	17.56	Pass
802.11ac(VHT40)			
5190	36.01	36.02	Pass
5230	36.03	36.01	Pass
802.11ac(VHT80)			
5210	74.89	74.78	Pass

Frequency (MHz)	ANT 3 99% Bandwidth (MHz)	ANT 4 99% Bandwidth (MHz)	Pass/Fail
802.11a			
5745	16.59	16.57	Pass
5785	16.56	16.56	Pass
5825	16.57	16.58	Pass
802.11n(HT20)			
5745	17.58	17.57	Pass
5785	17.56	17.57	Pass
5825	17.59	17.56	Pass
802.11n(HT40)			
5755	36.05	36.05	Pass
5795	36.02	36.01	Pass
802.11ac(VHT20)			
5745	17.57	17.57	Pass
5785	17.57	17.57	Pass
5825	17.58	17.57	Pass
802.11ac(VHT40)			
5755	36.02	36.00	Pass
5795	36.03	36.03	Pass
802.11ac(VHT80)			
5775	74.87	75.01	Pass

Test plot See Attachment B

5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth.

5.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.2 DEVIATION FROM STANDARD

No deviation.

5.3.3 TEST SETUP



5.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.3.5 TEST RESULTS**

Frequency (MHz)	ANT 3 6dB Bandwidth (MHz)	ANT 4 6dB Bandwidth (MHz)	Pass/Fail
802.11a			
5745	16.01	15.79	Pass
5785	16.31	15.77	Pass
5825	16.31	16.05	Pass
802.11n(HT20)			
5745	16.34	16.83	Pass
5785	17.04	16.95	Pass
5825	16.90	16.91	Pass
802.11n(HT40)			
5755	35.64	35.61	Pass
5795	35.13	35.17	Pass
802.11ac(VHT20)			
5745	16.98	16.01	Pass
5785	17.03	16.88	Pass
5825	16.88	15.78	Pass
802.11ac(VHT40)			
5755	35.46	35.61	Pass
5795	35.17	35.12	Pass
802.11ac(VHT80)			
5775	74.47	75.10	Pass

Test plots see Attachment C



6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 LIMIT

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Peak Output Power	1 watt	5150-5250	PASS
		The lesser of 250 mW or 11 dBm + 10 log (26 dB emission bandwidth)	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	


6.2 TEST PROCEDURE

The EUT was directly connected to the Power Sensor&PC

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.




6.6 TEST RESULTS

Note: The MIMO antenna gain is 8.01dBi, which is greater 6dBi, and the MIMO mode limit will be reduced by 2.01dBi.


Band I (5.15-5.25GHz)								
Test Channel	Frequency (MHz)	Direct measurement ANT 3 AV Power (dBm)	Direct measurement ANT 4_AV Power (dBm)	Duty cycle factor (dB)	Final ANT 3 AV Power (dBm)	Final ANT 4 AV Power (dBm)	AV Power Total (dBm)	LIMIT (dBm)
802.11a								
36	5180	8.81	4.58	0.378	9.19	4.96	--	30.00
40	5200	8.35	4.50	0.378	8.73	4.88	--	30.00
48	5240	7.76	4.55	0.378	8.14	4.93	--	30.00
802.11n(HT20)								
36	5180	8.16	4.23	0.237	8.40	4.47	9.87	27.99
40	5200	7.91	4.20	0.237	8.15	4.44	9.69	27.99
48	5240	7.78	4.36	0.237	8.02	4.60	9.65	27.99
802.11n(HT40)								
38	5190	7.78	3.98	0.463	8.24	4.44	9.76	27.99
46	5230	7.26	4.02	0.463	7.72	4.48	9.41	27.99
802.11ac(VHT20)								
36	5180	8.39	4.44	0.176	8.57	4.62	10.04	27.99
40	5200	8.04	4.43	0.176	8.22	4.61	9.79	27.99
48	5240	7.57	4.43	0.176	7.75	4.61	9.46	27.99
802.11ac(VHT40)								
38	5190	7.86	3.96	0.725	8.58	4.68	10.07	27.99
46	5230	7.37	3.98	0.725	8.09	4.70	9.73	27.99
802.11ac(VHT80)								
42	5210	14.51	9.77	0.415	14.93	10.19	16.18	27.99




Band IV (5.725-5.85GHz)								
Test Channel	Frequency (MHz)	Direct measurement ANT 3 AV Power (dBm)	Direct measurement ANT 4 AV Power (dBm)	Duty cycle factor (dB)	Final ANT 3 AV Power (dBm)	Final ANT 4 AV Power (dBm)	AV Power Total (dBm)	LIMIT (dBm)
802.11a								
149	5745	8.99	9.27	0.299	9.29	9.57	--	30.00
157	5785	8.64	9.29	0.299	8.94	9.59	--	30.00
165	5825	8.41	9.19	0.299	8.71	9.49	--	30.00
802.11n(HT20)								
149	5745	8.94	8.97	0.484	9.42	9.45	12.450	27.99
157	5785	8.52	9.02	0.484	9.00	9.50	12.272	27.99
165	5825	8.22	9.00	0.484	8.70	9.48	12.122	27.99
802.11n(HT40)								
151	5755	8.41	8.77	0.419	8.83	9.19	12.023	27.99
159	5795	7.92	8.78	0.419	8.34	9.20	11.800	27.99
802.11ac(VHT20)								
149	5745	8.74	9.27	0.200	8.94	9.47	12.224	27.99
157	5785	8.39	9.10	0.200	8.59	9.30	11.970	27.99
165	5825	8.17	9.21	0.200	8.37	9.41	11.932	27.99
802.11ac(VHT40)								
151	5755	8.23	8.85	0.465	8.70	9.32	12.027	27.99
159	5795	7.97	8.85	0.465	8.44	9.32	11.908	27.99
802.11ac(VHT80)								
155	5775	12.34	13.41	0.309	12.65	13.72	16.227	27.99




5210MHz_ANT 3



5775MHz_ANT 3



5210MHz_ANT 4



5775MHz_ANT 4



Duty cycle

Band1				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.452	1.584	91.67%	0.378
n20	1.356	1.432	94.69%	0.237
n40	0.676	0.752	89.89%	0.463
ac20	1.356	1.412	96.03%	0.176
ac40	0.672	0.794	84.63%	0.725
ac80	1.356	1.492	90.88%	0.415
Band4				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.452	1.556	93.34%	0.299
n20	1.356	1.516	89.45%	0.484
n40	0.672	0.740	90.81%	0.419
ac20	1.356	1.420	95.49%	0.200
ac40	0.672	0.748	89.84%	0.465
ac80	1.356	1.456	93.13%	0.309






Band 1-a20




Band 1-n20




Band 1-n40




Band 1-ac20



Band 1-ac40




Band 1-ac80



Band 4-a20




Band 4-n20



Band 4-n40



Band 4-ac20



Band 4-ac40



Band 4-ac80



7. AUTOMATICALLY DISCONTINUE TRANSMISSION

7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission





8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is Integral antenna. It comply with the standard requirement.



**APPENDIX - PHOTOS OF TEST SETUP**

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※

